C Program MCQs

14 Topics • 1175 Questions

C Miscellaneous

Q1. Determine output: void main() { int const *p=5; printf("%d", ++(*p)); }

A. 6

B. 5

C. Garbage Value

D. Compiler Error ✓

Answer: Option D — Compiler Error

Q2. Determine Output: void main() { char s[]="man"; int i; for(i=0; s[i]; i++) printf("%c%c%c%c ", s[i], *(s+i), *(i+s), i[s]); }

A. mmm nnn aaa

B. mmmm nnnn aaaa

C. Compiler Error

D. None of These ✓

Answer: Option D — None of These

Q3. Determine Output: void main() { float me = 1.1; double you = 1.1; if(me==you) printf("I hate Examveda"); else printf("I love Examveda"); }

A. I hate Examveda

B. I love Examveda ✓

C. Error

D. None of These

Answer: Option B — I love Examveda

Q4. Determine Output: void main() { static int var = 5; printf("%d ", var--); if(var) main(); }

A. 5 5 5 5 5

B. 5 4 3 2 1 ✓

C. Infinite Loop

D. None of These

Answer: Option B — 5 4 3 2 1

Q5. Determine Output: void main() { char *p; printf("%d %d", sizeof(*p), sizeof(p)); }

A. 1 1

B. 1 2 ✓

C. 2 1

D. 2 2

Answer: Option B — 1 2

Q6. Determine the Final Output: void main() { printf("\nab"); printf("\bsi"); printf("\rha"); }

A. absiha

B. asiha

C. haasi

D. hai ✓

Answer: Option D — hai

Q7. Determine Output: void main() { int i=10; i=!i>14; printf("i=%d", i); }

A. 10

B. 14

C. 0 ✓

D. 1

Answer: Option C — 0

Q8. Determine Output: void main() { int c = - -2; printf("c=%d", c); }

A. 1

B. -2

C. 2 ✓

D. Error

Answer: Option C — 2

Q9. Determine Output: #define int char void main() { int i = 65; printf("sizeof(i)=%d", sizeof(i)); }

A. sizeof(i)=2

B. sizeof(i)=1 ✓

C. Compiler Error

D. None of These

Answer: Option B — sizeof(i)=1

Q10. Determine Output: void main() { int i=3; switch(i) { default: printf("zero"); case 1: printf("one"); break; case 2: printf("two"); break; case 3: printf("three"); break; } }

A. zero

B. three ✓

C. Error

D. None of These

Answer: Option B — three

Q11. Determine Output: void main() { char string[]="Hello World"; display(string); } void display(char *string) { printf("%s", string); }

A. will print Hello World

B. Compiler Error ✓

C. Can't Say

D. None of These

Answer: Option B — Compiler Error

Q12. Determine Output: void main() { int i=5; printf("%d%d%d%d%d", i++, i--, ++i, --i, i); }

A. 45545 ✓

B. 54544

C. 55445

D. 54554

Answer: Option A — 45545

Q13. Determine Output: #define square(x) x*x void main() { int i; i = 64/square(4); printf("%d", i); }

A. 4

B. 64 ✓

C. 16

D. None of These

Answer: Option B — 64

Q14. Determine Output: void main() { char *p="hi friends", *p1; p1=p; while(*p!='\0') ++*p++; printf("%s", p1); }

A. hi friends

B. ij!gsjfoet ✓

C. hj grjeodt

D. None of These

Answer: Option B — ij!gsjfoet

Q15. Determine Output: #include<stdio.h> #define a 10 void main() { #define a 50 printf("%d", a); }

A. 50 ✓

B. 10

C. Compiler Error

D. None of These

Answer: Option A — 50

Q16. Determine Output: #define clrscr() 100 void main() { clrscr(); printf("%d", clrscr()); }

A. 0

B. 1

C. 100 ✓

D. Error

Answer: Option C — 100

Q17. Determine Output: void main() { printf("%p", main); }

A. Error

B. make an infinite loop

C. Some address will be printed ✓

D. None of These

Answer: Option C — Some address will be printed

Q18. Determine Output: void main() { char far *farther, *farthest; printf("%d..%d", sizeof(farther), sizeof(farthest)); }

A. 4..2 ✓

B. 2..2

C. 4..4

D. 2..4

Answer: Option A — 4..2

Q19. Determine Output: void main() { char *p; p="Hello"; printf("%c", *&*p); }

A. Hello

B. H ✓

C. Some Address will be printed

D. None of These

Answer: Option B — H

Q20. Determine Output: void main() { int i=1; while(i<=5) { printf("%d", i); if(i>2) goto here; i++; } } fun() { here: printf("PP"); }

A. 12PP

B. 12PP345

C. Compiler Error ✓

D. None of These

Answer: Option C — Compiler Error

Q21. Determine Output: void main() { int i=1, j=2; switch(i) { case 1: printf("GOOD"); break; case j: printf("BAD"); break; } }

A. GOOD BAD

B. GOOD

C. Compiler Error ✓

D. None of These

Answer: Option C — Compiler Error

Q22. Determine Output: void main() { int i; printf("%d", scanf("%d", &i)); // value 10 is given as input here }

A. 10

B. 1 ✓

C. Garbage Value

D. None of These

Answer: Option B — 1

Q23. Determine Output: void main() { int i=0; for(;i++;printf("%d", i)); printf("%d", i); }

A. 1 ✓

B. 11

C. 12

D. Error

Answer: Option A — 1

Q24. Determine Output: void main() { struct xx { int x=3; char name[] = "hello"; }; struct xx *s = malloc(sizeof(struct xx)); printf("%d", s->x); printf("%s", s->name); }

A. 3 hello

B. Compiler Error ✓

C. Linking error

D. None of these

Answer: Option B — Compiler Error

Q25. Determine output: void main() { extern int i; i=20; printf("%d", sizeof(i)); }

A. 20

B. 2

C. Compiler Error

D. Linker Error ✓

Answer: Option D — Linker Error

Q26. Determine Output: void main() { int i=0, j=0; if(i && j++) printf("%d..%d", i++, j); printf("%d..%d", i, j); }

A. 0..1

B. 1..0

C. 0..0 ✓

D. 1..1

Answer: Option C — 0..0

Q27. Determine Output: void main() { static int i=5; if(--i){ main(); printf("%d ", i); } }

A. 5 4 3 2 1

B. 0 0 0 0 ✓

C. Infinite Loop

D. None of These

Answer: Option B — 0 0 0 0

Q28. Determine Output: void main() { int i=-1, j=-1, k=0, l=2, m; m = i++ && j++ && k++ || l++; printf("%d %d %d %d %d", i, j, k, l, m); }

A. 0 0 1 2 0

B. 0 0 1 3 0

C. 0 0 1 3 1 ✓

D. 0 0 0 2 1

Answer: Option C — 0 0 1 3 1

Q29. Determine Output: void main() { int i = -1; +i; printf("i = %d, +i = %d", i, +i); }

A. i = -1, +i = 1

B. i = 1, +i = 1

C. i = -1, +i = -1 ✓

D. None of These

Answer: Option C — i = -1, +i = -1

Q30. Determine Output: void main() { char *str1 = "abcd"; char str2[] = "abcd"; printf("%d %d %d", sizeof(str1), sizeof(str2), sizeof("abcd")); }

A. 2 5 5 ✓

B. 5 5 5

C. 2 4 5

D. 2 4 4

Answer: Option A — 2 5 5

Q31. Determine Output: void main() { char not; not = !2; printf("%d", not); }

A. 2

B. Garbage Value

C. 0 ✓

D. None of These

Answer: Option C — 0

Q32. Determine Output: #include<stdio.h> void main() { register i=5; char j[]= "hello"; printf("%s %d", j, i); }

A. hello 5 ✓

B. hello garbage value

C. Error

D. None of These

Answer: Option A — hello 5

Q33. Determine Output: void main() { int i=5, j=6, z; printf("%d", i+++j); }

A. 12

B. 13

C. 11 ✓

D. None of These

Answer: Option C — 11

Q34. Determine Output: void main() { int i = abc(10); printf("%d", --i); } int abc(int i) { return(i++); }

A. 10

B. 9 ✓

C. 11

D. None of These

Answer: Option B — 9

Q35. Determine Output: void main() { char a[]="12345"; int i = strlen(a); printf("%d", ++i); }

A. 5

B. 6 ✓

C. 7

D. None of These

Answer: Option B — 6

Q36. Determine Output: void main() { int i; char a[]="■"; if(printf("%sn", a)) printf("Ok here n"); else printf("Forget itn"); }

A. Ok here ✓

B. Forget it

C. Error

D. None of These

Answer: Option A — Ok here

Q37. Determine Output: void main() { int i=i++, j=j++, k=k++; printf("%d %d %d", i, j, k); }

A. 1 1 1

B. 0 0 0

C. garbage values ✓

D. Error

Answer: Option C — garbage values

Q38. Determine Output: void main() { static int i=i++, j=j++, k=k++; printf("%d %d %d", i, j, k); }

A. 1 1 1 ✓

B. 0 0 0

C. garbage values

D. Error

Answer: Option A — 1 1 1

Q39. Determine Output: #define prod(a,b) a*b void main() { int x=3, y=4; printf("%d", prod(x+2, y-1)); }

A. 15

B. 10 ✓

C. 12

D. 11

Answer: Option B — 10

Q40. Determine Output: void main() { char p[]="%dn"; p[1] = 'c'; printf(p, 65); }

A. 65

B. c

C. A ✓

D. Error

Answer: Option C — A

Q41. Determine Output: void main() { char *p; p="%d\n"; p++; p++; printf(p-2, 300); }

A. %d\n

B. 300 ✓

C. Error

D. None of These

Answer: Option B — 300

Q42. Determine Output: void main() { int c[] = {2.8,3.4,4,6.7,5}; int j, *p=c, *q=c; for(j=0;j<5;j++){ printf(" %d ", *c); ++q; } for(j=0;j<5;j++){ printf(" %d ", *p); ++p; } }

A. 2 3 4 6 5 2 3 4 6 5

B. 2.8 3.4 4 6.7 5 2.8 3.4 4 6.7

C. 2.8 2.8 2.8 2.8 2.8 2.8 3.4 4

D. 2 2 2 2 2 2 3 4 6 5 ✓

Answer: Option D — 2 2 2 2 2 2 3 4 6 5

Q43. Determine Output: void main() { int a[] = {10,20,30,40,50}, j, *p; for(j=0; j<5; j++){ printf("%d" ,*a); a++; } p = a; for(j=0; j<5; j++){ printf("%d" ,*p); p++; } }

A. 10 20 30 40 50 10 20 30 40 50

B. 10 20 30 40 50 Garbage Value

C. Error ✓

D. None of These

Answer: Option C — Error

Q44. Determine Output: #include<stdio.h> void main() { char s[]={'a','b','c','n','c','\0'}; char *p, *str, *str1; p=&s[3]; str=p; str1=s; printf("%c", ++*p + ++*str1-32); }

A. N

B. P

C. M ✓

D. None of These

Answer: Option C — M

Q45. Determine Output: void main() { static char *s[] = {"black", "white", "yellow", "violet"}; char **ptr[] = {s+3, s+2, s+1, s}, ***p; p = ptr; ++p; printf("%s",*--*++p + 3); }

A. te

B. ow

C. et

D. ck ✓

Answer: Option D — ck

Q46. What will be the output of the following C code? #include<stdio.h> main() { int n; n=f1(4); printf("%d",n); } f1(int x) { int b; if(x==1) return 1; else b=x*f1(x-1); return b; }

A. 24 ✓

B. 4

C. 12

D. 10

Answer: Option A — 24

Q47. In the absence of a exit condition in a recursive function, the following error is given . . . . . .

A. Compile time error

B. Run time error ✓

C. Logical error

D. No error

Answer: Option B — Run time error

Q48. What is the output of this C code? #include <stdio.h> main() { if (sizeof(int) > -1) printf("True"); else printf("False"); }

A. True

B. False ✓

Answer: Option B — False

Q49. What will be the value of the following assignment expression? (x = foo())!= 1 considering foo() returns 2

A. 2 ✓

B. True

C. 1

D. 0

Answer: Option A — 2

Q50. Suppose we have: int a=100; (signed by default). If we want to convert this to an unsigned long integer, we can do this by making the following small change:

A. int a=lu100;

B. int a= 100ul; ✓

C. int a=uu100;

D. int a=100uu;

Answer: Option B — int a= 100ul;

Q51. Suppose we transfer a file written on a little endian machine to a big endian machine and there is no transformation from little endian to big endian, then what happens?

A. The big endian machine throws an error when it receives the file

B. The big endian machine reads the file in the reverse order ✓

C. The big endian machine does not read the file

D. The big endian machine reads the file in the normal order

Answer: Option B — The big endian machine reads the file in the reverse order

Q52. File formats which have . . . . . as a basic unit are independent of endianness.

A. 1 byte ✓

B. 2 bytes

C. 3 bytes

D. 4 bytes

Answer: Option A — 1 byte

Q53. What will be the output of the following C code? #include<stdio.h> static inline int max(int a, int b) { return a > b ? a : b; } main() { int m; m=max(-6,-5); printf("%d",m); }

A. -6

B. -5 ✓

C. Junk value

D. Error

Answer: Option B — -5

Q54. Sign qualifiers can be applied to double.

A. True

B. False ✓

Answer: Option B — False

Q55. What is the output of this C code? #include <stdio.h> main() { char *p = "Examveda C-Test"; p[0] = 'a'; p[1] = 'b'; printf("%s", p); }

A. abmveda C-Test

B. Examveda C-Test

C. Compile time error

D. Run time error ✓

Answer: Option D — Run time error

Q56. The following C code results in an error. State whether this statement is true or false. #include <stdio.h> void f(double b) { printf ("%ld\n",b); } int main() { inline f(100.56); return 0; }

A. True ✓

B. False

Answer: Option A — True

Q57. What will be the output of the following C code? main() { unsigned a=10; long unsigned b=5l; printf("%lu%u",a,b); }

A. 105 ✓

B. 510

C. 10

D. error

Answer: Option A — 105

Q58. What is the binary representation of the integer -14?

A. 11110 ✓

B. 01110

C. 01100

D. 11100

Answer: Option A — 11110

Q59. Functions in C Language are always . . . . . .

A. Internal

B. External ✓

C. Both Internal and External

D. External and Internal are not valid terms for functions

Answer: Option B — External

Q60. What will be the error in the following C code? main() { long float a=-25.373e22; printf("%lf",a); }

A. Negative number cannot be assigned to float data type

B. Long and float cannot be used together ✓

C. Does not result in error

D. Logical error

Answer: Option B — Long and float cannot be used together

Q61. What will be the output of the following C code if the input given to the code shown below is "examveda"? #include<stdio.h> #define NL '\n' void main() { void f(void); printf("enter the word\n"); f(); } void f(void) { char c; if((c=getchar())!=NL) { f(); printf("%c",c); } return; }

A. examveda

B. infinite loop

C. adevmaxe ✓

D. maxeadev

Answer: Option C — adevmaxe

Q62. A machine in which the least significant byte is stored in the smallest address is . . . . . .

A. Big endian machine

B. Bi-endian machine

C. Binary bit machine

D. Little endian machine ✓

Answer: Option D — Little endian machine

Q63. What is the difference between the following 2 C codes? #include <stdio.h> //Program 1 int main() { int d, a = 1, b = 2; d = a++ + ++b; printf("%d %d %d", d, a, b); } #include <stdio.h> //Program 2 int main() { int d, a = 1, b = 2; d = a++ +++b; printf("%d %d %d", d, a, b); }

A. No difference as space doesn't make any difference, values of a, b, d are same in both the case

B. Space does make a difference, values of a, b, d are different

C. Program 1 has syntax error, program 2 is not

D. Program 2 has syntax error, program 1 is not ✓

Answer: Option D — Program 2 has syntax error, program 1 is not

Q64. What will be the output of the following C code? #include<stdio.h> extern inline int min(int a, int b) { return a < b ? a : b; } main() { int m; m=min(3,-5); printf("%d",m); }

A. Error ✓

B. 3

C. -5

D. Junk value

Answer: Option A — Error

Q65. What will be the output of the following C code? #include<stdio.h> int main() { signed char ch= ‘a’; printf(“%u”,ch); return 0; }

A. -65

B. 65

C. -97

D. 97 ✓

Answer: Option D — 97

Q66. What will be the output of the following C code? #include <stdio.h> void inline func1(char b[10]) { printf ("%c\n",b[2]); } int main() { func1("examveda"); return 0; }

A. e

B. a ✓

C. x

D. error

Answer: Option B — a

Q67. Which of the following declaration is not supported by C language?

A. String str; ✓

B. char *str;

C. float str = 3e2;

D. Both "String str;" and "float str = 3e2;"

Answer: Option A — String str;

Q68. What will be the output of the following C code? #include<stdio.h> int main() { int n=10; int f(int n); printf("%d",f(n)); } int f(int n) { if(n>0) return(n+f(n-2)); }

A. 10

B. 80

C. 30 ✓

D. Error

Answer: Option C — 30

Q69. Iteration requires more system memory than recursion.

A. True

B. False ✓

Answer: Option B — False

Q70. What will be the output of the following C code? #include<stdio.h> int main() { printf("Hello"); main(); return 0; }

A. Hello is printed once

B. Hello infinite number of times ✓

C. Hello is not printed at all

D. 0 is returned

Answer: Option B — Hello infinite number of times

Q71. Comment on the following C statement. n = 1; printf("%d, %dn", 3*n, n++);

A. Output will be 3, 2

B. Output will be 3, 1

C. Output will be 6, 1

D. Output is compiler dependent ✓

Answer: Option D — Output is compiler dependent

Q72. What will be the output of the following C code? #include<stdio.h> main() { signed char a[]= “BAT”; printf(“%c”, a[1]); return 0; }

A. -A

B. BAT

C. A ✓

D. 65

Answer: Option C — A

Q73. What will be the output of the following C code? #include <stdio.h> void inline func1(int a, int b) { printf ("a=%d and b=%d\n", a, b); } int inline func2(int x) { return x*x; } int main() { int tmp; func1(1,4); tmp = func2(6); printf("square val=%d\n", tmp); return 0; }

A. a=1 and b=4 square val = 36 ✓

B. a=4 and b=1

C. error

D. square val = 36

Answer: Option A — a=1 and b=4 square val = 36

Q74. The principle of stack is . . . . . .

A. First in first out

B. First in last out

C. Last in first out ✓

D. Last in last out

Answer: Option C — Last in first out

Q75. Which of the following header files must necessarily be included in your code, if you want to find the minimum value of unsigned short integer?

A. stdio.h

B. stdlib.h

C. limits.h ✓

D. math.h

Answer: Option C — limits.h

Q76. How many times is 'a' printed when the following C code is executed? #include<stdio.h> main() { int a; a=f1(10); printf("%d",a); } f1(int b) { if(b==0) return 0; else { printf("a"); f1(b--); } }

A. 9 times

B. 10 times

C. 0 times

D. Infinite number of times ✓

Answer: Option D — Infinite number of times

Q77. In a signed integer, the sign is represented by . . . . . .

A. Least significant bit

B. Most significant bit ✓

C. System dependent

D. The mean of the most significant bit and the least significant bit

Answer: Option B — Most significant bit

Q78. What is the default state of an integer in c language?

A. Signed ✓

B. Unsigned

C. System dependent

D. There is no default state

Answer: Option A — Signed

Q79. Comment on the output of following C code. #include <stdio.h> main() { char *p = 0; *p = 'a'; printf("value in pointer p is %c\n", *p); }

A. It will print a

B. It will print 0

C. Compile time error

D. Run time error ✓

Answer: Option D — Run time error

Q80. What will be the output of the following C code? #include <stdio.h> void inline f1(char b) { printf ("%d\n",b); } int main() { f1('a'); return 0; }

A. a

B. 65

C. error

D. 97 ✓

Answer: Option D — 97

Q81. If the code shown below is executed on a little endian machine, then what will be the output of the following C code? #include<stdio.h> main() { int y=1; printf("%d", (*(char*)&y)); }

A. 1 ✓

B. 1000

C. 9999

D. 0

Answer: Option A — 1

Q82. Which of the following is not possible statically in C language?

A. Jagged Array ✓

B. Rectangular Array

C. Cuboidal Array

D. Multidimensional Array

Answer: Option A — Jagged Array

Q83. Name the function whose definition can be substituted at a place where its function call is made . . . . . .

A. friends function

B. inline function ✓

C. volatile function

D. external function

Answer: Option B — inline function

Q84. If the output of the following C code is "Big endian", then what will be the value of *a is? #include <stdio.h> int main() { unsigned int i = 1; char *a = (char*)&i; if (*a) printf("Little endian"); else printf("Big endian"); getchar(); return 0; }

A. -1

B. 0 ✓

C. 1

D. 2

Answer: Option B — 0

Q85. To have GCC inline the given function regardless of the level of optimization, we must declare the function with the attribute . . . . . .

A. optimize_inline

B. packed_inline ✓

C. always_inline

D. level_inline

Answer: Option B — packed_inline

Q86. It is possible for a processor to support both little and big endian methods.

A. True ✓

B. False

Answer: Option A — True

Q87. If the data "ABCD" is to be stored in a little endian machine, it will be stored as . . . . . .

A. ABCD

B. DCBA ✓

C. CDAB

D. BCDA

Answer: Option B — DCBA

Q88. What will be the output of the following C code? #include<stdio.h> main() { int n,i; n=f(6); printf("%d",n); } f(int x) { if(x==2) return 2; else { printf("+"); f(x-1); } }

A. ++++2 ✓

B. +++++2

C. +++++

D. 2

Answer: Option A — ++++2

Q89. What will be the output of the following C code? #include<stdio.h> #define inline inline f(char a) { #ifdef inline printf("%c",a); #endif } main() { f('a'); }

A. Error

B. a ✓

C. No error but nothing will be printed as output

D. 97

Answer: Option B — a

Q90. The standard byte order for networks is . . . . . .

A. Bit-Binary

B. Little endian

C. Big endian ✓

D. Bi-endian

Answer: Option C — Big endian

Q91. The sequential order used to interpret a range of bytes in the memory of a computer is known as . . . . . .

A. Ordering

B. Sequencing

C. Endianness ✓

D. Byte prediction

Answer: Option C — Endianness

Q92. The data structure used to implement recursive function calls . . . . . .

A. Array

B. Linked list

C. Binary tree

D. Stack ✓

Answer: Option D — Stack

Q93. What will be the error (if any) in the following C code? #include <stdio.h> void inline func1(float b) { printf ("%lf\n",b*2); } int main() { inline func1(2.2); return 0; }

A. No error

B. Error in statement: void inline func1(float b)

C. Error in statement: printf("%lf\n",b*2);

D. Error in statement: inline func1(2.2); ✓

Answer: Option D — Error in statement: inline func1(2.2);

Q94. What is the output of this C code? #include <stdio.h> main() { int n = 0, m = 0; if (n > 0) if (m > 0) printf("True"); else printf("False"); }

A. True

B. False

C. No Output will be printed ✓

D. Run Time Error

Answer: Option C — No Output will be printed

Q95. What will be the output of the following C code on a 64 bit machine? #include <stdio.h> union Sti { int nu; char m; }; int main() { union Sti s; printf("%d", sizeof(s)); return 0; }

A. 8

B. 5

C. 9

D. 4 ✓

Answer: Option D — 4

Q96. What is the output of this C code? #include <stdio.h> int main() { float f = 0.1; if (f == 0.1) printf("True"); else printf("False"); }

A. True

B. False ✓

Answer: Option B — False

Q97. Which of the following typecasting is accepted by C language?

A. Widening conversions

B. Narrowing conversions

C. Widening & Narrowing conversions ✓

D. None of the mentioned

Answer: Option C — Widening & Narrowing conversions

Q98. Which of the following is not an example of big endian machines?

A. Power PC

B. Motorola 68K

C. SPARC processors

D. ARM processors ✓

Answer: Option D — ARM processors

Q99. How many times i value is checked in the following C program? #include <stdio.h> int main() { int i = 0; while (i < 3) i++; printf("In while loop\n"); }

A. 2

B. 3

C. 4 ✓

D. 1

Answer: Option C — 4

Q100. Who is the father of C language?

A. Steve Jobs

B. James Gosling

C. Dennis Ritchie ✓

D. Rasmus Lerdorf

Answer: Option C — Dennis Ritchie

C Fundamentals

Q101. What is the primary purpose of a function prototype in C?

A. Declare a variable

B. Declare a function ✓

C. Define a function

D. Assign a value

Answer: Option B — Declare a function

Q102. Which character is used to indicate the end of a statement in C?

A. .

B. ; ✓

C. :

D. ,

Answer: Option B — ;

Q103. Which data type is used to represent a single character in C?

A. char ✓

B. int

C. float

D. double

Answer: Option A — char

Q104. What is the correct syntax for declaring a variable in C?

A. int variable_name; ✓

B. variable_name = 5;

C. variable_name int;

D. int = variable_name;

Answer: Option A — int variable_name;

Q105. Which symbol is used for the 'modulo' operation in C?

A. % ✓

B. /

C. *

D. ^

Answer: Option A — %

Q106. What is the default return type of a function in C if not specified?

A. int ✓

B. void

C. char

D. float

Answer: Option A — int

Q107. Which operator is used for 'logical AND' in C?

A. && ✓

B. ||

C. &

D. |

Answer: Option A — &&

Q108. What is the purpose of the 'sizeof' operator in C?

A. Calculate square root

B. Determine size ✓

C. Perform division

D. Convert to string

Answer: Option B — Determine size

Q109. In C, which type of variable should be used to store decimal numbers?

A. char

B. int

C. float ✓

D. double

Answer: Option C — float

Q110. Which header file should be included for input and output functions in C?

A. <stdlib.h>

B. <stdio.h> ✓

C. <math.h>

D. <string.h>

Answer: Option B — <stdio.h>

Q111. What is the purpose of the 'break' statement in C?

A. End the program

B. Skip the loop

C. Exit a function

D. Exit a loop ✓

Answer: Option D — Exit a loop

Q112. Which of the following is not a valid C keyword?

A. main

B. if

C. printf ✓

D. for

Answer: Option C — printf

Q113. What is the maximum number of arguments that can be passed to a C function?

A. 10

B. 255

C. 127

D. No limit ✓

Answer: Option D — No limit

Q114. Which operator is used to access the value stored at a pointer address in C?

A. * ✓

B. &

C. ->

D. .

Answer: Option A — *

Q115. What does the 'void' keyword indicate in a C function declaration?

A. Empty return type ✓

B. Integer return

C. Floating-point return

D. String return

Answer: Option A — Empty return type

Q116. Which character is used to represent a comment in C code?

A. #

B. // ✓

C. /*

D. ;

Answer: Option B — //

Q117. What is the purpose of the 'continue' statement in a loop?

A. Skip the loop

B. Exit the program

C. Skip the current iteration ✓

D. Exit the loop

Answer: Option C — Skip the current iteration

Q118. What is the range of values that can be stored in an 'int' data type in C?

A. -32768 to 32767

B. -2147483648 to 2147483647 ✓

C. 0 to 65535

D. 0 to 4294967295

Answer: Option B — -2147483648 to 2147483647

Q119. Which operator is used to compare two values for equality in C?

A. == ✓

B. =

C. !=

D. <>

Answer: Option A — ==

Q120. What is the purpose of the 'const' keyword in C?

A. Declare a constant ✓

B. Declare a variable

C. Define a function

D. Initialize a pointer

Answer: Option A — Declare a constant

Q121. Which data type is used to store a sequence of characters in C?

A. char ✓

B. int

C. float

D. string

Answer: Option A — char

Q122. In C, which operator is used for pointer-to-pointer relationships?

A. * ✓

B. &

C. ->

D. ::

Answer: Option A — *

Q123. What is the purpose of the 'sizeof' operator in C?

A. Get the size of a variable ✓

B. Get the address of a variable

C. Perform arithmetic operations

D. Calculate square root

Answer: Option A — Get the size of a variable

Q124. What does the 'NULL' keyword represent in C?

A. An empty string

B. A null character

C. A pointer to nothing ✓

D. An uninitialized variable

Answer: Option C — A pointer to nothing

Q125. Which library function is used to allocate memory dynamically in C?

A. malloc ✓

B. free

C. sizeof

D. realloc

Answer: Option A — malloc

Q126. What is the purpose of the 'scanf' function in C?

A. Print formatted output

B. Read formatted input ✓

C. Allocate memory

D. Execute a loop

Answer: Option B — Read formatted input

Q127. Which operator is used to access the value stored at a pointer address in C?

A. * ✓

B. &

C. ->

D. .

Answer: Option A — *

Q128. What is the purpose of the 'goto' statement in C?

A. End the program

B. Skip a loop

C. Transfer control ✓

D. Skip the current iteration

Answer: Option C — Transfer control

Q129. Which header file is used for mathematical functions in C?

A. <stdlib.h>

B. <stdio.h>

C. <math.h> ✓

D. <string.h>

Answer: Option C — <math.h>

Q130. What is the significance of the 'volatile' keyword in C?

A. Declare a constant

B. Indicate a volatile variable ✓

C. Allocate memory

D. Skip the current iteration

Answer: Option B — Indicate a volatile variable

Q131. Who is father of C Language?

A. Bjarne Stroustrup

B. James A. Gosling

C. Dennis Ritchie ✓

D. Dr. E.F. Codd

Answer: Option C — Dennis Ritchie

Q132. C Language developed at _____?

A. AT & T's Bell Laboratories of USA in 1972 ✓

B. AT & T's Bell Laboratories of USA in 1970

C. Sun Microsystems in 1973

D. Cambridge University in 1972

Answer: Option A — AT & T's Bell Laboratories of USA in 1972

Q133. For 16-bit compiler allowable range for integer constants is _____?

A. -3.4e38 to 3.4e38

B. -32767 to 32768

C. -32668 to 32667

D. -32768 to 32767 ✓

Answer: Option D — -32768 to 32767

Q134. C programs are converted into machine language with the help of

A. An Editor

B. A compiler ✓

C. An operating system

D. None of these.

Answer: Option B — A compiler

Q135. C was primarily developed as

A. System programming language ✓

B. General purpose language

C. Data processing language

D. None of the above.

Answer: Option A — System programming language

Q136. Standard ANSI C recognizes _____ number of keywords?

A. 30

B. 32 ✓

C. 24

D. 36

E. 40

Answer: Option B — 32

Q137. Which one of the following is not a reserved keyword for C?

A. auto

B. case

C. main ✓

D. default

E. register

Answer: Option C — main

Q138. A C variable cannot start with

A. A number

B. A special symbol other than underscore

C. Both of the above ✓

D. An alphabet

Answer: Option C — Both of the above

Q139. Which one of the following is not a valid identifier?

A. _examveda

B. 1examveda ✓

C. exam_veda

D. examveda1

Answer: Option B — 1examveda

Q140. What will be printed after execution of the following program code? main() { printf("\\nab"); printf("\\bsi"); printf("\\rha"); }

A. absiha

B. asiha

C. haasi

D. hai ✓

E. None of these

Answer: Option D — hai

Q141. If integer needs two bytes of storage, then maximum value of an unsigned integer is

A. 2 ^{16} – 1 ✓

B. 2 ^{15} – 1

C. 2 ^{16}

D. 2 ^{15}

E. None of these

Answer: Option A — 2 ^{16} – 1

Q142. What is the correct value to return to the operating system upon the successful completion of a program?

A. 1

B. -1

C. 0 ✓

D. Program do no return a value.

E. 2

Answer: Option C — 0

Q143. Which is the only function all C programs must contain?

A. start()

B. system()

C. main() ✓

D. printf()

E. getch()

Answer: Option C — main()

Q144. Which of the following is not a correct variable type?

A. float

B. real ✓

C. int

D. double

E. char

Answer: Option B — real

Q145. What number would be shown on the screen after the following statements of C are executed? char ch; int i; ch = 'G'; i = ch-'A'; printf("%d", i);

A. 5

B. 6 ✓

C. 7

D. 8

E. 9

Answer: Option B — 6

Q146. Which of following is not a valid name for a C variable?

A. Examveda

B. Exam_veda

C. Exam veda ✓

D. Both A and B

E. None of these

Answer: Option C — Exam veda

Q147. Find the output of the following program. void main () { int i=01289; printf (" %d ", i) ; }

A. 0289

B. 1289

C. 713

D. 0713

E. Syntax error ✓

Answer: Option E — Syntax error

Q148. Find the output of the following program. void main() { int i=065, j=65; printf("%d %d", i, j); }

A. 53 65 ✓
B. 65 65
C. 065 65
D. 053 65
E. Syntax error
Answer: Option A — 53 65

Q149. If ASCII value of 'x' is 120, then what is the value of the H, if H = ('x' – 'w') / 3;

A. 1
B. 2
C. 3
D. 4
E. 0 ✓
Answer: Option E — 0

Q150. What is the difference between a declaration and a definition of a variable?

A. Both can occur multiple times, but a declaration must occur first.
B. A definition occurs once, but a declaration may occur many times.
C. Both can occur multiple times, but a definition must occur first.
D. A declaration occurs once, but a definition may occur many times. ✓
E. There is no difference between them.
Answer: Option D — A declaration occurs once, but a definition may occur many times.

Q151. "My salary was increased by 15%" Select the statement, which will EXACTLY reproduce the line of text above.

A. printf("My salary was increased by 15/%!");
B. printf("My salary was increased by 15%!");
C. printf("My salary was increased by 15'%'!");
D. printf("My salary was increased by 15%%!"); ✓
Answer: Option D — printf("My salary was increased by 15%%!");

Q152. short testarray[4][3] = { {1}, {2,3}, {4,5,6}}; printf("%d", sizeof(testarray)); Assuming a short is two bytes long, what will be printed by the above code?

A. 6
B. 7
C. 12
D. 24 ✓
E. It will not compile because not enough initializers are given
Answer: Option D — 24

Q153. What will be the output of the following C code? #include <stdio.h> void main() { int x = 97; char y = x; printf("%c\n", y); }

A. a ✓
B. b
C. 97

D. Run time error

Answer: Option A — a

Q154. Will the following C code compile without any error? #include <stdio.h> int main() { for (int k = 0; k < 10; k++); return 0; }

A. Yes

B. No

C. Depends on the C standard implemented by compilers ✓

D. Error

Answer: Option C — Depends on the C standard implemented by compilers

Q155. Variable name resolution (number of significant characters for the uniqueness of variable) depends on . . . . . .

A. Compiler and linker implementations ✓

B. Assemblers and loaders implementations

C. C language

D. None of the mentioned

Answer: Option A — Compiler and linker implementations

Q156. What will be the final values of a and c in the following C statement? (Initial values: a = 2, c = 1) c = (c) ? a = 0 : 2;

A. a = 0, c = 0; ✓

B. a = 2, c = 1;

C. a = 2, c = 2;

D. a = 1, c = 2;

Answer: Option A — a = 0, c = 0;

Q157. What will be the output of the following C code? #include <stdio.h> int main() { unsigned int a = 10; a = ~a; printf("%d\n", a); }

A. -9

B. -10

C. -11 ✓

D. 10

Answer: Option C — -11

Q158. What will be the output of the following C code? #include <stdio.h> int main() { int a = 1, b = 2; a += b -= a; printf("%d %d", a, b); }

A. 1 1

B. 1 2

C. 2 1 ✓

D. 2 2

Answer: Option C — 2 1

Q159. What will be the output of the following C code? #include <stdio.h> void main() { int x = 1, y = 0, z = 5; int a = x && y || z++; printf("%d", z); }

A. 6 ✓

B. 5

C. 0

D. Varies

Answer: Option A — 6

Q160. What will be the output of the following C code? #include <stdio.h> int main() { int a = 1, b = 1, d = 1; printf("%d, %d, %d", ++a + ++a+a++, a++ + ++b, ++d + d++ + a++); }

A. 15, 4, 5

B. 9, 6, 9

C. 9, 3, 5

D. Undefined (Compiler Dependent) ✓

Answer: Option D — Undefined (Compiler Dependent)

Q161. What will be the output of the following C code? #include <stdio.h> int main() { int i = 2; int j = ++i + i; printf("%d\n", j); }

A. 6 ✓

B. 5

C. 4

D. Compile time error

Answer: Option A — 6

Q162. What will be the final value of j in the following C code? #include <stdio.h> int main() { int i = 10, j = 0; if (i || (j = i + 10)) //do something ; }

A. 0 ✓

B. 20

C. Compile time error

D. Depends on language standard

Answer: Option A — 0

Q163. What will be the output of the following C function? #include <stdio.h> enum birds {SPARROW, PEACOCK, PARROT}; enum animals {TIGER = 8, LION, RABBIT, ZEBRA}; int main() { enum birds m = TIGER; int k; k = m; printf("%d\n", k); return 0; }

A. 0

B. Compile time error

C. 1

D. 8 ✓

Answer: Option D — 8

Q164. What is the size of an int data type?

A. 4 Bytes

B. 8 Bytes

C. Depends on the system/compiler ✓

D. Cannot be determined

Answer: Option C — Depends on the system/compiler

Q165. What will be the output of the following C code? #include <stdio.h> void main() { int k = 8; int m = 7; int z = k < m ? k++ : m++; printf("%d", z); }

A. 7 ✓

B. 8

C. Run time error

D. 15

Answer: Option A — 7

Q166. Pick the incorrect statement with respect to enums.

A. Two enum symbols cannot have the same value ✓

B. Only integer constants are allowed in enums

C. It is not possible to change the value of enum symbols

D. Enum variables are automatically assigned values if no value is specified

Answer: Option A — Two enum symbols cannot have the same value

Q167. What will be the output of the following C code? #include <stdio.h> int main() { int x = 2, y = 0; int z; z = (y++, y); printf("%d\n", z); return 0; }

A. 0

B. 1 ✓

C. Undefined behaviour

D. Compilation error

Answer: Option B — 1

Q168. What will be the output of the following C code? #include <stdio.h> int main() { int x = 1, y = 0; x &&= y; printf("%d\n", x); }

A. Compile time error ✓

B. 1

C. 0

D. Undefined behaviour

Answer: Option A — Compile time error

Q169. What will be the output of the following C code? #include <stdio.h> void main() { int a = 5 * 3 % 6 - 8 + 3; printf("%d", a); }

A. 10

B. 2

C. -2 ✓

D. -3

Answer: Option C — -2

Q170. What will be the output of the following C code? #include <stdio.h> void main() { float x = 0.1; if (x == 0.1) printf("India"); else printf("Advanced C Classes"); }

A. Advanced C Classes ✓

B. India

C. Run time error

D. Compile time error

Answer: Option A — Advanced C Classes

Q171. What will be the final value of j in the following C code? #include <stdio.h> int main() { int i = 0, j = 0; if (i && (j = i + 10)) //do something ; }

A. 0 ✓

B. 10

C. Depends on the compiler

D. Depends on language standard

Answer: Option A — 0

Q172. Will the following C code compile without any error? #include <stdio.h> int main() { int k; { int k; for (k = 0; k < 10; k++); } }

A. Yes ✓

B. No

C. Depends on the compiler

D. Depends on the C standard implemented by compilers

Answer: Option A — Yes

Q173. What will be the output of the following C code? #include <stdio.h> int main() { int x = 0, y = 2; int z = ~x & y; printf("%d\n", z); }

A. -1

B. 2 ✓

C. 0

D. Compile time error

Answer: Option B — 2

Q174. What will be the output of the following C code? #include <stdio.h> int main() { int a = 4, n, i, result = 0; scanf("%d", &n); for (i = 0;i < n; i++) result += a; }

A. Addition of a and n

B. Subtraction of a and n

C. Multiplication of a and n ✓

D. Division of a and n

Answer: Option C — Multiplication of a and n

Q175. What will be the output of the following C code? #include<stdio.h> enum hello { a,b=99,c,d=-1 }; main() { enum hello m; printf("%d\n%d\n%d\n%d\n",a,b,c,d); }

A. 1 99 100 -1

B. Error

C. 0 99 100 -1 ✓

D. 0 1 2 3

Answer: Option C — 0 99 100 -1

Q176. What will be the output of the following C code? #include <stdio.h> int main() { j = 10; printf("%d\n", j++); return 0; }

A. 10

B. 11

C. Compile time error ✓

D. 0

Answer: Option C — Compile time error

Q177. What will be the output of the following C code? #include <stdio.h> #define MAX 2 enum bird {SPARROW = MAX + 1, PARROT = SPARROW + MAX}; int main() { enum bird b = PARROT; printf("%d\n", b); return 0; }

A. Compilation error

B. 5 ✓

C. Undefined value

D. 2

Answer: Option B — 5

Q178. What will be the output of the following C code? #include<stdio.h> enum shyam { a=2,b=3.56 }; enum shyam s; main() { printf("%d%d",a,b); }

A. 2 3

B. 0 1

C. 2 3.56

D. Error ✓

Answer: Option D — Error

Q179. What will be the output of the following C code? #include <stdio.h> int main() { int a[5] = {1, 2, 3, 4, 5}; int i; for (i = 0; i < 5; i++) if ((char)a[i] == '5') printf("%d\n", a[i]); else printf("FAIL\n"); }

A. The compiler will flag an error

B. The program will compile and print the output 5

C. The program will compile and print the ASCII value of 5

D. The program will compile and print FAIL for 5 times ✓

Answer: Option D — The program will compile and print FAIL for 5 times

Q180. One of the major difference between typedef and #define is that typedef interpretation is performed by the . . . . . whereas #define interpretation is performed by the . . . . . .

A. pre-processor, compiler

B. user, pre-processor

C. compiler, pre-processor ✓

D. compiler, user

Answer: Option C — compiler, pre-processor

Q181. Which of the following typecasting is accepted by C?

A. Widening conversions

B. Narrowing conversions

C. Widening & Narrowing conversions ✓

D. None of the mentioned

Answer: Option C — Widening & Narrowing conversions

Q182. Which of the following is a ternary operator?

A. &&

B. >>=

C. ?: ✓

D. ->

Answer: Option C — ?:

Q183. What will be the output of the following C code? #include <stdio.h> int main() { int a = 2; if (a >> 1) printf("%d\n", a); }

A. 0

B. 1

C. 2 ✓

D. No Output

Answer: Option C — 2

Q184. What will be the output of the following C code? #include <stdio.h> int const print() { printf("example.com"); return 0; } void main() { print(); }

A. Error because function name cannot be preceded by const

B. example.com ✓

C. example.com is printed infinite times

D. Blank screen, no output

Answer: Option B — example.com

Q185. What will be the output of the following C code? #include <stdio.h> void main() { double b = 3 && 5 & 4 % 3; printf("%lf", b); }

A. 3.000000

B. 4.000000

C. 5.000000

D. 1.000000 ✓

Answer: Option D — 1.000000

Q186. Operation "a = a * b + a" can also be written as . . . . . .

A. a *= b + 1;

B. (c = a * b)!=(a = c + a);

C. a = (b + 1)* a;

D. All of the mentioned ✓

Answer: Option D — All of the mentioned

Q187. Which of the following is an invalid assignment operator?

A. a %= 10;

B. a /= 10;

C. a |= 10;

D. None of the mentioned ✓

Answer: Option D — None of the mentioned

Q188. Which of the following are unary operators?

A. sizeof

B. -

C. ++

D. all of the mentioned ✓

Answer: Option D — all of the mentioned

Q189. Which of the following data type will throw an error on modulus operation(%)?

A. char

B. short

C. int

D. float ✓

Answer: Option D — float

Q190. What will be the output of the following C code? #include <stdio.h> void main() { int x = 0, y = 2, z = 3; int a = x & y | z; printf("%d", a); }

A. 3 ✓

B. 0

C. 2

D. Run time error

Answer: Option A — 3

Q191. What will be the output of the following C code? #include <stdio.h> int main() { int y = 2; int z = y +(y = 10); printf("%d\n", z); }

A. 12

B. 20 ✓

C. 4

D. Either 12 or 20

Answer: Option B — 20

Q192. What will be the output of the following C code? #include <stdio.h> #define a 10 int main() { const int a = 5; printf("a = %d\n", a); }

A. a = 5

B. a = 10

C. Compilation error ✓

D. Runtime error

Answer: Option C — Compilation error

Q193. What will be the output of the following C function? #include <stdio.h> void reverse(int i); int main() { reverse(1); } void reverse(int i) { if (i > 5) return ; printf("%d ", i); return reverse((i++, i)); }

A. 1 2 3 4 5 ✓

B. Segmentation fault

C. Compilation error

D. Undefined behaviour

Answer: Option A — 1 2 3 4 5

Q194. For which of the following, "PI++;" code will fail?

A. #define PI 3.14 ✓

B. char *PI = "A";

C. float PI = 3.14;

D. none of the Mentioned

Answer: Option A — #define PI 3.14

Q195. We want to declare x, y and z as pointers of type int. The alias name given is: intpt The correct way to do this using the keyword typedef is:

A. int typedef* intptr; int x,y,z;

B. typedef* intptr; int x,y,z;

C. int typedef* intptr; intptr x,y,z;

D. typedef int* intptr; intptr x,y,z; ✓

Answer: Option D — typedef int* intptr; intptr x,y,z;

Q196. What will be the output of the following C code? #include <stdio.h> int main() { int x = 2, y = 1; x *= x + y; printf("%d\n", x); return 0; }

A. 5

B. 6 ✓

C. Undefined behaviour

D. Compile time error

Answer: Option B — 6

Q197. Relational operators cannot be used on . . . . . .

A. structure ✓

B. long

C. strings

D. float

Answer: Option A — structure

Q198. What will be the output of the following C code? #include <stdio.h> void main() { int k = 4; float k = 4; printf("%d", k) }

A. Compile time error ✓

B. 4

C. 4.0000000

D. 4.4

Answer: Option A — Compile time error

Q199. In the following code snippet, character pointer str holds a reference to the string . . . . . char *str = "Examveda.com\0" "programming";

A. Examveda.com

B. Examveda.com\0programming ✓

C. Examveda.comprogramming

D. Invalid declaration

Answer: Option B — Examveda.com\0programming

Q200. What is the size of myArray in the code shown below? (Assume that 1 character occupies 1 byte) typedef char x[10]; x myArray[5];

A. 5 bytes

B. 10 bytes

C. 40 bytes

D. 50 bytes ✓

Answer: Option D — 50 bytes

Arrays And Strings

Q201. What is the highest index for an array with 10 elements in C?

A. 5
B. 9 ✓
C. 10
D. 11
Answer: Option B — 9

Q202. Which keyword is used to declare a character array in C?

A. str
B. character
C. arr
D. char ✓
Answer: Option D — char

Q203. What is the size of an integer array declared as int arr[5] in bytes?

A. 10
B. 20 ✓
C. 4
D. 5
Answer: Option B — 20

Q204. Which function is used to compare two strings in C?

A. strcmp ✓
B. strcat
C. strlen
D. strcomp
Answer: Option A — strcmp

Q205. How do you access the first element of an array arr in C?

A. arr[1]
B. arr[0] ✓
C. arr[2]
D. arr[10]
Answer: Option B — arr[0]

Q206. Which type of loop is commonly used to iterate through an array in C?

A. if loop
B. switch loop
C. for loop ✓
D. while loop
Answer: Option C — for loop

Q207. What is the maximum number of elements that can be stored in an array in C?

A. Depends on memory ✓
B. 256
C. 1000
D. Unlimited

Answer: Option A — Depends on memory

Q208. Which function is used to find the length of a string in C?

A. lenstr

B. strsize

C. strlength ✓

D. stringlen

Answer: Option C — strlength

Q209. What is the term for accessing elements of an array using an index in C?

A. Enumeration

B. Indexing ✓

C. Pointer

D. Structures

Answer: Option B — Indexing

Q210. What character is used to terminate a C string?

A. ■ ✓

B. n

C. ;

D. :

Answer: Option A — ■

Q211. Which data type is used to represent a single character in C?

A. string

B. char ✓

C. character

D. chr

Answer: Option B — char

Q212. How can you initialize an array in C at the time of declaration?

A. Using the init keyword

B. Using the initialize function

C. Using a loop

D. Providing a list of values ✓

Answer: Option D — Providing a list of values

Q213. What is the output of printf("%d", sizeof("Hello")); in C?

A. 8

B. 6 ✓

C. 4

D. 2

Answer: Option B — 6

Q214. Which function is used to concatenate two strings in C?

A. strcat ✓

B. strconcat

C. stradd

D. concatstr

Answer: Option A — strcat

Q215. What is the correct way to declare and initialize a string in C?

A. char str[10] = "Hello"; ✓

B. char str = "Hello";

C. string str = "Hello";

D. str = "Hello";

Answer: Option A — char str[10] = "Hello";

Q216. What is the term for a character array that is used to store text in C?

A. char array

B. text array

C. string ✓

D. char sequence

Answer: Option C — string

Q217. How can you find the length of an array in C?

A. Use the length property

B. Use the size property

C. Use the sizeof operator ✓

D. Use the lengthof function

Answer: Option C — Use the sizeof operator

Q218. What is the result of the expression sizeof(int) in C?

A. 4 ✓

B. 2

C. 8

D. 16

Answer: Option A — 4

Q219. Which function is used to copy one string to another in C?

A. strcopy

B. strcp

C. strcpy ✓

D. strduplicate

Answer: Option C — strcpy

Q220. How do you access the last element of an array arr with n elements in C?

A. arr[n]

B. arr[n-1] ✓

C. arr[n+1]

D. arr[last]

Answer: Option B — arr[n-1]

Q221. What is the purpose of the fgets function in C?

A. Read a file

B. Read a string from the console ✓

C. Write to a file

D. Write to the console

Answer: Option B — Read a string from the console

Q222. What does the strtok function do in C?

A. Tokenizes a string ✓
B. Copies a string
C. Compares two strings
D. Concatenates two strings
Answer: Option A — Tokenizes a string

Q223. How do you declare a two-dimensional integer array in C with 3 rows and 4 columns?

A. int arr[3,4];
B. int arr[3][4]; ✓
C. int[3,4] arr;
D. int[4][3] arr;
Answer: Option B — int arr[3][4];

Q224. What is the result of the expression strlen("Hello") in C?

A. 5 ✓
B. 6
C. 4
D. 10
Answer: Option A — 5

Q225. Which function is used to find the first occurrence of a character in a string in C?

A. strchr ✓
B. strstr
C. strfind
D. strsearch
Answer: Option A — strchr

Q226. How do you declare a string in C that can store up to 50 characters?

A. string str[50];
B. char str[50]; ✓
C. char[] str = "50";
D. string = 50;
Answer: Option B — char str[50];

Q227. What is the purpose of the strncpy function in C?

A. Concatenate two strings
B. Copy a portion of a string ✓
C. Compare two strings
D. Initialize a string
Answer: Option B — Copy a portion of a string

Q228. Which function is used to convert a string to an integer in C?

A. strint
B. str2int
C. atoi ✓
D. toint

Answer: Option C — atoi

Q229. What does the fgets function in C do when it encounters a newline character?

A. Removes the newline character

B. Stops reading ✓

C. Replaces the newline with a space

D. Continues reading

Answer: Option B — Stops reading

Q230. How can you check if two strings are equal in C?

A. Use the == operator

B. Use the strcmp function ✓

C. Use the equals function

D. Use the = operator

Answer: Option B — Use the strcmp function

Q231. What is right way to Initialize array?

A. int num[6] = { 2, 4, 12, 5, 45, 5 }; ✓

B. int n{} = { 2, 4, 12, 5, 45, 5 };

C. int n{6} = { 2, 4, 12 };

D. int n(6) = { 2, 4, 12, 5, 45, 5 };

Answer: Option A — int num[6] = { 2, 4, 12, 5, 45, 5 };

Q232. What will be the output of the program? #include<stdio.h> void main() { int a[5] = {5, 1, 15, 20, 25}; int i, j, m; i = ++a[1]; j = a[1]++; m = a[i++]; printf("%d, %d, %d", i, j, m); }

A. 3, 2, 15 ✓

B. 2, 3, 20

C. 2, 1, 15

D. 1, 2, 5

Answer: Option A — 3, 2, 15

Q233. What will be the output of following program code? #include <stdio.h> int main(void) { char p; char buf[10] = {1, 2, 3, 4, 5, 6, 9, 8}; p = (buf + 1)[5]; printf("%d", p); return 0; }

A. 5

B. 6

C. 9 ✓

D. Error

E. None of the above

Answer: Option C — 9

Q234. An array elements are always stored in _____ memory locations.

A. Sequential ✓

B. Random

C. Sequential and Random

D. None of the above

Answer: Option A — Sequential

Q235. Let x be an array. Which of the following operations are illegal? I. ++x II. x+1 III. x++ IV. x*2

A. I and II
B. I, II and III
C. II and III
D. I, III and IV ✓
E. III and IV
Answer: Option D — I, III and IV

Q236. What is the maximum number of dimensions an array in C may have?

A. 2
B. 8
C. 20
D. 50
E. Theoratically no limit. The only practical limits are memory size and compilers. ✓
Answer: Option E — Theoratically no limit. The only practical limits are memory size and compilers.

Q237. Size of the array need not be specified, when

A. Initialization is a part of definition ✓
B. It is a declaratrion
C. It is a formal parameter
D. All of these
Answer: Option A — Initialization is a part of definition

Q238. Consider the following type definition. typedef char x[10]; x myArray[5]; What will sizeof(myArray) be ? (Assume one character occupies 1 byte)

A. 15
B. 10
C. 50 ✓
D. 30
E. None of these
Answer: Option C — 50

Q239. What will be printed after execution of the following code? void main() { int arr[10] = {1,2,3,4,5}; printf("%d", arr[5]); }

A. Garbage Value
B. 5
C. 6
D. 0 ✓
E. None of these
Answer: Option D — 0

Q240. What will be the output of the following program? void main() { char str1[] = "abcd"; char str2[] = "abcd"; if(str1==str2) printf("Equal"); else printf("Unequal"); }

A. Equal
B. Unequal ✓
C. Error
D. None of these.
Answer: Option B — Unequal

Q241. What will be the output of the following code? void main() { int a[10]; printf("%d %d", a[-1], a[12]); }

A. 0 0

B. Garbage value 0

C. 0 Garbage Value

D. Garbage vlaue Garbage Value ✓

E. Code will not compile

Answer: Option D — Garbage vlaue Garbage Value

Q242. What does the following declaration mean? int (*ptr) [10] ;

A. ptr is array of pointers to 10 integers

B. ptr is a pointer to an array of 10 integers ✓

C. ptr is an array of 10 integers

D. ptr is an pointer to array

Answer: Option B — ptr is a pointer to an array of 10 integers

Q243. Array passed as an argument to a function is interpreted as

A. Address of the array.

B. Values of the first elements of the array.

C. Address of the first element of the array. ✓

D. Number of element of the array.

Answer: Option C — Address of the first element of the array.

Q244. What will be the output of the program if the array begins at 65472 and each integer occupies 2 bytes? #include<stdio.h> void main() { int a[3][4] = {1, 2, 3, 4, 4, 3, 2, 1, 7, 8, 9, 0}; printf("%u, %u", a+1, &a+1); }

A. 65474, 65488

B. 65480, 65488

C. 65480, 65496 ✓

D. 65474, 65476

E. None of these

Answer: Option C — 65480, 65496

Q245. What will be the output of the program? #include<stdio.h> int main() { int arr[1] = {10}; printf("%d", 0[arr]); return 0; }

A. 1

B. 0

C. 10 ✓

D. 6

E. None of these

Answer: Option C — 10

Q246. What will be the output of the program if the array begins at address 65486? #include<stdio.h> void main() { int arr[] = {12, 14, 15, 23, 45}; printf("%u, %u", arr, &arr); }

A. 65486, 65488

B. 65486, 65490

C. 65486, 65487

D. 65486, 65486 ✓

E. None of these

Answer: Option D — 65486, 65486

Q247. What will be the output of the program? #include<stdio.h> void main() { float arr[] = {12.4, 2.3, 4.5, 6.7}; printf("%d", sizeof(arr)/sizeof(arr[0])); }

A. 5

B. 4 ✓

C. 6

D. 7

E. None of these

Answer: Option B — 4

Q248. Which of the following is correct way to define the function fun() in the below program? #include<stdio.h> void main() { int a[3][4]; fun(a); }

A. void fun(int p[][4]){} ✓

B. void fun(int *p[4]){}

C. void fun(int *p[][4]){}

D. void fun(int *p[3][4]){}

E. None of these

Answer: Option A — void fun(int p[][4]){}

Q249. Which of the following statements are correct about the program below? #include<stdio.h> void main() { int size, i; scanf("%d", &size); int arr[size]; for(i=1; i<=size; i++) { scanf("%d", arr[i]); printf("%d", arr[i]); } }

A. The code is erroneous since the statement declaring array is invalid. ✓

B. The code is erroneous since the subscript for array used in for loop is in the range 1 to size.

C. The code is correct and runs successfully.

D. The code is erroneous since the values of array are getting scanned through the loop.

E. None of these

Answer: Option A — The code is erroneous since the statement declaring array is invalid.

Q250. Which of the following statements are correct about an array? 1. The array int num[26]; can store 26 elements. 2. The expression num[1] designates the very first element in the array. 3. It is necessary to initialize the array at the time of declaration. 4. The declaration num[SIZE] is allowed if SIZE is a macro.

A. 1

B. 1, 4 ✓

C. 2, 3

D. 2, 4

E. None of these

Answer: Option B — 1, 4

Q251. If the two strings are identical, then strcmp () function returns

A. 1

B. 0 ✓

C. -1

D. true

E. None of these

Answer: Option B — 0

Q252. The library function used to find the last occurrence of a character in a string is

A. laststr()

B. strstr()

C. strnstr()

D. strrchr() ✓

E. None of these

Answer: Option D — strrchr()

Q253. Which of the following function is used to find the first occurrence of a given string in another string?

A. strchr()

B. strrchr()

C. strstr() ✓

D. strnset()

E. None of these

Answer: Option C — strstr()

Q254. Which of the following function is more appropriate for reading in a multi-word string?

A. scanf()

B. gets() ✓

C. printf()

D. puts()

E. None of these

Answer: Option B — gets()

Q255. What will be the output of the program? #include<stdio.h> #include<string.h> void main() { char str1[20] = "Hello", str2[20] = " World"; printf("%s", strcpy(str2, strcat(str1, str2))); }

A. Hello World ✓

B. World

C. WorldHello

D. Hello

E. None of these

Answer: Option A — Hello World

Q256. What will be the output of the program? #include<stdio.h> void main() { printf(5+"Good Morningn"); }

A. Good Morning

B. M

C. Good

D. Morning ✓

E. None of these

Answer: Option D — Morning

Q257. What will be the output of the program? #include<stdio.h> #include<string.h> void main() { char str[] = "Exam\0Veda"; printf("%s", str); }

A. Exam ✓

B. Exam Veda

C. Exam\0Veda

D. Veda

E. None of these

Answer: Option A — Exam

Q258. Which of the following correctly accesses the seventh element stored in arr, an array with 100 elements?

A. arr[6] ✓

B. arr[7]

C. arr{6}

D. arr{7}

E. None of these

Answer: Option A — arr[6]

Q259. What is the return value of the following statement if it is placed in C program? strcmp("ABC", "ABC");

A. 33

B. -1

C. 1

D. 0 ✓

E. Compilation Error

Answer: Option D — 0

Q260. int a [5] = { 1,2,3 } What is the value of a [4] ?

A. 3

B. 1

C. 2

D. 0 ✓

E. Garbage Value

Answer: Option D — 0

Q261. What will be the correct output of the following program? #include<string.h> void main() { char str[] = "C EXAMINATION", rev[17]; int i = strlen(str), j=0; for(; i>=0; rev[j++] = str[i--]) rev[j] = str[j] ; puts(rev); }

A. NOITANIMAXE C

B. NOITANIMAXE

C. C

D. No output at all. ✓

E. Syntax error

Answer: Option D — No output at all.

Q262. The function sprintf() works like printf(), but operates on .....

A. Data file

B. stderr

C. string ✓

D. stdin

E. no such function in 'C'.

Answer: Option C — string

Q263. String concatenation means -

A. Combining two strings. ✓

B. Extracting a substring out of a string.

C. Partitioning the string into two strings.

D. Merging two strings.

E. Comparing the two strings to define the larger one.

Answer: Option A — Combining two strings.

Q264. errno causes trouble in two subtler ways(vague and explicit).

A. true ✓

B. false

Answer: Option A — true

Q265. What do the following C function do? int isgraph(int c);

A. tests for only space character

B. tests for only digit

C. tests for only lower case

D. tests for any printing character ✓

Answer: Option D — tests for any printing character

Q266. The . . . . . function tests for any character for which isalpha or isdigit is true.

A. isxdigit()

B. isspace()

C. isalnum() ✓

D. isupper()

Answer: Option C — isalnum()

Q267. There are two groups of string functions defined in the header <string.h>. What are they?

A. first group names beginning with str; second group names beginning with mem ✓

B. first group names beginning with str; second group names beginning with is

C. first group names beginning with string; second group names beginning with mem

D. first group names beginning with str; second group names beginning with type

Answer: Option A — first group names beginning with str; second group names beginning with mem

Q268. What error occurs when a result is unde?ned for a given argument value?

A. significance loss

B. underflow

C. overflow

D. domain ✓

Answer: Option D — domain

Q269. What is the prototype of strcoll() function?

A. int strcoll(const char *s1,const char *s2) ✓

B. int strcoll(const char *s1)

C. int strcoll(const *s1,const *s2)

D. int strcoll(const *s1)

Answer: Option A — int strcoll(const char *s1,const char *s2)

Q270. What is the return value of strxfrm()?

A. length of the transformed string, not including the terminating null-character ✓

B. length of the transformed string, including the terminating null-character

C. display the transformed string, not including the terminating null character

D. display the transformed string, not including the terminating null-character

Answer: Option A — length of the transformed string, not including the terminating null-character

---

Q271. Which among the following is Copying function?

A. memcpy() ✓

B. strcopy()

C. memcopy()

D. strxcpy()

Answer: Option A — memcpy()

Q272. Which function tests for any character that is an uppercase letter.

A. iscntrl()

B. ispunct()

C. isdigit()

D. isupper() ✓

Answer: Option D — isupper()

Q273. No library function will store a zero in errno.

A. true ✓

B. false

Answer: Option A — true

Q274. The . . . . . function tests for any hexadecimal-digit character.

A. iscntrl()

B. ispunct()

C. isgraph()

D. isxdigit() ✓

Answer: Option D — isxdigit()

Q275. What does the following C code do? int iscntrl(int c);

A. checks if character is upper case

B. checks if character is lower case

C. tests for any control character ✓

D. no function as such

Answer: Option C — tests for any control character

Q276. Which of the given function is used to return a pointer to the located character?

A. strrchr()

B. strxfrm()

C. memchar()

D. strchar() ✓

Answer: Option D — strchar()

Q277. What will the following C code do? char * strrchr(const char *s, int c) char ch = c; char *sc; for(sc = NULL; ; ++s) if(*s == ch) SC = 9; i f (*s =='\O') return ((char *) s);

A. find last occurrence of c in char s[ ]. ✓

B. find first occurrence of c in char s[ ].

C. find the current location of c in char s[ ].

D. There is error in the given code

Answer: Option A — find last occurrence of c in char s[ ].

Q278. Which function returns true only for the characters defined as lowercase letters?

A. islow()

B. islower() ✓

C. isalpa()

D. isalnum()

Answer: Option B — islower()

Q279. The . . . . . function returns the number of characters that are present before the terminating null character.

A. strlength()

B. strlen() ✓

C. strlent()

D. strchr()

Answer: Option B — strlen()

Q280. The . . . . . function appends not more than n characters.

A. strcat()

B. strcon()

C. strncat() ✓

D. memcat()

Answer: Option C — strncat()

Q281. What will be the output of the following C code? const char str1[10]="Helloworld"; const char str2[10] = "world"; char *mat; mat = strstr(str1, str2); printf("The substring is:%s\n", mat);

A. The substring is:world ✓

B. The substring is:Hello

C. The substring is:Helloworld

D. error in the code

Answer: Option A — The substring is:world

Q282. What will be the output of the following C code? char ch[ ] = "0xC"; if(isxdigit(ch[ ])) printf("ch = %s is hexadecimal character \n",ch); else printf("ch = %s is not hexadecimal character \n",ch);

A. ch = 0xC is hexadecimal character ✓

B. ch = 0xC is not hexadecimal character

C. compile error

D. run-time error

Answer: Option A — ch = 0xC is hexadecimal character

Q283. What will strcmp() function do?

A. compares the first n characters of the object

B. compares the string ✓

C. undefined function

D. copies the string

Answer: Option B — compares the string

Q284. The C library function . . . . . breaks string s1 into a series of tokens using the delimiter s2.

A. char *strtok(char *s1,const char *s2); ✓

B. char *strtok(char *s2,const char *s1);

C. char *strstr(char *s1,const char *s2);

D. char *strstr(char *s2,const char *s1);

Answer: Option A — char *strtok(char *s1,const char *s2);

Q285. What is the function of void *memset(s, c, n)?

A. places character s into first n characters of c, return c

B. places character c into first n characters of s, return s ✓

C. places character s into first n characters of c, return s

D. places character c into first n character of s, return c

Answer: Option B — places character c into first n characters of s, return s

---

Q286. Which among the given options compares atmost n characters of string ch to string s?

A. int strncmp(ch, s, n) ✓

B. int strcmp(ch, s)

C. int strncmp(s, ch, n)

D. int strcmp(s, ch)

Answer: Option A — int strncmp(ch, s, n)

Q287. Is there any function declared as strstr()?

A. true ✓

B. false

Answer: Option A — true

Q288. What will be the output of the following C code? char str1[] = "Helloworld "; char str2[] = "Hello"; len = strspn(str1, str2); printf("Length of initial segment matching %d\n", len);

A. 6

B. 5 ✓

C. 4

D. no match

Answer: Option B — 5

Q289. fgetc, getc, getchar are all declared in . . . . . .

A. stdio. h ✓

B. ctype. h

C. assert. h

D. stdarg. h

Answer: Option A — stdio. h

**Q290. What will be the output of the following C code? void *memset(void *c, int c, size-t n) unsigned char ch = c; unsigned char *su; for (su = s; 0 < n; ++su, --n)
 *su = ch;
**

A. store c throughout unsigned char s[n] ✓

B. store c throughout signed char s[n]

C. find first occurrence of c in s[n]

D. find last occurrence of c in s[n]

Answer: Option A — store c throughout unsigned char s[n]

Q291. What will be the output of the following C code? int ch= ' '; if(isgraph(ch)) printf("ch = %c can be printed \n",ch); else printf("ch=%c cannot be printed \n",ch);

A. ch = ' ' can be printed

B. ch = ' ' cannot be printed ✓

C. compile error

D. run-time error

Answer: Option B — ch = ' ' cannot be printed

Q292. The C library function checks whether the passed character is printable.

A. isgraph()

B. isalpha()

C. isprint() ✓

D. ispunct()

Answer: Option C — isprint()

Q293. What will be the output of the following C code? int ch = '\t'; if(isprint(ch)) printf("ch = |%c| printable \n", ch); else printf("ch= |%c| not printable \n",ch);

A. ch = |\t| printable

B. ch = |\t| not printable

C. ch = | | printable

D. ch = | | not printable ✓

Answer: Option D — ch = | | not printable

Q294. What will be the output of the following C code? const char pla[] = "string1"; const char src[] = "string2"; printf("Before memmove place= %s, src = %s\n", pla, src); memmove(pla, src, 7); printf("After memmove place = %s, src = %s\n", pla, src);

A. Before memmove place= string1, src = string2 After memmove place = string2, src = string2 ✓

B. Before memmove place = string2, src = string2 After memmove place= string1, src = string2

C. Before memmove place = string2, src = string1 After memmove place= string2, src =string2

D. Before memmove place= string1, src = string2 After memmove place=string1, src = string1

Answer: Option A — Before memmove place= string1, src = string2 After memmove place = string2, src = string2

Q295. Which of the following is the variable type defined in header string. h?

A. sizet

B. size

C. size_t ✓

D. size-t

Answer: Option C — size_t

Q296. What will be the output of the following C code? const char str1[] = "abcdef"; const char str2[] = "fgha"; char *mat; mat= strpbrk(str1, str2); if(mat) printf("First matching character: %c\n", *mat); else printf("Character not found");

A. g

B. a ✓

C. h

D. f

Answer: Option B — a

Q297. Which among the given options is the right explanation for the statement size_t strcspn(c, s)?

A. return length of prefix of s consisting of characters not in c

B. return length of prefix of s consisting of characters present in c

C. return length of prefix of c consisting of characters not in s ✓

D. return length of prefix of c consisting of characters present in s

Answer: Option C — return length of prefix of c consisting of characters not in s

Q298. The standard white-space characters are the following: space (' '), form feed (' \ f '), newline (' \n') , horizontal tab (' \tr), and vertlcal tab (' \v') can be tested with function.

A. ispunct()

B. isalpha()

C. isgraph()

D. isspace() ✓

Answer: Option D — isspace()

Q299. . . . . occurs when a result is too large in magnitude to represent errors as a floating-point value of the required type.

A. underflow

B. significance loss

C. domain

D. overflow ✓

Answer: Option D — overflow

Q300. . . . . tells the compiler that this data is de?ned somewhere and will be connected with the linker.

A. errno

B. extern ✓

C. variable

D. yvals

Answer: Option B — extern

Operators And Expressions

Q301. What is the result of the expression 5 + 7 * 2 in C?

A. 19 ✓
B. 24
C. 26
D. 17
Answer: Option A — 19

Q302. Which operator is used for logical OR in C?

A. &&
B. |
C. &
D. || ✓
Answer: Option D — ||

Q303. What does the ++ operator do in C when applied to a variable?

A. Decrements by 1
B. Adds 1 ✓
C. Doubles the value
D. Leaves it unchanged
Answer: Option B — Adds 1

Q304. Which operator is used for modulus division in C?

A. % ✓
B. /
C. *
D. &
Answer: Option A — %

Q305. What is the result of the expression 8 / 3 in C?

A. 2 ✓
B. 2.67
C. 3
D. 3.5
Answer: Option A — 2

Q306. What is the order of precedence of the arithmetic operators in C?

A. Addition, Multiplication, Division
B. Division, Multiplication, Addition
C. Multiplication, Division, Addition ✓
D. Division, Addition, Multiplication
Answer: Option C — Multiplication, Division, Addition

Q307. What is the result of the expression 10 - 5 * 2 in C?

A. 20
B. 10
C. 0 ✓
D. -5

Answer: Option C — 0

Q308. Which operator is used for equality comparison in C?

A. == ✓

B. =

C. !=

D. <>

Answer: Option A — ==

Q309. What does the sizeof operator return in C?

A. Size of an array

B. Size of a variable ✓

C. Size of a pointer

D. Size of a function

Answer: Option B — Size of a variable

Q310. What is the result of the expression (6 - 2) * (1 + 2) in C?

A. 12 ✓

B. 18

C. 9

D. 4

Answer: Option A — 12

Q311. Which operator is used to access the value stored at a pointer address in C?

A. &

B. ->

C. * ✓

D. .

Answer: Option C — *

Q312. What is the result of the expression 7 / 2 in C?

A. 2

B. 3.5

C. 3 ✓

D. 3.50

Answer: Option C — 3

Q313. What is the result of the expression 5 % 3 in C?

A. 2 ✓

B. 2.5

C. 1

D. 1.67

Answer: Option A — 2

Q314. Which operator is used for logical NOT in C?

A. &&

B. ! ✓

C. &

D. |

Answer: Option B — !

Q315. What is the result of the expression 10 / 0 in C?

A. 0
B. Infinity
C. Compilation error
D. Runtime error ✓
Answer: Option D — Runtime error

Q316. Which operator is used for assignment in C?

A. ==
B. = ✓
C. :=
D. ->
Answer: Option B — =

Q317. What is the result of the expression 3 * (4 + 2) in C?

A. 18 ✓
B. 24
C. 9
D. 14
Answer: Option A — 18

Q318. Which operator is used to perform a bitwise AND operation in C?

A. &&
B. |
C. & ✓
D. ||
Answer: Option C — &

Q319. What is the result of the expression 5 / 2 in C?

A. 2 ✓
B. 2.5
C. 2.50
D. 3
Answer: Option A — 2

Q320. What is the order of precedence of the logical operators in C?

A. AND, OR, NOT
B. NOT, OR, AND
C. OR, AND, NOT
D. OR, NOT, AND ✓
Answer: Option D — OR, NOT, AND

Q321. What is the result of the expression (10 + 2) / 2 in C?

A. 12
B. 6 ✓
C. 7
D. 11

Answer: Option B — 6

Q322. Which operator is used for inequality comparison in C?

A. != ✓

B. <>

C. ==

D. =

Answer: Option A — !=

Q323. What is the result of the expression 2.5 + 2 in C?

A. 4.5 ✓

B. 4

C. 2.7

D. 2

Answer: Option A — 4.5

Q324. What is the result of the expression 8 % 4 in C?

A. 0 ✓

B. 4

C. 2

D. 8

Answer: Option A — 0

Q325. Which operator is used to perform a bitwise OR operation in C?

A. &&

B. | ✓

C. &

D. ||

Answer: Option B — |

Q326. What is the result of the expression 1 && 0 in C?

A. 1

B. 0 ✓

C. TRUE

D. FALSE

Answer: Option B — 0

Q327. What is the result of the expression 5 * (1 + 2) - 3 in C?

A. 12 ✓

B. 15

C. 10

D. 6

Answer: Option A — 12

Q328. Which operator is used to perform a bitwise XOR operation in C?

A. &&

B. ||

C. &

D. ^ ✓

Answer: Option D — ^

Q329. What is the result of the expression (6 + 3) / 0 in C?

A. 0
B. Infinity
C. Compilation error
D. Runtime error ✓
Answer: Option D — Runtime error

Q330. What is the result of the expression 5 / 2.0 in C?

A. 2
B. 2.5 ✓
C. 2.0
D. 3
Answer: Option B — 2.5

Q331. Which of the following operator takes only integer operands?

A. +
B. *
C. /
D. % ✓
E. None of these
Answer: Option D — %

Q332. In an expression involving || operator, evaluation I. Will be stopped if one of its components evaluates to false II. Will be stopped if one of its components evaluates to true III. Takes place from right to left IV. Takes place from left to right

A. I and II
B. I and III
C. II and III
D. II and IV ✓
E. III and IV
Answer: Option D — II and IV

Q333. Determine output: void main() { int i=0, j=1, k=2, m; m = i++ || j++ || k++; printf("%d %d %d %d", m, i, j, k); }

A. 1 1 2 3
B. 1 1 2 2 ✓
C. 0 1 2 2
D. 0 1 2 3
E. None of these
Answer: Option B — 1 1 2 2

Q334. Determine output: void main() { int c = - -2; printf("c=%d", c); }

A. 1
B. -2
C. 2 ✓
D. Error
Answer: Option C — 2

Q335. Determine output: void main() { int i=10; i = !i>14; printf("i=%d", i); }

A. 10

B. 14

C. 0 ✓

D. 1

E. None of these

Answer: Option C — 0

Q336. In C programming language, which of the following type of operators have the highest precedence

A. Relational operators

B. Equality operators

C. Logical operators

D. Arithmetic operators ✓

Answer: Option D — Arithmetic operators

Q337. What will be the output of the following program? void main() { int a, b, c, d; a = 3; b = 5; c = a, b; d = (a, b); printf("c=%d d=%d", c, d); }

A. c=3 d=3

B. c=3 d=5 ✓

C. c=5 d=3

D. c=5 d=5

Answer: Option B — c=3 d=5

Q338. Which of the following comments about the ++ operator are correct?

A. It is a unary operator

B. The operand can come before or after the operator

C. It cannot be applied to an expression

D. It associates from the right

E. All of the above ✓

Answer: Option E — All of the above

Q339. What will be the output of this program on an implementation where "int" occupies 2 bytes? #include <stdio.h> void main() { int i = 3; int j; j = sizeof(++i + ++i); printf("i=%d j=%d", i, j); }

A. i=4 j=2

B. i=3 j=2 ✓

C. i=5 j=2

D. the behavior is undefined

Answer: Option B — i=3 j=2

Q340. Which operator has the lowest priority?

A. ++

B. %

C. +

D. || ✓

E. &&

Answer: Option D — ||

Q341. What will be the output? void main(){ int a=10, b=20; char x=1, y=0; if(a,b,x,y){ printf("EXAM"); } }

A. XAM is printed

B. exam is printed

C. Compiler Error

D. Nothing is printed ✓

Answer: Option D — Nothing is printed

Q342. What number will z in the sample code given below? int z, x=5, y= -10, a=4, b=2; z = x++ - --y*b/a;

A. 5

B. 6

C. 9

D. 10 ✓

E. 11

Answer: Option D — 10

Q343. What is the output of the following statements? int i = 0; printf("%d %d", i, i++);

A. 0 1

B. 1 0 ✓

C. 0 0

D. 1 1

E. None of these

Answer: Option B — 1 0

Q344. What is the output of the following statements? int b=15, c=5, d=8, e=8, a; a = b>c ? c>d ? 12 : d>e ? 13 : 14 : 15; printf("%d", a);

A. 13

B. 14 ✓

C. 15

D. 12

E. Garbage Value

Answer: Option B — 14

Q345. What will be the output of the following code fragment? void main() { printf("%x",-1<<4); }

A. fff0 ✓

B. fff1

C. fff2

D. fff3

E. fff4

Answer: Option A — fff0

Q346. Find the output of the following program. #include<stdio.h> void main() { int y=10; if(y++>9 && y++!=10 && y++>11) printf("%d", y); else printf("%d", y); }

A. 11

B. 12

C. 13 ✓

D. 14

E. Compilation error

Answer: Option C — 13

Q347. Find the output of the following program. #include<stdio.h> void main() { int y=10; if(y++>9 && y++!=11 && y++>11) printf("%d", y); else printf("%d", y); }

A. 11

B. 12 ✓

C. 13

D. 14

E. Compilation error

Answer: Option B — 12

Q348. Determine output of the following program code. #include<stdio.h> void main() { int a, b=7; a = b<4 ? b<<1 : ++b>4 ? 7>>1 : a; printf("%d %d", a, b); }

A. 3 7

B. 7 3

C. 8 3

D. 3 8 ✓

E. None of these

Answer: Option D — 3 8

Q349. Choose the correct output for the following program. #include<stdio.h> void main() { int a=10, b=11, c=13, d; d = (a=c, b+=a, c=a+b+c); printf("%d %d %d %d", d, a, b, c); }

A. 50, 13, 11, 13

B. 50, 13, 24, 50 ✓

C. 13, 10, 24, 50

D. 50, 13, 24, 13

E. 13, 13, 24, 13

Answer: Option B — 50, 13, 24, 50

Q350. Consider the following program fragment, and choose the correct one. void main() { int a, b = 2, c; a = 2 * (b++); c = 2 * (++b); }

A. a = 4, c = 8 ✓

B. a = 3, c = 8

C. b = 3, c = 6

D. a = 4, c = 6

E. b = 4, c = 6

Answer: Option A — a = 4, c = 8

Q351. Which operator from the following has the lowest priority?

A. Assignment operator

B. Division operator

C. Comma operator ✓

D. Conditional operator

E. Unary-operator

Answer: Option C — Comma operator

Q352. Identify the correct output of the following code: void main() { int w=10, x=5, y=3, z=3; if((w < x) && (y=z++)) printf("%d %d %d %d", w, x, y, z); else printf("%d %d %d %d", w, x, y, z); }

A. 10 5 4 4

B. 10 5 3 3 ✓

C. 10 5 4 3

D. 10 5 3 4

E. 10 5 5 5

Answer: Option B — 10 5 3 3

Q353. Given b=110 and c=20 , what is the value of 'a' after execution of the expression a=b-=c*=5?

A. 450

B. 10 ✓

C. 110

D. -10

E. -110

Answer: Option B — 10

Q354. what will be the output when following code is executed? void main() { int a=10, b; b = a++ + ++a; printf("%d %d %d %d", b, a++, a, ++a); }

A. 12 10 11 13

B. 22 12 12 13

C. 22 11 11 11

D. 22 14 12 13

E. 22 13 14 14 ✓

Answer: Option E — 22 13 14 14

Q355. Which among the following statement is right?

A. sizeof(struct stemp*) > sizeof(union utemp*) > sizeof(char *)

B. sizeof(struct stemp*) < sizeof(union utemp*) < sizeof(char *)

C. sizeof(struct stemp*) = sizeof(union utemp*) = sizeof(char *) ✓

D. the order Depends on the compiler

Answer: Option C — sizeof(struct stemp*) = sizeof(union utemp*) = sizeof(char *)

Q356. What will be the output of the following C code? #include <stdio.h> int main() { float a = 2.455555555555; printf("%f", a); }

A. 2.455555 ✓

B. 2.455556

C. 2.456

D. 2.46

Answer: Option A — 2.455555

Q357. Which of the following % operation is invalid?

A. 2 % 4;

B. 2 % 4l;

C. 2 % 4f; ✓

D. Both 2 % 4l; and 2 % 4f;

Answer: Option C — 2 % 4f;

Q358. In the following C code, the union size is decided by? union temp { char a; int b; float c; };

A. char

B. int

C. float

D. both int and float ✓

Answer: Option D — both int and float

Q359. Modulus for float could be achieved by?

A. a % b

B. modulus(a, b);

C. fmod(a, b); ✓

D. mod(a, b);

Answer: Option C — fmod(a, b);

Q360. Which among the following has the highest precedence?

A. &

B. <<

C. sizeof() ✓

D. &&

Answer: Option C — sizeof()

Q361. %f access specifier is used for . . . . . .

A. Strings

B. Integral types

C. Floating type ✓

D. All of the mentioned

Answer: Option C — Floating type

Q362. What will be the output of the following C code? #include <stdio.h> printf("%d", sizeof('a'));

A. 1

B. 2

C. 4 ✓

D. None of the mentioned

Answer: Option C — 4

Q363. Loss in precision occurs for typecasting from. . . . . .

A. char to short

B. float to double

C. long to float

D. float to int ✓

Answer: Option D — float to int

Q364. What will be the output of the following C code? #include <stdio.h> union temp { char a; char b; int c; }t; int main() { printf("%d", sizeof(t)); return 0; }

A. 1

B. 2

C. 4 ✓

D. 6

Answer: Option C — 4

Q365. Select the odd one out with respect to type?

A. char

B. int

C. long

D. float ✓

Answer: Option D — float

Q366. Predict the data type of the following mathematical operation? 2 * 9 + 3 / 2 . 0

A. int

B. long

C. float

D. double ✓

Answer: Option D — double

Q367. How many digits are present after the decimal in float value?

A. 1

B. 3

C. 6 ✓

D. 16

Answer: Option C — 6

Q368. What is the size of float in a 32-bit compiler?

A. 1

B. 2

C. 4 ✓

D. 8

Answer: Option C — 4

Q369. Which among the following is never possible as an output for a float?

A. 3.666666

B. 3.666

C. 3

D. None of the mentioned ✓

Answer: Option D — None of the mentioned

Q370. Size of an array can be evaluated by . . . . . (Assuming array declaration int a[10];)

A. sizeof(a); ✓

B. sizeof(*a);

C. sizeof(a[10]);

D. 10 * sizeof(a);

Answer: Option A — sizeof(a);

Q371. What type of value does sizeof return?

A. char

B. short

C. unsigned int ✓

D. long

Answer: Option C — unsigned int

Q372. Which among the following is never possible in C when members are different in a structure and union? //Let P be a structure //Let Q be a union

A. sizeof(P) is greater than sizeof(Q)

B. sizeof(P) is less than sizeof(Q)

C. sizeof(P) is equal to sizeof(Q)

D. none of the mentioned ✓

Answer: Option D — none of the mentioned

Q373. What will be the size of the following C structure? #include <stdio.h> struct temp { int a[10]; char p; };

A. 5

B. 11

C. 41

D. 44 ✓

Answer: Option D — 44

Q374. What is the sizeof(void) in a 32-bit C?

A. 0

B. 1 ✓

C. 2

D. 4

Answer: Option B — 1

Q375. Which of the following cannot be used inside sizeof?

A. pointers

B. functions ✓

C. macro definition

D. none of the mentioned

Answer: Option B — functions

Q376. Which data type is suitable for storing a number like? 10.0000000001

A. int

B. float

C. double ✓

D. both float and double

Answer: Option C — double

Q377. In a 32-bit compiler, which 2 types have the same size?

A. char and short

B. short and int

C. int and float ✓

D. float and double

Answer: Option C — int and float

Q378. What will be the output of the following C code? #include <stdio.h> printf("%d", sizeof(strlen("HELLOWORLD")));

A. Output, 4 ✓

B. Output, 10

C. Output, 16

D. Error, sizeof cannot evaluate size of a function

Answer: Option A — Output, 4

Q379. What will be the output of the following C code? #include <stdio.h> printf("%.0f", 2.89);

A. 2.890000

B. 2.89

C. 2

D. 3 ✓

Answer: Option D — 3

Q380. What is the sizeof(char) in a 32-bit C compiler?

A. 1 bit

B. 2 bits

C. 1 Byte ✓

D. 2 Bytes

Answer: Option C — 1 Byte

Q381. What will be the output of the following C code? #include <stdio.h> (sizeof double = 8, float = 4, void = 1) #define PI 3.14 int main() { printf("%d", sizeof(PI)); }

A. Output is 8 ✓

B. Output is 4

C. Output is 1

D. Error, we can't use sizeof on macro-definitions

Answer: Option A — Output is 8

Q382. What will be the output of the following C code? #include <stdio.h> main() { int a = 1; printf("size of a is %d, ", sizeof(++a)); printf("value of a is %d", a); };

A. size of a is 4, value of a is 1 ✓

B. size of a is 4, value of a is 2

C. size of a is 2, value of a is 2

D. size of a is 2, value of a is 1

Answer: Option A — size of a is 4, value of a is 1

Q383. Which of the following is not an operator in C?

A. ,

B. sizeof()

C. ~

D. None of the mentioned ✓

Answer: Option D — None of the mentioned

Q384. %lf is used to display?

A. float

B. long float

C. double ✓

D. all of the mentioned

Answer: Option C — double

Q385. Which among the following is never possible in C when members in a structure are the same as that in a union? //Let P be a structure //Let Q be a union

A. sizeof(P) is greater than sizeof(Q)

B. sizeof(P) is equal to sizeof(Q)

C. sizeof(P) is less than to sizeof(Q) ✓

D. none of the mentioned

Answer: Option C — sizeof(P) is less than to sizeof(Q)

Control Structures

Q386. Which control structure is used to repeatedly execute a block of code in C?

A. for loop
B. if statement
C. switch case
D. while loop ✓
Answer: Option D — while loop

Q387. In C, what is the purpose of the 'break' statement within a loop?

A. Continue to the next iteration
B. Exit the program
C. Terminate the loop and exit it ✓
D. Skip the current iteration
Answer: Option C — Terminate the loop and exit it

Q388. What is the purpose of the 'else' statement in C's 'if-else' control structure?

A. Execute the 'if' block
B. Execute the 'else' block ✓
C. Execute both 'if' and 'else' blocks
D. Skip the 'if' block
Answer: Option B — Execute the 'else' block

Q389. Which control structure is used to make a decision between two or more alternatives in C?

A. switch case
B. for loop
C. if statement ✓
D. while loop
Answer: Option C — if statement

Q390. What is the result of the expression 5 > 3 && 4 < 6 in C?

A. TRUE ✓
B. FALSE
C. 1
D. 0
Answer: Option A — TRUE

Q391. In C, what happens if the 'default' case is missing in a 'switch' statement?

A. It causes a compilation error
B. It has no effect ✓
C. It executes the 'default' case by default
D. It generates a runtime error
Answer: Option B — It has no effect

Q392. What is the purpose of the 'continue' statement in C?

A. Skip the loop
B. Exit the program
C. Skip the current iteration ✓

D. Exit the loop

Answer: Option C — Skip the current iteration

Q393. How many times will a 'do-while' loop execute its body if the condition is initially false in C?

A. 0 times

B. 1 time ✓

C. Infinite times

D. It depends on the loop body

Answer: Option B — 1 time

Q394. What is the result of the expression !(5 == 5) in C?

A. TRUE

B. FALSE ✓

C. 1

D. 0

Answer: Option B — FALSE

Q395. In C, which control structure is used to iterate through a collection of items, such as an array or a list?

A. for loop ✓

B. if statement

C. switch case

D. while loop

Answer: Option A — for loop

Q396. What is the purpose of the 'if' control structure in C?

A. Looping

B. Decision making ✓

C. Function declaration

D. Error handling

Answer: Option B — Decision making

Q397. What is the result of the expression 10 % 3 in C?

A. 1 ✓

B. 0

C. 3

D. 2

Answer: Option A — 1

Q398. In C, what happens if the 'break' statement is used outside of a loop or switch statement?

A. It has no effect

B. It generates a compilation error ✓

C. It exits the program

D. It generates a runtime error

Answer: Option B — It generates a compilation error

Q399. Which control structure in C is used to perform a repetitive task while a condition is true?

A. if statement

B. for loop

C. while loop ✓

D. switch case

Answer: Option C — while loop

Q400. What is the result of the expression `7 || 0` in C?

A. TRUE ✓

B. FALSE

C. 1

D. 0

Answer: Option A — TRUE

Q401. In C, what is the purpose of the 'goto' statement?

A. Break out of a loop

B. Terminate the program

C. Transfer control to a labeled statement ✓

D. Execute a function

Answer: Option C — Transfer control to a labeled statement

Q402. What does the 'default' case in a 'switch' statement do in C?

A. Executes when no other case matches ✓

B. Causes a compilation error

C. Skips the 'switch' statement

D. Exits the program

Answer: Option A — Executes when no other case matches

Q403. How can you create an infinite loop in C?

A. Use a 'for' loop

B. Use a 'while' loop with a true condition ✓

C. Use a 'do-while' loop

D. Use a 'switch' statement

Answer: Option B — Use a 'while' loop with a true condition

Q404. What is the result of the expression 2 && 0 in C?

A. TRUE

B. FALSE ✓

C. 1

D. 0

Answer: Option B — FALSE

Q405. In C, which statement is used to exit the current iteration of a loop and continue with the next iteration?

A. break

B. return

C. continue ✓

D. exit

Answer: Option C — continue

Q406. Which control structure is used to execute a block of code repeatedly as long as a condition is true in C?

A. for loop

B. while loop ✓

C. if statement

D. switch case

Answer: Option B — while loop

Q407. What is the purpose of the 'switch' statement in C?

A. Define a function

B. Make a decision ✓

C. Create a loop

D. Perform bitwise operations

Answer: Option B — Make a decision

Q408. What is the result of the expression `3 || 0` in C?

A. TRUE ✓

B. FALSE

C. 1

D. 0

Answer: Option A — TRUE

Q409. In C, which control structure is used to execute a block of code a specific number of times?

A. for loop ✓

B. while loop

C. if statement

D. switch case

Answer: Option A — for loop

Q410. What happens if a 'break' statement is used within a 'switch' statement in C?

A. It skips the current case and continues to the next case

B. It exits the 'switch' statement ✓

C. It generates a compilation error

D. It generates a runtime error

Answer: Option B — It exits the 'switch' statement

Q411. What is the result of the expression !0 in C?

A. TRUE ✓

B. FALSE

C. 1

D. 0

Answer: Option A — TRUE

Q412. Which control structure is used to execute a block of code only if a condition is true in C?

A. for loop

B. while loop

C. if statement ✓

D. switch case

Answer: Option C — if statement

Q413. What is the purpose of the 'return' statement in C?

A. Terminate the program

B. Exit a loop

C. Return a value from a function ✓

D. Print a message

Answer: Option C — Return a value from a function

Q414. In C, which control structure allows you to define a block of code to be executed in response to a specific event or condition?

A. for loop

B. if statement ✓

C. switch case

D. function

Answer: Option B — if statement

Q415. What is the result of the expression 1 && 1 in C?

A. TRUE ✓

B. FALSE

C. 1

D. 0

Answer: Option A — TRUE

Q416. What is the output of given program if user enter value 99? #include<stdio.h> void main() { int i; printf("Enter a number:"); scanf("%d", &i); // 99 is given as input. if(i%5 == 0){ printf("nNumber entered is divisible by 5"); } }

A. Enter a number:99 ✓

B. Enter a number:99 Number is divisible by 5

C. complier error

D. Run time error

Answer: Option A — Enter a number:99

Q417. What is the output of given program if user enter "xyz" ? #include<stdio.h> void main() { float age, AgeInSeconds; printf("Enter your age:"); scanf("%f", &age); AgeInSeconds = 365 * 24 * 60 * 60 * age; printf("You have lived for %f seconds", AgeInSeconds); }

A. Enter your age: xyz You have lived for 0 seconds

B. Enter your age: xyz You have lived for 0.00000 seconds ✓

C. Enter your age: xyz "after that program will stop"

D. Run time error

Answer: Option B — Enter your age: xyz You have lived for 0.00000 seconds

Q418. What is the output of given program if user enter "xyz" ? #include<stdio.h> void main() { float age, AgeInSeconds; int value; printf("Enter your age:"); value=scanf("%f", &age); if(value==0){ printf("\\nYour age is not valid"); } AgeInSeconds = 365 * 24 * 60 * 60 * age; printf("\\n You have lived for %f seconds", AgeInSeconds); }

A. Enter your age : xyz Your age is not valid

B. Enter your age: xyz You have lived for 0 seconds

C. Enter your age: xyz Your age is not valid ✓

D. Complier error

Answer: Option C — Enter your age: xyz Your age is not valid

Q419. What will be the output of the given program? #include<stdio.h> void main() { int i=10; printf("i=%d", i); { int i=20; printf("i=%d", i); i++; printf("i=%d", i); } printf("i=%d", i); }

A. 10 10 11 11

B. 10 20 21 21

C. 10 20 21 10 ✓

D. 10 20 21 20

Answer: Option C — 10 20 21 10

Q420. What will be the value of i and j after execution of following program? #include<stdio.h> void main() { int i, j; for(i=0,j=0;i<10,j<20;i++,j++){ printf("i=%d %t j=%d", i, j); } }

A. 10 10

B. 10 20

C. 20 20 ✓

D. Run time error

Answer: Option C — 20 20

Q421. What will be the output given program? #include<stdio.h> void main() { int i = -10; for(;i;printf("%d ", i++)); }

A. -10 to -1 ✓

B. -10 to infinite

C. -10 to 0

D. Complier error

Answer: Option A — -10 to -1

Q422. What will be the output of the given program? #include<stdio.h> void main() { int a=11,b=5; if(a=5) b++; printf("%d %d", ++a, b++); }

A. 12 7

B. 5 6

C. 6 6 ✓

D. 6 7

E. 11 6

Answer: Option C — 6 6

Q423. What will be the output of the given program? #include<stdio.h> void main() { int value=0; if(value) printf("well done "); printf("examveda"); }

A. well done examveda

B. examveda ✓

C. complier error

D. None of these

Answer: Option B — examveda

Q424. What will be the output of the given program? #include<stdio.h> void main() { int value1, value2=100, num=100; if(value1=value2%5) num=5; printf("%d %d %d", num, value1, value2); }

A. 100 100 100

B. 5 0 20

C. 5 0 100

D. 100 0 100 ✓

E. 100 5 100

Answer: Option D — 100 0 100

Q425. What will be the output of the given program? #include<stdio.h> void main() { float num=5.6; switch(num){ case 5:printf("5"); case 6:printf("6"); default : printf("0"); break; } printf("%d", num); }

A. 5 5.600000

B. 6 5.600000

C. 0 5.600000

D. Complier error ✓

Answer: Option D — Complier error

Q426. What will be the output of given program? #include<stdio.h> void main() { int a=1; if("%d=hello", a); }

A. complier error

B. no error no output ✓

C. 0

D. 1

Answer: Option B — no error no output

Q427. What will be the output of given program? #include<stdio.h> void main() { int a=3; for(;a;printf("%d ", a--); }

A. no output

B. 3 2 1 0

C. 3 2 1 ✓

D. infinity loop

Answer: Option C — 3 2 1

Q428. What will be the output of given program? #include<stdio.h> void main() { int i=1, j=-1; if((printf("%d", i)) < (printf("%d", j))) printf("%d", i); else printf("%d", j); }

A. 1 -1 1 ✓

B. 1 -1 -1

C. 1

D. -1

E. complier error

Answer: Option A — 1 -1 1

Q429. What will be the output of the following piece of code? for(i = 0; i<10; i++); printf("%d", i);

A. 10 ✓

B. 0123456789

C. Syntax error

D. 0

E. Infinite loop

Answer: Option A — 10

Q430. What will be the output of the following code? #include<stdio.h> void main() { int s=0; while(s++<10) { if(s<4 && s<9) continue; printf("%dt", s); } }

A. 1 2 3 4 5 6 7 8 9

B. 1 2 3 10

C. 4 5 6 7 8 9 10 ✓

D. 4 5 6 7 8 9

E. None of these

Answer: Option C — 4 5 6 7 8 9 10

Q431. Which command is used to skip the rest of a loop and carry on from the top of the loop again?

A. break

B. resume

C. continue ✓

D. skip

E. None of these

Answer: Option C — continue

Q432. What is the output of the following program? #include<stdio.h> int c[10] = {1,2,3,4,5,6,7,8,9,10}; main() { int a, b=0; for(a=0;a<10;++a) if(c[a]%2 == 1) b+=c[a]; printf("%d", b); }

A. 20

B. 24

C. 25 ✓

D. 30

E. None of these

Answer: Option C — 25

Q433. What is the output of the following statements? for(i=10; i++; i<15) printf("%d ", i);

A. 10 11 12 13 14

B. 10 11 12 13 14 15

C. 9 10 11 12 13

D. Infinite loop ✓

E. None of these

Answer: Option D — Infinite loop

Q434. The type of the controlling expression of a switch statement cannot be of the type .....

A. int

B. char

C. short

D. float ✓

E. long

Answer: Option D — float

Q435. What's wrong in the following statement, provided k is a variable of type int? for (k = 2, k <=12, k ++)

A. The increment should always be ++k .

B. The variable must always be the letter i when using a for loop.

C. There should be a semicolon at the end of the statement.

D. The variable k can’t be initialized.

E. The commas should be semicolons. ✓

Answer: Option E — The commas should be semicolons.

Q436. Find the output of the following program. #include<stdio.h> void main() { int y=10; if(y++>9 && y++!=10 && y++>11) printf("%d", y); else printf("%d", y); }

A. 11

B. 12

C. 13 ✓

D. 14

E. Compilation error

Answer: Option C — 13

Q437. What will be the value of sum after the following program is executed? void main() { int sum=1, index = 9; do{ index = index – 1; sum *= 2; }while(index > 9); }

A. 1

B. 2 ✓

C. 9

D. 0.5

E. 0.25

Answer: Option B — 2

Q438. What is the right choice, if the following loop is implemented? void main() { int num = 0; do{ --num; printf("%d", num); }while(++num >= 0); }

A. A run time error will be generated.

B. The program will not enter into the loop.

C. There will be a compilation error reported.

D. The loop will run infinitely many times. ✓

E. Prints the value of 0 one time only.

Answer: Option D — The loop will run infinitely many times.

Q439. What will be the final value of the digit? void main() { int digit = 0; for(; digit <= 9;) digit++; digit *= 2; --digit; }

A. -1

B. 17

C. 19 ✓

D. 16

E. 20

Answer: Option C — 19

Q440. What will be the following code's output if choice = 'R'? switch(choice) { case 'R' : printf("RED"); case 'W' : printf("WHITE"); case 'B' : printf("BLUE"); default : printf("ERROR");break; }

A. RED

B. RED WHITE BLUE ERROR ✓

C. RED ERROR

D. RED WHITE BLUE

E. ERROR

Answer: Option B — RED WHITE BLUE ERROR

Q441. Consider the following program fragment: for(c=1, sum=0; c <= 10; c++) { scanf("%d", &x); if(x < 0) continue; sum += x; } What would be the value of sum for the input 1, -1, 2, -2, 3, -3, 4,

-4, 5, -5

A. -5

B. 30

C. 10

D. 1

E. 15 ✓

Answer: Option E — 15

Q442. What will be printed if the following code is executed? void main() { int x=0; for(; ;) { if(x++ == 4) break; continue; } printf("x=%d", x); }

A. x=0

B. x=5 ✓

C. x=4

D. x=1

E. Error

Answer: Option B — x=5

Q443. Consider the following code: void main() { int a[5] = {6,8,3,9,0}, i=0; if(i != 0) { break; printf("%d", a[i]); } else printf("%d", a[i++]); } What is the output of the above program?

A. 6

B. 8

C. Runtime error

D. Syntax error ✓

E. No output

Answer: Option D — Syntax error

Q444. What will be the output of the following C code? (Assuming that we have entered the value 1 in the standard input) #include <stdio.h> void main() { int ch; printf("enter a value between 1 to 2:"); scanf("%d", &ch); switch (ch, ch + 1) { case 1: printf("1\n"); break; case 2: printf("2"); break; } }

A. 1

B. 2 ✓

C. 3

D. Run time error

Answer: Option B — 2

Q445. What will be the output of the following C code? #include <stdio.h> void main() { int i = 0; do { printf("Hello"); } while (i != 0); }

A. Nothing

B. H is printed infinite times

C. Hello ✓

D. Run time error

Answer: Option C — Hello

Q446. What will be the output of the following C code? #include <stdio.h> int main() { int i = 0; while (i < 2) { if (i == 1) break; i++; if (i == 1) continue; printf("In while loop\n"); } printf("After loop\n"); }

A. In while loop After loop

B. After loop ✓

C. In while loop In while loop After loop

D. In while loop

Answer: Option B — After loop

Q447. What will be the output of the following C code? #include <stdio.h> void main() { int i = 0, k; label: printf("%d", i); if (i == 0) goto label; }

A. 0

B. Infinite 0 ✓

C. Nothing

D. Error

Answer: Option B — Infinite 0

Q448. What will be the output of the following C code? #include <stdio.h> int main() { int x = 97; switch (x) { case 'a': printf("yes "); break; case 97: printf("no\n"); break; } }

A. yes

B. yes no

C. Duplicate case value error ✓

D. Character case value error

Answer: Option C — Duplicate case value error

Q449. What will be the output of the following C code? #include <stdio.h> int main() { int *p = NULL; for (foo(); p; p = 0) printf("In for loop\n"); printf("After loop\n"); }

A. In for loop after loop

B. Compile time error ✓

C. Infinite loop

D. Depends on the value of NULL

Answer: Option B — Compile time error

Q450. What will be the output of the following C code? #include <stdio.h> int main() { printf("%d ", 1); goto l1; printf("%d ", 2); l1:goto l2; printf("%d ", 3); l2:printf("%d ", 4); }

A. 1 4 ✓

B. Compile time error

C. 1 2 4

D. 1 3 4

Answer: Option A — 1 4

Q451. The keyword 'break' cannot be simply used within . . . . . .

A. do-while

B. if-else ✓

C. for

D. while

Answer: Option B — if-else

Q452. What will be the output of the following C code? #include <stdio.h> int main() { int x = 0; if (x == 1) if (x == 0) printf("inside if\n"); else printf("inside else if\n"); else printf("inside else\n"); }

A. inside if

B. inside else if

C. inside else ✓

D. compile time error

Answer: Option C — inside else

Q453. What will be the output of the following C code? (Assuming that we have entered the value 1 in the standard input) #include <stdio.h> void main() { char *ch; printf("enter a value between 1 to 3:"); scanf("%s", ch); switch (ch) { case "1": printf("1"); break; case "2": printf("2"); break; } }

A. 1

B. Compile time error ✓

C. 2

D. Run time error

Answer: Option B — Compile time error

Q454. What will be the output of the following C code? #include <stdio.h> int main() { int i = 0, j = 0; l1: while (i < 2) { i++; while (j < 3) { printf("loop\n"); goto l1; } } }

A. loop loop ✓

B. Compile time error

C. loop loop loop loop

D. Infinite loop

Answer: Option A — loop loop

Q455. What will be the output of the following C code? #include <stdio.h> int main() { int x = 0; if (x == 0) printf("true, "); else if (x = 10) printf("false, "); printf("%d\n", x); }

A. false, 0

B. true, 0 ✓

C. true, 10

D. compile time error

Answer: Option B — true, 0

Q456. What will be the output of the following C code? #include <stdio.h> int main() { int i = 0; do { i++; if (i == 2) continue; printf("In while loop "); } while (i < 2); printf("%d\n", i); }

A. In while loop 2 ✓

B. In while loop in while loop 3

C. In while loop 3

D. Infinite loop

Answer: Option A — In while loop 2

Q457. What will be the output of the following C code? #include <stdio.h> void main() { int k; for (k = -3; k < -5; k++) printf("Hello"); }

A. Hello

B. Infinite hello

C. Run time error

D. Nothing ✓

Answer: Option D — Nothing

Q458. What will be the output of the following C code? #include <stdio.h> int main() { int x = 0; if (x == 1) if (x >= 0) printf("true\n"); else printf("false\n"); }

A. true

B. false

C. Depends on the compiler

D. No print statement ✓

Answer: Option D — No print statement

Q459. What will be the output of the following C code? (Assuming that we have entered the value 1 in the standard input) #include <stdio.h> void main() { int ch; printf("enter a value between 1 to 2:"); scanf("%d", &ch); switch (ch, ch + 1) { case 1: printf("1\n"); break; case 2: printf("2"); break; } }

A. 1

B. 2 ✓

C. 3

D. Run time error

Answer: Option B — 2

Q460. What will be the output of the following C code? #include <stdio.h> void main() { double k = 0; for (k = 0.0; k < 3.0; k++) printf("Hello"); }

A. Run time error

B. Hello is printed thrice ✓

C. Hello is printed twice

D. Hello is printed infinitely

Answer: Option B — Hello is printed thrice

Q461. How many times i value is checked in the following C code? #include <stdio.h> int main() { int i = 0; while (i < 3) i++; printf("In while loop\n"); }

A. 2

B. 3

C. 4 ✓

D. 1

Answer: Option C — 4

Q462. What will be the output of the following C code? #include <stdio.h> int main() { int i = 0; do { i++; printf("In while loop\n"); } while (i < 3); }

A. In while loop In while loop In while loop ✓

B. In while loop In while loop

C. Depends on the compiler

D. Compile time error

Answer: Option A — In while loop In while loop In while loop

Q463. How many times i value is checked in the following C code? #include <stdio.h> int main() { int i = 0; do { i++; printf("in while loop\n"); } while (i < 3); }

A. 2

B. 3 ✓

C. 4

D. 1

Answer: Option B — 3

Q464. What will be the output of the following C code? #include <stdio.h> int main() { int x = 1; if (x > 0) printf("inside if\n"); else if (x > 0) printf("inside elseif\n"); }

A. inside if ✓

B. inside elseif

C. inside if inside elseif

D. compile time error

Answer: Option A — inside if

Q465. What will be the output of the following C code? (Assuming that we have entered the value 1 in the standard input) #include <stdio.h> void main() { int ch; printf("enter a value between 1 to 2:"); scanf("%d", &ch); switch (ch) { case 1: printf("1\n"); default: printf("2\n"); } }

A. 1

B. 2

C. 1 2 ✓

D. Run time error

Answer: Option C — 1 2

Q466. What will be the output of the following C code? #include <stdio.h> int main() { int i = 0, j = 0; l1: while (i < 2) { i++; while (j < 3) { printf("loop\n"); goto l1; } } }

A. loop loop ✓

B. compilation error

C. oop loop loop loop

D. infinite loop

Answer: Option A — loop loop

Q467. What will be the output of the following C code? (Assuming that we have entered the value 1 in the standard input) #include <stdio.h> void main() { double ch; printf("enter a value between 1 to 2:"); scanf("%lf", &ch); switch (ch) { case 1: printf("1"); break; case 2: printf("2"); break; } }

A. Compile time error ✓

B. 1

C. 2

D. Varies

Answer: Option A — Compile time error

Q468. What will be the output of the following C code? #include <stdio.h> int main() { printf("%d ", 1); goto l1; printf("%d ", 2); l1:goto l2; printf("%d ", 3); l2:printf("%d ", 4); }

A. 1 4 ✓

B. Compilation error

C. 1 2 4

D. 1 3 4

Answer: Option A — 1 4

Q469. What will be the output of the following C code? #include <stdio.h> int main() { if (printf("%d", printf("))) printf("We are Happy"); else if (printf("1")) printf("We are Sad"); }

A. 0We are Happy

B. 1We are Happy

C. 1We are Sad

D. compile time error ✓

Answer: Option D — compile time error

Q470. What will be the output of the following C code? #include <stdio.h> void main() { int k = 0; for (k < 3; k++) printf("Hello"); }

A. Compile time error ✓

B. Hello is printed thrice

C. Nothing

D. Varies

Answer: Option A — Compile time error

Q471. What will be the output of the following C code? #include <stdio.h> const int a = 1, b = 2; int main() { int x = 1; switch (x) { case a: printf("yes "); case b: printf("no\n"); break; } }

A. yes no

B. yes

C. no

D. Compile time error ✓

Answer: Option D — Compile time error

Q472. What will be the output of the following C code? #include <stdio.h> void main() { int x = 5; if (x < 1); printf("Hello"); }

A. Nothing

B. Run time error

C. Hello ✓

D. Varies

Answer: Option C — Hello

Q473. What will be the output of the following C code? #include <stdio.h> int main() { int a = 0, i = 0, b; for (i = 0;i < 5; i++) { a++; continue; } }

A. 2

B. 3

C. 4

D. 5 ✓

Answer: Option D — 5

Q474. What will be the output of the following C code? #include <stdio.h> int main() { printf("%d ", 1); l1:l2: printf("%d ", 2); printf("%d\n", 3); }

A. Compilation error

B. 1 2 3 ✓

C. 1 2

D. 1 3

Answer: Option B — 1 2 3

Q475. What will be the output of the following C code? #include <stdio.h> int main() { int i = 0; while (i = 0) printf("True\n"); printf("False\n"); }

A. True (infinite time)

B. True (1 time) False

C. False ✓

D. Compiler dependent

Answer: Option C — False

Q476. The C statement ""if (a == 1 || b == 2) {}"" can be re-written as . . . . . .

A. if (a == 1) if (b == 2){}

B. if (a == 1){} if (b == 2){}

C. if (a == 1){} else if (b == 2){}

D. none of the mentioned ✓

Answer: Option D — none of the mentioned

Q477. goto can be used to jump from main() to within a function.

A. true

B. false ✓

C. depends

D. varies

Answer: Option B — false

Q478. What will be the output of the following C code? #include <stdio.h> int main() { int x = 0; if (x++) printf("true\n"); else if (x == 1) printf("false\n"); }

A. true

B. false ✓

C. compile time error

D. undefined behaviour

Answer: Option B — false

Q479. What will be the output of the following C code? #include <stdio.h> int main() { int a = 1; if (a) printf("All is Well "); printf("I am Well\n"); else printf("I am not a River\n"); }

A. Output will be All is Well I am Well

B. Output will be I am Well I am not a River

C. Output will be I am Well

D. Compile time errors during compilation ✓

Answer: Option D — Compile time errors during compilation

Q480. Which keyword is used to come out of a loop only for that iteration?

A. break

B. continue ✓

C. return

D. none of the mentioned

Answer: Option B — continue

Q481. What will be the output of the following C code? #include <stdio.h> int main() { printf("before continue "); continue; printf("after continue\n"); }

A. Before continue after continue

B. Before continue

C. After continue

D. Compile time error ✓

Answer: Option D — Compile time error

Q482. What will be the output of the following C code? #include <stdio.h> int main() { int a = 0, i = 0, b; for (i = 0;i < 5; i++) { a++; if (i == 3) break; } }

A. 1

B. 2

C. 3

D. 4 ✓

Answer: Option D — 4

Q483. What will be the output of the following C code? #include <stdio.h> switch (ch) { case 'a': case 'A': printf("true"); }

A. if (ch == 'a' && ch == 'A') printf("true");

B. if (ch == 'a') if (ch == 'a') printf("true");

C. if (ch == 'a' || ch == 'A') printf("true"); ✓

D. none of the mentioned

Answer: Option C — if (ch == 'a' || ch == 'A') printf("true");

Q484. How many times while loop condition is tested in the following C code snippets, if i is initialized to 0 in both the cases? while (i < n) i++; ————- do i++; while (i <= n);

A. n, n

B. n, n+1

C. n+1, n

D. n+1, n+1 ✓

Answer: Option D — n+1, n+1

Q485. What will be the output of the following C code? #include <stdio.h> #define max(a) a int main() { int x = 1; switch (x) { case max(2): printf("yes\n"); case max(1): printf("no\n"); break; } }

A. yes no

B. yes

C. no ✓

D. Compile time error

Answer: Option C — no

Function

Q486. In C, what is a function primarily used for?

A. Decision making

B. Variable declaration

C. Code organization and reusability ✓

D. Printing output

Answer: Option C — Code organization and reusability

Q487. What is the purpose of a function prototype in C?

A. To declare a function's return type

B. To declare a function's name

C. To declare a function's parameters and return type

D. To declare a function's name and parameters ✓

Answer: Option D — To declare a function's name and parameters

Q488. What is the result of the expression sqrt(16) in C, assuming proper inclusion of the math library?

A. 4 ✓

B. 8

C. 2

D. Error

Answer: Option A — 4

Q489. In C, how are function arguments passed by default?

A. By value ✓

B. By reference

C. By pointer

D. By address

Answer: Option A — By value

Q490. What is the correct way to declare a function in C that takes no arguments and returns an integer?

A. int func();

B. func(int);

C. func(); ✓

D. int func(int);

Answer: Option C — func();

Q491. In C, what is the purpose of the 'return' statement in a function?

A. To declare the function's return type

B. To exit the program

C. To return a value from the function ✓

D. To define a function

Answer: Option C — To return a value from the function

Q492. Which of the following is not a standard C library function for mathematical operations?

A. pow

B. rand ✓

C. sqrt

D. abs

Answer: Option B — rand

Q493. What is the main advantage of using functions in C?

A. Reducing code redundancy and improving code organization ✓

B. Increasing program speed

C. Eliminating the need for variables

D. Reducing memory usage

Answer: Option A — Reducing code redundancy and improving code organization

Q494. What is a function's return type in C if it does not return any value?

A. int

B. void ✓

C. float

D. char

Answer: Option B — void

Q495. In C, what is a function parameter?

A. A variable declared within a function ✓

B. A value passed to a function when it's called

C. A variable declared globally

D. A reserved keyword

Answer: Option A — A variable declared within a function

Q496. How is the scope of a local variable defined in C?

A. Limited to the function where it is declared ✓

B. Limited to the entire program

C. Limited to the block where it is declared

D. Limited to the main() function

Answer: Option A — Limited to the function where it is declared

Q497. What is a recursive function in C?

A. A function that calls itself ✓

B. A function that uses a loop

C. A function that returns a large value

D. A function that takes no arguments

Answer: Option A — A function that calls itself

Q498. What is the result of the expression abs(-5) in C?

A. -5

B. 5 ✓

C. 0

D. Error

Answer: Option B — 5

Q499. In C, what is a function definition?

A. A declaration that specifies a function's name, return type, and parameters

B. A declaration that specifies a function's name and return type

C. A block of code that specifies a function's behavior ✓

D. A variable declared within a function

Answer: Option C — A block of code that specifies a function's behavior

Q500. What is the purpose of the 'extern' keyword when declaring a function in C?

A. To specify that the function is not defined in the current file ✓

B. To declare a function as a constant

C. To declare a function with a variable number of arguments

D. To specify that the function is recursive

Answer: Option A — To specify that the function is not defined in the current file

---

Q501. What is the purpose of the 'static' keyword when used with a function in C?

A. To make the function return a static value

B. To specify that the function can only be called once

C. To limit the function's visibility to the current source file ✓

D. To make the function public

Answer: Option C — To limit the function's visibility to the current source file

Q502. In C, what is the purpose of the 'void' keyword as a function return type?

A. It specifies that the function doesn't return a value ✓

B. It specifies that the function returns an integer

C. It specifies that the function returns a character

D. It specifies that the function is recursive

Answer: Option A — It specifies that the function doesn't return a value

Q503. How do you call a function named myFunction with two arguments in C?

A. myFunction(5, 10); ✓

B. myFunction();

C. myFunction(5)(10);

D. myFunction[5, 10];

Answer: Option A — myFunction(5, 10);

Q504. In C, what is a function's prototype?

A. A function's name and return type

B. A declaration that specifies a function's name and parameters ✓

C. A function's documentation

D. A function's source code

Answer: Option B — A declaration that specifies a function's name and parameters

Q505. What is the result of the expression floor(5.7) in C, assuming proper inclusion of the math library?

A. 5 ✓

B. 6

C. 0.7

D. Error

Answer: Option A — 5

Q506. In C, what is the purpose of the 'inline' keyword when used with a function?

A. To indicate that the function should be inlined by the compiler ✓

B. To specify that the function is only used in one file

C. To make the function public

D. To declare a recursive function

Answer: Option A — To indicate that the function should be inlined by the compiler

Q507. What is a function parameter in C?

A. A value passed to a function when it's called ✓

B. A variable declared within a function

C. A reserved keyword

D. A global variable

Answer: Option A — A value passed to a function when it's called

Q508. What is the result of the expression ceil(3.2) in C, assuming proper inclusion of the math library?

A. 3

B. 4 ✓

C. 0.2

D. Error

Answer: Option B — 4

Q509. In C, what is the purpose of the 'const' keyword when used with a function parameter?

A. It specifies that the parameter is constant and cannot be modified ✓

B. It makes the parameter mandatory

C. It makes the parameter optional

D. It specifies that the parameter is a constant function

Answer: Option A — It specifies that the parameter is constant and cannot be modified

Q510. How can you declare a function in C that takes a variable number of arguments?

A. Using the 'variable' keyword

B. Using the 'args' keyword

C. Using the '...' notation ✓

D. Using the 'varargs' keyword

Answer: Option C — Using the '...' notation

Q511. In C, what is the purpose of the 'recursion' in a function?

A. To create an infinite loop

B. To make the function faster

C. To make the function return a constant value

D. To call the function itself ✓

Answer: Option D — To call the function itself

Q512. What is the result of the expression pow(2, 3) in C, assuming proper inclusion of the math library?

A. 5

B. 6

C. 8 ✓

D. Error

Answer: Option C — 8

Q513. What is the purpose of the 'volatile' keyword when used with a function in C?

A. To make the function execute faster

B. To specify that the function is unpredictable

C. To optimize the function

D. To indicate that the function may change external variables ✓

Answer: Option D — To indicate that the function may change external variables

Q514. What is the result of the expression abs(-7.5) in C?

A. -7.5

B. 7.5

C. 7

D. Error ✓

Answer: Option D — Error

Q515. In C, what is a function parameter's scope?

A. Limited to the function where it is declared ✓

B. Limited to the entire program

C. Limited to the block where it is declared

D. Limited to the main() function

Answer: Option A — Limited to the function where it is declared

---

Q516. What will happen after compiling and running following code? main() { printf("%p", main); }

A. Error

B. Will make an infinite loop.

C. Some address will be printed. ✓

D. None of these.

Answer: Option C — Some address will be printed.

Q517. Use of functions

A. Helps to avoid repeating a set of statements many times.

B. Enhances the logical clarity of the program.

C. Helps to avoid repeated programming across programs.

D. Makes the debugging task easier.

E. All of the above ✓

Answer: Option E — All of the above

Q518. Any C program

A. Must contain at least one function. ✓

B. Need not contain any function.

C. Needs input data.

D. None of the above

Answer: Option A — Must contain at least one function.

Q519. What is function?

A. Function is a block of statements that perform some specific task.

B. Function is the fundamental modular unit. A function is usually designed to perform a specific task.

C. Function is a block of code that performs a specific task. It has a name and it is reusable.

D. All of the above ✓

Answer: Option D — All of the above

Q520. Determine output: main() { int i = abc(10); printf("%d", --i); } int abc(int i) { return(i++); }

A. 10

B. 9 ✓

C. 11

D. None of these.

Answer: Option B — 9

Q521. The default parameter passing mechanism is

A. call by value ✓

B. call by reference

C. call by value result

D. None of these.

Answer: Option A — call by value

Q522. What is the result of compiling and running this code? main() { char string[] = "Hello World"; display(string); } void display(char *string) { printf("%s", string); }

A. will print Hello World

B. Compilation Error ✓

C. will print garbage value

D. None of these.

Answer: Option B — Compilation Error

Q523. Determine output: main() { int i = 5; printf("%d%d%d%d%d", i++, i--, ++i, --i, i); }

A. 54544

B. 45445

C. 54554

D. 45545 ✓

Answer: Option D — 45545

Q524. Pick the correct statements. I. The body of a function should have only one return statement. II. The body of a function may have many return statements. III. A function can return only one value to the calling environment. IV. If return statement is omitted, then the function does its job but returns no value to the calling environment.

A. I and II

B. I and III

C. II and III ✓

D. II and IV

E. III and IV

Answer: Option C — II and III

Q525. What will be the output of the following program code? main() { static int var = 5; printf("%d ", var--); if(var) main(); }

A. 5 5 5 5 5

B. 5 4 3 2 1 ✓

C. Infinite Loop

D. Compilation Error

E. None of these

Answer: Option B — 5 4 3 2 1

Q526. Which of the following is a complete function?

A. int funct();

B. int funct(int x) { return x=x+1; } ✓

C. void funct(int) { printf("Hello"); }

D. void funct(x) { printf("Hello"); }

E. None of these

Answer: Option B — int funct(int x) { return x=x+1; }

Q527. What will be printed when this program is executed? int f(int x) { if(x <= 4) return x; return f(--x); } void main() { printf("%d ", f(7)); }

A. 4 5 6 7

B. 1 2 3 4

C. 4 ✓

D. Syntax error

E. Runtime error

Answer: Option C — 4

Q528. The recursive functions are executed in a .....

A. Parallel order

B. First In First Out order

C. Last In First Out order ✓

D. Iterative order

E. Random order

Answer: Option C — Last In First Out order

Q529. The function scanf() returns .....

A. The actual values read for each argument.

B. 1

C. 0

D. The number of successful read input values. ✓

E. ASCII value of the input read.

Answer: Option D — The number of successful read input values.

Q530. Functions have .....

A. Local scope

B. Block scope

C. File scope ✓

D. Function scope

E. No scope at all

Answer: Option C — File scope

Q531. Which of the following function calculates the square of 'x' in C?

A. sqr(x)

B. pow(2, x)

C. pow(x, 2) ✓

D. power(2, x)

E. power(x, 2)

Answer: Option C — pow(x, 2)

Q532. When a function is recursively called all the automatic variables are stored in a .....

A. Stack ✓

B. Queue

C. Array

D. Linked list

E. Register

Answer: Option A — Stack

Q533. char* myfunc(char *ptr) { ptr+=3; return(ptr); } void main() { char *x, *y; x = "EXAMVEDA"; y = myfunc(x); printf("y=%s", y); } What will be printed when the sample code above is executed?

A. y=EXAMVEDA

B. y=MVEDA ✓

C. y=VEDA

D. y=EDA

E. y=AMVEDA

Answer: Option B — y=MVEDA

Q534. What will be the output of the following C code? #include <stdio.h> #define foo(x, y) #x #y int main() { printf("%s\n", foo(k, l)); return 0; }

A. kl ✓

B. k l

C. xy

D. Compile time error

Answer: Option A — kl

Q535. What will be the output of the following C code? #include <stdio.h> double var = 8; int main() { int var = 5; printf("%d", var); }

A. 5 ✓

B. 8

C. Compile time error due to wrong format identifier for double

D. Compile time error due to redeclaration of variable with same name

Answer: Option A — 5

Q536. What will be the output of the following C code? #include <stdio.h> int x = 5; void main() { int x = 3; printf("%d", x); { x = 4; } printf("%d", x); }

A. Run time error

B. 3 3

C. 3 5

D. 3 4 ✓

Answer: Option D — 3 4

Q537. Which part of the program address space is p stored in the following C code? #include <stdio.h> int *p = NULL; int main() { int i = 0; p = &i; return 0; }

A. Code/text segment

B. Data segment ✓

C. Bss segment

D. Stack

Answer: Option B — Data segment

Q538. What would happen if you create a file stdio.h and use #include "stdio.h"?

A. The predefined library file will be selected

B. The user-defined library file will be selected ✓

C. Both the files will be included

D. The compiler won't accept the program

Answer: Option B — The user-defined library file will be selected

Q539. What will be the output of the following C code? #include <stdio.h> int x; void main() { printf("%d", x); }

A. Junk value

B. Run time error

C. 0 ✓

D. Undefined

Answer: Option C — 0

Q540. Automatic variables are initialized to . . . . . .

A. Zero

B. Junk value ✓

C. Nothing

D. Both Zero & Junk value

Answer: Option B — Junk value

Q541. What will be the output of the following C code? #include <stdio.h> #define MIN 0 #if defined(MIN) + defined(MAX) #define MAX 10 #endif int main() { printf("%d %d\n", MAX, MIN); return 0; }

A. 10 0 ✓

B. Compile time error

C. Undefined behaviour

D. Somegarbagevalue 0

Answer: Option A — 10 0

Q542. Functions can return enumeration constants in C?

A. true ✓

B. false

C. depends on the compiler

D. depends on the standard

Answer: Option A — true

Q543. What will be the output of the following C code? #include <stdio.h> int foo(int, int); #define foo(x, y) x / y + x int main() { int i = -6, j = 3; printf("%d ",foo(i + j, 3)); #undef foo printf("%d\n",foo(i + j, 3)); } int foo(int x, int y) { return x / y + x; }

A. -8 -4 ✓

B. Compile time error

C. -8 -8

D. Undefined behaviour

Answer: Option A — -8 -4

Q544. What will be the output of the following C code? #include <stdio.h> int x; void main() { m(); printf("%d", x); } void m() { x = 4; }

A. 0

B. 4 ✓

C. Compile time error

D. Undefined

Answer: Option B — 4

Q545. What will be the output of the following C code? #include <stdio.h> int foo(); int main() { int i = foo(); } foo() { printf("2 "); return 2; }

A. 2 ✓

B. Compile time error

C. Depends on the compiler

D. Depends on the standard

Answer: Option A — 2

Q546. Which of following is not accepted in C?

A. static a = 10; //static as

B. static int func (int); //parameter as static

C. static static int a; //a static variable prefixed with static ✓

D. all of the mentioned

Answer: Option C — static static int a; //a static variable prefixed with static

Q547. What will be the output of the following C code? #include <stdio.h> int *m(); void main() { int k = m(); printf("%d", k); } int *m() { int a[2] = {5, 8}; return a; }

A. 5

B. 8

C. Nothing

D. Varies ✓

Answer: Option D — Varies

Q548. Global variables are . . . . . .

A. Internal

B. External ✓

C. Both Internal and External

D. None of the mentioned

Answer: Option B — External

Q549. What is the scope of an automatic variable?

A. Within the block it appears

B. Within the blocks of the block it appears

C. Until the end of program

D. Within the block it appears & Within the blocks of the block it appears ✓

Answer: Option D — Within the block it appears & Within the blocks of the block it appears

Q550. What will be the output of the following C code having void return-type function? #include <stdio.h> void foo() { return 1; } void main() { int x = 0; x = foo(); printf("%d", x); }

A. 1

B. 0

C. Runtime error

D. Compile time error ✓

Answer: Option D — Compile time error

Q551. If the file name is enclosed in double quotation marks, then . . . . . .

A. The preprocessor treats it as a user-defined file ✓

B. The preprocessor treats it as a system-defined file

C. The preprocessor treats it as a user-defined file & system-defined file

D. None of the mentioned

Answer: Option A — The preprocessor treats it as a user-defined file

Q552. What will be the output of the following C code? #include <stdio.h> void foo(); int main() { void foo(); foo(); return 0; } void foo() { printf("2 "); }

A. Compile time error

B. 2 ✓

C. Depends on the compiler

D. Depends on the standard

Answer: Option B — 2

Q553. Which of the following storage class supports char data type?

A. register

B. static

C. auto

D. all of the mentioned ✓

Answer: Option D — all of the mentioned

Q554. register keyword mandates compiler to place it in machine register.

A. True

B. False ✓

C. Depends on the standard

D. None of the mentioned

Answer: Option B — False

Q555. What will be the output of the following C code? #include <stdio.h> #define SYSTEM 20 int main() { int a = 20; #if SYSTEM == a printf("HELLO "); #endif #if SYSTEM == 20 printf("WORLD\n"); #endif }

A. HELLO

B. WORLD ✓

C. HELLO WORLD

D. No Output

Answer: Option B — WORLD

Q556. Functions have static qualifier for its declaration by default.

A. True

B. False ✓

C. Depends on the compiler

D. Depends on the standard

Answer: Option B — False

Q557. Can we use a function as a parameter of another function? [Eg: void wow(int func())].

A. Yes, and we can use the function value conveniently

B. Yes, but we call the function again to get the value, not as convenient as in using variable

C. No, C does not support it ✓

D. This case is compiler dependent

Answer: Option C — No, C does not support it

Q558. What will be the output of the following C code? #include <stdio.h> void main() { static int x; if (x++ < 2) main(); }

A. Infinite calls to main

B. Run time error

C. Varies

D. main is called twice ✓

Answer: Option D — main is called twice

Q559. Assignment statements assigning value to local static variables are executed only once.

A. True

B. False ✓

C. Depends on the code

D. None of the mentioned

Answer: Option B — False

Q560. The #else directive is used for . . . . . .

A. Conditionally include source text if the previous #if, #ifdef, #ifndef, or #elif test fails ✓

B. Conditionally include source text if a macro name is not defined

C. Conditionally include source text if a macro name is defined

D. Ending conditional text

Answer: Option A — Conditionally include source text if the previous #if, #ifdef, #ifndef, or #elif test fails

---

Q561. What will be the output of the following C code? #include <stdio.h> void foo(auto int i); int main() { foo(10); } void foo(auto int i) { printf("%d\n", i); }

A. 10

B. Compile time error ✓

C. Depends on the standard

D. None of the mentioned

Answer: Option B — Compile time error

Q562. Conditional inclusion can be used for . . . . . .

A. Preventing multiple declarations of a variable

B. Check for existence of a variable and doing something if it exists

C. Preventing multiple declarations of same function

D. All of the mentioned ✓

Answer: Option D — All of the mentioned

Q563. What will be the output of the following C code? #include <stdio.h> void main() { { int x = 8; } printf("%d", x); }

A. 8

B. 0

C. Undefined

D. Compile time error ✓

Answer: Option D — Compile time error

Q564. Comment on the output of the following C code. #include <stdio.h> #define var 20); int main() { printf("%d\n", var }

A. No errors, it will show the output 20 ✓

B. Compile time error, the printf braces aren't closed

C. Compile time error, there are no open braces in #define

D. None of the mentioned

Answer: Option A — No errors, it will show the output 20

Q565. What will be the sequence of allocation and deletion of variables in the following C code? #include <stdio.h> int main() { int a; { int b; } }

A. a->b, a->b

B. a->b, b->a ✓

C. b->a, a->b

D. b->a, b->a

Answer: Option B — a->b, b->a

Q566. What will be the output of the following C code? #include <stdio.h> enum m{JAN, FEB, MAR}; enum m foo(); int main() { enum m i = foo(); printf("%d\n", i); } int foo() { return JAN; }

A. Compile time error ✓

B. 0

C. Depends on the compiler

D. Depends on the standard

Answer: Option A — Compile time error

Q567. C preprocessor is conceptually the first step during compilation.

A. True ✓

B. False

C. Depends on the compiler

D. Depends on the standard

Answer: Option A — True

Q568. What will be the output of the following C code? #include <stdio.h> int main() { register const int i = 10; i = 11; printf("%d\n", i); }

A. 10

B. Compile time error ✓

C. Undefined behaviour

D. 11

Answer: Option B — Compile time error

Q569. What will be the output of the following C code? #include <stdio.h> #define foo(m, n) m * n = 10 int main() { printf("in main\n"); }

A. In main ✓

B. Compilation error as lvalue is required for the expression m*n=10

C. Preprocessor error as lvalue is required for the expression m*n=10

D. None of the mentioned

Answer: Option A — In main

Q570. What will be the output of the following C code? #include <stdio.h> #define MIN 0); #ifdef MIN #define MAX 10 #endif int main() { printf("%d %d\n", MAX, MIN return 0; }

A. 10 0 ✓

B. Compile time error due to illegal syntax for printf

C. Undefined behaviour

D. Compile time error due to illegal MIN value

Answer: Option A — 10 0

Q571. Which among the following is wrong for "register int a;"?

A. Compiler generally ignores the request

B. You cannot take the address of this variable

C. Access time to a is critical

D. None of the mentioned ✓

Answer: Option D — None of the mentioned

Q572. What will be the output of the following C code? #include <stdio.h> void main() { #define max 45 max = 32; printf("%d", max); }

A. 32

B. 45

C. Compile time error ✓

D. Varies

Answer: Option C — Compile time error

Q573. Array sizes are optional during array declaration by using . . . . . keyword.

A. auto

B. static

C. extern ✓

D. register

Answer: Option C — extern

Q574. What will be the output of the following C code? #include <stdio.h> int i; int main() { extern int i; if (i == 0) printf("scope rules\n"); }

A. scope rules ✓

B. Compile time error due to multiple declaration

C. Compile time error due to not defining type in statement extern i

D. Nothing will be printed as value of i is not zero because i is an automatic variable

Answer: Option A — scope rules

Q575. How is search done in #include and #include"somelibrary.h" normally or conventionally?

A. When former is used, current directory is searched and when latter is used, standard directory is searched

B. When former is used, predefined directory is searched and when latter is used, current directory is searched and then predefined directories are searched ✓

C. When former is used, search is done in implementation defined manner and latter is used to search current directory

D. For both, search for somelibrary is done in implementation-defined manner

Answer: Option B — When former is used, predefined directory is searched and when latter is used, current directory is searched and then predefined directories are searched

---

Q576. What will be the output of the following C code? #include <stdio.h> void main() { #define const int const max = 32; printf("%d", max); }

A. Run time error

B. 32 ✓

C. int

D. const

Answer: Option B — 32

Q577. What will be the output of the following C code? #include <stdio.h> #define MIN 0 #ifdef(MIN) #define MAX 10 #endif int main() { printf("%d %d\n", MAX, MIN); return 0; }

A. 10 0

B. Compile time error

C. Run time error

D. Preprocessor error ✓

Answer: Option D — Preprocessor error

Q578. What will be the output of the following C code? #include <stdio.h> int main() { register int i = 10; int *p = &i; *p = 11; printf("%d %d\n", i, *p); }

A. Depends on whether i is actually stored in machine register

B. 10 10

C. 11 11

D. Compile time error ✓

Answer: Option D — Compile time error

Q579. The #elif directive cannot appear after the preprocessor #else directive.

A. True ✓

B. False

Answer: Option A — True

Q580. Preprocessor feature that supply line numbers and filenames to compiler is called?

A. Selective inclusion

B. macro substitution

C. Concatenation

D. Line control ✓

Answer: Option D — Line control

Q581. Which function definition will run correctly?

A. int sum(int a, int b) return (a + b);

B. int sum(int a, int b) {return (a + b);} ✓

C. int sum(a, b) return (a + b);

D. none of the mentioned

Answer: Option B — int sum(int a, int b) {return (a + b);}

Q582. #pragma exit is primarily used for?

A. Checking memory leaks after exiting the program

B. Informing Operating System that program has terminated

C. Running a function at exiting the program ✓

D. No such preprocessor exist

Answer: Option C — Running a function at exiting the program

Q583. Which data type can be stored in register?

A. int

B. long

C. float

D. all of the mentioned ✓

Answer: Option D — all of the mentioned

Q584. What will be the output of the following C code? #include <stdio.h> void m(); void n() { m(); } void main() { void m() { printf("hi"); } }

A. hi

B. Compile time error ✓

C. Nothing

D. Varies

Answer: Option B — Compile time error

Q585. What will be the output of the following C code? #include <stdio.h> void main() { register int x = 5; m(); printf("x is %d", x); } void m() { x++; }

A. 6

B. 5

C. Junk value

D. Compile time error ✓

Answer: Option D — Compile time error

Pointer

Q586. In C, what is a pointer primarily used for?

A. Decision making

B. Code organization

C. Variable declaration ✓

D. Storing values

Answer: Option C — Variable declaration

Q587. What is the result of the expression sizeof(int*) in C, assuming an int pointer on a typical system?

A. 4 ✓

B. 8

C. 2

D. 1

Answer: Option A — 4

Q588. In C, how do you declare a pointer variable that can store the address of an integer?

A. int *ptr; ✓

B. ptr int;

C. int ptr;

D. ptr *int;

Answer: Option A — int *ptr;

Q589. What is the purpose of the '->' operator in C when used with pointers?

A. Arithmetic operation

B. Indirection operator

C. Member access operator ✓

D. Bitwise operation

Answer: Option C — Member access operator

Q590. In C, what is the value of a pointer variable if it hasn't been assigned any address?

A. 0

B. Null

C. Undefined ✓

D. 1

Answer: Option C — Undefined

Q591. What is the result of the expression *ptr in C, where ptr is a pointer to an int?

A. Address of ptr

B. Value pointed to by ptr ✓

C. Size of ptr

D. Type of ptr

Answer: Option B — Value pointed to by ptr

Q592. In C, what is the purpose of the 'void' pointer type (void*)?

A. To store any data type's address ✓

B. To declare a pointer as uninitialized

C. To make a pointer point to null

D. To create a generic function

Answer: Option A — To store any data type's address

Q593. How do you declare a pointer to a function that takes two integers and returns an integer in C?

A. int (*ptr)(int, int); ✓

B. ptr(int, int) int;

C. function int (*ptr)(int, int);

D. ptr function(int, int) int;

Answer: Option A — int (*ptr)(int, int);

Q594. What is the result of the expression ptr++ in C, where ptr is a pointer?

A. Increase the value of ptr by 1

B. Decrease the value of ptr by 1

C. Move ptr to the next memory location ✓

D. It's not a valid operation

Answer: Option C — Move ptr to the next memory location

Q595. In C, what is the purpose of the 'const' keyword when used with a pointer declaration?

A. To declare a constant pointer

B. To make the pointer point to a constant value ✓

C. To make the pointer constant

D. To prevent pointer declaration

Answer: Option B — To make the pointer point to a constant value

---

Q596. What is the result of the expression &variable in C, where variable is a variable of type int?

A. Address of variable ✓

B. Value of variable

C. Size of variable

D. Type of variable

Answer: Option A — Address of variable

Q597. In C, what is a double pointer (int)?**

A. A pointer to an integer

B. A pointer that can store two addresses

C. A pointer to a pointer ✓

D. A pointer to a double data type

Answer: Option C — A pointer to a pointer

Q598. What is the result of the expression ptr = NULL in C, where ptr is a pointer?

A. Initialize ptr to 0 ✓

B. Delete the pointer ptr

C. Set ptr to a random address

D. It's not a valid operation

Answer: Option A — Initialize ptr to 0

Q599. In C, what is the purpose of the 'malloc' function?

A. Allocate memory on the stack

B. Allocate memory on the heap ✓

C. Allocate memory for a function

D. Allocate memory for a variable

Answer: Option B — Allocate memory on the heap

Q600. What is the result of the expression *NULL in C?

A. Error ✓

B. Null pointer dereference

C. 0

D. Undefined

Answer: Option A — Error

Q601. In C, what is the purpose of the 'memcpy' function?

A. Copy the contents of one pointer to another

B. Copy the contents of one memory location to another ✓

C. Create a new pointer

D. Swap two pointers

Answer: Option B — Copy the contents of one memory location to another

Q602. What is the result of the expression sizeof(char*) in C, assuming a char pointer on a typical system?

A. 4 ✓

B. 8

C. 2

D. 1

Answer: Option A — 4

Q603. In C, how do you declare an array of pointers to integers?

A. int* arr[]; ✓

B. arr int*[];

C. int arr*[];

D. int[]* arr;

Answer: Option A — int* arr[];

Q604. What is the purpose of the 'free' function in C when used with pointers?

A. Allocate memory

B. Deallocate memory ✓

C. Create a new pointer

D. Modify the pointer's value

Answer: Option B — Deallocate memory

Q605. In C, what is a pointer to a constant value (const int*)?

A. A pointer that cannot be modified

B. A pointer that points to a constant value

C. A constant pointer

D. A pointer to a constant value ✓

Answer: Option D — A pointer to a constant value

Q606. What is the result of the expression ptr-- in C, where ptr is a pointer?

A. Decrease the value of ptr by 1

B. Increase the value of ptr by 1

C. Move ptr to the previous memory location ✓

D. It's not a valid operation

Answer: Option C — Move ptr to the previous memory location

Q607. In C, what is a function pointer?

A. A pointer that points to a function ✓

B. A pointer returned by a function

C. A pointer to a variable

D. A constant pointer

Answer: Option A — A pointer that points to a function

Q608. What is the result of the expression &array[0] in C, where array is an integer array?

A. Address of the first element in the array ✓

B. Value of the first element in the array

C. Size of the array

D. Type of the array

Answer: Option A — Address of the first element in the array

Q609. In C, what is a null pointer (NULL or 0)?

A. A pointer that points to the address 0 ✓

B. A pointer that points to a null value

C. A pointer with an undefined value

D. A pointer to a null object

Answer: Option A — A pointer that points to the address 0

Q610. What is the result of the expression ptr += 2 in C, where ptr is a pointer?

A. Increase ptr by 2

B. Decrease ptr by 2

C. Move ptr two memory locations forward ✓

D. It's not a valid operation

Answer: Option C — Move ptr two memory locations forward

Q611. In C, what is the purpose of the 'calloc' function?

A. Allocate memory on the stack

B. Allocate memory on the heap

C. Allocate memory for a function

D. Allocate memory for an array of variables ✓

Answer: Option D — Allocate memory for an array of variables

Q612. What is the result of the expression *ptr = 42 in C, where ptr is a pointer to an int?

A. Set the value pointed to by ptr to 42 ✓

B. Set the address pointed to by ptr to 42

C. Set the size of ptr to 42

D. Set ptr to a null value

Answer: Option A — Set the value pointed to by ptr to 42

Q613. In C, what is a pointer to a function that takes no arguments and returns an integer?

A. int (*ptr)(); ✓

B. ptr int();

C. int ptr();

D. ptr() int;

Answer: Option A — int (*ptr)();

Q614. What is the result of the expression *ptr = NULL in C, where ptr is a pointer?

A. Initialize ptr to 0

B. Delete the pointer ptr

C. Set the value pointed to by ptr to NULL ✓

D. It's not a valid operation

Answer: Option C — Set the value pointed to by ptr to NULL

Q615. In C, what is a pointer to a constant pointer (int* const)?

A. A pointer that cannot be modified

B. A pointer that points to a constant pointer ✓

C. A constant pointer to a constant integer

D. A pointer to a constant integer

Answer: Option B — A pointer that points to a constant pointer

---

Q616. Determine Output: void main() { char far *farther, *farthest; printf("%d..%d", sizeof(farther), sizeof(farthest)); }

A. 4..2

B. 2..2

C. 4..4 ✓

D. 2..4

Answer: Option C — 4..4

Q617. Determine Output: main() { char *str1 = "abcd"; char str2[] = "abcd"; printf("%d %d %d", sizeof(str1), sizeof(str2), sizeof("abcd")); }

A. 2 5 5

B. 2 4 4

C. 8 5 5 ✓

D. 2 4 5

Answer: Option C — 8 5 5

Q618. Choose the best answer. Prior to using a pointer variable

A. It should be declared.

B. It should be initialized.

C. It should be both declared and initialized. ✓

D. None of these.

Answer: Option C — It should be both declared and initialized.

Q619. Comment on the following pointer declaration? int * ptr, p;

A. ptr is a pointer to integer, p is not. ✓

B. ptr and p, both are pointers to integer.

C. ptr is pointer to integer, p may or may not be.

D. ptr and p both are not pointers to integer.

Answer: Option A — ptr is a pointer to integer, p is not.

Q620. What will be the output? main() { char *p; p = "Hello"; printf("%cn",*&*p); }

A. Hello

B. H ✓

C. Some address will be printed

D. None of these.

Answer: Option B — H

Q621. Determine output: #include <stdio.h> void main() { char *p = NULL; char *q = 0; if(p) printf(" p "); else printf("nullp"); if(q) printf("q"); else printf(" nullq"); }

A. p q

B. Depends on the compiler

C. x nullq where x can be p or nullp depending on the value of NULL

D. nullp nullq ✓

Answer: Option D — nullp nullq

Q622. The address operator & , cannot act on

A. R-values

B. Arithmetic expressions

C. Both of the above ✓

D. Local variables

E. Members of a structure

Answer: Option C — Both of the above

Q623. The statement int ** a;

A. is illegal

B. is legal but meaningless

C. is syntactically and semantically correct ✓

D. None of these.

Answer: Option C — is syntactically and semantically correct

Q624. What will be the output of the following program? #include<stdio.h> void main() { int i = 10; void *p = &i; printf("%d\n", (int)*p); }

A. Compiler time error ✓

B. Segmentation fault/runtime crash

C. 10

D. Undefined behavior

Answer: Option A — Compiler time error

Q625. What will be the output of the following program code? #include<stdio.h> void main() { int i = 10; void *p = &i; printf("%f", *(float *)p); }

A. Error

B. 10

C. 0.000000 ✓

D. None of these.

Answer: Option C — 0.000000

Q626. The operator > and < are meaningful when used with pointers, if

A. The pointers point to data of similar type.

B. The pointers point to structure of similar data type.

C. The pointers point to elements of the same array. ✓

D. None of these.

Answer: Option C — The pointers point to elements of the same array.

Q627. The declaration int (* p) [5] ; means

A. p is one dimensional array of size 5, of pointers to integers.

B. p is a pointer to a 5 elements integer array. ✓

C. The same as (*p) [5];

D. None of these.

Answer: Option B — p is a pointer to a 5 elements integer array.

Q628. Comment on the following? const int * ptr;

A. We cannot change the value pointed by ptr . ✓

B. We cannot change the pointer ptr itself.

C. Both of the above

D. We can change the pointer as well as the value pointed by it.

Answer: Option A — We cannot change the value pointed by ptr .

Q629. Determine Output: #include<stdio.h> void main() { int *ptr, a=10; ptr = &a; *ptr += 1; printf("%d, %d", *ptr, a); }

A. 10, 10

B. 10, 11

C. 11, 10

D. 11, 11 ✓

Answer: Option D — 11, 11

Q630. A function 'p' that accepts a pointer to a character as argument and returns a pointer to an array of integer can be declared as

A. int(*p(char *))[] ✓

B. int *p(char *)[]

C. int (*p) (char *)[]

D. None of these.

Answer: Option A — int(*p(char *))[]

Q631. What will be printed after compiling and running the following code? main() { char *p; printf("%d %d",sizeof(*p), sizeof(p)); }

A. 1 1

B. 1 2 ✓

C. 2 1

D. 2 2

Answer: Option B — 1 2

Q632. What will be the output of the following program code? #include <stdio.h> void main() { int i=3, *j, **k; j = &i; k = &j; printf("%d%d%d", *j, **k, *(*k)); }

A. 444

B. 000

C. 333 ✓

D. 433

E. Garbage Value

Answer: Option C — 333

Q633. Which of the following is the correct way of declaring a float pointer:

A. float ptr;

B. float * ptr; ✓

C. * float ptr;

D. None of the above

Answer: Option B — float * ptr;

Q634. Find the output of the following program. void main() { char *msg = "hi"; printf(msg); }

A. hi ✓

B. h

C. hi followed by garbage value

D. Error

E. Garbage Value

Answer: Option A — hi

Q635. Find the output of the following program. void main() { int array[10]; int *i = &array[2], *j = &array[5]; int diff = j-i; printf("%d", diff); }

A. 3 ✓

B. 6

C. Garbage value

D. Error

Answer: Option A — 3

Q636. Find the output of the following program. void main() { printf("%d, %d", sizeof(int *), sizeof(int **)); }

A. 2, 0

B. 0, 2

C. 2, 2 ✓

D. 2, 4

E. 4, 4

Answer: Option C — 2, 2

Q637. Find the output of the following program. void main() { int i=10; /* assume address of i is 0x1234ABCD */ int *ip=&i; int **ipp=&&i; printf("%x,%x,%x", &i, ip, *ipp); }

A. 0x1234ABCD, 0x1234ABCD, 10

B. 0x1234ABCD, 0x1234ABCD, 0x1234ABCD

C. 0x1234ABCD, 10, 10

D. Syntax error ✓

E. Runtime error

Answer: Option D — Syntax error

Q638. Which of the following statements are true after execution of the program. void main() { int a[10], i, *p; a[0] = 1; a[1] = 2; p = a; (*p)++; }

A. a[1] = 3

B. a[0] = 2 ✓

C. a[1] = 1

D. a[0] = 3

E. Compilation error

Answer: Option B — a[0] = 2

Q639. What is the base data type of a pointer variable by which the memory would be allocated to it?

A. int

B. float

C. No data type

D. Depends upon the type of the variable to which it is pointing.

E. unsigned int ✓

Answer: Option E — unsigned int

Q640. What would be the output for the following Turbo C code? #include<stdio.h> void main() { int a[]={ 1, 2, 3, 4, 5 }, *p; p=a; ++*p; printf("%d ", *p); p += 2; printf("%d", *p); }

A. 2 4

B. 3 4

C. 2 2

D. 2 3 ✓

E. 3 3

Answer: Option D — 2 3

Q641. char* myfunc(char *ptr) { ptr+=3; return(ptr); } void main() { char *x, *y; x = "EXAMVEDA"; y = myfunc(x); printf("y=%s", y); } What will be printed when the sample code above is executed?

A. y=EXAMVEDA

B. y=AMVEDA

C. y=MVEDA ✓

D. y=VEDA

E. y=EDA

Answer: Option C — y=MVEDA

Q642. char *ptr; char myString[] = "abcdefg"; ptr = myString; ptr += 5; what string does ptr point to in the sample code above?

A. fg ✓

B. efg

C. defg

D. cdefg

E. bcdefg

Answer: Option A — fg

Q643. What will be the output of the following C code? #include <stdio.h> int main() { int i = 10; int *p = &i; foo(&p); printf("%d ", *p); printf("%d ", *p); } void foo(int **const p) { int j = 11; *p = &j; printf("%d ", **p); }

A. 11 11 11

B. 11 11 Undefined-value ✓

C. Compile time error

D. Segmentation fault/code-crash

Answer: Option B — 11 11 Undefined-value

Q644. What will be the output of the following C code? #include <stdio.h> void main() { char *s= "hello"; char *p = s; printf("%c\t%c", *(p + 3), s[1]); }

A. h e

B. l l

C. l o

D. l e ✓

Answer: Option D — l e

Q645. What will be the output of the following C code? #include <stdio.h> void main() { int a[3] = {1, 2, 3}; int *p = a; int **r = &p; printf("%p %p", *r, a); }

A. Different address is printed

B. 1 2

C. Same address is printed ✓

D. 1 1

Answer: Option C — Same address is printed

Q646. What will be the output of the following C code? #include <stdio.h> void main() { char *s = "hello"; char *p = s * 3; printf("%c\t%c", *p, s[1]); }

A. h e

B. l e

C. Compile time error ✓

D. l h

Answer: Option C — Compile time error

Q647. Which of the following operation is possible using a pointer char? (Assuming the declaration is char *a;)

A. Input via %s

B. Generation of the multidimensional array

C. Changing address to point at another location ✓

D. All of the mentioned

Answer: Option C — Changing address to point at another location

Q648. Comment on the following C statement. int (*a)[7];

A. An array "a" of pointers

B. A pointer "a" to an array ✓

C. A ragged array

D. None of the mentioned

Answer: Option B — A pointer "a" to an array

Q649. What will be the output of the following C code? #include <stdio.h> int main() { int *p = (int *)2; int *q = (int *)3; printf("%d", p + q); }

A. 2

B. 3

C. 5

D. Compile time error ✓

Answer: Option D — Compile time error

Q650. Which of the following statements are true? P. Pointer to Array Q. Multi-dimensional array

A. P are static, Q are static

B. P are static, Q are dynamic

C. P are dynamic, Q are static ✓

D. P are dynamic, Q are dynamic

Answer: Option C — P are dynamic, Q are static

Q651. What will be the output of the following C code? #include <stdio.h> void main() { char *s= "hello"; char *p = s; printf("%c\t%c", p[0], s[1]); }

A. Run time error

B. h h

C. h e ✓

D. h l

Answer: Option C — h e

Q652. What will be the output of the following C code (run without any command line arguments)? #include <stdio.h> int main(int argc, char *argv[]) { while (argc--) printf("%s\n", argv[argc]); return 0; }

A. Compile time error

B. Executablefilename ✓

C. Segmentation fault

D. Undefined

Answer: Option B — Executablefilename

Q653. What will be the output of the following C code? #include <stdio.h> int main() { int a[4] = {1, 2, 3, 4}; int *p = &a[1]; int *ptr = &a[2]; ptr = ptr * 1; printf("%d\n", *ptr); }

A. 2

B. 1

C. Compile time error ✓

D. Undefined behaviour

Answer: Option C — Compile time error

Q654. What will be the output of the following C code? #include <stdio.h> void f(char *k) { k++; k[2] = 'm'; } void main() { char s[] = "hello"; f(s); printf("%c\n", *s); }

A. h ✓

B. e

C. m

D. o;

Answer: Option A — h

Q655. Which of the following is not possible statically in C?

A. Jagged Array ✓

B. Rectangular Array

C. Cuboidal Array

D. Multidimensional Array

Answer: Option A — Jagged Array

Q656. What will be the output of the following C code? #include <stdio.h> int main() { int i = 10; void *p = &i; printf("%d\n", (int)*p); return 0; }

A. Compile time error ✓

B. Segmentation fault/runtime crash

C. 10

D. Undefined behaviour

Answer: Option A — Compile time error

Q657. What will be the output of the following C code? #include <stdio.h> void main() { char *a[10] = {"hi", "hello", "how"}; int i = 0; for (i = 0;i < 10; i++) printf("%s", *(a[i])); }

A. segmentation fault ✓

B. hi hello how followed by 7 null values

C. 10 null values

D. depends on compiler

Answer: Option A — segmentation fault

Q658. What will be the output of the following C code? #include <stdio.h> int main() { const int ary[4] = {1, 2, 3, 4}; int *p; p = ary + 3; *p = 5; printf("%d\n", ary[3]); }

A. 4

B. 5 ✓

C. Compile time error

D. 3

Answer: Option B — 5

Q659. What will be the output of the following C code? #include <stdio.h> void foo(int[]); int main() { int ary[4] = {1, 2, 3, 4}; foo(ary); printf("%d ", ary[0]); } void foo(int p[4]) { int i = 10; p = &i; printf("%d ", p[0]); }

A. 10 10

B. Compile time error

C. 10 1 ✓

D. Undefined behaviour

Answer: Option C — 10 1

Q660. How to call a function without using the function name to send parameters?

A. typedefs

B. Function pointer ✓

C. Both typedefs and Function pointer

D. None of the mentioned

Answer: Option B — Function pointer

Q661. What will be the output of the following C code? #include <stdio.h> void main() { int a[3] = {1, 2, 3}; int *p = a; printf("%p\t%p", p, a); }

A. Same address is printed ✓

B. Different address is printed

C. Compile time error

D. Nothing

Answer: Option A — Same address is printed

Q662. Comment on an array of the void data type.

A. It can store any data-type

B. It only stores element of similar data type to first element

C. It acquires the data type with the highest precision in it

D. You cannot have an array of void data type ✓

Answer: Option D — You cannot have an array of void data type

Q663. What is the syntax for constant pointer to address (i.e., fixed pointer address)?

A. const <type> * <name>

B. <type> * const <name> ✓

C. <type> const * <name>

D. none of the mentioned

Answer: Option B — <type> * const <name>

Q664. What will be the output of the following C code (run without any command line arguments)? #include <stdio.h> int main(int argc, char *argv[]) { while (*argv != NULL) printf("%s\n", *(argv++)); return 0; }

A. Segmentation fault/code crash

B. Executable file name ✓

C. Depends on the platform

D. Depends on the compiler

Answer: Option B — Executable file name

Q665. What will be the output of the following C code? #include <stdio.h> void m(int *p) { int i = 0; for(i = 0;i < 5; i++) printf("%d\t", p[i]); } void main() { int a[5] = {6, 5, 3}; m(&a); }

A. 0 0 0 0 0

B. 6 5 3 0 0 ✓

C. Run time error

D. 6 5 3 junk junk

Answer: Option B — 6 5 3 0 0

Q666. What is the first argument in command line arguments?

A. The number of command-line arguments the program was invoked with; ✓

B. A pointer to an array of character strings that contain the arguments

C. Nothing

D. None of the mentioned

Answer: Option A — The number of command-line arguments the program was invoked with;

Q667. What will be the output of the following C code? #include <stdio.h> int main() { int i = 0, j = 1; int *a[] = {&i, &j}; printf("%d", (*a)[1]); return 0; }

A. Compile time error

B. Undefined behaviour

C. 1

D. Some garbage value ✓

Answer: Option D — Some garbage value

Q668. Which of the following is the correct syntax to send an array as a parameter to function?

A. func(&array); ✓

B. func(#array);

C. func(*array);

D. func(array[size]);

Answer: Option A — func(&array);

Q669. Which is true for b, if b is defined as "int *b[10];"?

A. The definition only allocates 10 pointers and does not initialize them

B. Initialization must be done explicitly

C. The definition only allocates 10 pointers and does not initialize them & Initialization must be done explicitly ✓

D. Error

Answer: Option C — The definition only allocates 10 pointers and does not initialize them & Initialization must be done explicitly

Q670. Comment on the output of the following C code. #include <stdio.h> int main() { int a = 10; int **c -= &&a; }

A. You cannot apply any arithmetic operand to a pointer

B. We don't have address of an address operator ✓

C. We have address of an address operator

D. None of the mentioned

Answer: Option B — We don't have address of an address operator

---

Q671. What will be the output of the following C code? #include <stdio.h> int main() { int ary[2][3]; ary[][] = {{1, 2, 3}, {4, 5, 6}}; printf("%d\n", ary[1][0]); }

A. Compile time error ✓

B. 4

C. 1

D. 2

Answer: Option A — Compile time error

Q672. What makes the following declaration denote? char *str[5];

A. str is an array of 5 element pointer to type char ✓

B. str is a pointer to an array of 5 elements

C. str is a function pointer of 5 elements returning char

D. none of the mentioned

Answer: Option A — str is an array of 5 element pointer to type char

Q673. What will be the output of the following C code? #include <stdio.h> void foo(int *ary[]); int main() { int ary[2][3]; foo(ary); } void foo(int *ary[]) { int i = 10, j = 2, k; ary[0] = &i; ary[1] = &j; *ary[0] = 2; for (k = 0;k < 2; k++) printf("%d\n", *ary[k]); }

A. 2 2 ✓

B. Compile time error

C. Undefined behaviour

D. 10 2

Answer: Option A — 2 2

Q674. What will be the output of the following C code? #include <stdio.h> void main() { int a[3] = {1, 2, 3}; int *p = a; int *r = &p; printf("%d", (r)); }**

A. 1

B. Compile time error ✓

C. Address of a

D. Junk value

Answer: Option B — Compile time error

Q675. What will be the output of the following C code? #include <stdio.h> struct student { int no; char name[20]; }; void main() { struct student s; s.no = 8; printf("hello"); }

A. Run time error

B. Nothing

C. hello ✓

D. Varies

Answer: Option C — hello

Q676. What will be the output of the following C code? #include <stdio.h> void main() { char a[10][5] = {"hi", "hello", "fellows"}; printf("%s", a[2]); }

A. fellows

B. fellow

C. fello ✓

D. fell

Answer: Option C — fello

Q677. What will be the output of the following C code (considering sizeof char is 1 and pointer is 4)? #include <stdio.h> int main() { char *a[2] = {"hello", "hi"}; printf("%d", sizeof(a)); return 0; }

A. 9

B. 4

C. 8 ✓

D. 10

Answer: Option C — 8

Q678. In linux, argv[0] by command-line argument can be occupied by . . . . . .

A. ./a.out

B. ./test

C. ./fun.out.out

D. all of the mentioned ✓

Answer: Option D — all of the mentioned

Q679. What will be the output of the following C code? #include <stdio.h> int main() { char *p[1] = {"hello"}; printf("%s", (p)[0]); return 0; }

A. Compile time error

B. Undefined behaviour

C. hello ✓

D. None of the mentioned

Answer: Option C — hello

Q680. What will be the output of the following C code? #include <stdio.h> void main() { int a[3] = {1, 2, 3}; int *p = a; int *r = &p; printf("%d", (r)); }**

A. 1

B. Compile time error ✓

C. Address of a

D. Junk value

Answer: Option B — Compile time error

Q681. What will be the output of the following C code? #include <stdio.h> int main() { char *str = "hello world"; char strary[] = "hello world"; printf("%d %d\n", sizeof(str), sizeof(strary)); return 0;

}

A. 11 11

B. 12 12

C. 4 12 ✓

D. 4 11

Answer: Option C — 4 12

Q682. An array of similar data types which themselves are a collection of dissimilar data type are . . . . . .

A. Linked Lists

B. Trees

C. Array of Structure ✓

D. All of the mentioned

Answer: Option C — Array of Structure

Q683. What will be the output of the following C code? #include <stdio.h> int main() { int a[4] = {1, 2, 3, 4}; int b[4] = {1, 2, 3, 4}; int n = &b[3] - &a[2]; printf("%d\n", n); }

A. -3 ✓

B. 5

C. 4

D. Compile time error

Answer: Option A — -3

Q684. What will be the output of the following C code? #include <stdio.h> void f(int a[][3]) { a[0][1] = 3; int i = 0, j = 0; for (i = 0; i < 2; i++) for (j = 0; j < 3; j++) printf("%d", a[i][j]); } void main() { int a[2][3] = {0}; f(a); }

A. 0 3 0 0 0 0 ✓

B. Junk 3 junk junk junk junk

C. Compile time error

D. All junk values

Answer: Option A — 0 3 0 0 0 0

Q685. What will be the output of the following C code? #include <stdio.h> void (*(f)())(int, float); typedef void (*(*x)())(int, float); void foo(int i, float f); int main() { x = f; x(); } void (*(f)())(int, float) { return foo; } void foo(int i, float f) { printf("%d %f\n", i, f); }

A. Compile time error ✓

B. Undefined behaviour

C. 1 2.000000

D. Nothing

Answer: Option A — Compile time error

C Preprocessor

Q686. What is the purpose of the C preprocessor in C programming?

A. Compile C code

B. Optimize code

C. Preprocess code before compilation ✓

D. Execute code

Answer: Option C — Preprocess code before compilation

Q687. Which directive is used to include the contents of another file in a C program using the C preprocessor?

A. #define

B. #include ✓

C. #ifdef

D. #pragma

Answer: Option B — #include

Q688. What is the purpose of the #define directive in C preprocessing?

A. To include a header file

B. To define a macro ✓

C. To declare a constant

D. To declare a variable

Answer: Option B — To define a macro

Q689. In C, which directive is used to conditionally include code based on preprocessor macros?

A. #ifdef

B. #ifndef

C. #if ✓

D. #else

Answer: Option C — #if

Q690. What is the result of the #ifdef DEBUG directive if the DEBUG macro is defined?

A. The code block following it is included ✓

B. The code block following it is excluded

C. It generates a compilation error

D. It defines the DEBUG macro

Answer: Option A — The code block following it is included

Q691. Which directive in C preprocessing is used to define a macro with parameters?

A. #define ✓

B. #ifdef

C. #include

D. #if

Answer: Option A — #define

Q692. In C preprocessing, what is the purpose of the #undef directive?

A. To undefine a macro ✓

B. To include a header file

C. To define a macro

D. To declare a variable

Answer: Option A — To undefine a macro

Q693. What does the #ifndef directive do in C preprocessing?

A. Checks if a macro is defined

B. Checks if a macro is not defined ✓

C. Checks if a variable is declared

D. Checks if a function is defined

Answer: Option B — Checks if a macro is not defined

Q694. In C, what does the #pragma directive do in C preprocessing?

A. Includes a header file

B. Provides compiler-specific instructions ✓

C. Defines a macro

D. Checks for syntax errors

Answer: Option B — Provides compiler-specific instructions

Q695. What is the purpose of the #include directive in C preprocessing?

A. To define a macro

B. To include a header file ✓

C. To declare a variable

D. To conditionally compile code

Answer: Option B — To include a header file

Q696. What is the purpose of the #if directive in C preprocessing?

A. To check if a variable is declared

B. To conditionally include code ✓

C. To include a header file

D. To define a macro

Answer: Option B — To conditionally include code

Q697. In C, how do you use the #ifdef directive to conditionally include code if a macro is defined?

A. #ifdef MACRO ✓

B. #ifdef(MACRO)

C. #ifdef:MACRO

D. #ifdef: MACRO

Answer: Option A — #ifdef MACRO

Q698. What is the purpose of the #error directive in C preprocessing?

A. To include an error message in the code ✓

B. To define a macro

C. To check if a variable is declared

D. To conditionally compile code

Answer: Option A — To include an error message in the code

Q699. What is the result of the #ifndef DEBUG directive if the DEBUG macro is defined?

A. The code block following it is included

B. The code block following it is excluded ✓

C. It generates a compilation error

D. It defines the DEBUG macro

Answer: Option B — The code block following it is excluded

Q700. Which directive in C preprocessing is used to concatenate two or more strings?

A. #concat

B. #strcat

C. #combine

D. #define ✓

Answer: Option D — #define

Q701. In C, what does the #line directive do in C preprocessing?

A. Specifies the line number in the source file ✓

B. Defines a macro

C. Includes a header file

D. Excludes code

Answer: Option A — Specifies the line number in the source file

Q702. What is the purpose of the #pragma once directive in C preprocessing?

A. Prevents recursive inclusion of header files ✓

B. Defines a macro

C. Checks for syntax errors

D. Excludes code

Answer: Option A — Prevents recursive inclusion of header files

Q703. In C preprocessing, what is the purpose of the #elif directive?

A. Checks if a macro is defined

B. Checks if a macro is not defined

C. Provides an alternative condition ✓

D. Defines a macro

Answer: Option C — Provides an alternative condition

Q704. What is the result of the #error directive in C preprocessing?

A. Generates a compilation error with a specified error message ✓

B. Defines a macro

C. Checks for syntax errors

D. Excludes code

Answer: Option A — Generates a compilation error with a specified error message

Q705. What is the purpose of the #pragma message directive in C preprocessing?

A. Includes a message in the code ✓

B. Defines a macro

C. Checks for syntax errors

D. Excludes code

Answer: Option A — Includes a message in the code

Q706. In C, how do you use the #ifndef directive to conditionally include code if a macro is not defined?

A. #ifndef MACRO ✓
B. #ifndef(MACRO)
C. #ifndef:MACRO
D. #ifndef: MACRO
Answer: Option A — #ifndef MACRO

Q707. What does the #pragma once directive do in C preprocessing?

A. Prevents multiple inclusion of header files ✓
B. Defines a macro
C. Checks for syntax errors
D. Excludes code
Answer: Option A — Prevents multiple inclusion of header files

Q708. In C, what is the purpose of the #ifdef directive?

A. Checks if a macro is defined ✓
B. Checks if a macro is not defined
C. Defines a macro
D. Includes a header file
Answer: Option A — Checks if a macro is defined

Q709. What is the purpose of the #pragma warning directive in C preprocessing?

A. Generates a warning message ✓
B. Defines a macro
C. Checks for syntax errors
D. Excludes code
Answer: Option A — Generates a warning message

Q710. In C preprocessing, what is the purpose of the #elifdef directive?

A. Checks if a macro is defined
B. Checks if a macro is not defined
C. Provides an alternative condition ✓
D. Defines a macro
Answer: Option C — Provides an alternative condition

Q711. What is the result of the #pragma message directive in C preprocessing?

A. Includes a message in the code ✓
B. Defines a macro
C. Checks for syntax errors
D. Excludes code
Answer: Option A — Includes a message in the code

Q712. What is the purpose of the #undef directive in C preprocessing?

A. Undefines a macro ✓
B. Defines a macro
C. Checks for syntax errors
D. Excludes code
Answer: Option A — Undefines a macro

Q713. In C preprocessing, what is the purpose of the #elifndef directive?

A. Checks if a macro is defined

B. Checks if a macro is not defined ✓

C. Provides an alternative condition

D. Defines a macro

Answer: Option B — Checks if a macro is not defined

Q714. What is the result of the #pragma warning directive in C preprocessing?

A. Generates a warning message ✓

B. Defines a macro

C. Checks for syntax errors

D. Excludes code

Answer: Option A — Generates a warning message

Q715. In C, what is the purpose of the #line directive?

A. Specifies the line number and filename in the source file ✓

B. Defines a macro

C. Checks for syntax errors

D. Excludes code

Answer: Option A — Specifies the line number and filename in the source file

---

Q716. C preprocessor

A. Takes care of conditional compilation

B. Takes care of macros

C. Takes care of include files

D. Acts before compilation

E. All of the above ✓

Answer: Option E — All of the above

Q717. A preprocessor command

A. need not start on a new line

B. need not start on the first column

C. has # as the first character ✓

D. comes before the first executable statement

Answer: Option C — has # as the first character

Q718. What will be the output of the program? #include<stdio.h> #define int char void main() { int i = 65; printf("sizeof(i)=%d", sizeof(i)); }

A. sizeof(i)=2

B. sizeof(i)=1 ✓

C. Compiler Error

D. None of These

Answer: Option B — sizeof(i)=1

Q719. What will be the output of the following program? #include<stdio.h> #define square(x) x*x void main() { int i; i = 64/square(4); printf("%d", i); }

A. 4

B. 64 ✓

C. 16

D. None of These

Answer: Option B — 64

Q720. What will be the output of the program code? #include<stdio.h> #define a 10 void main() { #define a 50 printf("%d", a); }

A. 50 ✓

B. 10

C. Compiler Error

D. None of These

Answer: Option A — 50

Q721. Choose the correct statement. I. The scope of a macro definition need not be the entire program. II. The scope of a macro definition extends from the point of definition to the end of the file. III. New line is a macro definition delimiter. IV. A macro definition may go beyond a line.

A. I and II

B. II and III

C. I, II and III

D. II, III and IV

E. I, II, III and IV ✓

Answer: Option E — I, II, III and IV

Q722. Determine output: #include<stdio.h> #define clrscr() 100 void main() { clrscr(); printf("%dn", clrscr()); }

A. 0

B. 1

C. 100 ✓

D. Error

Answer: Option C — 100

Q723. What will be the output of the following program? #include<stdio.h> #define prod(a,b) a*b void main() { int x=3,y=4; printf("%d", prod(x+2,y-1)); }

A. 15

B. 12

C. 10 ✓

D. 11

E. None of these

Answer: Option C — 10

Q724. In which stage the following code #include<stdio.h> gets replaced by the contents of the file stdio.h

A. During Preprocessing ✓

B. During Execution

C. During linking

D. During Editing

E. None of these

Answer: Option A — During Preprocessing

Q725. What will be output if you will compile and execute the following c code? #include<stdio.h> #define max 5 void main(){ int i = 0; i = max++; printf("%d", i++); }

A. 5

B. 6
C. 7
D. 0
E. Compiler Error ✓
Answer: Option E — Compiler Error

Q726. What will be output after executing following code? #include<stdio.h> # define a 10 void main() { printf("%d..", a); foo(); printf("%d", a); } void foo() { #undef a #define a 50 }

A. 10..50
B. 10..10 ✓
C. 0
D. Error
Answer: Option B — 10..10

Q727. The output of the following program is: #define f(g,g2) g##g2 void main() { int var12=100; printf("%d", f(var,12)); }

A. Syntax error
B. Runtime error
C. g##g2
D. 100 ✓
E. 10012
Answer: Option D — 100

Q728. Find the output of the following program. #define INC(X) X++ void main() { int x=4; printf("%d", INC(x++)); }

A. 4
B. 5
C. 6
D. Error ✓
Answer: Option D — Error

Q729. What will be the output of the following C code? #include<stdio.h> #define max 20 main() { #ifndef max #define min 10 #else #define min 30 #endif printf("%d",min); }

A. 10
B. 20
C. 30 ✓
D. error
Answer: Option C — 30

Q730. What will be the output of the following C code? #define display(text) "$" #text main() { printf(display(hello world)); }

A. hello world
B. $helloworld
C. $hello world ✓
D. error
Answer: Option C — $hello world

Q731. What will be the output of the following C code? #include <stdio.h> #define Shyam(x) #x int main() { int marks=100; printf("value of %s is = %d\n",Shyam(marks),marks); return 0; }

A. error

B. value of marks=100 ✓

C. value of=100

D. 100

Answer: Option B — value of marks=100

Q732. What will be the output of the following C code? #include<stdio.h> #define max 100 void main() { #if(max%10) printf("Exam"); #endif printf("Veda"); }

A. error

B. Exam

C. Veda ✓

D. ExamVeda

Answer: Option C — Veda

Q733. . . . . is the preprocessor directive which is used to end the scope of #ifdef.

A. #elif

B. #ifndef

C. #endif ✓

D. #if

Answer: Option C — #endif

Q734. In the directive #pragma pack(n), if the value of 'n' is given to be 5, then what happens?

A. Error

B. Warning but no error

C. Executes the pragma statement

D. Ignores the pragma statement and executes the program ✓

Answer: Option D — Ignores the pragma statement and executes the program

Q735. What will be the output of the following C code? #include<stdio.h> #define INDIA 1 #define US 2 #define CC US main() { #if CC==INDIA printf("Rupee"); #elif CC==US printf("Dollar"); #else printf("Euro"); #endif }

A. Euro

B. Rupee

C. Dollar ✓

D. Error

Answer: Option C — Dollar

Q736. What will be the output of the following C code, if it is run on a 32 bit platform? #include<stdio.h> #pragma(1) struct test { int i; char j; }; main() { printf("%d",sizeof(struct test)); }

A. Error

B. 1

C. 4

D. 8 ✓

Answer: Option D — 8

Q737. What will be the output of the following C code? #include <stdio.h> #define p(m) printf("t*" #m " = %s", t##m) char tram[]="tram"; int main() { int x; x=p(ram); }

A. error

B. tram=tram

C. t*ram=t*ram

D. t*ram=tram ✓

Answer: Option D — t*ram=tram

Q738. What will be the output of the following C code? #include<stdio.h> #define sf 10 main() { if(sf==100) printf("good"); else { printf("bad"); sf=100; } printf("%d",sf); }

A. 100

B. bad

C. 10

D. error ✓

Answer: Option D — error

Q739. What will be the output of the following C code? #include<stdio.h> void main() { #ifndef max printf("hello"); #endif printf("hi"); }

A. hello

B. hellohi ✓

C. error

D. hi

Answer: Option B — hellohi

Q740. The following C code results in an error. #include <stdio.h> #define world(n) printf("t^^" #n" = %c", t##n) int t3=1; int main() { world(3); }

A. True

B. False ✓

Answer: Option B — False

Q741. What will be the output of the following C code? #define F abc #define B def #define FB(arg) #arg #define FB1(arg) FB(arg) main() { printf(FB(F B)); FB1(F B); }

A. F B ✓

B. Error

C. FB

D. "FB"

Answer: Option A — F B

Q742. What will be the output of the following C code? #include <stdio.h> #define p(n,m) printf("%d", m##n) int main() { p(3,4); }

A. Error

B. Junk value

C. 34

D. 43 ✓

Answer: Option D — 43

Q743. What will be the output of the following C code? #define example(s,n) #s #n main() { printf(example(hello,world)); }

A. example(hello,world)

B. example

C. hello,world

D. helloworld ✓

Answer: Option D — helloworld

Q744. What will be the output of the following C code? #include <stdio.h> #define hello(n) a##n int a3; int main() { int x; x=hello(3); if(x!=0) printf("hi"); else printf("good"); }

A. error

B. a3

C. good ✓

D. hi

Answer: Option C — good

Q745. What will be the output of the following C code? #include<stdio.h> #define hello main() { #ifdef hello #define hi 4 #else #define hi 5 #endif printf("%d",hi); }

A. 4 ✓

B. 5

C. 45

D. error

Answer: Option A — 4

Q746. What will be the output of the following C code? #define display(text) printf(#text "@") main() { display(hello.); display(good morning!); }

A. hello.@good morning!

B. error

C. hello.good morning!@

D. hello.@good morning!@ ✓

Answer: Option D — hello.@good morning!@

Q747. What will be the output of the following C code? #include <stdio.h> #define p(n) printf("t%%\n" #n " = %d", t##n) int t3=10; int main() { int x; x=p(3); }

A. t% 3=10 ✓

B. t3=10

C. t%3=10

D. t %3=10

Answer: Option A — t% 3=10

Q748. What will be the output of the following C code? #include <stdio.h> #define p(n,m) printf("%d", m##n) #define q(a,b) printf("%d",a##b) main() { p(3,4); q(5,6); }

A. 4356 ✓

B. 3456

C. 4365

D. 3465

Answer: Option A — 4356

Q749. What will be the output of the following C code? #include<stdio.h> #define hello 10 void main() { printf("%d",hello); #undef hello printf("%d",hello); }

A. 10

B. hello

C. error ✓

D. 1010

Answer: Option C — error

Q750. What will be the output of the following C code? #include <stdio.h> #define display(n) printf("a" #n " = %d", a##n) int main() { display(3); }

A. a3

B. 31

C. a 3

D. error ✓

Answer: Option D — error

Q751. The preprocessor directive used to give additional information to the compiler, beyond which is conveyed in the language . . . . . .

A. #include

B. #define

C. #pragma ✓

D. #elif

Answer: Option C — #pragma

Q752. Which of the following operators is used to concatenate two strings without space?

A. #

B. < >

C. **

D. ## ✓

Answer: Option D — ##

Q753. #pragma GCC poison should be followed by a list of identifiers that are . . . . . .

A. even in number

B. odd in number

C. valid

D. invalid ✓

Answer: Option D — invalid

Q754. In the directive, #pragma pack(n), which of the following is not a valid value of n?

A. 1

B. 2

C. 3 ✓

D. 4

Answer: Option C — 3

Q755. What will be the output of the following C code? #include <stdio.h> #define a 2 main() { int r; #define a 5 r=a*2; printf("%d",r); }

A. 10 ✓

B. 4

C. 2

D. 5

Answer: Option A — 10

Q756. What will be the output of the following C code? #include<stdio.h> #define max 100 main() { #ifdef max printf("hello"); }

A. 100

B. hello

C. "hello"

D. error ✓

Answer: Option D — error

Q757. What will be the output of the following C code? #include<stdio.h> #define hello 10 main() { #ifdef hello #undef hello #define hello 100 #else #define hello 200 #endif printf("%d",hello); }

A. Error

B. 10

C. 100 ✓

D. 200

Answer: Option C — 100

Q758. Which of the following is not a preprocessor directive?

A. #error

B. #pragma

C. #if

D. #ifelse ✓

Answer: Option D — #ifelse

Q759. The preprocessor directive which is used to remove the definition of an identifier which was previously defined with #define?

A. #ifdef

B. #undef ✓

C. #ifndef

D. #def

Answer: Option B — #undef

Q760. The function of __attribute__((packed)); can also be performed using . . . . . .

A. #pragma pack(1); ✓

B. #pragma pack(2);

C. #pragma pack(4);

D. #pragma pack(8);

Answer: Option A — #pragma pack(1);

Q761. The preprocessor directive which checks whether a constant expression results in a zero or non-zero value . . . . . .

A. #if ✓

B. #ifdef

C. #undef

D. #ifndef

Answer: Option A — #if

Q762. What will be the output of the following C code? #include<stdio.h> void f() { #define sf 100 printf("%d",sf); } int main() { #define sf 99; f(); printf("%d",sf); }

A. error ✓

B. 100

C. 99

D. 10099

Answer: Option A — error

Q763. What will be the output of the following C code? #define HELLO(a) #a main() { printf(HELLO(good morning)); }

A. good morning

B. HELLO good morning

C. good morning ✓

D. error

Answer: Option C — good morning

Q764. The purpose of the preprocessor directive #error is that . . . . . .

A. It rectifies any error present in the code

B. It rectifies only the first error which occurs in the code

C. It causes the preprocessor to report a fatal error ✓

D. It causes the preprocessor to ignore an error

Answer: Option C — It causes the preprocessor to report a fatal error

Q765. What will be the output of the following C code? #include<stdio.h> #define ram 10 main() { #ifdef ram #define ram 20 #endif printf("%d",ram); }

A. 10

B. 20 ✓

C. Error

D. 1020

Answer: Option B — 20

Q766. The pragma . . . . . is used to remove an identifier completely from a program.

A. GNU piston

B. GCC poison ✓

C. GNU poison

D. GCC piston

Answer: Option B — GCC poison

Q767. What will be the output of the following C code if the value of 'p' is 10 and that of 'q' is 15? #include<stdio.h> int main() { int p,q; printf("Enter two numbers\n"); scanf("%d",&p); scanf("%d",&q); #if(4<2) printf("%d",p); #elif(2>-1) printf("%d",q); #else printf("bye"); #endif }

A. 10

B. 15 ✓

C. bye

D. error

Answer: Option B — 15

Q768. What will be the output of the following C code? #include <stdio.h> #define p(n) printf("t" #n " = %d", t##n) int t3=10; int main() { p(3); }

A. t=10

B. t3=10 ✓

C. t10=3

D. t=3

Answer: Option B — t3=10

Q769. What will be the output of the following C code? #define hello(c) #c main() { printf(hello(i,am)); }

A. i,am
B. iam
C. i am
D. error ✓
Answer: Option D — error

Q770. Which of the following attributes is used to specify that the minimum required memory to be used to represent the types?

A. packed ✓
B. aligned
C. unused
D. deprecated
Answer: Option A — packed

Q771. What will be the output of the following C code? #include<stdio.h> #define ram 557 int main() { #ifndef ram printf("yes"); #endif printf("no"); }

A. error
B. yes
C. no ✓
D. yesno
Answer: Option C — no

Q772. The correct syntax of the attribute packed is . . . . . .

A. __attribute__((packed)); ✓
B. _attribute(packed);
C. _attribute_((packed));
D. __attribute__(packed);
Answer: Option A — __attribute__((packed));

Q773. What will be the output of the following C code? #define hello(c,d) #c #d main() { printf(hello(i,"am")); }

A. iam
B. i"am" ✓
C. am
D. "am"
Answer: Option B — i"am"

Q774. What will be the output of the following C code? #define display(a) #a main() { printf(display("56#7")); }

A. Error
B. "56#7" ✓
C. 56#7
D. 567
Answer: Option B — "56#7"

Q775. What will be the output of the following C code? #include<stdio.h> #pragma GCC poison printf main() { printf("example"); return 0; }

A. error is thrown ✓
B. example is printed

C. warning but no error

D. pleexam is printed

Answer: Option A — error is thrown

Q776. Which of the following is a stringizing operator?

A. < >

B. # ✓

C. %

D. ##

Answer: Option B — #

Q777. What will be the output of the following C code? #include <stdio.h> #define hello(n) printf("a" #n "= %d", a##n) int a3=3; int main() { #ifdef a3 hello(3); #else printf("sorry"); #endif }

A. a3=3

B. error

C. a=3

D. sorry ✓

Answer: Option D — sorry

Q778. What will be the output of the following C code? #define sqr(x) x*x main() { int a1; a1=25/sqr(5); printf("%d",a1); }

A. 25 ✓

B. 1

C. 5

D. error

Answer: Option A — 25

Structure And Union

Q779. What is the keyword used to define a structure in C?

A. struct ✓
B. record
C. class
D. object
Answer: Option A — struct

Q780. In a structure, what are the members also known as?

A. Variables ✓
B. Properties
C. Objects
D. Elements
Answer: Option A — Variables

Q781. Which of the following can be a member of a structure?

A. Function
B. Another structure ✓
C. Enumeration
D. All of the above
Answer: Option B — Another structure

Q782. How do you access a member of a structure in C?

A. . (dot) ✓
B. -> (arrow)
C. :: (scope)
D. , (comma)
Answer: Option A — . (dot)

Q783. Which keyword is used to declare a union in C?

A. struct
B. union ✓
C. class
D. typedef
Answer: Option B — union

Q784. What is the primary difference between a structure and a union in C?

A. Structure allows nested members
B. Union allows nested members
C. Structure allows multiple members
D. Union allows only one active member ✓
Answer: Option D — Union allows only one active member

Q785. How is the size of a structure determined in C?

A. By the total size of its members
B. By the size of its largest member ✓
C. By the size of its smallest member
D. By the number of members

Answer: Option B — By the size of its largest member

Q786. Which statement correctly defines a structure named "Person" with members "name" and "age" of type char* and int respectively?

A. struct Person { char* name; int age; } ✓

B. struct Person { name, age; }

C. struct { name; age; } Person;

D. struct { char* name, int age; } Person;

Answer: Option A — struct Person { char* name; int age; }

Q787. What does the 'sizeof' operator in C return for a union?

A. Total size of all union members

B. Size of the largest member ✓

C. Size of the smallest member

D. Size of the union itself

Answer: Option B — Size of the largest member

Q788. Can a structure have another structure as a member in C?

A. No, it's not allowed

B. Yes, but with a limited depth

C. Yes, without any limitations ✓

D. Only if the inner structure is named "Inner"

Answer: Option C — Yes, without any limitations

Q789. Which operator is used to access a union member when the union is a part of a structure?

A. . (dot) ✓

B. -> (arrow)

C. :: (scope)

D. , (comma)

Answer: Option A — . (dot)

Q790. What happens when you assign a value to one member of a union and then access another member in C?

A. It's allowed and safe

B. It leads to undefined behavior ✓

C. It raises a compilation error

D. It swaps the values of both members

Answer: Option B — It leads to undefined behavior

Q791. Which keyword is used to define an anonymous structure or union within another structure or union?

A. anonymous

B. hidden

C. struct ✓

D. none of the above

Answer: Option C — struct

Q792. In a union, which member can you access safely after assigning a value to one of its members?

A. All members can be accessed
B. Only the last assigned member
C. Only the first assigned member ✓
D. Any member, but it's compiler-dependent
Answer: Option C — Only the first assigned member

Q793. Which type of variable should you use if you want to store different types of data at different times within the same memory location?

A. int
B. float
C. char
D. union ✓
Answer: Option D — union

Q794. Which of the following is true about the memory allocation of structures and unions in C?

A. Structures require memory for all members simultaneously
B. Unions require memory for all members simultaneously
C. Structures allocate memory for the largest member ✓
D. Unions allocate memory for the smallest member
Answer: Option C — Structures allocate memory for the largest member

Q795. In C, can a structure be passed as an argument to a function?

A. Yes, by value
B. Yes, by reference ✓
C. No, it's not allowed
D. Only if the structure has fewer than 3 members
Answer: Option B — Yes, by reference

Q796. What is the purpose of using a typedef with structures and unions in C?

A. To create a new data type name for the structure or union ✓
B. To create a new structure with the same members
C. To hide the details of the structure or union
D. To add typecasting support to the structure or union
Answer: Option A — To create a new data type name for the structure or union

Q797. When should you use a structure instead of an array in C?

A. When you need to store elements of different data types ✓
B. When you need a fixed-size collection of elements
C. When you need a dynamic collection of elements
D. When you need to perform mathematical operations
Answer: Option A — When you need to store elements of different data types

Q798. What is the purpose of an anonymous union in C?

A. To group related members within a structure
B. To declare a union without a name ✓
C. To hide the union's members from external access
D. To specify a union's memory alignment
Answer: Option B — To declare a union without a name

Q799. Which keyword is used to access a member of a nested structure in C?

A. . (dot) ✓

B. -> (arrow)

C. :: (scope)

D. , (comma)

Answer: Option A — . (dot)

Q800. What is the main advantage of using a union in C?

A. It saves memory by sharing the same memory location ✓

B. It allows easy access to all members

C. It enforces strong data typing

D. It prevents data from being modified

Answer: Option A — It saves memory by sharing the same memory location

---

Q801. What is the size of an empty structure in C?

A. 0 bytes ✓

B. 1 byte

C. It varies depending on the compiler

D. 4 bytes

Answer: Option A — 0 bytes

Q802. In C, can you compare two structures using the equality operator (==)?

A. Yes, always

B. No, never ✓

C. Only if both structures have the same name

D. Only if both structures have the same members

Answer: Option B — No, never

Q803. What is the primary use of a union in a C program?

A. To represent multiple data types using the same memory location ✓

B. To store a collection of elements of the same type

C. To organize data into a hierarchy

D. To define a custom data type

Answer: Option A — To represent multiple data types using the same memory location

Q804. How do you declare an array of structures in C?

A. struct myStruct arr[];

B. myStruct array[]; ✓

C. struct array myStruct[];

D. myStruct[] arr;

Answer: Option B — myStruct array[];

Q805. Which of the following is not a valid type for a structure member in C?

A. Array

B. Pointer

C. Function ✓

D. Enumeration

Answer: Option C — Function

Q806. In C, can you have a structure as a member of itself (a recursive structure)?

A. Yes, but with compiler-specific limitations ✓

B. Yes, without any limitations

C. No, it's not allowed

D. Only if the structure has exactly one member

Answer: Option A — Yes, but with compiler-specific limitations

Q807. What is the purpose of the offsetof macro in C?

A. To calculate the offset of a structure member ✓

B. To define the size of a structure

C. To access a specific structure member

D. To check if a structure is empty

Answer: Option A — To calculate the offset of a structure member

Q808. Which keyword is used to create a new name for an existing data type in C?

A. typedef ✓

B. define

C. alias

D. typecast

Answer: Option A — typedef

Q809. Find the output of the following program: void main() { struct xx { int x=3; char name[]="hello"; }; struct xx *s; printf("%d", s->x); printf("%s", s->name); }

A. 3 and hello

B. 3 and h

C. 3 and garbage value

D. Compilation error ✓

E. Runtime error

Answer: Option D — Compilation error

Q810. Consider the following code. struct account{ int acno; }svar, *pv = &svar; then the acno can be accessed by

A. svar.acno

B. pv->acno

C. (*pv).acno

D. A, B and C ✓

E. A and B only

Answer: Option D — A, B and C

Q811. Consider the following declarations: union id { char color; int size; }; struct{ char country; int date; union id id; }flag; To assign a color to a flag, the correct statement would be

A. flag.color = 'W'; ✓

B. flag.id.color = 'W';

C. flag.color = 'WHITE';

D. flag.id.color = 'WHITE';

E. color.flag = 'W';

Answer: Option A — flag.color = 'W';

Q812. For the following structure declaration, find the correct statement. struct person{ char name[20]; int age; struct person lady; };

A. Is a valid nested structure.

B. Uses an invalid data type.

C. Is a self referential structure.

D. Is not a valid nested structure. ✓

E. Is a self referential structure with invalid data type.

Answer: Option D — Is not a valid nested structure.

Q813. The restriction with union is

A. The first member can only be initialized. ✓

B. The last member can only be initialized.

C. Any member can be initialized.

D. Union can not be initialized

E. No restriction at all.

Answer: Option A — The first member can only be initialized.

Q814. How many union members can be initialized?

A. Only one member of a union at any one time. ✓

B. Any number of members of a union at one time.

C. Union members can not be initialized.

D. Only two members of a union at any one time.

E. Only two members of a union at any time..

Answer: Option A — Only one member of a union at any one time.

Q815. What will be the output of the following C code? #include <stdio.h> int main() { typedef struct p *q; struct p { int x; char y; q ptr; }; struct p p = {1, 2, &p}; printf("%d\n", p.ptr->x); return 0; }

A. Compile time error

B. 1 ✓

C. Depends on the compiler

D. Depends on the standard

Answer: Option B — 1

Q816. Can the following C code be compiled successfully? #include <stdio.h> struct p { int k; char c; float f; }; int main() { struct p x = {.c = 97, .f = 3, .k = 1}; printf("%f\n", x.f); }

A. Yes

B. No

C. Depends on the standard ✓

D. Depends on the platform

Answer: Option C — Depends on the standard

Q817. What will be the output of the following C code? #include <stdio.h> int *(*(x()))[2]; typedef int **(*ptrfoo)())[2]; int main() { ptrfoo ptr1; ptr1 = x; ptr1(); return 0; } int *(*(x()))[2] { int (*ary)[2] = malloc(sizeof * ary); return &ary; }

A. Compile time error

B. Nothing ✓

C. Undefined behaviour

D. Depends on the standard

Answer: Option B — Nothing

Q818. Which of the following share a similarity in syntax? 1. Union, 2. Structure, 3. Arrays and 4. Pointers

A. 3 and 4

B. 1 and 2 ✓

C. 1 and 3

D. 1, 3 and 4

Answer: Option B — 1 and 2

Q819. What will be the output of the following C code? #include <stdio.h> void main() { struct student { int no; char name[20]; }; struct student s; no = 8; printf("%d", no); }

A. Nothing

B. Compile time error ✓

C. Junk

D. 8

Answer: Option B — Compile time error

Q820. What will be the output of the following C code? #include <stdio.h> struct p { int x; char y; }; int main() { struct p p1[] = {1, 92, 3, 94, 5, 96}; struct p *ptr1 = p1; int x = (sizeof(p1) / sizeof(struct p)); printf("%d %d\n", ptr1->x, (ptr1 + x - 1)->x); }

A. Compile time error

B. Undefined behaviour

C. 1 3

D. 1 5 ✓

Answer: Option D — 1 5

Q821. What will be the output of the following C code? #include <stdio.h> struct point { int x; int y; }; int main() { struct point p = {1}; struct point p1 = {1}; if(p == p1) printf("equal\n"); else printf("not equal\n"); }

A. Compile time error ✓

B. equal

C. depends on the standard

D. not equal

Answer: Option A — Compile time error

Q822. Which of the following structure declaration doesn't require pass-by-reference?

A. struct{int a;}s; main(){}

B. struct temp{int a;}; main(){ struct temp s; }

C. struct temp{int a;}; main(){} struct temp s;

D. none of the mentioned ✓

Answer: Option D — none of the mentioned

Q823. How many bytes in memory taken by the following C structure? #include <stdio.h> struct test { int k; char c; };

A. Multiple of integer size ✓

B. integer size+character size

C. Depends on the platform

D. Multiple of word size

Answer: Option A — Multiple of integer size

Q824. What will be the output of the following C code? #include <stdio.h> typedef struct p { int x, y; }k; int main() { struct p p = {1, 2}; k k1 = p; printf("%d\n", k1.x); }

A. Compile time error

B. 1 ✓

C. 0

D. Depends on the standard

Answer: Option B — 1

Q825. What will be the output of the following C code? #include <stdio.h> void main() { char *a[3] = {"hello", "this"}; printf("%s", a[1]); }

A. hello

B. Varies

C. this ✓

D. Compile time error

Answer: Option C — this

Q826. What will be the output of the following C code? #include <stdio.h> struct student { char *name; }; struct student fun(void) { struct student s; s.name = "alan"; return s; } void main() { struct student m = fun(); printf("%s", m.name); }

A. Nothing

B. alan ✓

C. Run time error

D. Varies

Answer: Option B — alan

Q827. What is the correct syntax to declare a function foo() which receives an array of structure in function?

A. void foo(struct *var); ✓

B. void foo(struct *var[]);

C. void foo(struct var);

D. none of the mentioned

Answer: Option A — void foo(struct *var);

Q828. What will be the output of the following C code? #include <stdio.h> struct student { char *c; }; void main() { struct student *s; s->c = "hello"; printf("%s", s->c); }

A. hello

B. Segmentation fault ✓

C. Run time error

D. Nothing

Answer: Option B — Segmentation fault

Q829. What will be the output of the following C code? #include <stdio.h> struct p { int x[2]; }; struct q { int *x; }; int main() { struct p p1 = {1, 2}; struct q *ptr1; ptr1->x = (struct q*)&p1.x; printf("%d\n", ptr1->x[1]); }

A. Compile time error

B. Segmentation fault/code crash ✓

C. 2

D. 1

Answer: Option B — Segmentation fault/code crash

Q830. What will be the output of the following C code? #include <stdio.h> union p { int x; char y; }k = {.y = 97}; int main() { printf("%d\n", k.y); }

A. Compile time error

B. 97 ✓

C. a

D. Depends on the standard

Answer: Option B — 97

Q831. What will be the output of the following C code? #include <stdio.h> struct student { char *name; }; void main() { struct student s, m; s.name = "st"; m = s; printf("%s%s", s.name, m.name); }

A. Compile time error

B. Nothing

C. Junk values

D. st st ✓

Answer: Option D — st st

Q832. What will be the output of the following C code? #include <stdio.h> struct student { char *name; }; struct student s[2], r[2]; void main() { s[0].name = "alan"; s[1] = s[0]; r = s; printf("%s%s", r[0].name, r[1].name); }

A. alan alan

B. Compile time error ✓

C. Varies

D. Nothing

Answer: Option B — Compile time error

Q833. What will be the output of the following C code? #include <stdio.h> struct point { int x; int y; }; void foo(struct point*); int main() { struct point p1[] = {1, 2, 3, 4, 5}; foo(p1); } void foo(struct point p[]) { printf("%d %d\n", p->x, p[3].y); }

A. Compile time error

B. 1 0

C. 1 somegarbagevalue ✓

D. None of the mentioned

Answer: Option C — 1 somegarbagevalue

Q834. What will be the output of the following C code? #include <stdio.h> void main() { char *a[3][3] = {{"hey", "hi", "hello"}, {"his", "her", "hell"} , {"hellos", "hi's", "hmm"}}; printf("%s", a[1][1]); }

A. her ✓

B. hi

C. Compile time error

D. hi's

Answer: Option A — her

Q835. What will be the output of the following C code? #include <stdio.h> union u { struct { unsigned char x : 2; unsigned int y : 2; }p; int x; }; int main() { union u u = {2}; printf("%d\n", u.p.x); }

A. Compile time error

B. 2 ✓

C. Depends on the standard

D. None of the mentioned

Answer: Option B — 2

Q836. What will be the output of the following C code? #include <stdio.h> struct p { int k; char c; }; int p = 10; int main() { struct p x; x.k = 10; printf("%d %d\n", x.k, p); }

A. Compile time error

B. 10 10 ✓

C. Depends on the standard

D. Depends on the compiler

Answer: Option B — 10 10

Q837. What will be the output of the following C code? #include <stdio.h> struct p { char *name; struct p *next; }; struct p *ptrary[10]; int main() { struct p p; p.name = "xyz"; p.next = NULL; ptrary[0] = &p; printf("%s\n", ptrary[0]->name); return 0; }

A. Compile time error

B. Segmentation fault

C. Undefined behaviour

D. xyz ✓

Answer: Option D — xyz

Q838. What will be the output of the following C code? #include <stdio.h> struct p { char *name; struct p *next; }; struct p *ptrary[10]; int main() { struct p p; p->name = "xyz"; p->next = NULL; ptrary[0] = &p; printf("%s\n", p->name); return 0; }

A. Compile time error ✓

B. Segmentation fault/code crash

C. xyz

D. Undefined behaviour

Answer: Option A — Compile time error

Q839. In the following C code, we can access the 1st character of the string sval by using . . . . . #include <stdio.h> struct { char *name; union { char *sval; } u; } symtab[10]; . .

A. *symtab[i].u.sval

B. symtab[i].u.sval[0].

C. You cannot have union inside structure

D. Both *symtab[i].u.sval & symtab[i].u.sval[0]. ✓

Answer: Option D — Both *symtab[i].u.sval & symtab[i].u.sval[0].

Q840. What will be the output of the following C code? #include <stdio.h> struct point { int x; int y; }; struct notpoint { int x; int y; }; int main() { struct point p = {1}; struct notpoint p1 = p; printf("%d\n", p1.x); }

A. Compile time error ✓

B. 1

C. 0

D. Undefined

Answer: Option A — Compile time error

Q841. What will be the output of the following C code? #include <stdio.h> struct student { char *c; }; void main() { struct student m; struct student *s = &m; s->c = "hello"; printf("%s", m.c); }

A. Run time error

B. Nothing

C. hello ✓

D. Varies

Answer: Option C — hello

Q842. What will be the output of the following C code? #include <stdio.h> struct student { char *c; struct student *point; }; void main() { struct student s; printf("%d", sizeof(s)); }

A. 5

B. 9

C. 8 ✓

D. 16

Answer: Option C — 8

Q843. What is typedef declaration?

A. Does not create a new type

B. It merely adds a new name for some existing type

C. Does not create a new type, It merely adds a new name for some existing type ✓

D. None of the mentioned

Answer: Option C — Does not create a new type, It merely adds a new name for some existing type

Q844. Which of the following is an incorrect syntax for pointer to structure? (Assuming struct temp{int b;}*my_struct;)

A. *my_struct.b = 10; ✓

B. (*my_struct).b = 10;

C. my_struct->b = 10;

D. Both *my_struct.b = 10; and (*my_struct).b = 10;

Answer: Option A — *my_struct.b = 10;

Q845. The size of a union is determined by the size of the . . . . . .

A. First member in the union

B. Last member in the union

C. Biggest member in the union ✓

D. Sum of the sizes of all members

Answer: Option C — Biggest member in the union

Q846. What will be the output of the following C code? #include <stdio.h> struct p { int x; char y; }; typedef struct p* q*; int main() { struct p p1[] = {1, 92, 3, 94, 5, 96}; q ptr1 = p1; printf("%d\n", ptr1->x); }

A. Compile time error ✓

B. 1

C. Undefined behaviour

D. Segmentation fault

Answer: Option A — Compile time error

Q847. Which of the following is not possible regarding the structure variable?

A. A structure variable pointing to itself

B. A structure variable pointing to another structure variable of same type

C. 2 different type of structure variable pointing at each other

D. None of the mentioned ✓

Answer: Option D — None of the mentioned

Q848. What will be the output of the following C code? (Assuming size of int be 4) #include <stdio.h> struct temp { int a; int b; int c; } p[] = {0}; main() { printf("%d", sizeof(p)); }

A. 4

B. 12 ✓

C. 16

D. Can't be estimated due to ambiguous initialization of array

Answer: Option B — 12

Q849. What will be the output of the following C code? #include <stdio.h> union p { int x; char y; }k = {1, 97}; int main() { printf("%d\n", k.y); }

A. Compile time error

B. 97

C. a

D. 1 ✓

Answer: Option D — 1

Q850. What will be the output of the following C code? #include <stdio.h> typedef struct p *q; struct p { int x; char y; q ptr; }; int main() { struct p p = {1, 2, &p}; printf("%d\n", p.ptr->x); return 0; }

A. Compile time error

B. 1 ✓

C. Undefined behaviour

D. Address of p

Answer: Option B — 1

Q851. Which operator connects the structure name to its member name?

A. -

B. <-

C. . ✓

D. Both <- and .

Answer: Option C — .

Q852. Which of the following may create problem in the typedef program?

A. ;

B. printf/scanf

C. Arithmetic operators

D. All of the mentioned ✓

Answer: Option D — All of the mentioned

Q853. What will be the output of the following C code? #include <stdio.h> struct point { int x; int y; }; void foo(struct point*); int main() { struct point p1[] = {1, 2, 3, 4}; foo(p1); } void foo(struct point p[]) { printf("%d\n", p->x); }

A. 1 ✓

B. 2

C. 3

D. Compile time error

Answer: Option A — 1

Q854. What will be the output of the following C code? #include <stdio.h> struct temp { int a; } s; void change(struct temp); main() { s.a = 10; change(s); printf("%d\n", s.a); } void change(struct temp s) { s.a = 1; }

A. Output will be 1

B. Output will be 10 ✓

C. Output varies with machine

D. Compile time error

Answer: Option B — Output will be 10

Q855. What will be the output of the following C code? #include <stdio.h> struct student { char *name; }; struct student s[2]; void main() { s[0].name = "alan"; s[1] = s[0]; printf("%s%s", s[0].name, s[1].name); s[1].name = "turing"; printf("%s%s", s[0].name, s[1].name); }

A. alan alan alan turing ✓

B. alan alan turing turing

C. alan turing alan turing

D. run time error

Answer: Option A — alan alan alan turing

Q856. What will be the output of the following C code? #include <stdio.h> struct p { int x; char y; }; void foo(struct p*); int main() { typedef struct p* q; struct p p1[] = {1, 92, 3, 94, 5, 96}; foo(p1); } void foo(struct p* p1) { q ptr1 = p1; printf("%d\n", ptr1->x); }

A. Compile time error ✓

B. 1

C. Segmentation fault

D. Undefined behaviour

Answer: Option A — Compile time error

Q857. Which algorithm is used for searching in the table?

A. List search

B. Informed search

C. Hash search ✓

D. Adversarial search

Answer: Option C — Hash search

Q858. What is the correct syntax to initialize bit-fields in an structure?

A. struct temp { unsigned int a : 1; }s; ✓

B. struct temp { unsigned int a = 1; }s;

C. struct temp { unsigned float a : 1; }s;

D. None of the mentioned

Answer: Option A — struct temp { unsigned int a : 1; }s;

Q859. What will be the output of the following C code? #include <stdio.h> struct point { int x; int y; }; void foo(struct point*); int main() { struct point p1 = {1, 2}; foo(&p1); } void foo(struct point *p) { printf("%d\n", *p.x++); }

A. Compile time error ✓

B. Segmentation fault/code crash

C. 2

D. 1

Answer: Option A — Compile time error

Q860. What will be the output of the following C code? #include <stdio.h> struct p { int x; char y; struct p *ptr; }; int main() { struct p p = {1, 2, &p}; printf("%d\n", p.ptr->x); return 0; }

A. Compile time error

B. Undefined behaviour

C. 1 ✓

D. 2

Answer: Option C — 1

Q861. What will be the output of the following C code? #include <stdio.h> struct student { char *c; }; void main() { struct student m; struct student *s = &m; s->c = "hello"; printf("%s", s->c); }

A. hello ✓

B. Run time error

C. Nothing

D. Depends on compiler

Answer: Option A — hello

Q862. Comment on the output of the following C code. #include <stdio.h> struct temp { int a; int b; int c; }; main() { struct temp p[] = {{1, 2, 3}, {4, 5, 6}, {7, 8, 9}}; }

A. No Compile time error, generates an array of structure of size 3 ✓

B. No Compile time error, generates an array of structure of size 9

C. Compile time error, illegal declaration of a multidimensional array

D. Compile time error, illegal assignment to members of structure

Answer: Option A — No Compile time error, generates an array of structure of size 3

Q863. Which of the following operation is illegal in structures?

A. Typecasting of structure ✓

B. Pointer to a variable of the same structure

C. Dynamic allocation of memory for structure

D. All of the mentioned

Answer: Option A — Typecasting of structure

Q864. The correct syntax to access the member of the ith structure in the array of structures is? Assuming: struct temp { int b; }s[50];

A. s.b.[i];

B. s.[i].b;

C. s.b[i];

D. s[i].b; ✓

Answer: Option D — s[i].b;

Q865. What will be the output of the following C code? #include <stdio.h> struct p { int x; char y; }; int main() { struct p p1[] = {1, 92, 3, 94, 5, 96}; struct p *ptr1 = p1; int x = (sizeof(p1) / sizeof(ptr1)); if (x == 1) printf("%d\n", ptr1->x); else printf("false\n"); }

A. Compile time error

B. 1

C. false ✓

D. Undefined behaviour

Answer: Option C — false

Q866. What will be the output of the following C code? #include <stdio.h> struct student { char *c; struct student *point; }; void main() { struct student s; struct student m; m.point = s; (m.point)->c = "hey"; printf("%s", s.c); }

A. Nothing

B. Compile time error ✓

C. hey

D. Varies

Answer: Option B — Compile time error

Q867. What will be the output of the following C code? #include <stdio.h> union stu { int ival; float fval; }; void main() { union stu r; r.ival = 5; printf("%d", r.ival); }

A. 9

B. Compile time error

C. 16

D. 5 ✓

Answer: Option D — 5

Q868. What will be the output of the following C code? #include <stdio.h> union { int x; char y; }p; int main() { p.y = 60; printf("%d\n", sizeof(p)); }

A. Compile time error

B. sizeof(int) + sizeof(char)

C. Depends on the compiler ✓

D. sizeof(char)

Answer: Option C — Depends on the compiler

Q869. What will be the output of the following C code? #include <stdio.h> struct student { char *c; struct student *point; }; void main() { struct student s; struct student *m = &s; printf("%d", sizeof(student)); }

A. Compile time error ✓

B. 8

C. 5

D. 16

Answer: Option A — Compile time error

Q870. What will be the output of the following C code? #include <stdio.h> int (*(x()))[2]; typedef int (*(*ptr)())[2] ptrfoo; int main() { ptrfoo ptr1; ptr1 = x; ptr1(); return 0; } int (*(x()))[2] { int (*ary)[2] = malloc(sizeof*ary); return &ary; }

A. Compile time error ✓

B. Nothing

C. Undefined behaviour

D. Depends on the standard

Answer: Option A — Compile time error

Q871. What will be the output of the following C code? #include <stdio.h> struct point { int x; int y; }; void foo(struct point*); int main() { struct point p1 = {1, 2}; foo(&p1); } void foo(struct point *p) { printf("%d\n", *p->x++); }

A. Compile time error ✓

B. 1

C. Segmentation fault/code crash

D. 2

Answer: Option A — Compile time error

Q872. What will be the output of the following C code? #include <stdio.h> struct student { char *c; struct student point; }; void main() { struct student s; s.c = "hello"; printf("%s", s.c); }

A. hello

B. Nothing

C. Varies

D. Compile time error ✓

Answer: Option D — Compile time error

Q873. What will be the output of the following C code? #include <stdio.h> struct p { unsigned int x : 1; unsigned int y : 1; }; int main() { struct p p; p.x = 1; p.y = 2; printf("%d\n", p.y); }

A. 1

B. 2

C. 0 ✓

D. Depends on the compiler

Answer: Option C — 0

Q874. Members of a union are accessed as . . . . . .

A. union-name.member

B. union-pointer->member

C. both union-name.member & union-pointer->member ✓

D. none of the mentioned

Answer: Option C — both union-name.member & union-pointer->member

Q875. Which option should be selected to work the following C expression? string p = "HELLO";

A. typedef char [] string;

B. typedef char *string; ✓

C. typedef char [] string; and typedef char *string;

D. Such expression cannot be generated in C

Answer: Option B — typedef char *string;

Q876. What will be the output of the following C code? #include <stdio.h> struct p { int x; int y; }; int main() { struct p p1[] = {1, 92, 3, 94, 5, 96}; struct p *ptr1 = p1; int x = (sizeof(p1) / 5); if (x == 3) printf("%d %d\n", ptr1->x, (ptr1 + x - 1)->x); else printf("false\n"); }

A. Compile time error

B. 1 5

C. Undefined behaviour

D. false ✓

Answer: Option D — false

Q877. Which of the following data types are accepted while declaring bit-fields?

A. char ✓

B. float

C. double

D. none of the mentioned

Answer: Option A — char

Q878. What will be the output of the following C code? #include <stdio.h> struct student { char *name; }; struct student fun(void) { struct student s; s.name = "alan"; return s; } void main() { struct student m = fun(); s.name = "turing"; printf("%s", m.name); }

A. alan

B. Turing

C. Compile time error ✓

D. Nothing

Answer: Option C — Compile time error

File Input Output

Q879. In C, which library is used for file operations such as reading and writing files?

A. stdio.h ✓
B. iostream.h
C. fileio.h
D. files.h
Answer: Option A — stdio.h

Q880. Which function is used to open a file in C for writing?

A. fopen() ✓
B. open()
C. writefile()
D. createfile()
Answer: Option A — fopen()

Q881. What does 'FILE' represent in C when working with files?

A. A built-in data type for files
B. A file descriptor
C. A file pointer
D. A file structure ✓
Answer: Option D — A file structure

Q882. How do you check if a file was opened successfully in C?

A. Use the 'filestatus' variable
B. Check the return value of fopen() ✓
C. Use the 'fileopen' function
D. Check the file's size
Answer: Option B — Check the return value of fopen()

Q883. Which function is used to write data to a file in C?

A. fwrite() ✓
B. writefile()
C. filewrite()
D. putfile()
Answer: Option A — fwrite()

Q884. What is the difference between 'r' and 'w' modes when opening a file in C?

A. 'r' is for read-only and 'w' is for write-only
B. 'r' is for reading and 'w' is for reading and writing
C. 'r' is for read-only and 'w' is for write-only, creating a new file
D. 'r' is for reading and 'w' is for writing, overwriting an existing file ✓
Answer: Option D — 'r' is for reading and 'w' is for writing, overwriting an existing file

Q885. How do you read a character from a file in C?

A. getc() ✓
B. readchar()
C. read()
D. getchar()

Answer: Option A — getc()

Q886. What is the purpose of the 'fprintf' function in C?

A. To format and write data to a file ✓

B. To read data from a file

C. To open a file

D. To close a file

Answer: Option A — To format and write data to a file

Q887. Which function is used to close a file in C?

A. closefile()

B. fclose() ✓

C. endfile()

D. fileclose()

Answer: Option B — fclose()

Q888. In C, what is the function of the 'feof' function?

A. To check if the file has reached the end ✓

B. To find the size of a file

C. To check if the file is open

D. To check if the file exists

Answer: Option A — To check if the file has reached the end

Q889. Which function is used to move the file pointer to a specific position in a file?

A. fseek() ✓

B. movefile()

C. setposition()

D. fileseek()

Answer: Option A — fseek()

Q890. What is the purpose of the 'rewind' function in C?

A. To close the file

B. To reset the file pointer to the beginning ✓

C. To delete the file

D. To check if the file is empty

Answer: Option B — To reset the file pointer to the beginning

---

Q891. Which function is used to read a line of text from a file in C?

A. readtext()

B. getline()

C. fgets() ✓

D. readline()

Answer: Option C — fgets()

Q892. What is the difference between 'r+' and 'w+' modes when opening a file in C?

A. 'r+' is for reading and writing, 'w+' is for reading only

B. 'r+' is for reading and writing, 'w+' is for writing only, creating a new file ✓

C. 'r+' is for reading and writing, 'w+' is for writing only, overwriting an existing file

D. 'r+' is for reading only, 'w+' is for reading and writing, creating a new file

Answer: Option B — 'r+' is for reading and writing, 'w+' is for writing only, creating a new file

Q893. Which function is used to delete a file in C?

A. deletefile()

B. remove() ✓

C. erasefile()

D. delete()

Answer: Option B — remove()

Q894. What does the 'fread' function in C do?

A. Reads binary data from a file ✓

B. Reads formatted data from a file

C. Reads a specific line from a file

D. Reads a character from a file

Answer: Option A — Reads binary data from a file

Q895. Which function is used to rename a file in C?

A. rename() ✓

B. changename()

C. movefile()

D. setfilename()

Answer: Option A — rename()

Q896. In C, what does the 'feof' function return if the end of the file is reached?

A. 0

B. 1

C. -1

D. EOF ✓

Answer: Option D — EOF

Q897. How do you check if a file exists in C?

A. Use the 'fileexist' function

B. Check the return value of fopen() ✓

C. Use the 'filestatus' variable

D. Use the 'fileopen' function

Answer: Option B — Check the return value of fopen()

Q898. What is the purpose of the 'ftell' function in C?

A. To find the current position of the file pointer ✓

B. To find the total number of bytes in a file

C. To check if a file is open

D. To find the file's size

Answer: Option A — To find the current position of the file pointer

Q899. Which function is used to write a character to a file in C?

A. putc() ✓

B. writechar()

C. putchar()

D. fileputchar()

Answer: Option A — putc()

Q900. What happens if you try to open a file in 'r' mode that doesn't exist in C?

A. A new file is created

B. An error occurs, and the file remains unchanged ✓

C. The program terminates

D. The file is deleted

Answer: Option B — An error occurs, and the file remains unchanged

---

Q901. How do you read a string from a file in C?

A. fscanf()

B. readstring()

C. getline()

D. fgets() ✓

Answer: Option D — fgets()

Q902. What does the 'remove' function in C do?

A. Deletes a file ✓

B. Renames a file

C. Closes a file

D. Appends data to a file

Answer: Option A — Deletes a file

Q903. In C, what is the purpose of the 'fflush' function?

A. To flush the standard input buffer

B. To flush the standard output buffer ✓

C. To close a file

D. To check if a file exists

Answer: Option B — To flush the standard output buffer

Q904. Which function is used to create a new directory in C?

A. createdir()

B. makedir()

C. mkdir() ✓

D. newfolder()

Answer: Option C — mkdir()

Q905. How do you write an integer to a file in C?

A. putint()

B. fprintf() ✓

C. writeint()

D. filewriteint()

Answer: Option B — fprintf()

Q906. What is the return value of 'putc' if it fails to write a character to a file in C?

A. 0

B. 1

C. -1

D. EOF ✓

Answer: Option D — EOF

Q907. Which function is used to read and write data in binary mode in C?

A. fread() ✓
B. fwritedata()
C. readbinary()
D. writebinary()
Answer: Option A — fread()

Q908. What is the purpose of the 'fileno' function in C?

A. To find the file number associated with a file ✓
B. To check if a file exists
C. To get the file's size
D. To close a file
Answer: Option A — To find the file number associated with a file

Q909. The given statement FILE *fptr;

A. Defines a pointer to the pre-defined structure type FILE ✓
B. Defines a pointer to the user-defined structure type FILE
C. Defines a pointer to the pre-defined data type FILE DESCRIPTOR
D. Creates a file with the name fptr
E. Creates a file pointed by fptr
Answer: Option A — Defines a pointer to the pre-defined structure type FILE

Q910. The function fprintf is used in the program .....

A. When too many printf calls have been used in the program.
B. In place of printf, as it uses more memory.
C. When the output is to be printed on to a file. ✓
D. When the type of the variables to be printed are not known.
E. If mixed data type variables are required to be printed on to the memory.
Answer: Option C — When the output is to be printed on to a file.

Q911. What are the two predefined FILE pointers in C?

A. console and error
B. stdout and stdio
C. stdout and stderr ✓
D. stdio and stderr
E. console and stdio.
Answer: Option C — stdout and stderr

Q912. Which one of the following is valid for opening a read-only ASCII file?

A. fileOpen(filename, "r");
B. fopen(filename, "ra");
C. fileOpne(filename, read);
D. fopen(filename, "read");
E. fopen(filename, "r"); ✓
Answer: Option E — fopen(filename, "r");

Q913. Choose the correct difference between getc() and fgetc().

A. If it is not a macro, it may evaluate stream more than once

B. if it is amacro, it may not evaluate stream more than once

C. if it is a macro, it may evaluate stream more than once ✓

D. no difference between fgetc() and getc()

Answer: Option C — if it is a macro, it may evaluate stream more than once

Q914. . . . . is an optional argument that gives the maximum number of characters to be read.

A. modifiers

B. width ✓

C. precision

D. length

Answer: Option B — width

Q915. What will be the output of the following C code? #include <stdio.h> struct p { struct p *next; int x; }; int main() { struct p* p1 = malloc(sizeof(struct p)); p1->x = 1; p1->next = malloc(sizeof(struct p)); printf("%d\n", p1->next->x); return 0; }

A. Compile time error

B. 1

C. Somegarbage value ✓

D. 0

Answer: Option C — Somegarbage value

Q916. If the conversion characters of int d, i, o, u and x are preceded by h, it indicates?

A. A pointer to int

B. A pointer to short ✓

C. A pointer to long

D. A pointer to char

Answer: Option B — A pointer to short

Q917. Which among the following mathematical function do not have a "double" return-type?

A. srand(x); ✓

B. ceil(x);

C. floor(x);

D. both ceil(x); and floor(x);

Answer: Option A — srand(x);

Q918. Which of the following function compares 2 strings with case-insensitively?

A. strcmp(s, t)

B. strcmpcase(s, t)

C. strcasecmp(s, t) ✓

D. strchr(s, t)

Answer: Option C — strcasecmp(s, t)

Q919. What is FILE reserved word?

A. A structure tag declared in stdio.h

B. One of the basic data types in c

C. Pointer to the structure defined in stdio.h

D. It is a type name defined in stdio.h ✓

Answer: Option D — It is a type name defined in stdio.h

Q920. What will be the output of the following C code? #include <stdio.h> #include <math.h> int main() { unsigned int i = -1; printf("%f\n", fabs(i)); return 0; }

A. Compile time error

B. 1

C. -1

D. None of the mentioned ✓

Answer: Option D — None of the mentioned

Q921. Each call of va_arg . . . . . .

A. Returns one argument

B. Steps va_list variable to the next

C. Returns one argument & Steps va_list variable to the next ✓

D. None of the mentioned

Answer: Option C — Returns one argument & Steps va_list variable to the next

Q922. setvbuf() and setbuf() function controls buffering for the stream.

A. true ✓

B. false

Answer: Option A — true

Q923. What will be the output of the following C code if following commands are used to run (considering myfile exists)? gcc -otest test.c ./test < myfile #include <stdio.h> int main() { char c = 'd'; putchar(c); }

A. Compile time error (after first command)

B. d in the myfile file

C. d on the screen ✓

D. Undefined behaviour

Answer: Option C — d on the screen

Q924. What will be the output of the following C code? #include <stdio.h> #include <ctype.h> int main() { int i = 0; if (isspace(i)) printf("space\n"); else printf("not space\n"); return 0; }

A. Compile time error

B. space

C. not space ✓

D. None of the mentioned

Answer: Option C — not space

Q925. fputs() function writes a string to a file that only ends with a newline.

A. True

B. False ✓

C. Depends on the standard

D. Depends on the compiler

Answer: Option B — False

Q926. . . . . removes the named file, so that a subsequent attempt to open it will fail.

A. remove(const *filename) ✓

B. remove(filename)

C. remove()

D. fclose(filename)

Answer: Option A — remove(const *filename)

Q927. Escape sequences are prefixed with . . . . . .

A. %

B. /

C. "

D. None of the mentioned ✓

Answer: Option D — None of the mentioned

Q928. What is the default return-type of getchar()?

A. char

B. int ✓

C. char *

D. reading character doesn't require a return-type

Answer: Option B — int

Q929. Choose the correct description for control string %-+7.2f.

A. - means display the sign, + means left justify, 7 specifies the width and 2 specifies the precision

B. - means left justify, + means display the sign, 7 specifies the width and 2 specifies the precision ✓

C. - means display the sign, + means left justify, 7 specifies the precision and 2 specifies the width

D. - means left justify, + means display the sign, 7 specifies the precision and 2 specifies the width

Answer: Option B — - means left justify, + means display the sign, 7 specifies the width and 2 specifies the precision

Q930. What will be the output of the following C code? #include <stdio.h> #include <ctype.h> int main() { char c = 't'; printf("is :%c\n", tolower('A')); }

A. A

B. a ✓

C. Non-zero number

D. Zero

Answer: Option B — a

Q931. ungetc() is used . . . . . .

A. to get a char

B. to get an int

C. to push a character back to file ✓

D. nothing

Answer: Option C — to push a character back to file

Q932. Which mathematical function among the following does NOT require int parameters?

A. div(x, y);

B. srand(x);

C. sqrt(x); ✓

D. all of the mentioned

Answer: Option C — sqrt(x);

Q933. Which pre-defined function returns a pointer to the last occurence of a character in a string?

A. strchr(s, c);

B. strrchr(s, c); ✓

C. strlchr(s, c);

D. strfchr(s, c);

Answer: Option B — strrchr(s, c);

Q934. Select the correct value of i from given options i=scanf("%d %d", &a, &b);

A. 1

B. 2 ✓

C. 3

D. No value assigned

Answer: Option B — 2

Q935. What error will generate if the read and write parameters are not separated by commas?

A. run-time error

B. compile error ✓

C. logical error

D. no error

Answer: Option B — compile error

Q936. gets() and puts() operate on . . . . . .

A. stdin and stdout ✓

B. files

C. stderr

D. nothing

Answer: Option A — stdin and stdout

Q937. What will be the output of the following C code? #include <stdio.h> int main() { char str[11] = "hello"; char *str1 = "world"; strcat(str, str1); printf("%s %d", str, str[10]); }

A. helloworld 0 ✓

B. helloworld anyvalue

C. worldhello 0

D. Segmentation fault/code crash

Answer: Option A — helloworld 0

Q938. Only . . . . . character of pushback is guaranteed per file when ungetc is used.

A. Two

B. One ✓

C. Many

D. Zero

Answer: Option B — One

Q939. Which of the following statements about stdout and stderr are true?

A. Same

B. Both connected to screen always

C. Both connected to screen by default ✓

D. stdout is line buffered but stderr is unbuffered

Answer: Option C — Both connected to screen by default

Q940. What is the meaning of the following C statement? printf("%10s", state);

A. 10 spaces before the string state is printed

B. Print empty spaces if the string state is less than 10 characters ✓

C. Print the last 10 characters of the string

D. None of the mentioned

Answer: Option B — Print empty spaces if the string state is less than 10 characters

---

Q941. What will be the output of the following C code? #include <stdio.h> int main() { short int i; scanf("%*d", &i); printf("%hd", i); return 0; }

A. Compilation error

B. Somegarbage value ✓

C. Whatever user types

D. Depends on the standard

Answer: Option B — Somegarbage value

Q942. On freeing a dynamic memory, if the pointer value is not modified, then the pointer points to.

A. NULL

B. Other dynamically allocated memory

C. The same deallocated memory location ✓

D. It points back to the location it was initialized with

Answer: Option C — The same deallocated memory location

Q943. void * malloc(size_t n) returns?

A. Pointer to n bytes of uninitialized storage ✓

B. NULL if the request can be satisfied

C. Nothing

D. None of the mentioned

Answer: Option A — Pointer to n bytes of uninitialized storage

Q944. What does the following segment of C code do? fprintf(fp, "Copying!");

A. It writes "Copying!" into the file pointed by fp ✓

B. It reads "Copying!" from the file and prints on display

C. It writes as well as reads "Copying!" to and from the file and prints it

D. None of the mentioned

Answer: Option A — It writes "Copying!" into the file pointed by fp

Q945. Which of the following represents the function for scanf()?

A. void scanf(char *format, ...)

B. int scanf(char *format, ...) ✓

C. char scanf(int format, ...)

D. char *scanf(char *format, ...)

Answer: Option B — int scanf(char *format, ...)

Q946. Which of the following can be used for random number generation?

A. random() ✓

B. rnd()

C. rndm()

D. none of the mentioned

Answer: Option A — random()

Q947. What will be the output of the following C code? #include <stdio.h> int main() { char *s = "myworld"; int i = 9; printf("%*s", i, s); }

A. myworld

B. myworld(note: spaces to the left of myworld) ✓

C. myworld (note:followed by two spaces after myworld)

D. Undefined

Answer: Option B — myworld(note: spaces to the left of myworld)

Q948. What will be the output of the following C statement? fprintf(stderr, "error: could not open filen");

A. The diagnostic output is directly displayed in the output ✓

B. The diagnostic output is pipelined to the output file

C. The line which caused error is compiled again

D. The program is immediately aborted

Answer: Option A — The diagnostic output is directly displayed in the output

Q949. Which among the following is the odd one out?

A. printf

B. fprintf

C. putchar

D. scanf ✓

Answer: Option D — scanf

Q950. The syntax of the scanf() is scanf("control string ", arg1,arg2,arg3,....,argn); the prototype of control string is

A. [=%[width][modifiers]type=] ✓

B. [=%[modifiers][width]type=]

C. [=%[width] [modifiers]]

D. [width][modifiers]

Answer: Option A — [=%[width][modifiers]type=]

Q951. Output justification such as decimal point, numerical sign, trailing zeros or octal are specified.

A. specifier

B. flags ✓

C. precision

D. decimal

Answer: Option B — flags

Q952. function fabs defined math.h header file takes the argument of type integer.

A. True

B. False ✓

C. Depends on the implementation

D. Depends on the standard

Answer: Option B — False

Q953. What will be the output of the following C code considering user typed jkl? #include <stdio.h> int main() { char n[20]; fgets(n, 19, stdin); ungetc(n[0], stdin); printf("%s\n", n); return 0; }

A. jkl ✓

B. kl

C. Undefined behaviour

D. jk

Answer: Option A — jkl

Q954. Which of the following is NOT a delimiter for an input in scanf?

A. Enter

B. Space

C. Tab

D. None of the mentioned ✓

Answer: Option D — None of the mentioned

Q955. Which is true about isupper(c), where c is an int that can be represented as an unsigned? char or EOF.isupper(c) returns

A. Non-zero if c is upper case

B. 0 if c is not upper case

C. Nothing

D. Both Non-zero if c is upper case & 0 if c is not upper case ✓

Answer: Option D — Both Non-zero if c is upper case & 0 if c is not upper case

---

Q956. What will be the output of the following C code? #include <stdio.h> #include <math.h> void main() { int k = fabs(-87); printf("%d\n", k); }

A. -87

B. 87 ✓

C. 78

D. error

Answer: Option B — 87

Q957. gets() function checks overflow run.

A. True

B. False ✓

C. Depends on the standard

D. Undefined behaviour

Answer: Option B — False

Q958. In linux, apart from including math header file, the program is successfully executed by which of the following?

A. cc filename.c

B. cc filename.c -lc

C. cc -math filename.c

D. cc -lm filename.c ✓

Answer: Option D — cc -lm filename.c

Q959. What will be the output of the following C code? #include <stdio.h> int main() { char i = '9'; if (isdigit(i)) printf("digit\n"); else printf("not digit\n"); return 0; }

A. digit ✓

B. not digit

C. Depends on the compiler

D. None of the mentioned

Answer: Option A — digit

Q960. What will be the output of the following C code? #include <stdio.h> #include <stdlib.h> int main() { FILE *fp = stdout; int n; fprintf(fp, "%d", 45); }

A. Compilation error

B. 45 ✓

C. Nothing

D. Depends on the standard

Answer: Option B — 45

Q961. Which of the following is the correct declaration for ungetc?

A. int ungetc(int c, FILE fp);

B. int ungetc(int *c, FILE fp);

C. int ungetc(int c, FILE *fp); ✓

D. int ungetc(int *c, FILE *fp);

Answer: Option C — int ungetc(int c, FILE *fp);

Q962. What is the purpose of sprintf?

A. It prints the data into stdout

B. It writes the formatted data into a string ✓

C. It writes the formatted data into a file

D. None of the mentioned

Answer: Option B — It writes the formatted data into a string

Q963. What will be the output of the following C code? #include <stdio.h> #include <math.h> int main() { int i = 10; printf("%f\n", log10(i)); return 0; }

A. Compile time error

B. 1.000000 ✓

C. 2.302585

D. None of the mentioned

Answer: Option B — 1.000000

Q964. Memory allocation using malloc() is done in . . . . . .

A. Static area

B. Stack area

C. Heap area ✓

D. Both Stack & Heap area

Answer: Option C — Heap area

Q965. Which is true about isaplpha(c), where c is an int that can be represented as an unsigned? char or EOF.isalpha(c) returns

A. Non-zero if c is alphabetic

B. 0 if c is not alphabetic

C. Both Non-zero if c is alphabetic & 0 if c is not alphabetic ✓

D. None of the mentioned

Answer: Option C — Both Non-zero if c is alphabetic & 0 if c is not alphabetic

---

Q966. For the function call time(), what type of parameter is accepted?

A. int

B. int *

C. time_t

D. time_t * ✓

Answer: Option D — time_t *

Q967. fwrite() can be used only with files that are opened in binary mode.

A. true ✓

B. false

Answer: Option A — true

Q968. What is meant by 'a' in the following C operation? fp = fopen("Random.txt", "a");

A. Attach

B. Append ✓

C. Apprehend

D. Add

Answer: Option B — Append

Q969. The parameter control string in the printf () is a C String that contains text to be . . . . . .

A. taken from a standard output device

B. written on to the standard output device ✓

C. received from the standard output device

D. nothing can be said

Answer: Option B — written on to the standard output device

Q970. What will be the output of the following C code? printf("\n Output: %5d \t %x \t %#x", 234,234,234);

A. Output:234EA0xEA

B. Output:00234 EA 0xEA

C. Output: 234 EA 0xEA ✓

D. ERROR

Answer: Option C — Output: 234 EA 0xEA

Q971. The syntax to print a % using printf statement can be done by . . . . . .

A. %

B. \%

C. '%'

D. %% ✓

Answer: Option D — %%

Q972. What will be the output of the following C code? #include <stdio.h> #include <stdlib.h> int main() { srand(9000); printf("%d\n", rand()); return 0; }

A. Compile time error

B. An integer in the range 0 to RAND_MAX ✓

C. A double in the range 0 to 1

D. A float in the range 0 to 1

Answer: Option B — An integer in the range 0 to RAND_MAX

Q973. The conversion characters d, i, o, u, and x may be preceded by h in scanf() to indicate?

A. A pointer to short ✓

B. A pointer to long

C. Nothing

D. Error

Answer: Option A — A pointer to short

Q974. The maximum number of characters to be printed is specified by . . . . . .

A. precision ✓

B. width

C. length

D. flags

Answer: Option A — precision

Q975. In function free(p), p is a . . . . . .

A. int

B. pointer returned by malloc()

C. pointer returned by calloc()

D. pointer returned by malloc() & calloc() ✓

Answer: Option D — pointer returned by malloc() & calloc()

Q976. What will be the output of the following code? char t='N'; printf("\n %c \n %3c \n %5c",t,t,t);

A. N N N

B. N N N ✓

C. N N N

D. N N N

Answer: Option B — N N N

Q977. What will be the output of the following C code? #include <stdio.h> int main(int argc, char argv) { char *s = "myworld"; int i = 3; printf("%10.*s", i, s); }**

A. myw(note:7 spaces before myw) ✓

B. myworld(note:2 spaces before myworld)

C. myworld (note:2 spaces after myworld)

D. myw(note:6 spaces after myw)

Answer: Option A — myw(note:7 spaces before myw)

Q978. What is the output of the following C code if there is no error in stream fp? #include <stdio.h> int main() { FILE *fp; fp = fopen("newfile", "w"); printf("%d\n", ferror(fp)); return 0; }

A. Compilation error

B. 0 ✓

C. 1

D. Any nonzero value

Answer: Option B — 0

Storage Class

Q979. What is the default storage class for global variables?

A. auto

B. static

C. extern ✓

D. register

Answer: Option C — extern

Q980. Which storage class is used for local variables?

A. register

B. auto ✓

C. static

D. extern

Answer: Option B — auto

Q981. What is the primary purpose of the 'static' storage class?

A. Extend scope

B. Preserve value ✓

C. Allocate memory

D. Register access

Answer: Option B — Preserve value

Q982. Which storage class specifies automatic storage duration?

A. auto ✓

B. static

C. extern

D. register

Answer: Option A — auto

Q983. When does a 'register' storage class make sense to use?

A. For global vars

B. For function args ✓

C. For local vars

D. For static vars

Answer: Option B — For function args

Q984. What is the significance of the 'extern' storage class?

A. Local scope

B. External linkage ✓

C. Automatic alloc.

D. Static duration

Answer: Option B — External linkage

Q985. Which storage class allocates memory and retains its value between function calls?

A. extern

B. auto

C. static ✓

D. register

Answer: Option C — static

Q986. What is the maximum scope of a variable with 'static' storage class?

A. File scope ✓
B. Function scope
C. Block scope
D. No scope (invalid)
Answer: Option A — File scope

Q987. What is the storage duration of a variable with 'auto' storage class?

A. Static
B. Automatic ✓
C. Register
D. External
Answer: Option B — Automatic

Q988. In which storage class is the variable's storage duration throughout the program's execution?

A. extern
B. static ✓
C. auto
D. register
Answer: Option B — static

Q989. Which storage class is used for function arguments by default?

A. extern
B. auto ✓
C. static
D. register
Answer: Option B — auto

Q990. What is the primary advantage of using 'register' storage class for variables?

A. Larger scope
B. Faster access ✓
C. Longer duration
D. Automatic alloc.
Answer: Option B — Faster access

Q991. What storage class should be used for a variable that needs to be shared across multiple source files?

A. auto
B. register
C. extern ✓
D. static
Answer: Option C — extern

Q992. In which storage class is the variable's storage duration limited to the function where it's declared?

A. extern

B. static

C. auto ✓

D. register

Answer: Option C — auto

Q993. Which storage class is often used for variables with block scope within functions?

A. register

B. extern

C. auto ✓

D. static

Answer: Option C — auto

Q994. What storage class is used for function parameters in C by default?

A. static

B. auto ✓

C. register

D. extern

Answer: Option B — auto

Q995. Which storage class is used to define variables that are not initialized to any default value?

A. auto ✓

B. static

C. extern

D. register

Answer: Option A — auto

Q996. When is memory allocated for a 'static' variable in C?

A. During compile time ✓

B. During runtime

C. During function call

D. During program termination

Answer: Option A — During compile time

Q997. Which storage class should be used for a variable that should be accessed quickly and frequently?

A. static

B. extern

C. register ✓

D. auto

Answer: Option C — register

Q998. What is the primary difference between 'auto' and 'register' storage classes?

A. Scope

B. Initialization

C. Memory allocation

D. Storage duration ✓

Answer: Option D — Storage duration

Q999. In which storage class are variables allocated memory in the data segment of the program's memory?

A. auto
B. extern
C. static ✓
D. register
Answer: Option C — static

Q1000. Which storage class can only be used for local variables?

A. register ✓
B. static
C. extern
D. auto
Answer: Option A — register

Q1001. What storage class is typically used for function definitions in header files?

A. extern ✓
B. static
C. auto
D. register
Answer: Option A — extern

Q1002. What happens when you declare a variable with the 'extern' storage class in a C source file?

A. It becomes a global variable ✓
B. It becomes a constant
C. It cannot be accessed by other files
D. It becomes a local variable
Answer: Option A — It becomes a global variable

Q1003. In which storage class is a variable's memory allocated on the stack?

A. auto ✓
B. extern
C. register
D. static
Answer: Option A — auto

Q1004. Which storage class can help improve execution speed by allowing variables to be stored in CPU registers?

A. static
B. extern
C. auto
D. register ✓
Answer: Option D — register

Q1005. What is the storage duration of a variable with 'static' storage class?

A. Automatic
B. Register
C. External

D. Static ✓

Answer: Option D — Static

Q1006. What is the default value of an uninitialized 'static' variable in C?

A. Zero ✓

B. Undefined

C. Garbage value

D. one

Answer: Option A — Zero

Q1007. In which storage class are variables typically stored in the heap memory?

A. static

B. extern

C. auto ✓

D. register

Answer: Option C — auto

Q1008. What is the main purpose of the 'volatile' storage class in C?

A. Prevents memory allocation

B. Forces a variable to be stored in registers

C. Indicates that a variable may change unexpectedly ✓

D. Increases variable scope

Answer: Option C — Indicates that a variable may change unexpectedly

Q1009. Which of the following is not a storage class in C?

A. auto

B. struct ✓

C. extern

D. static

E. register

Answer: Option B — struct

Q1010. The storage class controls

A. Life time of a variable.

B. Linkage of a variable.

C. Scope of a variable.

D. A and B

E. A, B and C ✓

Answer: Option E — A, B and C

Q1011. When a function is recursively called all the automatic variables are stored in a

A. Stack ✓

B. Queue

C. Array

D. Linked list

E. Register

Answer: Option A — Stack

Q1012. What does the "auto" specifier do?

A. It automatically initializes a variable to 0

B. It indicates that a variable's memory will automatically be preserved ✓

C. It automatically increments the variable when used

D. It automatically initializes a variable to NULL

E. It indicates that a variable's memory space is allocated upon entry into the block.

Answer: Option B — It indicates that a variable's memory will automatically be preserved

Q1013. How is a variable accessed from another file?

A. The global variable is referenced via the extern specifier. ✓

B. The global variable is referenced via the auto specifier.

C. The global variable is referenced via the global specifier.

D. The global variable is referenced via the pointer specifier.

E. The global variable is referenced via the ext specifier.

Answer: Option A — The global variable is referenced via the extern specifier.

Memory Allocation

Q1014. In C, which header file should be included to use dynamic memory allocation functions?

A. stdlib.h ✓
B. malloc.h
C. memory.h
D. alloc.h
Answer: Option A — stdlib.h

Q1015. What is the purpose of the 'malloc' function in C?

A. To allocate dynamic memory ✓
B. To allocate static memory
C. To deallocate memory
D. To find memory leaks
Answer: Option A — To allocate dynamic memory

Q1016. Which function is used to allocate an array of elements in C?

A. calloc() ✓
B. malloc()
C. alloc()
D. array()
Answer: Option A — calloc()

Q1017. What does the 'calloc' function in C do?

A. Allocates and initializes memory to zero ✓
B. Allocates memory and leaves it uninitialized
C. Deallocates memory
D. Checks for memory leaks
Answer: Option A — Allocates and initializes memory to zero

Q1018. Which function is used to change the size of an allocated block of memory in C?

A. resize()
B. realloc() ✓
C. modify()
D. change()
Answer: Option B — realloc()

Q1019. What is the return value of the 'malloc' function if it fails to allocate memory?

A. NULL ✓
B. -1
C. 0
D. 1
Answer: Option A — NULL

Q1020. How do you release dynamically allocated memory in C?

A. free() ✓
B. release()
C. deallocate()
D. clear()

Answer: Option A — free()

Q1021. What is the purpose of the 'memset' function in C?

A. To allocate memory

B. To set memory to zero ✓

C. To find memory leaks

D. To copy memory

Answer: Option B — To set memory to zero

Q1022. Which function is used to copy a block of memory in C?

A. memcpy() ✓

B. copymem()

C. memcopy()

D. memorycopy()

Answer: Option A — memcpy()

Q1023. What is a memory leak in C?

A. Failure to deallocate dynamically allocated memory ✓

B. Memory allocation error

C. Excessive memory deallocation

D. Memory corruption

Answer: Option A — Failure to deallocate dynamically allocated memory

Q1024. What is the purpose of the 'free' function in C?

A. To deallocate dynamically allocated memory ✓

B. To allocate memory

C. To copy memory

D. To check for memory leaks

Answer: Option A — To deallocate dynamically allocated memory

Q1025. How do you check if the 'malloc' function has successfully allocated memory in C?

A. Check if the return value is not NULL ✓

B. Check if the return value is 1

C. Check if the return value is -1

D. Check if the return value is 0

Answer: Option A — Check if the return value is not NULL

Q1026. Which function is used to return the number of bytes allocated by 'malloc'?

A. malloc_size()

B. sizeofmalloc() ✓

C. size()

D. malloc_bytes()

Answer: Option B — sizeofmalloc()

Q1027. What is the return value of the 'realloc' function if it fails to reallocate memory?

A. NULL ✓

B. -1

C. 0

D. 1

Answer: Option A — NULL

Q1028. In C, what is the purpose of the 'calloc' function?

A. To allocate and initialize a block of memory ✓

B. To deallocate memory

C. To copy memory

D. To check for memory leaks

Answer: Option A — To allocate and initialize a block of memory

Q1029. What does the 'sizeof' operator in C return for a dynamically allocated array?

A. Size of a single element ✓

B. Size of the entire array

C. Size of the pointer

D. Size of the first element

Answer: Option A — Size of a single element

Q1030. Which function is used to allocate memory for an array of character strings in C?

A. malloc()

B. calloc() ✓

C. alloc()

D. stralloc()

Answer: Option B — calloc()

Q1031. What is a segmentation fault in C?

A. An error that occurs when accessing an invalid memory location ✓

B. An error in memory allocation

C. An error when allocating a string

D. An error in file I/O

Answer: Option A — An error that occurs when accessing an invalid memory location

Q1032. How do you check if the 'realloc' function has successfully reallocated memory in C?

A. Check if the return value is not NULL ✓

B. Check if the return value is 1

C. Check if the return value is -1

D. Check if the return value is 0

Answer: Option A — Check if the return value is not NULL

Q1033. Which function is used to free allocated memory but does not remove the pointer in C?

A. clear()

B. free() ✓

C. release()

D. deallocate()

Answer: Option B — free()

Q1034. What is the maximum number of bytes that can be allocated using 'malloc' in C?

A. It depends on the system and available memory ✓

B. 2^16 bytes

C. 2^32 bytes

D. 2^64 bytes

Answer: Option A — It depends on the system and available memory

Q1035. What is the difference between 'malloc' and 'calloc' in C?

A. 'malloc' allocates uninitialized memory, 'calloc' allocates and initializes to zero ✓

B. 'malloc' allocates and initializes to zero, 'calloc' allocates uninitialized memory

C. 'malloc' is used for arrays, 'calloc' is used for single elements

D. 'malloc' allocates memory from the stack, 'calloc' allocates from the heap

Answer: Option A — 'malloc' allocates uninitialized memory, 'calloc' allocates and initializes to zero

---

Q1036. In C, which function is used to allocate memory from the stack?

A. alloc()

B. stackalloc()

C. malloc() ✓

D. calloc()

Answer: Option C — malloc()

Q1037. What happens if you attempt to free the same block of memory twice in C?

A. It leads to undefined behavior ✓

B. The program terminates

C. Memory is released, but the pointer remains valid

D. Memory is leaked

Answer: Option A — It leads to undefined behavior

Q1038. What is the primary advantage of using dynamic memory allocation in C?

A. Flexibility to allocate memory at runtime ✓

B. Faster execution of programs

C. Smaller memory footprint

D. Elimination of memory leaks

Answer: Option A — Flexibility to allocate memory at runtime

Q1039. Which function is used to allocate memory for a structure in C?

A. malloc() ✓

B. structurealloc()

C. structalloc()

D. calloc()

Answer: Option A — malloc()

Q1040. What is the difference between 'free' and 'delete' in C?

A. 'free' is used for dynamic memory, 'delete' is used for static memory ✓

B. 'free' is used for dynamic memory, 'delete' is used for freeing memory

C. 'free' is used for C, 'delete' is used for C++

D. 'free' is used for static memory, 'delete' is used for dynamic memory

Answer: Option A — 'free' is used for dynamic memory, 'delete' is used for static memory

---

Q1041. Which function is used to release all dynamically allocated memory in C?

A. clearall()

B. deallocateall()

C. freeall() ✓

D. clearmemory()

Answer: Option C — freeall()

Q1042. In C, what is the purpose of the 'realloc' function?

A. To change the size of a previously allocated block of memory ✓

B. To allocate memory for a structure

C. To copy memory

D. To check for memory leaks

Answer: Option A — To change the size of a previously allocated block of memory

Q1043. What is a memory fragment in C?

A. Unused memory between allocated blocks ✓

B. A type of data structure

C. A reserved portion of memory

D. A function to allocate memory

Answer: Option A — Unused memory between allocated blocks

Q1044. The number of arguments for realloc() function is/are:

A. 0

B. 1

C. 2 ✓

D. 3

E. Depends upon user choice.

Answer: Option C — 2

Q1045. With every use of a memory allocation function, what function should be used to release allocated memory, which is no longer needed?

A. unalloc()

B. dropmem()

C. dealloc()

D. release()

E. free() ✓

Answer: Option E — free()

Q1046. Array is preferred over linked list for the implementation of . . . . . .

A. Radix sort

B. Insertion sort

C. Binary search ✓

D. Polynomial evaluation

Answer: Option C — Binary search

Q1047. The free() function frees the memory state pointed to by a pointer and returns . . . . . .

A. the same pointer

B. the memory address

C. no value ✓

D. an integer value

Answer: Option C — no value

Q1048. When the pointer is NULL, then the function realloc is equivalent to the function . . . . . .

A. malloc ✓

B. calloc

C. free

D. alloc

Answer: Option A — malloc

Q1049. What will be the output of the following C code if the input entered as first and second number is 5 and 6 respectively? #include<stdio.h> #include<stdlib.h> main() { int *p; p=(int*)calloc(3*sizeof(int)); printf("Enter first number\n"); scanf("%d",p); printf("Enter second number\n"); scanf("%d",p+2); printf("%d%d",*p,*(p+2)); free(p); }

A. 56

B. Address of the locations where the two numbers are stored

C. 57

D. Error ✓

Answer: Option D — Error

Q1050. What will be the output of the following C code? #include<stdio.h> #include<stdlib.h> void main() { char *p = calloc(100, 1); p = "welcome"; printf("%s\n", p); }

A. error

B. welcome ✓

C. memory location stored by the pointer

D. junk value

Answer: Option B — welcome

Q1051. Which of the following is an example for non linear data type?

A. Tree ✓

B. Array

C. Linked list

D. Queue

Answer: Option A — Tree

Q1052. Local variables are stored in an area called . . . . . .

A. Heap

B. Permanent storage area

C. Free memory

D. Stack ✓

Answer: Option D — Stack

Q1053. If the space in memory allocated by malloc is not sufficient, then an allocation fails and returns . . . . . .

A. NULL pointer ✓

B. Zero

C. Garbage value

D. The number of bytes available

Answer: Option A — NULL pointer

Q1054. The following C code is an example of . . . . . #include<stdio.h> #include<stdlib.h> #include<string.h> main() { char *p,*q; p=(char*)malloc(3*sizeof(char)); q=p; strcpy(p,"hello"); printf("p=%s",p); printf("q=%s",q); free(q); q=NULL; gets(p); gets(q); printf("%s",p);

printf(“%s”,q); }

A. Memory leak

B. Dangling pointer ✓

C. Static memory allocation

D. Linked list

Answer: Option B — Dangling pointer

Q1055. If malloc() and calloc() are not type casted, the default return type is . . . . . .

A. void* ✓

B. void**

C. int*

D. char*

Answer: Option A — void*

Q1056. Which of the following functions allocates multiple blocks of memory, each block of the same size?

A. malloc()

B. realloc()

C. calloc() ✓

D. free()

Answer: Option C — calloc()

Q1057. A condition where in memory is reserved dynamically but not accessible to any of the programs is called . . . . . .

A. Memory leak ✓

B. Dangling pointer

C. Frozen memory

D. Pointer leak

Answer: Option A — Memory leak

Q1058. Which of the following header files must necessarily be included to use dynamic memory allocation functions?

A. stdlib.h ✓

B. stdio.h

C. memory.h

D. dos.h

Answer: Option A — stdlib.h

Q1059. What will be the error (if any) in the following C code? #include<stdio.h> #include<stdlib.h> #include<string.h> int main() { char *p; *p = (char)calloc(10); strcpy(p, "HELLO"); printf("%s", p); free(p); return 0; }

A. No error

B. Error in the statement: strcpy(p,"HELLO");

C. Error in the statement: *p=(char)calloc(10); ✓

D. Error in the statement: free(p);

Answer: Option C — Error in the statement: *p=(char)calloc(10);

Q1060. What will happens if the statement free(a) is removed in the following C code? #include<stdio.h> #include<stdlib.h> main() { int *a; a=(int*)malloc(sizeof(int)); *a=100;

printf("*a%d",*a); free(a); a=(int*)malloc(sizeof(int)); *a=200; printf("a%p",a); *a=200; printf("a%d",*a); }

A. Error

B. Memory leak ✓

C. Dangling pointer arises

D. 200 is printed as output

Answer: Option B — Memory leak

Q1061. In the function realloc(), if the new size of the memory block is larger than the old size, then the added memory . . . . . .

A. is initialized to junk values

B. is initialized to zero

C. results in an error

D. is not initialized ✓

Answer: Option D — is not initialized

Q1062. What will be the output of the following C code if it is executed on a 32 bit processor? #include<stdio.h> #include<stdlib.h> int main() { int *p; p = (int *)malloc(20); printf("%d\n", sizeof(p)); free(p); return 0; }

A. 2

B. 4 ✓

C. 8

D. Junk value

Answer: Option B — 4

Q1063. Garbage collector frees the programmer from worrying about . . . . . .

A. Dangling pointers

B. Creating new objects

C. Memory leak ✓

D. Segmentation errors

Answer: Option C — Memory leak

Q1064. Suppose we have a one dimensional array, named 'x', which contains 10 integers. Which of the following is the correct way to allocate memory dynamically to the array 'x' using malloc()?

A. x=(int*)malloc(10);

B. x=(int*)malloc(10,sizeof(int));

C. x=malloc(int 10,sizeof(int));

D. x=(int*)malloc(10*sizeof(int)); ✓

Answer: Option D — x=(int*)malloc(10*sizeof(int));

Q1065. Queue data structure works on the principle of . . . . . .

A. Last In First Out (LIF0)

B. First In Last Out (FILO)

C. First In First Out (FIFO) ✓

D. Last In Last Out (LILO)

Answer: Option C — First In First Out (FIFO)

Q1066. Which of the following is an example of static memory allocation?

A. Linked list

B. Stack

C. Queue

D. Array ✓

Answer: Option D — Array

Q1067. What will be the output of the following C code? (Given that the size of array is 4 and new size of array is 5) #include<stdio.h> #include<stdlib.h> main() { int *p,i,a,b; printf("Enter size of array"); scanf("%d",&a); p=(int*)malloc(a*sizeof(int)); for(i=0;i<a;i++) printf("%d\n",i); printf("Enter new size of array"); scanf("%d",&b); realloc(p,b); for(i=0;i<b;i++) printf("%d\n",i); free(p); }

A. 1234 12345

B. Error

C. 0123 01234 ✓

D. 0123 12345

Answer: Option C — 0123 01234

Q1068. The type of linked list in which the node does not contain any pointer or reference to the previous node is . . . . . .

A. Circularly singly linked list

B. Singly linked list ✓

C. Circular doubly linked list

D. Doubly linked list

Answer: Option B — Singly linked list

Q1069. In the function malloc(), each byte of allocated space is initialized to zero.

A. True

B. False ✓

Answer: Option B — False

Q1070. The number of arguments taken as input which allocating memory dynamically using malloc() is . . . . . .

A. 0

B. 1 ✓

C. 2

D. 3

Answer: Option B — 1

Q1071. Choose the statement which is incorrect with respect to dynamic memory allocation.

A. Memory is allocated in a less structured area of memory, known as heap

B. Used for unpredictable memory requirements

C. Execution of the program is faster than that of static memory allocation ✓

D. Allocated memory can be changed during the run time of the program based on the requirement of the program

Answer: Option C — Execution of the program is faster than that of static memory allocation

Q1072. Pick out the correct statement with respect to the heap.

A. Local variables are stored on the heap

B. Static variables are stored on the heap

C. Heap is the data structure that is used to implement recursive function calls

D. Everything on the heap is anonymous ✓

Answer: Option D — Everything on the heap is anonymous

Q1073. The size of both stack and heap remains the same during run time.

A. True

B. False ✓

Answer: Option B — False

Q1074. The advantage of using linked lists over arrays is that . . . . . .

A. Linked list is an example of linear data structure

B. Insertion and deletion of an element can be done at any position in a linked list ✓

C. Linked list can be used to store a collection of homogenous and heterogeneous data types

D. The size of a linked list is fixed

Answer: Option B — Insertion and deletion of an element can be done at any position in a linked list

Q1075. The incorrect statement with respect to dangling pointers is . . . . . .

A. Pointer pointing to non-existent memory location is called dangling pointer

B. When a dynamically allocated pointer references the original memory after it has been freed, a dangling pointer arises

C. If memory leak occurs, it is mandatory that a dangling pointer arises ✓

D. Dangling pointer may result in segmentation faults and potential security risks

Answer: Option C — If memory leak occurs, it is mandatory that a dangling pointer arises

Standard Library Functions

Q1076. Which standard library function is used to calculate the length of a string in C?

A. strlen() ✓
B. strlength()
C. stringlen()
D. strsize()
Answer: Option A — strlen()

Q1077. What is the purpose of the 'printf' function in C?

A. To print formatted text to the standard output ✓
B. To read text from the standard input
C. To open a file
D. To close a file
Answer: Option A — To print formatted text to the standard output

Q1078. Which library should be included to use the 'sqrt' function in C?

A. math.h ✓
B. stdlib.h
C. cmath.h
D. algorithm.h
Answer: Option A — math.h

Q1079. What does the 'strcmp' function in C do?

A. Compares two strings and returns an integer indicating their relationship ✓
B. Copies one string to another
C. Concatenates two strings
D. Searches for a substring
Answer: Option A — Compares two strings and returns an integer indicating their relationship

Q1080. What is the purpose of the 'scanf' function in C?

A. To read formatted input from the standard input ✓
B. To print text to the standard output
C. To open a file
D. To close a file
Answer: Option A — To read formatted input from the standard input

---

Q1081. Which function is used to convert a string to an integer in C?

A. atoi() ✓
B. itoa()
C. str2int()
D. int2str()
Answer: Option A — atoi()

Q1082. What is the return value of the 'rand' function in C?

A. A random integer ✓
B. A float between 0 and 1
C. A character
D. A boolean value

Answer: Option A — A random integer

Q1083. Which function is used to generate a random number in C?

A. rand() ✓
B. random()
C. randomize()
D. generate_random()
Answer: Option A — rand()

Q1084. What is the purpose of the 'atoi' function in C?

A. Converts a string to an integer ✓
B. Converts an integer to a string
C. Copies a string
D. Searches for a substring
Answer: Option A — Converts a string to an integer

Q1085. Which library should be included to use the 'sin' function in C?

A. math.h ✓
B. stdlib.h
C. cmath.h
D. algorithm.h
Answer: Option A — math.h

Q1086. What does the 'fgets' function in C do?

A. Reads a line of text from a file ✓
B. Reads a single character from the standard input
C. Compares two strings
D. Converts a string to an integer
Answer: Option A — Reads a line of text from a file

Q1087. Which function is used to open a file in C?

A. fopen() ✓
B. openfile()
C. readfile()
D. closefile()
Answer: Option A — fopen()

Q1088. What is the purpose of the 'abs' function in C?

A. To calculate the absolute value of an integer ✓
B. To find the maximum value in an array
C. To convert a string to lowercase
D. To calculate the square root of a number
Answer: Option A — To calculate the absolute value of an integer

Q1089. Which standard library function is used to clear the standard input buffer in C?

A. fflush() ✓
B. clearbuffer()
C. clearinput()
D. clrscr()

Answer: Option A — fflush()

Q1090. What does the 'strcpy' function in C do?

A. Copies one string to another ✓
B. Compares two strings
C. Searches for a substring
D. Concatenates two strings
Answer: Option A — Copies one string to another

Q1091. Which function is used to find the smallest integer greater than or equal to a given floating-point number in C?

A. ceil() ✓
B. floor()
C. round()
D. nextint()
Answer: Option A — ceil()

Q1092. What is the purpose of the 'strcpy' function in C?

A. Copies one string to another ✓
B. Compares two strings
C. Searches for a substring
D. Converts a string to an integer
Answer: Option A — Copies one string to another

Q1093. Which library should be included to use the 'pow' function in C?

A. math.h ✓
B. stdio.h
C. cmath.h
D. algorithm.h
Answer: Option A — math.h

Q1094. What does the 'strcat' function in C do?

A. Concatenates two strings ✓
B. Compares two strings
C. Copies one string to another
D. Searches for a substring
Answer: Option A — Concatenates two strings

Q1095. Which standard library function is used to find the largest integer less than or equal to a given floating-point number in C?

A. floor() ✓
B. ceil()
C. round()
D. prevint()
Answer: Option A — floor()

Q1096. What is the purpose of the 'tolower' function in C?

A. Converts a character to lowercase ✓
B. Converts a character to uppercase

C. Removes leading spaces from a string

D. Converts a string to lowercase

Answer: Option A — Converts a character to lowercase

Q1097. Which function is used to close a file in C?

A. fclose() ✓

B. close()

C. endfile()

D. fileclose()

Answer: Option A — fclose()

Q1098. What is the return value of the 'getchar' function in C?

A. The character read from the standard input ✓

B. A random integer

C. -1

D. 0

Answer: Option A — The character read from the standard input

Q1099. Which library should be included to use the 'sin' function in C?

A. math.h ✓

B. stdlib.h

C. cmath.h

D. algorithm.h

Answer: Option A — math.h

Q1100. What does the 'getch' function in C do?

A. Reads a character from the standard input without echoing ✓

B. Reads a character from the standard input with echoing

C. Copies one string to another

D. Compares two strings

Answer: Option A — Reads a character from the standard input without echoing

---

Q1101. What is the purpose of the 'toupper' function in C?

A. Converts a character to uppercase ✓

B. Converts a character to lowercase

C. Removes trailing spaces from a string

D. Converts a string to uppercase

Answer: Option A — Converts a character to uppercase

Q1102. Which function is used to find the square root of a number in C?

A. sqrt() ✓

B. sqrtr()

C. sqrtroot()

D. squareroot()

Answer: Option A — sqrt()

Q1103. What is the purpose of the 'isalpha' function in C?

A. Checks if a character is alphabetic ✓

B. Checks if a character is numeric

C. Checks if a character is a special character

D. Checks if a character is uppercase

Answer: Option A — Checks if a character is alphabetic

Q1104. Which standard library function is used to open a file in C?

A. fopen() ✓

B. openfile()

C. readfile()

D. closefile()

Answer: Option A — fopen()

Q1105. What does the 'abs' function in C do?

A. Calculates the absolute value of an integer ✓

B. Finds the maximum value in an array

C. Converts a string to lowercase

D. Calculates the square root of a number

Answer: Option A — Calculates the absolute value of an integer

---

Q1106. The C library macro type . . . . . retrieves the next argument in the parameter list of the function with type.

A. va_end

B. va_arg ✓

C. va_start

D. no macros

Answer: Option B — va_arg

Q1107. What will be the output of the following C code? char str[20]; strcpy(str, "123456"); res = atoi(str); printf("%s %d\n", str, res);

A. 123456 0

B. 123456 0.0

C. 123456 123456 ✓

D. 123456 123456.0

Answer: Option C — 123456 123456

Q1108. MB_CUR_MAX is not defined in stdlib.h.

A. true

B. false ✓

Answer: Option B — false

Q1109. What is the type declared by the header file signal.h?

A. sig_atomic_t ✓

B. sig_signal_t

C. sig_signal_h

D. sig_stomic_h

Answer: Option A — sig_atomic_t

Q1110. The source filename and line number come from the preprocessor macros . . . . . and . . . . . .

A. _ _FILE_ _ and _ _LINE_ _ ✓

B. _ _NAME_ _ and _ _NUMBER_ _

C. _ _FILENAME_ _ and _ _NMN_ _

D. _ _FILE_ _ and _ _NUM_ _

Answer: Option A — _ _FILE_ _ and _ _LINE_ _

Q1111. What will the given C code do? #include <stdlib.h> _Mbsave_Mbxlen={0}; int (mblen)(const char *s ,size_t n) { return(_Mbtowc(NULL s,n,&_Mbxlen)); }

A. determine length of next multibyte code ✓

B. determine next multibyte code

C. translate multibyte string to wide char string

D. translate wide character to multibyte string

Answer: Option A — determine length of next multibyte code

Q1112. Which of the given statement is true with respect to the function atexit()?

A. The atexit() function cannot return to its caller

B. The atexit() function is used to return zero if the registration succeeds, nonzero if it fails ✓

C. The atexit() function returns no value

D. The atexit() function causes abnormal program termination to occur

Answer: Option B — The atexit() function is used to return zero if the registration succeeds, nonzero if it fails

Q1113. What will be the output of the following C code? #include <assert. h> #include <stdio . h> #include <stdlib.h> void -Assert (char *mesg) { fputs (mesg, stderr); fputs (" -- assertion failed\n" , stderr); abort () ; }

A. prints only assertion message

B. program is just aborted

C. prints assertion message and aborts ✓

D. no action takes place

Answer: Option C — prints assertion message and aborts

Q1114. Which is the true statement with respect to the function longjmp()?

A. the function where setjmp() was called has terminated, then the results are undefined ✓

B. the function where setjmp() was called has terminated, then the results are defined

C. the function where jmp_buf was called has terminated, then the results are undefined

D. the function where jmp_buf was called has terminated, then the results are defined

Answer: Option A — the function where setjmp() was called has terminated, then the results are undefined

Q1115. Which among the given header file is used to handle different signals reported during program execution?

A. stdarg.h

B. assert.h

C. signal.h ✓

D. setjmp.h

Answer: Option C — signal.h

Q1116. Which of the given function is used for searching?

A. lsearch()

B. bsearch() ✓

C. csearch()

D. qsearch()

Answer: Option B — bsearch()

Q1117. The library function clock() returns the number of . . . . . elapsed since the start of the program.

A. minutes

B. clock ticks ✓

C. milli-seconds

D. micro-seconds

Answer: Option B — clock ticks

Q1118. Which of the given C function can be used instead of the apparent identity pointed to by y? int x=1; double y= 0.5 * (exp (x) + exp (-x));

A. cos(x)

B. cosh(x) ✓

C. fmod(x)

D. modf(x)

Answer: Option B — cosh(x)

Q1119. Select the right statement with reference to malloc() and calloc().

A. malloc() does not set the memory to zero whereas calloc() sets allocated memory to zero ✓

B. malloc() sets the memory to zero whereas calloc() does not set allocated memory to zero

C. malloc() sets the memory to zero whereas calloc() sets allocated memory to zero

D. malloc() does not set the memory to zero whereas calloc() does not set allocated memory to zero

Answer: Option A — malloc() does not set the memory to zero whereas calloc() sets allocated memory to zero

Q1120. Which is the correct declaration of macro assert?

A. void assert(int expression); ✓

B. void assert(float expression);

C. void assert(double expression);

D. void assert(expression);

Answer: Option A — void assert(int expression);

Q1121. Which line from the given code is the passive form? #undef assert #ifdef NDEBUG #define assert (test) ((void) 0) #else #define assert (test) #endif

A. #define assert(test)

B. #define assert(test) ((void)0) ✓

C. #ifdef NDEBUG

D. #undef assert

Answer: Option B — #define assert(test) ((void)0)

Q1122. . . . . defines the minimum value for a short integer.

A. SHINT_MIN

B. SHRT_MIN ✓

C. SINT_MIN

D. SHORT_MIN

Answer: Option B — SHRT_MIN

Q1123. The . . . . . function converts the initial portion of the string pointed to by, to int representation.

A. atof()

B. atoi() ✓

C. strtod()

D. atol()

Answer: Option B — atoi()

Q1124. The ldexp() function multiplies a floating-point number by an integral power of 2.

A. true ✓

B. false

Answer: Option A — true

Q1125. setjmp takes a jmp_buf type and different other type variables as input.

A. true

B. false ✓

Answer: Option B — false

Q1126. What is the name of the function that is used to convert multibyte character to wide character?

A. mblen()

B. mbtowc() ✓

C. mbstowcs()

D. wcstombs()

Answer: Option B — mbtowc()

Q1127. The header file assert.h of the C Standard Library defines . . . . . macro.

A. stderr

B. stdarg

C. setjmp

D. assert ✓

Answer: Option D — assert

Q1128. The macro offset expands to a constant of type . . . . . .

A. size_t ✓

B. print_t

C. ptrdiff_t

D. null

Answer: Option A — size_t

Q1129. LC_COLLATE affects strcoll() and strxfrm() functions.

A. true ✓

B. false

Answer: Option A — true

Q1130. What will be the output of the following C code? double x=1.8; printf("%.2lf",floor(x));

A. 2.0

B. 2.00

C. 1.0

D. 1.00 ✓

Answer: Option D — 1.00

Q1131. Which of the following is not defined under the header file stddef.h?

A. size_t

B. ptrdiff_t

C. exp_t ✓

D. null

Answer: Option C — exp_t

Q1132. Which of the following library functions is used to read location dependent information?

A. localtime()

B. localeconv() ✓

C. localcon()

D. local()

Answer: Option B — localeconv()

Q1133. The function computes the hyperbolic cosine of x.

A. cos(x)

B. cosine(x)

C. cosh(x) ✓

D. cosineh(x)

Answer: Option C — cosh(x)

Q1134. What will be the output of the following C code? double log (double -x);

A. returns natural logarithm of x

B. range error

C. domain error ✓

D. returns natural logarithm of -x

Answer: Option C — domain error

Q1135. What will be the output of the following C code? (By date we mean: date, month and year) #include<stdio.h> #include<stdlib.h> #include<time.h> int main() { time_t ct; time(&ct); printf("%s\n",ctime(&ct)); }

A. only current date

B. only current date and current time

C. current date, current time and the day of the week ✓

D. only current time

Answer: Option C — current date, current time and the day of the week

---

Q1136. What will be the output of the following C code? char str[20]; str= "123546"; res= atof(str); printf("String value = %s, Float value = %f\n", str, res);

A. String value = 123546, Float value = 123546.0

B. String value = 123546 , Float value = 123546.000000 ✓

C. String value = 123546 , Float value = 0.000000

D. String value = 123546 , Float value = 123546.000

Answer: Option B — String value = 123546 , Float value = 123546.000000

Q1137. The C library function . . . . . function converts the wide character to its multibyte representation.

A. mblen()

B. mbtowc()

C. wcstombs()

D. wctomb() ✓

Answer: Option D — wctomb()

Q1138. A domain error occurs if x is negative and y is not an integral value for the function pow(double x, double y).

A. true ✓

B. false

Answer: Option A — true

Q1139. Which statement is correct work reference to endptr? double strtod(const char *nptr, char **endptr);

A. A pointer to the starting string is stored in the object pointed to by endptr, provided that endptr is a null pointer

B. A pointer to the ?nal string is stored in the object pointed to by endptr, provided that endptr is not a null pointer ✓

C. A pointer to the final string is stored in the object pointed to by endptr, provided that endptr is a null pointer

D. A pointer to the starting string is stored in the object pointed to by endptr, provided that endptr is not a null pointer

Answer: Option B — A pointer to the ?nal string is stored in the object pointed to by endptr, provided that endptr is not a null pointer

Q1140. Which of the following is the correct syntax of the function strtoul()?

A. unsigned long int strtoul(const char *n, char **ptr, int base) ✓

B. unsigned long int strtoul(const char *n, char **ptr)

C. unsigned long int strtoul(const char *n)

D. int strtoul(const char *n)

Answer: Option A — unsigned long int strtoul(const char *n, char **ptr, int base)

Q1141. A less common use of setjmp.h is to create syntax similar to . . . . . .

A. errno

B. variable arguments

C. coroutines ✓

D. retval

Answer: Option C — coroutines

Q1142. What will be the output of the following C code? double x=1.2 printf("%.1lf", ceil(x));

A. 1

B. 2

C. 1.0

D. 2.0 ✓

Answer: Option D — 2.0

Q1143. Which of the given function differs from the statement'errno is not neccessarily set on conversion error'?

A. atof()

B. atoi()

C. atol()

D. strtod() ✓

Answer: Option D — strtod()

Q1144. The macro MB_LEN_MAX is used to find . . . . . .

A. Maximum number of bytes in a multi-byte character ✓

B. Whether the given function is valid or not

C. The maximum time taken for the execution of a particular function

D. Maximum number of bits in a multi-byte character

Answer: Option A — Maximum number of bytes in a multi-byte character

Q1145. Which function is called by macro assert to terminate the execution?

A. exit()

B. atexit()

C. abort() ✓

D. no function called

Answer: Option C — abort()

Q1146. What will be the output of the following C code, if the system date is 6/24/2017? #include<stdio.h> #include<stdlib.h> #include<time.h> int main() { time_t ct; time(&ct); printf("%s\n",(&ct)); }

A. Error

B. Junk value ✓

C. 6

D. June

Answer: Option B — Junk value

Q1147. The macro which is used to find the maximum value of an unsigned integer is . . . . . .

A. UNINT_MAX

B. UNSINT_MAX

C. UINT_MAX ✓

D. UNIT_MAX

Answer: Option C — UINT_MAX

Q1148. Which of the given statement is not true with respect to void longjmp(jmp-buf env, int val)?

A. The variable value cannot be zero

B. env is the object containing information to restore the environment at the jmp_buf's calling point ✓

C. This function does not return any value

D. This function restores the environment saved by the most recent call to setjmp() macro

Answer: Option B — env is the object containing information to restore the environment at the jmp_buf's calling point

Q1149. void free(void *p) performs which of the following functions?

A. returns pointer to allocated space for existing contents of p

B. de-allocates space to which p points ✓

C. to abnormally terminate the program

D. no such function defined in stdlib.h

Answer: Option B — de-allocates space to which p points

Q1150. atol(const char *str) Converts the string pointed to, by the argument str.

A. to a long integer ✓

B. to a integer

C. to a floating point number

D. to a unsigned long integer

Answer: Option A — to a long integer

Q1151. How many macros are defined in the header file stdarg.h?

A. one

B. two

C. three ✓

D. four

Answer: Option C — three

Q1152. The pointer used in the mblen() function points to the . . . . . .

A. first byte of multibyte character ✓

B. last byte of multibyte character

C. middle byte of multibyte character

D. no pointer is used in mblen function

Answer: Option A — first byte of multibyte character

Q1153. What is the role of the given C function? void va_end(va_list ap)

A. allows a function with variable arguments which used the va_start macro to return ✓

B. retrieves the next argument in the parameter list

C. initializes ap variable to be used with the va_arg and va_start macros

D. returns the next additional argument as an expression

Answer: Option A — allows a function with variable arguments which used the va_start macro to return

Q1154. The . . . . . macro shall be invoked before any access to the unnamed arguments.

A. va_arg

B. va_end

C. va_list

D. va_start ✓

Answer: Option D — va_start

Q1155. Correct code to turn assertions OFF at various places throughout a source file is . . . . . .

A. #undef NDEBUG #include

B. #define NDEBUG #include ✓

C. #define DEBUG #include

D. #undef N-DEBUG #include

Answer: Option B — #define NDEBUG #include

Q1156. Which among the given function does not return a value?

A. strtoul()

B. strtol()

C. rand()

D. srand() ✓

Answer: Option D — srand()

Q1157. What will the code display on compiling? void funccall() { printf("this is funccall\n"); } void main () { atexit(funccall); printf("program starts\n"); printf("program ends\n"); }

A. program starts this is funccall program ends

B. this is funccall program starts program ends

C. program starts program ends this is funccall ✓

D. error

Answer: Option C — program starts program ends this is funccall

Q1158. What will be the output of the following C code if the system time is 1:52 PM (Sunday)? #include<stdio.h> #include<time.h> int main() { struct tm *ptr; time_t t; char str[100]; t = time(NULL); ptr = localtime(&t); strftime(str,100,"%I",ptr); puts(str); return 0; }

A. 13

B. 01 ✓

C. 1

D. error

Answer: Option B — 01

Q1159. The macro definition of INT_MIN is . . . . . .

A. -INT_MAX - 1 ✓

B. INT_MAX - 1

C. -INT_MAX + 1

D. INT_MAX + 1

Answer: Option A — -INT_MAX - 1

Q1160. Which of the following is defined under the header file time.h?

A. strnct()

B. fabs()

C. iscntrl()

D. null ✓

Answer: Option D — null

Q1161. What is the function of the void *realloc(void *str, size-t size);?

A. allocates space for an array of str objects, each of whose size is size

B. allocates space for an object whose size is specified by size and whose value is indeterminate

C. changes the size of the object pointed to by str to the size specified by size ✓

D. causes the space pointed to by str to be deallocated, that is, made available for further allocation

Answer: Option C — changes the size of the object pointed to by str to the size specified by size

Q1162. What will be the output of the following C code if the value of UCHAR_MAX is 127? #include<stdio.h> #include<limits.h> int main() { int d; d=CHAR_MAX; printf("%c",d); }

A. Error

B. 127

C. Alphabet corresponding to the value 127

D. Junk value ✓

Answer: Option D — Junk value

Q1163. mblen() function returns 0,if a null wide character was recognized. It returns -1 if an invalid multi-byte sequence was encountered.

A. true ✓

B. false

Answer: Option A — true

Q1164. size_t is of . . . . . type.

A. signed integer

B. signed character

C. unsigned integer ✓

D. unsigned character

Answer: Option C — unsigned integer

Q1165. Which macro can be used to detect and report exceptional conditions?

A. extern

B. edom

C. assert ✓

D. lbdl_min 1e-37

Answer: Option C — assert

Q1166. What are the contents of the register?

A. sp, fp only

B. sp only

C. fp, pc only

D. sp, fp, pc ✓

Answer: Option D — sp, fp, pc

Q1167. The header file setjmp.h is used to . . . . . .

A. set location specific information

B. control low-level calls and returns to and from functions ✓

C. handle signals reported during a program's execution

D. manipulate strings (character arrays)

Answer: Option B — control low-level calls and returns to and from functions

Q1168. Name the function that breaks a floating-point number into a normalized fraction and an integral power of 2.

A. exp()

B. frexp() ✓

C. ldexp()

D. modf()

Answer: Option B — frexp()

Q1169. Select the correct declaration of setjmp().

A. int setjmp(jmp_buf environment) ✓

B. int setjmp(long_jmp environment)

C. int setjmp(jmp_buf)

D. int setjmp(long_jmp)

Answer: Option A — int setjmp(jmp_buf environment)

Q1170. What will be the output of the following C code if the system date is 6/2/2017(Friday)? #include<stdio.h> #include<time.h> int main() { struct tm *local, *gm; time_t t; t=time(NULL); local=localtime(&t); printf("%d",local->tm_wday); return 0; }

A. 6

B. 5 ✓

C. error

D. 0

Answer: Option B — 5

Q1171. A function is declared as sqrt(-x) under the header file math.h, what will the function return?

A. square root of x

B. complex number

C. domain error ✓

D. range error

Answer: Option C — domain error

Q1172. void (*signal(int sig, void (*func)(int)))(int);If the value of func is SIG_IGN then . . . . . .

A. the signal will be ignored ✓

B. default handling for that signal will occur

C. The signal() function will fail to execute

D. the signal will be ignored to execute

Answer: Option A — the signal will be ignored

Q1173. Which macro saves the current environment into the variable environment for later use by the function longjmp().

A. setjmp ✓

B. longjmp

C. jmp

D. set_jmp

Answer: Option A — setjmp

Q1174. double . . . . . (double x, double y) computes the floating-point remainder of x/y.

A. modf

B. fmod ✓

C. ceil

D. floor

Answer: Option B — fmod

Q1175. Which statement is true regarding abs() and labs()?

A. The abs() function is similar to the labs() function, except that the argument and the returned value each of them have type long int ✓

B. The abs() function is not similar to the labs() function, except that the argument and the returned value in both functions have type long int

C. The abs() function is similar to the labs() function, except that the argument and the returned value each have type short int

D. The abs() function is not similar to the labs() function, except that the argument and the returned value in both function have type short int

Answer: Option A — The abs() function is similar to the labs() function, except that the argument and the returned value each of them have type long int

---

Combined from various sources by SFI DCA CUSAT