PROJECT: EXPLORING LONDON'S TRAVEL NETWORK

datalab

London, or as the Romans called it "Londonium"! Home to over 8.5 million residents who speak over 300 languages. While the City of London is a little over one square mile (hence its nickname "The Square Mile"), Greater London has grown to encompass 32 boroughs spanning a total area of 606 square miles!

How likely are you to recommend DataLab to a friend or co-worker?

Not at all likely 0 1 2 3 4 5 6 7 8 9 10 Extremely likely

powered by InMoment

London Mayor's office. Their remit covers the London Underground, Overground, Docklands Light Railway (DLR), buses, trams, river services (clipper and Emirates Airline cable car), roads, and even taxis.

The Mayor of London's office make their data available to the public here. In this project, you will work with a slightly modified version of a dataset containing information about public transport journey volume by transport type.

The data has been loaded into a **Snowflake** database called `TFL` with a single table called `JOURNEYS`, including the following data:

TFL.JOURNEYS

Column	Definition	Data type
`MONTH`	Month in number format, e.g., `1` equals January	`INTEGER`
`YEAR`	Year	`INTEGER`
`DAYS`	Number of days in the given month	`INTEGER`
`REPORT_DATE`	Date that the data was reported	`DATE`
`JOURNEY_TYPE`	Method of transport used	`VARCHAR`
`JOURNEYS_MILLIONS`	Millions of journeys, measured in decimals	`FLOAT`

Note that *in Snowflake all databases, tables, and columns are **upper case*** by default.

You will execute SQL queries to answer three questions, as listed in the instructions.

How likely are you to recommend DataLab to a friend or co-worker?

Not at all likely 0 1 2 3 4 5 6 7 8 9 10 *Extremely likely*

powered by **InMoment**

London Public Transport DataFrame as most_popular_transport_types

```
-- most_popular_transport_types
SELECT JOURNEY_TYPE,
    SUM(JOURNEYS_MILLIONS) as TOTAL_JOURNEYS_MILLIONS
FROM TFL.JOURNEYS
GROUP BY JOURNEY_TYPE
ORDER BY TOTAL_JOURNEYS_MILLIONS DESC;
```

index	JOURNEY_TYPE	TOTAL_JOURNEYS_MILLIONS
0	Bus	24905.19394
1	Underground & DLR	15020.466543
2	Overground	1666.8456664
3	TfL Rail	411.3134209
4	Tram	314.6898754
5	Emirates Airline	14.5837175

Rows: 6 Expand

How likely are you to recommend DataLab to a friend or co-worker?

Not at all likely 0 1 2 3 4 5 6 7 8 9 10 *Extremely likely*

powered by **InMoment**

London Public Transport DataFrame as emirates_airline_popularity

```
-- emirates_airline_popularity
SELECT MONTH,
    YEAR,
    ROUND(JOURNEYS_MILLIONS,2) AS ROUNDED_JOURNEYS_MILLIONS
FROM TFL.JOURNEYS
WHERE JOURNEY_TYPE = 'Emirates Airline' AND ROUNDED_JOURNEYS_MILLIONS IS NOT NULL
ORDER BY ROUNDED_JOURNEYS_MILLIONS DESC
LIMIT 5;
```

index	MONTH	YEAR	ROUNDED_JOURNEYS_MILLIONS
0	5	2012	
1	6	2012	
2	4	2012	
3	5	2013	
4	5	2015	

Rows: 5 Expand

How likely are you to recommend DataLab to a friend or co-worker?

Not at all likely 0 1 2 3 4 5 6 7 8 9 10 *Extremely likely*

powered by **InMoment**

London Public Transport DataFrame as l

```
-- least_popular_years_tube
SELECT YEAR,
    JOURNEY_TYPE,
    SUM(JOURNEYS_MILLIONS) as TOTAL_JOURNEYS_MILLIONS
FROM TFL.JOURNEYS
WHERE JOURNEY_TYPE LIKE '%Underground%'
GROUP BY YEAR, JOURNEY_TYPE
ORDER BY TOTAL_JOURNEYS_MILLIONS
LIMIT 5;
```

		JOURNEY_TY...	TOTAL_JOURNEYS_MIL...
0	2020	Underground & DLR	310.179316314
1	2021	Underground & DLR	748.4525442
2	2022	Underground & DLR	1064.8590086
3	2010	Underground & DLR	1096.14558838
4	2011	Underground & DLR	1156.64765448

Rows: 5 Expand

How likely are you to recommend DataLab to a friend or co-worker?

Not at all likely 0 1 2 3 4 5 6 7 8 9 10 *Extremely likely*

powered by **InMoment**