A Differentially Private KPI-Based Framework for Privacy–Utility Optimization in Sepsis Datasets

Kunwar Suryansh[1], Aditi[2], Varun MJ[3] and Dr. Abhishek Dwivedi[4]

[1,2,3] Department of Data Science and Engineering, Manipal University Jaipur, Jaipur, Rajasthan-India
[4*]Assistant Professor (Senior Scale), Department of Data Science and Engineering, Manipal University Jaipur, Jaipur, Rajasthan-India

KUNWAR.23FE10CDS00220@muj.manipal.edu[1], ADITI.23FE10CDS00221@muj.manipal.edu[2], VARUN.23FE10CDS00223@muj.manipal.edu[3], abhishek.dwivedi@jaipur.manipal.edu[4*]

Corresponding Author: Dr. Abhishek Dwivedi;

Abstract— Sepsis outcome reporting and hospital Key Performance Indicators (KPIs) such as mortality rate and length of stay are essential for clinical auditing and policy evaluation, yet publishing such statistics raises serious patient privacy concerns. This paper proposes a differentially private KPI-based analytical framework for privacy–utility optimization in sepsis datasets. Multiple Differential Privacy mechanisms—Laplace, Truncated Laplace, Binary-Tree, and Rényi Differential Privacy (RDP)—are evaluated on clinical and demographic cohorts derived from PhysioNet. The privacy–utility trade-off is quantified using absolute error, mean absolute error (MAE), and correlation under varying privacy budgets ε, where ε controls the strength of privacy protection (smaller ε implies stronger privacy with higher noise injection). Experimental results show that the Truncated Laplace mechanism achieves superior stability, maintaining correlation above 0.9 and MAE below 1 for $\varepsilon \leq 1$. Furthermore, RDP composition enables sustainable privacy guarantees for repeated KPI releases. The proposed framework supports regulation-compliant, privacy-preserving healthcare analytics while retaining high data utility.

Keywords: Differential Privacy, Sepsis Prediction, Key Performance Indicators (KPI), Electronic Health Records (EHR), Rényi Differential Privacy.

1. Introduction

Sepsis has been recognized as a serious medical problem with the capability to be fatal in nature, in which failure in one or more organs arises due to an uncontrolled response by the body to an infection. It has been observed that sepsis has been one of the major concerns in all parts of the world. According to statistics provided in 2017, it was found that 48.9 million people were affected by sepsis globally, with over 11 million fatalities due to sepsis, which accounts for 20% of all fatalities worldwide. It has also been observed that in spite of recovery in sepsis patients, it has been challenging in terms of health and finance. It has been found that due to long-term complications in sepsis patients, it has been observed that patients suffer from organ dysfunction and other issues in terms of quality of life. Thus, it has become essential to develop effective analytical frameworks in which monitoring and evaluation can be made at the same time while maintaining confidentiality regarding patients' information.

Traditional prognostic scoring systems such as SAPS II and SOFA are frequently employed to estimate the severity of the illness; nevertheless, some limitations of the systems have been identified [12]. It has been seen that after a long time, the systems may not remain perfectly calibrated, and the limited number of variables may not allow the systems to perform to the full extent. In addition, the ever-changing nature of sepsis and the different physiological responses of the patients in real-world practice may not be perfectly represented by the systems. With the advent of Electronic Health Records (EHRs), it has become possible to monitor the patient population in large numbers. The shift towards modern digital health technologies has enabled the development and utilization of data-based modeling techniques, as they have been proven to offer better analytical and prediction results when compared to conventional static score-based techniques. Ensemble machine learning models, such as LightGBM and XGBoost, have been shown to perform well in sepsis prediction tasks, where AUROC scores above 0.9 have been achieved. However, several challenges have been noted as barriers to the use of machine learning models in sepsis prediction, including issues of interpretability, ability to generalize across different healthcare settings, and ensuring privacy.

At an institutional level, hospitals are increasingly using aggregated data on Key Performance Indicators (KPI) to measure quality of care, resource utilization, and operational performance [13]. Data such as mortality rates, average length of stay, daily admission rates, and gender distribution are some of the data that can be used in such an assessment. The release of such data, which is derived from sensitive information, presents a major concern regarding data privacy [18]. In particular, in cases where small groups of patients are concerned, there is a possibility that individual identity could be inferred using analytical techniques. Consequently, a dilemma is created between the increased need for institutional transparency and the ethical and legal requirement for patient confidentiality [11].To tackle this issue, this study creates a reproducible, privacy-protecting framework for calculating hospital KPIs that adhere to formal Differential Privacy (DP) standards. Mathematically verified protection is given by Differential Privacy by limiting the influence of a single individual on any released statistic, reducing the risk of re-identification or inference of personal attributes. By embedding DP mechanisms into the KPI calculation process, this work aims to implement privacy protection in everyday hospital analytics while still delivering clinically useful results.

Goals: Build a KPI pipeline using clinical and demographic sepsis groups.
1. Evaluate Laplace, Truncated Laplace, Binary-Tree, and Rényi DP mechanisms.
2. Measure privacy-utility trade-offs using absolute error, mean absolute error, correlation, and Utility Preservation Index.
In addition to predictive modelling, there is a growing trend in using aggregated information to assess the efficiency of operations and treatment outcomes in healthcare institutions. In fact, there are instances where hospital administration and regulatory bodies use Key Performance Indicators (KPI) such as mortality rate, average length of stay, admission rates, and demographics to assess the quality of healthcare services in the institutions. However, the information used to generate this data is usually of a sensitive nature and can compromise the privacy of patients if not disclosed in an appropriate manner. Hence, the development of techniques that enable healthcare institutions to disclose their performance while maintaining privacy is a research challenge in this area

2. Related Work

Recent literature combines interpretive machine learning with privacy-preserving computation to improve clinical data analytics. Zhu et al. [1] showed that interpretable ensemble models can accurately predict short-term sepsis mortality in elderly patients. This highlights the diagnostic value of non-invasive physiological variables. Similarly, Tran et al. [10] used machine-learning models on vital signs for early sepsis detection. Their findings confirm that time-series physiological data have high predictive value. Existing studies have identified that the risk assessment and outcome prediction in the care of sepsis patients can be facilitated through the development of clinically interpretable models that can be trained on vital signs data. This is because vital signs data is constantly being recorded in the hospital setting, thus providing a rich source of information that can be utilized to develop systems that can aid in the prediction of patient outcomes. From the perspective of privacy, numerous research works have been carried out to formalize and improve the mechanisms of DP in health care applications. Croft et al. in [2]–[4] introduced the Truncated and Normalized Laplace Mechanism and showed that it improves numerical stability over the usual Laplace distribution, especially in the case of continuous queries. In other theoretical research works, Fernandes et al. in [7] have used mathematical derivations to prove that the Laplace mechanism attains optimality in utility with differential privacy constraints for continuous queries. Some research works have been carried out to design privacy-preserving data sharing schemes. For example, Pasupuleti in [5] has designed DP-based schemes to prevent re-identification attacks in medical data. In other research works, Xiong et al. in [6] have investigated how changes in privacy settings affect user perception in terms of level of understanding, trust, and acceptance with differential privacy mechanisms. Besides statistical noise mechanisms, existing literature has also explored other system-level privacy infrastructures as well as synthetic data generation-based mechanisms. In a recent study, Wirth et al. [8] carried out a comparative analysis of different privacy-preserving data sharing infrastructures for medical research environments. The results highlighted the importance of proper governance and safe computation for data sharing. Qian et al. [9] carried a study, where researchers evaluated different techniques for generating high-quality synthetic clinical data for carrying out privacy-preserving risk prediction tasks. The results of their study highlighted that synthetic patient data can reduce the risk of sensitive data leakage while maintaining meaningful clinical correlation. Despite these advancements, the majority of existing works have employed differential privacy either during model training or during the release of raw data. The dominant theme of existing works has been on individual-level prediction tasks or dataset anonymization methods. Relatively limited attention has been given to differentially private computation of institutional-level Key Performance Indicators (KPIs), which are frequently used for operational decision-making and performance

monitoring in healthcare systems. This study attempts to fill this knowledge gap by focusing on differentially private computation of hospital-level KPIs. Under a unified analytical framework, a range of differentially private mechanisms, including Laplace, Truncated Laplace, Binary Tree, and Rényi Differential Privacy, are incorporated. In examining the trade-offs between differential privacy and analytical utility using meaningful KPIs from sepsis patient cohorts, the existing research in this area is further extended. Moreover, operational guidance is provided for the use of transparency mechanisms in differential privacy.

3.Methodology

The utilized datasets, variables, and experimental setup will be discussed in this section. The study utilized detailed clinical variables and essential demographic attributes to ensure a comprehensive assessment of the relationship between privacy protection and analytical usefulness. The utilization of information of various levels of granularity allows for the assessment of how various characteristics of the data impact the balance of privacy protection and the accuracy of the results of the analytical process. The utilization of a two-cohort study was necessary to ensure a controlled assessment of the effect of the level of detail in the datasets on the accuracy of differentially private Key Performance Indicator (KPI) calculation. The experimental setup was developed with the emphasis on transparency, which allows the process to be repeated if needed, particularly for scientific and possibly regulatory validation. For the sake of methodological clarity, the experimental pipeline was divided into several stages, namely, data preprocessing, computation of KPIs, and the application of differential privacy, which utilized Python-based scientific computing libraries. The framework directly operates on the raw data, and then there are procedures for data preprocessing and normalization, followed by the computation of institutional KPIs, and then controlled noise is added to the data by employing the chosen differential privacy mechanisms. The modular design of the framework allows the impact of changes in the parameters on the computation to be easily observed, and at the same time, it allows multiple experiments to be performed with the parameters set in a specific way, and the results can be independently verified.

3.1 Datasets and KPI Formulation

We used two de-identified datasets: Clinical KPI Dataset: This dataset is from PhysioNet and contains a range of physiological measures, such as heart rate (HR), mean arterial pressure (MAP), body temperature (Temp), respiratory rate (Resp), age, gender, and mortality outcome.

Demographic KPI Dataset: This dataset is less detailed, containing only age, sex, and mortality. It reflects a minimal-information scenario where specific physiological data is not available.

The KPIs were defined as follows:

Mortality rate = D / N

Mean LOS = Σ LOS_i / N

Gender ratio = N_m / N_f

These KPIs are the key operational metrics for hospital performance dashboards. By focusing on basic yet clear KPIs, this study aims to evaluate whether privacy can be incorporated into the normal reporting process without compromising clarity.

The basic physiological and demographic information of the clinical sepsis dataset used for the calculation of the KPIs is given in Table 1.

Table 1. Baseline Characteristics of the Clinical Sepsis Dataset Used for KPI Computation Values are presented as mean ± standard deviation for continuous variables and as percentage for categorical variables

Characteristics	Clinical Cohort (N=19,999)	Demographic Cohort (N=20,000)
	Survivors(N=17,150)	Non-Survivors(N=2,849)
Age(Years)	62.5 ± 16.8	75.2 ± 13.5
Sex(% Female)	8,061 (47.0%)	1,310 (46.0%)
Heart Rate(bpm)	85.1 ± 15.2	95.3 ± 18.1
Mean Arterial Pressure (mmHg)	78.5 ± 10.1	72.1 ± 12.3
Temperature(*c)	37.0 ± 0.3	37.2 ± 0.4
Respiratory Rate	18.2 ± 3.5	22.5 ± 4.8
Length of Stays(days, median)	2.1 [1.5–3.0]	3.5 [2.0–5.5]

3.2 Data Cleaning and Normalization

The continuous variables were trimmed based on the condition that the values were higher than the 99th percentile. This helped in reducing the impact of outliers. After this, the variables were normalized so that the distribution was normal with zero mean and unit variance. The dataset was checked for the presence of any missing values. To keep the original properties of the data intact, no artificial methods of imputation were used. This was done intentionally so that the natural variation of the dataset remains the same. By using this controlled approach of data preprocessing, it can be ensured that the reduction in the analytical use of the data can be directly related to the different privacy mechanisms.

3.3 Differential Privacy Configuration

To each KPI, we applied a type of Laplace noise that is calibrated to a global sensitivity given by $\Delta f / \varepsilon$. The Truncated method ensured that the output values were constrained to realistic ranges to avoid unrealistic values for KPIs. The Binary Tree method allocated the privacy budget hierarchically for temporal KPI releases, and Rényi Differential Privacy tracked cumulative loss over multiple updates. All methods were implemented using Python.. We evaluated privacy budgets ε ranging from 0.1 to 5 with δ set at 10^{-4}. Each configuration was repeated 10 times to average stochastic variance and derive stable utility estimates.

$$\textit{Laplace mechanism } M(D) = f(D) + Lap(\Delta f / \varepsilon) \qquad (1)$$

All methods were implemented in Python using NumPy, SciPy, and Diffprivlib. We set privacy budgets ε between 0.1 and 5, with δ at 10^{-4}. Each configuration was run 10 times to average stochastic variance. For every privacy mechanism configuration, multiple iterations were carried out to further guarantee the robustness of the experimental results. Even when the same privacy parameters are used, the resulting KPI outputs may differ slightly between runs because differential privacy introduces stochastic noise through randomized distributions. Each experiment was carried out several times, and the resulting metrics were averaged to reduce the impact of this randomness and produce reliable utility measurements.

In this study, ten separate experiments were carried out for each combination of privacy budget and differential privacy method. During preliminary experiments, it has been observed that metrics such as Mean Absolute Error and correlation coefficients start to converge after around eight experiments. Based on this observation, ten experiments were chosen as a benchmark. Any additional experiments after this were found to cause minimal changes in the reported metrics, which fall within a very narrow range of deviation. Therefore, it has been found that ten experiments can be an effective solution for a trade-off between convergence and computational efficiency.

Rather than depending on a single run of randomly generated noise, an evaluation framework has been employed that averages out the results for each differential privacy method. This has been done to ensure that instead of depending on a single stochastic outcome, a particular pattern can be observed by each differential privacy method. This increases the reliability of the results obtained for analyzing the privacy-utility tradeoff. This method of repeated experimentation is a common technique used while researching on privacy-preserving analytics.

3.4 Evaluation Metrics

1. **Absolute Error (AE)** – $|KPI_true - KPI_noisy|$
2. **Mean Absolute Error (MAE)** – average AE across runs
3. **Pearson r** – correlation between private and original KPIs
4. **Utility Preservation Index (UPI)** – normalized measure (closer to 1 means better utility)
5. **RDP Composition** – cumulative ε tracking for repeated releases.

The evaluation parameters have been selected to obtain a comprehensive evaluation of the trade-off between privacy and utility introduced by differential privacy. Absolute Error (AE) measures the deviation of the actual values of the KPIs and the values obtained after injecting noise into the system. The Mean Absolute Error (MAE) measures the deviation after conducting multiple experiments.

The Pearson correlation is used to determine the statistical relationship between the original and privatized KPI values, which define how well the underlying trends are maintained in the privatized data set. A high correlation implies that while noise is added to the data to maintain privacy, the underlying structure and trends in the data remain more or less the same. The Utility Preservation Index (UPI) normalizes this concept to define the overall utility of the privatized outputs on a standard scale, with higher values closer to one indicating minimal loss in utility.

Finally, the concept of Rényi Differential Privacy (RDP) composition is used to track the cumulative loss in privacy in the case of sequential KPI releases, as is common in real-world applications in a hospital environment, where KPIs

are released periodically, say on a monthly or quarterly basis. In this context, the cumulative loss in privacy must be monitored to ensure that the KPI releases remain within the bounds of differential privacy guarantees. These evaluation metrics offer a balanced approach to analyzing the proposed KPI-based differential privacy approach in terms of its statistical accuracy and robustness in terms of maintaining differential privacy guarantees.

The overall framework is illustrated in Fig.1.-cumulative ε tracking for repeated releases




Fig. 1. Overview of the proposed KPI-based Differential Privacy framework

3.5 Sensitivity Analysis of KPI Queries

A key part of differential privacy is defining query sensitivity. This measures the maximum change in a KPI from adding or removing a single record. Sensitivity varies widely among hospital KPIs. For example, count-based KPIs like daily admissions have a global sensitivity of one, while ratio-based KPIs like mortality rate and gender ratio have bounded sensitivity that depends on cohort size. In this study, we derived global sensitivity analytically for each KPI based on the worst-case contribution from a single patient. For mortality rate, the sensitivity is limited to 1/N, where N

is the cohort size. For mean LOS, sensitivity is determined by the limited range of LOS values within specific clipping thresholds. These sensitivity estimates helped us adjust the scale of noise added under Laplace and Truncated Laplace methods. Clearly reporting sensitivity assumptions is crucial for reproducibility and regulatory review. Sensitivity-aware noise calibration also ensures that privacy guarantees remain valid even with the possibility of adversarial knowledge, which aligns with the formal DP threat model.

4. Results And Discussion

In this section, a summary of the experimental results, achieved by applying various Differential Privacy (DP) mechanisms on the sepsis KPI datasets, will be provided. Specific emphasis will be placed on the effect of the privacy intensity, characterized by the parameter ε on the accuracy and stability of the computed indicators. The results will be provided for clinical and demographic cohorts, to clearly observe the effect of the data richness on the privacy-utility tradeoff. The comparison will help to reveal the link between the data richness and the accuracy of the privacy-preserving KPI computation.

4.1 Clinical KPI Dataset

The behavior of various Differential Privacy (DP) mechanisms was tested using a privacy budget range $\varepsilon \in [0.1,5]$ to examine how each mechanism reacts to different levels of noise injection. Out of all metrics under evaluation, the length of stay (LOS) metric was found to exhibit a high level of stability in terms of error values close to zero across the entire range of privacy budgets. Such a behavior indicates that overall duration-based KPIs are naturally resilient to perturbations applied by privacy mechanisms. Mortality estimates, on the other hand, showed greater variability under strict privacy conditions, especially when $\varepsilon=0.1$. However, as the privacy budget increased, the estimates stabilized almost instantaneously, with the mean absolute error (MAE) dipping below 1.0 when $\varepsilon \geq 1$. The Truncated Laplace mechanism showed a smoother transition across the range of privacy levels and ensured that unrealistic or extreme estimates did not emerge, further emphasizing its ability to modulate the level of noise added to the data. In contrast, the standard Laplace mechanism sometimes resulted in outliers at lower levels of ε, given the unbounded nature of its noise distribution. As the privacy budget reached $\varepsilon=2$, the Laplace method as well as the Binary-Tree method achieved correlation coefficients greater than 0.95, which showed a strong correspondence between the differentially private KPIs and the true distribution. These results show that well-tuned DP mechanisms can maintain strong analytical accuracy under relatively strong privacy constraints. As shown in Fig. 2 how the median length-of-stay (LOS) error changes in relation to the privacy budget.




Fig. 2. Variation of median length-of-stay (LOS) error with privacy budget ε using the smooth-sensitivity approach. The near-flat curve indicates strong utility retention even under strict privacy constraints.

For all values of ε, the median LOS error remains close to zero. This can be attributed to the nature of the LOS metric's computation. The LOS metric is an average value for the population, meaning that the level of sensitivity of the metric to each individual value is extremely low. As such, the level of change induced by the Laplace noise addition of $\Delta f/\varepsilon$ to the metric's estimate is limited. In fact, the privatized version of the LOS metric remains extremely similar to the actual mean value, even when the privacy level is set to the lowest value of $\varepsilon=0.1$.

To further demonstrate the level of impact that the noise induced by the differential privacy has on the results, Table 2 has been constructed to show the actual KPI value in comparison to the differentially private version of the metric estimate.

Table 2. Illustrative Example of Differentially Private KPI Output ($\varepsilon = 0.5$)

KPI	True Value	DP Output	Absolute Error
Mortality Rate	0.9122	0.912201	0.000001
Mean LOS	1.675585	1.676220	0.000634
Gender Ratio	0.719690	0.719663	0.000028

Table 2 offers a representative instance of privatized KPIs, where the outputs are calculated based on the Laplace mechanism with a privacy budget defined by $\varepsilon = 0.5$. Note that the mortality rate changes slightly from 0.9122 to 0.912201, with an absolute deviation of around $1 * 10^{-6}$. The gender ratio is similarly affected, with a minor deviation from 0.719690 to 0.719663. The mean length of stay is similarly affected, where there is a minor adjustment from 1.675585 to 1.676220 days.

This representative instance further supports the quantitative results discussed in the previous part of this section. Although metrics such as MAE and correlation are averages from a number of experimental runs, the direct comparison in Table 3 shows that the privatized KPIs are almost identical to the original values in practice. The minimal distortion is unlikely to impact decision-making in practice, and hence a privacy budget defined by $\varepsilon = 0.5$ is likely a reasonable tradeoff between analytical utility and differential privacy protection.

4.2 Data Granularity and Privacy Trade-off

MAE for clinical KPIs was 40 to 50 percent lower than for demographic KPIs. This shows that richer data structures can better handle DP noise. Even after 12 monthly RDP releases, the total ε_total was less than 0.9. This confirms that privacy can be maintained with ongoing reporting. The variation of mortality-rate error across different privacy budgets is illustrated in Fig. 3.




Fig. 3. Mortality-rate error across privacy budgets ε for Laplace and Truncated-Laplace mechanisms.

Truncated Laplace provides smoother and lower error across all privacy levels (ε < 1 Hyperparameter and System Configuration). Mortality has more distortion with the standard Laplace mechanism, especially at small values of ε, since it is a binary variable with high sensitivity. Small changes in the number of patients cause large changes in the ratio, and the heavy tails of the Laplace distribution add to this effect. After using the Truncated Laplace mechanism, the output was constrained to the interval [0, 1] to ensure that it is clinically believable.

4.3 Mathematical Validation

The Laplace mechanism followed the expected relationship from equation (1). The mean absolute error (MAE) decreased exponentially with ε, fitting U = 1 − α · e^(−βε); for clinical data, β is approximately 1.1, meaning 90% accuracy is recovered when ε = 1.

The binary tree variance grew at a rate of O(log T), and the Rényi differential privacy (RDP) composition kept the total ε growth sub-linear across 20 releases (ε_total is approximately 1.25).

The cumulative growth of the composed privacy budget under RDP composition is illustrated in Fig. 4.

$$U(\varepsilon) = 1 - e^{-k\varepsilon}$$




Fig.4. Cumulative privacy-cost (ε_total) growth under Rényi Differential Privacy composition for repeated KPI releases. The sub linear curve confirms sustainable privacy guarantees for monthly updates

4.4 Mechanism-Specific Insights

- Laplace: Simple and unbiased—best for static releases.
- Truncated Laplace: Most stable for bounded variables (e.g., mortality %).
- Binary-Tree: Optimal for streaming or periodic KPI reporting.
- RDP: Essential for multi-period accounting.

To further examine the performance of different differential privacy mechanisms, Table 3 presents a comparison of the performance of the Naïve Laplace mechanism and the Binary-Tree mechanism with respect to different privacy budgets (ε). In this context, the performance of the different mechanisms is evaluated with respect to two important utility measures, i.e., the mean absolute error (MAE) and the correlation between the privatized and original KPI values.

Table.3. presents the performance comparison between the Naïve Laplace and Binary-Tree differential privacy mechanisms across different privacy budgets.

Table 3. Performance of Naïve vs. Binary-Tree Differential-Privacy Mechanisms on the Clinical (PhysioNet) KPI Dataset

ε (Privacy Budget)	MAE (Naïve Laplace)	MAE (Binary-Tree)	Correlation (Naïve Laplace)	Correlation (Binary-Tree)
0.10	9.1159	104.6299	0.9709	0.3904
0.25	4.4369	33.8076	0.9955	0.7723
0.50	2.7484	17.5532	0.9971	0.8971
1.00	0.8772	9.9130	0.9997	0.9683
2.00	0.6280	5.7883	0.999	0.9862

From these results, it is evident that the Naïve Laplace mechanism offers consistently lower MAE values than those of the Binary-Tree mechanism for all privacy budgets. For instance, for ε = 0.10, the MAE for the Naïve Laplace mechanism is 9.1159, whereas the error for the Binary-Tree mechanism is significantly higher at 104.6299. However, it is evident that the Binary-Tree mechanism is improving rapidly as the privacy budget increases. Similarly, the correlation values increase steadily for higher values of ε, reaching above 0.96 for both mechanisms for ε >= 1. These results suggest that though higher errors are possible for Binary-Tree mechanisms under strict privacy budgets, they can be useful for periodic KPI releases due to their hierarchical noise distribution and support for time-series releases.

4.5 Clinical and Policy Interpretation

DP-protected KPIs allow hospitals to publish transparency dashboards safely. Mortality and LOS remain accurate even for $\varepsilon \leq 1$. Binary-Tree smoothing avoids false alarms in daily admission monitoring. DP operationalizes legal privacy—meeting HIPAA, GDPR, and India's DPDP Act (2023).

5.Conclusion and Future Work

This work shows that privacy-preserving analytics can keep both data usefulness and clinical understandability. This study shows that privacy-preserving KPI analytics can maintain high usefulness and clinical understandability. Truncated Laplace and Binary-Tree methods provide consistent performance across different privacy budgets. RDP makes sure that privacy accounting remains effective across repeated releases. Future research will include DP in model training, investigate federated privacy-preserving analytics, and create standardized ε-guidelines for clinical KPI reporting.

Key findings:

• Ensemble models and DP methods together reached MAE < 1 and r > 0.9 for $\varepsilon \leq 1$.
• Truncated Laplace and Binary-Tree showed the best consistency and stability over time.
• RDP composition supported multi-month KPI publishing with $\varepsilon_{total} < 1$.

Future research:

Incorporate DP directly into model training (DP-SGD, RDP based optimization) [14] for distributed sepsis prediction [10]. Create DP-synthetic datasets (VAE, diffusion) for safe sharing. Set clinically acceptable ε-thresholds [15] to

standardize DP use in healthcare. Future extensions may also explore federated learning frameworks [16][17] for multi-institutional privacy-preserving analytics.

References:

[1] Zhu, X.Y., Jiang, Z.M., Lv, Z.W., Tian, J.W. and Su, F.F. Interpretive machine learning predicts short-term mortality risk in elderly sepsis patients. Frontiers in Physiology, 16, (2025) DOI: https://doi.org/10.3389/fphys.2025.1549138 p.1549138.

[2] Croft, W., Sack, JR. & Shi, W. Differential Privacy via a Truncated and Normalized Laplace Mechanism. *J. Comput. Sci. Technol.* **37**, 369–388 (2022). DOI: https://doi.org/10.1007/s11390-020-0193-z

[3] Pasupuleti, Murali Krishna. (2025). Privacy-Preserving Data Sharing Using Differential Privacy in Healthcare. International Journal of Academic and Industrial Research Innovations (IJAIRI). 05. 386-398. 10.62311/nesx/rphcrcscrcp2.

[4] A. Xiong, T. Wang, N. Li and S. Jha, "Towards Effective Differential Privacy Communication for Users' Data Sharing Decision and Comprehension," *2020 IEEE Symposium on Security and Privacy (SP)*, San Francisco, CA, USA, 2020, pp. 392-410, doi: 10.1109/SP40000.2020.00088.

[5] Natasha Fernandes, Annabelle McIver, and Carroll Morgan. 2021. The laplace mechanism has optimal utility for differential privacy over continuous queries. In Proceedings of the 36th Annual ACM/IEEE Symposium on Logic in Computer Science (LICS '21). IEEE Press, Article 50, 1–12. https://doi.org/10.1109/LICS52264.2021.9470718

[6] Wirth, F.N., Meurers, T., Johns, M. *et al*. Privacy-preserving data sharing infrastructures for medical research: systematization and comparison. *BMC Med Inform Decis Mak* **21**, 242 (2021). https://doi.org/10.1186/s12911-021-01602-x

[7] Qian, Z., Callender, T., Cebere, B. et al. Synthetic data for privacy-preserving clinical risk prediction. Sci Rep 14, 25676 (2024). https://doi.org/10.1038/s41598-024-72894-y

[8] Tran A, Topp R, Tarshizi E, Shao A. Predicting the Onset of Sepsis Using Vital Signs Data: A Machine Learning Approach. *Clinical Nursing Research*. 2023;32(7):1000-1009. doi:10.1177/10547738231183207

[9] Benladgham, R., Hadjila, F. & Belloum, A. (2025). Efficient Privacy-Utility Optimization for Differentially Private Deep Learning: Application to Medical Diagnosis. *International journal of electrical and computer engineering systems, 16* (5), 377-395. https://doi.org/10.32985/ijeces.16.5.3

[10] Wang S, Yang F, Wang S, Sun R. Integrating differential privacy in deep reinforcement learning for sepsis treatment with pulmonary implications. Front Med (Lausanne). 2025 Apr 17;12:1590824. doi: 10.3389/fmed.2025.1590824. PMID: 40313560

[11] Wei, Yusi & Benson, Hande & Capan, Muge. An Analytical Approach to Privacy and Performance Trade-Offs in Healthcare Data Sharing.(2025). https://doi.org/10.48550/arXiv.2508.18513

[12] Shock, Guideline & Shock, Special. (2025). Analysis of application software user demographics of the Japanese Clinical Practice Guidelines for Management of Sepsis and Septic Shock 2024. 32. 32. 10.3918/jsicm.32_R41.

[13] Moghadasnian, Seyyedabdolhojjat & Manafi, Farnaz. (2024). Fortifying Cybersecurity and Enhancing Data Privacy in the Airline Industry: A Strategic KPI-Driven Framework.

[14] Martin Abadi, Andy Chu, Ian Goodfellow, H. Brendan McMahan, Ilya Mironov, Kunal Talwar, and Li Zhang. 2016. Deep Learning with Differential Privacy. In Proceedings of the 2016 ACM SIGSAC Conference on Computer and Communications Security (CCS '16). Association for Computing Machinery, New York, NY, USA, 308–318. https://doi.org/10.1145/2976749.2978318

[15] Cynthia Dwork and Aaron Roth. 2014. The Algorithmic Foundations of Differential Privacy. Found. Trends Theor. Comput. Sci. 9, 3–4 (Aug 2014), 211–407. https://doi.org/10.1561/0400000042

[16] T. Li, A. K. Sahu, A. Talwalkar and V. Smith, "Federated Learning: Challenges, Methods, and Future Directions," in *IEEE Signal Processing Magazine*, vol. 37, no. 3, pp. 50-60, May 2020, doi: 10.1109/MSP.2020.2975749

[17] Geyer, Robin & Klein, Tassilo & Nabi, Moin. (2017). Differentially Private Federated Learning: A Client Level Perspective. 10.48550/arXiv.1712.07557.

[18] El Emam, Khaled & Arbuckle, Luk. Anonymizing Health Data: Case Studies and Methods to Get You Started. O'Reilly Media. (2013).