[6 C]

c. Write a program to explain the different ways for taking input.

Program:

```
<html>
<head> <title>JavaScript Input Methods</title> </head>
<body>
 <h1>JavaScript Input Methods</h1>
 <label for="textInput">Enter something:</label>
 <input type="text" id="textInput">
 <button onclick="useInputField()">Get Input</button> <br><br>
 <button onclick="usePrompt()">Prompt Box</button> <br><br>
 <p id="output"></p>
 <script>
 function useInputField() {
 let userInput = document.getElementById("textInput").value;
 document.getElementById("output").innerText = "Input Field
Value: " + userInput; }
 function usePrompt() {let userInput = prompt("Enter
something:");
 if (userInput !== null) {
 document.getElementById("output").innerText = "Prompt
Input: " + userInput; }}
 </script>
</body>
</html>
```

[3B]

b. Write a HTML program, to embed audio and video into HTML web page

```
<html>
<head>
<title>Audio and Video Embedding</title>
</head>
<body>
<h1>Embedding Audio and Video in HTML</h1>
<h2>Audio Example</h2>
<audio controls>
<source
src="https://www.soundhelix.com/examples/mp3/SoundHelix-Song-1.mp3"
type="audio/mpeg">
Your browser does not support the audio element. </audio>
<h2>Video Example</h2>
<video width="640" height="360" controls>
<source src="https://www.w3schools.com/html/mov_bbb.mp4"
type="video/mp4">
Your browser does not support the video tag.</video>
</body></html>
```

[7A]

```
<html>
<head><title>DOM Properties & Methods</title>
<style>
body {
font-family: Arial, sans-serif;
text-align: center;
margin: 50px;
}
button {
margin: 5px;
padding: 10px;
font-size: 16px;
}
```

```
</style>
</head>
<body>
<h1 id="heading">JavaScript DOM Example</h1>
<button onclick="changeTitle()">Change Page Title</button>
<button onclick="changeBgColor()">Change Background
Color</button>
<button onclick="addNewParagraph()">Add
Paragraph</button>
<p id="message"></p>
<script>
function changeTitle() {
document.title = "New Page Title!";
document.getElementById("message").innerText = "Title
changed successfully!";
}
function changeBgColor() {
document.body.style.backgroundColor = getRandomColor();
document.getElementById("message").innerText =
"Background color changed!";
}
function addNewParagraph() {
let newPara = document.createElement("p");
newPara.innerText = "This is a dynamically added paragraph!";
document.body.appendChild(newPara);
}
function getRandomColor() {
let letters = "0123456789ABCDEF";
let color = "#";
for (let i = 0; i < 6; i++) {
color += letters[Math.floor(Math.random() * 16)];
}
return color;
}
</script>
</body>
</html>
```

[5C]

```
<!DOCTYPE html>
<html> <head>
 <title>CSS Font and Text Properties</title>
 <style>
 body { font-family: Arial, sans-serif; margin: 20px; }
 .font-size { font-size: 24px; /* Font size */}
 .font-weight { font-weight: bold; /* Font weight */}
 .font-style { font-style: italic; /* Font style */}
 .text-decoration {text-decoration: underline; }
 .text-transform { text-transform: uppercase; }
 .text-align { text-align: center; /* Text alignment */}
 </style> </head>
<body>
<h1 class="text-align">CSS Font and Text Properties</h1>
<p class="font-size">This paragraph demonstrates <strong>font-
size</strong>. The text is larger
than normal.</p>
<p class="font-weight">This paragraph demonstrates
<strong>font-weight</strong>. The text is
bold.</p>
<p class="font-style">This paragraph demonstrates <strong>font-
style</strong>. The text is
italicized.</p>
<p class="text-decoration">This paragraph demonstrates
<strong>text-decoration</strong>. The
text is underlined.</p>
<p class="text-transform">This paragraph demonstrates
<strong>text-transform</strong>. The text
is transformed to uppercase.</p>
<p class="text-align">This paragraph demonstrates <strong>text-
align</strong>. The text is
centered.</p>
</body> </html>
```

[8D]

```
<!DOCTYPE html>
<html>
<head>
 <title>Object Data Looping</title>
</head>
<body>
 <script>
 const person = { firstname: "John", lastname: "Doe", age: 25 };
 document.write("<h3>Using for-in loop:</h3>");
 for (let key in person) {
 document.write(key + ": " + person[key] + "<br>");
 }
 document.write("<h3>Using forEach loop on object keys:</h3>");
 Object.keys(person).forEach(function(key) {
 document.write(key + ": " + person[key] + "<br>");
 });
 document.write("<h3>Using for-of loop on object entries:</h3>");
 for (let entry of Object.entries(person)) {
 document.write(entry[0] + ": " + entry[1] + "<br>");
 }
 </script>
</body>
</html>
```

[2 B]

Program:

```
<!DOCTYPE html>
<html>
<head> <title>Time Table</title> </head>
<body>
<table border="1">
<tr>
<th>Day/Periods</th>
 <th>1 <p>9:30-10:20</p> </th>
<th>2 <p>10:20-11:10</p> </th>
<th>3 <p>11:10-12:00</p> </th>
<th>4 <p>12:00-12:50</p> </th>
<th > <p><br>12:50-1:50</p> </th>
<th>5 <p>1:50-2:40</p> </th>
<th>6 <p>2:40-3:30</p> </th>
<th>7 <p>3:30-4:10</p> </th>
</tr>
<tr>
<th>Monday</th>
<td>DBMS</td>
<td>P&S</td>
<td>OS</td>
<td>DT</td>
<td rowspan="6"> <center><b>L <br> U <br> N <br> C <br> H
</b></center></td>
<td>SE</td>
<td>DBMS</td>
<td>OS</td>
</tr>
<tr>
<th>Tuesday</th>
<td>P&S</td>
<td>DBMS</td>
<td>MEFA</td>
<td>DT</td>
<td>SE</td>
<td>P&S</td>
<td>MEFA</td>
</tr>
```

```
<tr>
<th>Wednesday</th>
<td>DBMS</td>
<td>MEFA</td>
<td>P&S</td>
<td>SE</td>
<td colspan="3">
<center>
DT LAB
</center>
</td>
</tr>
<tr>
<th>Thursday</th>
<td>OS</td>
<td colspan="3">
<center>
DBMS LAB
</center>
</td>
<td>DBMS</td>
<td>MEFA</td>
<td>P&S</td>
</tr>
<tr>
<th>Friday</th>
<td>SE</td>
<td colspan="3">
<center>
OS LAB
</center>
</td>
<td>OS</td>
<td>MEFA</td>
<td>SE</td>
</tr>
<tr>
<th>Saturday</th>
<td>OS</td>
<td>SE</td>
<td>OS</td>
<td>DBMS</td>
<td colspan="3">
<center>
</td>
</tr>
</table>
</body>
</html>
```

[8B]

```
<html>
<head> <title>Display Weekday</title> </head>
<body>
 <script>
 let dayNumber = parseInt(prompt("Enter a number between
1 and 7:"));
 let dayName;
 switch (dayNumber) {
 case 1:
 dayName = "Monday";
 break;
 case 2:
 dayName = "Tuesday";
 break;
 case 3:
 dayName = "Wednesday";
 break;
 case 4:
 dayName = "Thursday";
 break;
 case 5:
 dayName = "Friday";
 break;
 case 6:
 dayName = "Saturday";
 break;
 case 7:
 dayName = "Sunday";
 break;
 default:
 dayName = "Invalid input! Please enter a number between 1
and 7.";  }
document.write(dayName);
 </script>
</body></html>
```

```
function addFirst() {
fruits.unshift("Grapes");
updateDisplay();
document.getElementById("message").innerText = "Added
'Grapes' to the start of the
array."; }
function sortArray() {
fruits.sort();
updateDisplay();
document.getElementById("message").innerText = "Array
sorted."; }
function reverseArray() {
fruits.reverse();
updateDisplay();
document.getElementById("message").innerText = "Array
reversed."; }
function joinArray() {
let joinedString = fruits.join(" - ");
document.getElementById("message").innerText = "Joined
Array: " + joinedString; }
</script>
</body>
</html>
```