

```
mysql> show databases;
```

```
+-----+
| Database      |
+-----+
| classwork_db  |
| information_schema |
| new_hr_db     |
| performance_schema |
| sales_db      |
| spj           |
```

```
create table s(`S#` char(5) not null, Sname char(20), status smallint,city char(20));
```

```
Query OK, 0 rows affected (0.272 sec)
```

```
mysql> INSERT INTO s values("S1","Smith",20,"London");
```

```
Query OK, 1 row affected (0.107 sec)
```

```
mysql> INSERT INTO s values("S2","Jones",10,"Paris");
```

```
Query OK, 1 row affected (0.101 sec)
```

```
mysql> INSERT INTO s values("S3","Blake",30,"Paris");
```

```
Query OK, 1 row affected (0.106 sec)
```

```
mysql> INSERT INTO s values("S4","Clark",20,"London");
```

```
Query OK, 1 row affected (0.098 sec)
```

```
mysql> INSERT INTO s values("S5","Adams",30,"Athens");
```

```
Query OK, 1 row affected (0.118 sec)
```

```
mysql> select *from P;
+----+-----+-----+-----+-----+
| P# | Pname | color | weight | city |
+----+-----+-----+-----+-----+
| P1 | Nut   | Red   | 12     | London |
| P2 | Bolt  | Green | 17     | Paris  |
| P3 | Screw | Blue  | 17     | Rome   |
| P3 | Screw | Blue  | 17     | Rome   |
| P4 | Screw | Red   | 14     | London |
| P5 | Cam   | Blue  | 12     | Paris  |
| P6 | Cog   | Red   | 19     | London |
+----+-----+-----+-----+-----+
7 rows in set (0.009 sec)
```

--CREATE TABLE P

```
CREATE TABLE P(`P#` CHAR(6) NOT NULL,Pname CHAR(20), color CHAR(6),weight
SMALLINT,city CHAR(15));
```

Query OK, 0 rows affected (0.314 sec)

```
mysql> INSERT INTO P(`P#`,Pname, color,weight,city)
```

```
-> values("P1","Nut","Red",12,"London");
```

Query OK, 1 row affected (0.144 sec)

```
mysql> INSERT INTO P(`P#`,Pname, color,weight,city)
```

```
-> values("P2","Bolt","Green",17,"Paris");
```

Query OK, 1 row affected (0.091 sec)

```
mysql> INSERT INTO P(`P#`,Pname, color,weight,city)
```

```
-> values("P3","Screw","Blue",17,"Rome");
```

Query OK, 1 row affected (0.096 sec)

```
mysql> INSERT INTO P(`P#`,Pname, color,weight,city)
```

```
-> values("P3","Screw","Blue",17,"Rome");
```

Query OK, 1 row affected (0.031 sec)

```
mysql> INSERT INTO P(`P#`,Pname, color,weight,city)
```

```
-> values("P4","Screw","Red",14,"London");
```

Query OK, 1 row affected (0.104 sec)

```
mysql> INSERT INTO P(`P#`,Pname, color,weight,city)
```

```
-> values("P5","Cam","Blue",12,"Paris");
```

Query OK, 1 row affected (0.109 sec)

```
mysql> INSERT INTO P(`P#`,Pname, color,weight,city)
```

```
-> values("P6","Cog","Red",19,"London");
```

Query OK, 1 row affected (0.092 sec)

```
mysql> select *from P;
```

P#	Pname	color	weight	city
P1	Nut	Red	12	London
P2	Bolt	Green	17	Paris
P3	Screw	Blue	17	Rome
P3	Screw	Blue	17	Rome
P4	Screw	Red	14	London
P5	Cam	Blue	12	Paris
P6	Cog	Red	19	London

7 rows in set (0.009 sec)

```
CREATE TABLE J(`J#` CHAR(4) NOT NULL, Jname CHAR(10), City CHAR(15));
```

Query OK, 0 rows affected (0.234 sec)

```
INSERT INTO J(`J#`,Jname, City)
```

```
-> values("J1","Sorter","Paris");
```

Query OK, 1 row affected (0.092 sec)

```
mysql> INSERT INTO J(`J#`,Jname, City)
```

```
-> values("J2","Punch","Rome");
```

```
Query OK, 1 row affected (0.089 sec)
```

```
mysql> INSERT INTO J(`J#`,Jname, City)
```

```
-> values("J2","Punch","Rome");
```

```
Query OK, 1 row affected (0.052 sec)
```

```
mysql> INSERT INTO J(`J#`,Jname, City)
```

```
-> values("J3","Reader","Athens");
```

```
Query OK, 1 row affected (0.030 sec)
```

```
mysql> INSERT INTO J(`J#`,Jname, City)
```

```
-> values("J4","Console","Athens");
```

```
Query OK, 1 row affected (0.098 sec)
```

```
mysql> INSERT INTO J(`J#`,Jname, City)
```

```
-> values("J5", "Collator", "London");
```

```
Query OK, 1 row affected (0.098 sec)
```

```
mysql> INSERT INTO J(`J#`,Jname, City)
```

```
-> values("J6","Terminal", "Oslo");
```

```
Query OK, 1 row affected (0.100 sec)
```

```
mysql> select * from J;
+-----+-----+-----+
| J# | Jname   | City   |
+-----+-----+-----+
| J1 | Sorter  | Paris  |
| J2 | Punch   | Rome   |
| J2 | Punch   | Rome   |
| J3 | Reader  | Athens |
| J4 | Console | Athens |
| J5 | Collator | London |
| J6 | Terminal | Oslo   |
+-----+-----+-----+
7 rows in set (0.007 sec)
```

create table sp(`S#` CHAR(4) NOT NULL, `P#` CHAR(4) NOT NULL, `J#` CHAR(4) NOT NULL, QTY INT);

Query OK, 0 rows affected (0.386 sec)

INSERT INTO SP (`S#`, `P#`, `J#`, QTY)

-> VALUES

-> ('S1', 'P1', 'J1', 200),

-> ('S1', 'P1', 'J4', 700),

-> ('S2', 'P3', 'J1', 400),

-> ('S2', 'P3', 'J2', 200),

-> ('S2', 'P3', 'J3', 200),

-> ('S2', 'P3', 'J4', 500),

-> ('S2', 'P3', 'J5', 600),

-> ('S2', 'P3', 'J6', 400),

-> ('S2', 'P3', 'J7', 800),

-> ('S2', 'P5', 'J2', 100),

-> ('S3', 'P3', 'J1', 200),

-> ('S3', 'P4', 'J2', 500),

-> ('S4', 'P6', 'J3', 300),

-> ('S4', 'P6', 'J7', 300),

-> ('S5', 'P2', 'J2', 200),

-> ('S5', 'P2', 'J4', 100),

-> ('S5', 'P5', 'J5', 500),

-> ('S5', 'P5', 'J7', 100),

-> ('S5', 'P6', 'J2', 200),

-> ('S5', 'P1', 'J4', 100),

-> ('S5', 'P3', 'J4', 200),

-> ('S5', 'P4', 'J4', 800),

-> ('S5', 'P5', 'J4', 400),

-> ('S5', 'P6', 'J4', 500);

Query OK, 24 rows affected (0.180 sec)

Records: 24 Duplicates: 0 Warnings: 0

```
mysql> select * from sp;
+-----+-----+-----+-----+
| S# | P# | J# | QTY |
+-----+-----+-----+-----+
| S1 | P1 | J1 | 200 |
| S1 | P1 | J4 | 700 |
| S2 | P3 | J1 | 400 |
| S2 | P3 | J2 | 200 |
| S2 | P3 | J3 | 200 |
| S2 | P3 | J4 | 500 |
| S2 | P3 | J5 | 600 |
| S2 | P3 | J6 | 400 |
| S2 | P3 | J7 | 800 |
| S2 | P5 | J2 | 100 |
| S3 | P3 | J1 | 200 |
| S3 | P4 | J2 | 500 |
| S4 | P6 | J3 | 300 |
| S4 | P6 | J7 | 300 |
| S5 | P2 | J2 | 200 |
| S5 | P2 | J4 | 100 |
| S5 | P5 | J5 | 500 |
| S5 | P5 | J7 | 100 |
| S5 | P6 | J2 | 200 |
| S5 | P1 | J4 | 100 |
| S5 | P3 | J4 | 200 |
| S5 | P4 | J4 | 800 |
| S5 | P5 | J4 | 400 |
| S5 | P6 | J4 | 500 |
+-----+-----+-----+-----+
24 rows in set (0.093 sec)
```