Selected terminal contract by history and policy

Cells: passing runs / applicable operation profiles; shading: fraction passing

Specified execution history	D0P0R0	D0P0R1	D0P1R0	D0P1R1	D1P0R0	D1P0R1	D1P1R0	D1P1R1
No fault	4/4	4/4	4/4	4/4	4/4	4/4	4/4	4/4
Redelivery: fixed tape	0/4	4/4	0/4	4/4	4/4	4/4	4/4	4/4
Redelivery: changed tape	0/4	4/4	0/4	4/4	0/4	4/4	4/4	4/4
Exit after prepare: fixed	4/4	4/4	4/4	4/4	4/4	4/4	4/4	4/4
Exit after prepare: changed	0/4	0/4	4/4	4/4	0/4	0/4	4/4	4/4
Exit after first put: fixed	2/4	2/4	2/4	2/4	4/4	4/4	4/4	4/4
Exit after first put: changed	0/4	0/4	2/4	2/4	0/4	0/4	4/4	4/4
Lost put reply: fixed	2/4	2/4	2/4	2/4	4/4	4/4	4/4	4/4
Lost put reply: changed	0/4	0/4	2/4	2/4	0/4	0/4	4/4	4/4
Exit after all effects: fixed	0/4	0/4	0/4	0/4	4/4	4/4	4/4	4/4
Exit after all effects: changed	0/4	0/4	0/4	0/4	0/4	0/4	4/4	4/4
Exit after finalize: changed	0/4	4/4	0/4	4/4	0/4	4/4	4/4	4/4
Bounded-input control	4/4	4/4	4/4	4/4	4/4	4/4	4/4	4/4
Disabled-source control	4/4	4/4	4/4	4/4	4/4	4/4	4/4	4/4
Reset before retry	4/4	4/4	4/4	4/4	4/4	4/4	4/4	4/4
Reset between effects	4/4	4/4	4/4	4/4	4/4	4/4	4/4	4/4
Lost delete reply	1/2	1/2	1/2	1/2	2/2	2/2	2/2	2/2

D = stable addresses; P = retained plan; R = receipt

Terminal = exact expected fact set + expected physical cardinality + final acknowledgement.

17 specified histories × 4 profiles, with two inapplicable delete cells omitted per policy.