# Phase 1 - foundation and durable join

**Goal:** A buyer can view the event, enter through a demo account session, join once, and recover the same authoritative state after refresh. Estimated time: 0:00-1:45.

## Build

1. Initialize the Next.js App Router and TypeScript app, Supabase PostgreSQL connection, and basic styling. Seed one event and fixed demo accounts.
2. Create the core schema in architecture §8: events, demo_accounts, queue_entries, reservations, orders, idempotency_records, audit_events, and simulation_runs. Add nonnegative inventory checks, the inventory-sum check, unique (event_id, account_id) queue entries, unique assigned positions, and unique orders per account/event. Later phases may add columns and functions.
3. Implement demo account selection/login using a signed HTTP-only cookie. Read the account from the verified cookie on buyer routes. Add a separate organizer session or secret-backed login for later admin routes. Keep server database credentials server-side.
4. Build the event page with event details, entry window, inventory summary, one-ticket rule, and published queue policy. Display server-provided event state.
5. Implement GET /api/events/:id, POST /api/events/:id/join, and GET /api/events/:id/me. Join must validate the entry window and use database uniqueness/conflict handling; repeated joins return the existing row without changing its timestamp or position. /me returns the account's actual state on every page load.
6. Build the initial queue page: call /me on load, poll every 2-3 seconds, show a pre-order status, and mark stale data if polling fails.

## Acceptance checks

- One event and demo accounts are seeded and visible.
- Ten repeated joins by one account produce exactly one queue entry and return the same entry ID. Refresh restores it.
- A client-provided userId cannot change the authenticated account. Entry outside the allowed window returns a clear reason code.
- The event inventory constraint holds in the database.

## Handoff to Phase 2

Phase 2 needs the event and queue schema, authenticated buyer context, join/resume behavior, and /me response shape. Record the actual event ID or seed command, migration command, local start command, endpoint shapes, and unresolved setup issues below.

### Handoff record

_Fill in after implementation: files/commits, commands, results, and open issues._