Phase 2 - queue ordering and admission

Goal: The organizer closes the entry window, the server assigns one stable random order, and buyers are admitted in controlled batches. Estimated time: 1:45-2:45.

Build

1. Implement event transitions DRAFT to ENTRY_OPEN to ENTRY_CLOSED to SELLING. Reject invalid transitions with explicit reason codes. Use an event-level database lock for close/order and admission operations.
2. Add organizer-only POST /api/admin/events/:id/close-entry. Freeze the eligible entries and persist server-generated random positions, cutoff, eligible count, and ordering policy version. Repeated calls must return the existing order without reshuffling.
3. Choose the smallest late-join rule: close entry completely at cutoff. State that rule on the buyer page. Keep the join endpoint consistent with it.
4. Add organizer-only POST /api/admin/events/:id/admit. Select the next queued entries by persisted position, admit up to batch_size, and set admission expiry. Use an idempotency key so repeating the same organizer action returns the same batch. Enforce the configured capacity rule for outstanding admissions.
5. Update /me and queue UI to show assigned position, people ahead when computable, admitted state, and expiry. The server decides these values. Refresh must preserve position and admission.
6. Log ordering and admission decisions in audit_events without secrets.

Acceptance checks

- One account retains one queue entry after repeated joins and refreshes.
- Closing twice leaves all positions unchanged; positions are unique for the event.
- Only eligible entries receive positions. A late join follows the published closed-entry rule.
- Admission selects the next positions, respects batch/capacity settings, and an identical retry does not admit another batch.
- Buyer requests cannot call organizer endpoints or assign their own position/admission.

Handoff to Phase 3

Phase 3 depends on the persisted ADMITTED state, admission expiry, and session-bound queue entry. Record the precise admission validity rule, any token format, and the database function/API used to test admission during reservation.

Handoff record

Fill in after implementation: files/commits, commands, results, and open issues.