

LiquidButton.tsx

```
// Original liquid-hover button for your portfolio.
//
// Visual direction:
// - Light button at rest.
// - Dark fill expands across the button on hover.
// - Arrow remains visible.
// - Works as a Next.js link or regular button.
// - Reduced-motion users get an instant state change.

"use client";

import Link from "next/link";
import { ReactNode, useState } from "react";

type LiquidButtonProps = {
  children: ReactNode;
  href?: string;
  external?: boolean;
  onClick?: () => void;
};

export function LiquidButton({
  children,
  href,
  external = false,
  onClick,
}: LiquidButtonProps) {
  const [active, setActive] = useState(false);

  const content = (
    <>
      <span
        aria-hidden="true"
        className={`absolute inset-0 origin-left rounded-full bg-black
          transition-transform duration-500 ease-out
          motion-reduce:transition-none
          ${active ? "scale-x-100" : "scale-x-0"}`}
      />

      <span className="relative z-10 flex items-center gap-3 px-2 py-2 pr-5">
        <span className="flex h-9 w-9 items-center justify-center rounded-full bg-black text-white transition-colors duration-300">
          <svg
            viewBox="0 0 24 24"
            className="h-4 w-4"
            fill="none"
            stroke="currentColor"
            strokeWidth="2.5"
          >
            <path d="M5 12h14M13 6l6 6 6" />
          </svg>
        </span>
        <span
          className={`font-semibold tracking-tight transition-colors duration-300
            motion-reduce:transition-none
            ${active ? "text-white" : "text-black"}`}
        >
          {children}
        </span>
      </span>
    </>
  );

  const common = {
    className:
      "relative inline-flex overflow-hidden rounded-full bg-white ring-1 " +
      "ring-neutral-300 transition-shadow hover:ring-white " +
      "focus-visible:outline-none focus-visible:ring-2 focus-visible:ring-white",
    onMouseEnter: () => setActive(true),
    onMouseLeave: () => setActive(false),
    onFocus: () => setActive(true),
    onBlur: () => setActive(false),
  };

  if (href && external) {
    return (
      <a {...common} href={href} target="_blank" rel="noreferrer">
        {content}
      </a>
    );
  }

  if (href) {
    return (
      <Link {...common} href={href}>

```

```
        {content}
      </Link>
    );
  }
  return (
    <button {...common} type="button" onClick={onClick}>
      {content}
    </button>
  );
}
```