Department of Computer Science and Engineering

FACULTY OF ENGINEERING AND TECHNOLOGY UNIVERSITY OF LUCKNOW LUCKNOW




Dr. Zeeshan Ali Siddiqui Assistant Professor Deptt. of C.S.E.

RESOURCE-ALLOCATION GRAPH


Resource-Allocation Graph_{1/2}

- This graph consists of a set of vertices V and a set of edges E.
- V is partitioned into two types:
 - > P = {P1, P2, ..., Pn}, the set of all the *processes* in the system
 - > R = {R1, R2, ..., Rm}, the set of all *resource* types in the system



- Request edge directed edge Pi -> Rj (Pi has requested an instance of resource type Rj and is currently waiting for that resource).
- Assignment edge directed edge Rj -> Pi (an instance of resource type Rj has been allocated to process Pi).

Example 1



Request edge


$$P_1 \rightarrow R_1, P_2 \rightarrow R_3$$

Assignment edge

$$R_1 \rightarrow P_2, R_2 \rightarrow P_2, R_2 \rightarrow P_1, R_3 \rightarrow P_3$$

No deadlock

Example 2



Request edge


$$P_1 \rightarrow R_1 \qquad P_2 \rightarrow R_3 \qquad P_3 \rightarrow R_2$$

Assignment edge

$$R_2 \rightarrow P_1 \mid R_2 \rightarrow P_2 \mid R_1 \rightarrow P_2 \mid R_3 \rightarrow P_3$$


P1, P2, and P3: deadlocked

Question?



Request edge ?

Assignment edge ?



Basic Facts

- If graph contains no cycles -> no deadlock
- If graph contains a cycle

- ➤ If only *one instance* per resource type, then *deadlock*
- ➤ If several instances per resource type, possibility of deadlock.

References

- 1. Silberschatz, Galvin and Gagne, "Operating Systems Concepts", Wiley.
- 2. William Stallings, "Operating Systems: Internals and Design Principles", 6th Edition, Pearson Education.
- 3. D M Dhamdhere, "Operating Systems: A Concept based Approach", 2nd Edition, TMH.

