

Edge Detection in Computer Vision

Submitted in Partial Fulfillment of the Second Continuous Assessment

Bachelor of Technology

In

Computer Science and Engineering (AI & ML)

7th semester

NAME: ADITIYA KUMAR

UNIVERSITY ROLL NO: 34230821034

UNIVERSITY REGISTRATION NO: 213420130810039 OF 2021-22.

PAPER NAME: - Computer Vision

PAPER CODE: PEC-AIML 701B



Under the guidance of

Paper Faculty

Name: Payel Bag

Designation: Professor

Department of CSE (AI&ML)

Future Institute of Technology

September 2024

INDEX

Sl.No.	TOPIC	Page No.
1.	Abstract	3
2.	Introduction	3
3.	Canny Edge Detection	4
4.	Hough Transform	5
5.	Corner Detection	6
6.	Practical Applications of Edge Detection	7
7.	Conclusion	8
8.	References	8

ABSTRACT

Edge detection is a key technique in computer vision and image processing that focuses on identifying significant transitions in pixel intensity, often corresponding to object boundaries, surface changes, and texture discontinuities. In this report, we explore various edge detection techniques, focusing on the Canny edge detection, Hough Transform, and corner detection methods. These algorithms have transformed numerous applications, including image segmentation, object recognition, and motion tracking. The effectiveness of each technique, as well as their strengths and limitations, are discussed. Graphical representations, diagrams, and sample images will illustrate the concepts to provide a comprehensive understanding of edge detection.

INTRODUCTION

Edge detection is a fundamental technique in computer vision that aims to identify and extract significant boundaries in images. These boundaries, known as edges, mark sudden changes in image intensity, representing transitions between different objects, regions, or textures. Edge detection is a crucial step in many computer vision tasks, such as object recognition, image segmentation, and motion tracking many algorithms has been developed for detecting edges, each with different approaches and success rates. This report focuses on three widely used methods:


Canny Edge Detection: A multi-stage algorithm that is renowned for its optimal edge detection.

Hough Transform: A technique primarily used to detect lines, circles, and other simple shapes.

Corner Detection: This method focuses on identifying points in an image where multiple edges converge, helping to locate important features like corners in objects.

Canny Edge Detection

The Canny edge detector is a widely used and highly effective edge detection algorithm. It was developed by John Canny in 1986 and is known for its robustness, accuracy, and efficiency. The Canny algorithm is based on the following steps:



1. Noise reduction: The image is first smoothed using a Gaussian filter to reduce noise and prevent spurious edge detection.

2. Gradient calculation: The smoothed image is then processed to calculate the gradient magnitude and direction at each pixel. This information helps identify potential edges based on the rate of change in intensity.

3. Non-maximum suppression: This step eliminates false edge pixels by ensuring that only the most prominent edge pixels along the gradient direction are retained.

4. Hysteresis thresholding: Two thresholds are used to determine which edge pixels are considered true edges. Pixels exceeding the high threshold are automatically classified as edges, while those below the low threshold are discarded. Pixels between the thresholds are classified as edges only if they are connected to high-threshold edge pixels.

Benefits and Limitations

Benefits:

- i. Finds optimal edges, reducing the risk of detecting false edges.
- ii. Robust to noise due to the Gaussian smoothing stage.

Limitations:

- i. Computationally expensive due to the multi-step process.
- ii. Sensitive to the selection of threshold values, which can affect results.

Hough Transform

The Hough transform is a powerful technique used for detecting lines, circles, and other geometric shapes in images. It operates on the principle of parameter space transformation. The Hough transform represents each image point as a set of possible lines or curves that could pass through that point. By accumulating these votes in parameter space, the algorithm identifies the most likely lines or curves present in the image.

The Hough transform for line detection works by transforming each image point (x, y) into a line in parameter space (ρ, θ) . ρ represents the distance from the origin to the line, and θ represents the angle of the line with respect to the horizontal axis. By accumulating the votes for each line in parameter space, the algorithm finds the most likely lines present in the image.


Applications and Challenges

Applications:

- i. Lane detection in autonomous vehicles.
- ii. Recognizing geometric shapes in machine vision tasks.
- iii. Detecting patterns in satellite images or medical scans.

Challenges:

- i. The accuracy of detection relies heavily on proper edge detection.
- ii. Performance degrades in noisy images.



Corner Detection

Corner detection aims to identify points in an image where two or more edges intersect. Corners are important features that provide information about the shape, structure, and orientation of objects in the scene. They are often used in object recognition, image matching, and motion estimation.

Various corner detection algorithms have been developed, including the Harris corner detector and the Shi-Tomasi corner detector. These algorithms work by measuring the changes in image intensity in different directions around a pixel. A high change in intensity in multiple directions indicates a corner. Corner detection algorithms typically involve computing a corner response function that scores each pixel based on its corner likelihood.

Harris Corner Detector

The Harris Corner Detector is one of the most widely used methods. It calculates the difference in intensity between the corner and the neighboring pixels. A corner is detected if there are significant changes in intensity in multiple directions.

Shi-Tomasi Corner Detector


An improvement over the Harris method, the Shi-Tomasi algorithm considers the smallest Eigen-value of the intensity gradient matrix, which improves the detection of more subtle corners.

Applications

Object Tracking: Identifying distinct points on an object to track its movement.

Image Stitching: Using corner detection to align overlapping images in panoramic photography.

3D Reconstruction: Detecting corners to help reconstruct a 3D scene from 2D images.



Practical Applications of Edge Detection

Edge detection plays a vital role in a wide range of computer vision applications, including:

- a. **Object Recognition:** Edge information helps identify the boundaries and shapes of objects, facilitating their recognition and classification.
- b. **Image Segmentation:** Edges are used to separate different regions and objects in an image, allowing for the analysis and understanding of individual components.
- c. **Motion Tracking:** Edge detection enables the detection and tracking of moving objects by identifying changes in image intensity over time.
- d. **Medical Imaging:** Edge detection is employed in medical imaging to identify abnormalities and structures, aiding in diagnosis and treatment planning.
- e. **Autonomous Vehicles:** Edge detection is crucial for self-driving cars to perceive their surroundings, recognize objects, and navigate safely.
- f. **Image restoration:** Morphological operations can be used to extract the skeletons and boundaries of damaged regions in an image.
- g. **Lane detection:** The Hough Transform is a technique that uses binary images from edge detection to detect lines in an image, such as lanes.
- h. **Brain tumor MRI image analysis:** The Sobel edge detection technique can be used to improve the detection of edges in brain tumor MRI images.
- i. **Fault detection in rolling element bearings:** The Laplacian of Gaussian (LOG) filter can be used to detect faults in rolling element bearings.



CONCLUSION

Edge detection is a fundamental technique in computer vision, providing essential information about the structure and content of images. The Canny edge detector, Hough transforms, and corner detection algorithms represent powerful tools for extracting significant boundaries and features. Understanding these techniques is crucial for developing robust and effective computer vision systems across various domains, from image processing and objects recognition to medical imaging and autonomous vehicles.

REFERENCES

1. **Canny, J. (1986).** A Computational Approach to Edge Detection. *IEEE Transactions on Pattern Analysis and Machine Intelligence*, 8(6), 679–698.
DOI: 10.1109/TPAMI.1986.4767851
2. **Ballard, D.H. (1981).** Generalizing the Hough Transform to Detect Arbitrary Shapes. *Pattern Recognition*, 13(2), 111–122.
DOI: 10.1016/0031-3203(81)90009-1
3. **Harris, C., & Stephens, M. (1988).** A Combined Corner and Edge Detector. *Proceedings of the Alvey Vision Conference*, 147-151.
URL: <https://www.bmva.org/bmvc/1988/avc-88-023.pdf>
4. **Shi, J., & Tomasi, C. (1994).** Good Features to Track. *Proceedings of the IEEE Conference on Computer Vision and Pattern Recognition (CVPR)*, 593–600.
DOI: 10.1109/CVPR.1994.323794
5. **Duda, R.O., & Hart, P.E. (1972).** Use of the Hough Transformation to Detect Lines and Curves in Pictures. *Communications of the ACM*, 15(1), 11–15.
DOI: 10.1145/361237.361242
6. **Gonzalez, R.C., & Woods, R.E. (2008).** *Digital Image Processing* (3rd ed.). Pearson Prentice Hall.
ISBN: 978-0131687288
7. **Szeliski, R. (2010).** *Computer Vision: Algorithms and Applications*. Springer.
DOI: 10.1007/978-1-84882-935-0
8. **Forsyth, D.A., & Ponce, J. (2011).** *Computer Vision: A Modern Approach* (2nd ed.). Pearson.
ISBN: 978-013608592