

Experiment 27: Splay Tree

Code:

```
#include <stdio.h>
```

```
#include <stdlib.h>
```

```
struct Node {
```

```
    int key;
```

```
    struct Node *left, *right;
```

```
};
```

```
// Function to create new node
```

```
struct Node* newNode(int key) {
```

```
    struct Node* node = (struct Node*)malloc(sizeof(struct Node));
```

```
    node->key = key;
```

```
    node->left = node->right = NULL;
```

```
    return node;
```

```
}
```

```
// Right rotate
```

```
struct Node* rightRotate(struct Node* x) {
```

```
    struct Node* y = x->left;
```

```
    x->left = y->right;
```

```
    y->right = x;
```

```
    return y;
```

```
}
```

// Left rotate

```
struct Node* leftRotate(struct Node* x) {  
    struct Node* y = x->right;  
    x->right = y->left;  
    y->left = x;  
    return y;  
}
```

// Splay operation

```
struct Node* splay(struct Node* root, int key) {  
    if (root == NULL || root->key == key)  
        return root;
```

// Key lies in left subtree

```
if (key < root->key) {  
    if (root->left == NULL) return root;
```

// Zig-Zig (Left Left)

```
if (key < root->left->key) {  
    root->left->left = splay(root->left->left, key);  
    root = rightRotate(root);  
}
```

// Zig-Zag (Left Right)

```
else if (key > root->left->key) {  
    root->left->right = splay(root->left->right, key);  
    if (root->left->right != NULL)  
        root->left = leftRotate(root->left);  
}
```

```
return (root->left == NULL) ? root : rightRotate(root);
```

```
}
```

```

// Key lies in right subtree
else {
    if (root->right == NULL) return root;

    // Zag-Zig (Right Left)
    if (key < root->right->key) {
        root->right->left = splay(root->right->left, key);
        if (root->right->left != NULL)
            root->right = rightRotate(root->right);
    }

    // Zag-Zag (Right Right)
    else if (key > root->right->key) {
        root->right->right = splay(root->right->right, key);
        root = leftRotate(root);
    }

    return (root->right == NULL) ? root : leftRotate(root);
}
}

```

```

// Insert operation
struct Node* insert(struct Node* root, int key) {
    if (root == NULL) return newNode(key);

    root = splay(root, key);

    if (root->key == key) return root;

    struct Node* node = newNode(key);

```

```

if (key < root->key) {
    node->right = root;
    node->left = root->left;
    root->left = NULL;
} else {
    node->left = root;
    node->right = root->right;
    root->right = NULL;
}

return node;
}

```

// Preorder traversal

```

void preorder(struct Node* root) {
    if (root != NULL) {
        printf("%d ", root->key);
        preorder(root->left);
        preorder(root->right);
    }
}

```

// Menu-driven main function

```

int main() {
    struct Node* root = NULL;
    int choice, key;

    while (1) {
        printf("\n--- Splay Tree Menu ---\n");
        printf("1. Insert\n2. Splay\n3. Display (Preorder)\n4. Exit\n");
        printf("Enter your choice: ");
    }
}

```

```

scanf("%d", &choice);

switch (choice) {
    case 1:
        printf("Enter value to insert: ");
        scanf("%d", &key);
        root = insert(root, key);
        printf("Value inserted and splayed to root.\n");
        break;
    case 2:
        printf("Enter value to search: ");
        scanf("%d", &key);
        root = splay(root, key);
        if (root && root->key == key)
            printf("Element %d found and splayed to root.\n", key);
        else
            printf("Element %d not found.\n", key);
        break;
    case 3:
        printf("Preorder traversal: ");
        preorder(root);
        printf("\n");
        break;
    case 4:
        exit(0);
    default:
        printf("Invalid choice!\n");
}
}
}

```

Output:

```
--- Splay Tree Menu ---
1. Insert
2. Splay
3. Display (Preorder)
4. Exit
Enter your choice: 1
Enter value to insert: 10
Value inserted and splayed to root.

--- Splay Tree Menu ---
1. Insert
2. Splay
3. Display (Preorder)
4. Exit
Enter your choice: 1
Enter value to insert: 0
Value inserted and splayed to root.

--- Splay Tree Menu ---
1. Insert
2. Splay
3. Display (Preorder)
4. Exit
Enter your choice: 1
Enter value to insert: 15
Value inserted and splayed to root.

--- Splay Tree Menu ---
1. Insert
2. Splay
3. Display (Preorder)
4. Exit
Enter your choice: 2
Enter value to search: 15
Element 15 found and splayed to root.

--- Splay Tree Menu ---
1. Insert
2. Splay
3. Display (Preorder)
4. Exit
Enter your choice: 3
Preorder traversal: 15 10 0
```