

OIL INDIA LIMITED - eRTMAC OPERATIONS

OFFICIAL WELL COMPLETION REPORT (WCR) & DRILLING HISTORY
WELL IDENTIFIER: 16/2-7

1. Well Location & Technical Header

Operator: Oil India Limited / Joint North Sea	Well Name: 16/2-7
UTM Easting (X): 480020.5 m	UTM Northing (Y): 6515756.8 m
Latitude: 58.781347° N	Longitude: 2.654429° E
Total Depth (MD): 2480.5 m	Spud Depth: 704.1 m
Drilling Rig: eRTMAC Semi-Submersible Rig-07	Status: Plugged & Abandoned (P&A;) / Offset Reference

2. Stratigraphic Progression & Formation Tops

Formation / Stratum Name	Top Depth MD (m)	Lithology Characterization	Drillability / Risk Profile
Utsira Fm.	704.1 m	Interbedded Sand / Shale	Loss / Depletion
Skade Fm.	792.9 m	Interbedded Sand / Shale	Loss / Depletion
Balder Fm.	881.7 m	Interbedded Sand / Shale	Loss / Depletion
Sele Fm.	970.6 m	Shale / Claystone with interbedded siltstone	Tight Hole / Swelling
Lista Fm.	1059.4 m	Interbedded Sand / Shale	Loss / Depletion
Vaale Fm.	1148.2 m	Interbedded Sand / Shale	Loss / Depletion
Ekofisk Fm.	1237.0 m	Chalk / Hard Calcareous Limestone	Fractured / Losses
Tor Fm.	1325.8 m	Chalk / Hard Calcareous Limestone	Fractured / Losses
Hod Fm.	1414.7 m	Interbedded Sand / Shale	Loss / Depletion
Blodoeks Fm.	1503.5 m	Interbedded Sand / Shale	Loss / Depletion
Svarte Fm.	1592.3 m	Interbedded Sand / Shale	Loss / Depletion
Roedby Fm.	1681.1 m	Interbedded Sand / Shale	Loss / Depletion
Sola Fm.	1769.9 m	Interbedded Sand / Shale	Loss / Depletion
Aasgard Fm.	1858.8 m	Interbedded Sand / Shale	Loss / Depletion
Draupne Fm.	1947.6 m	Interbedded Sand / Shale	Loss / Depletion
Intra Draupne Fm. Sst.	2036.4 m	Interbedded Sand / Shale	Loss / Depletion
Sleipner Fm.	2125.2 m	Interbedded Sand / Shale	Loss / Depletion
Staffjord Fm.	2214.0 m	Interbedded Sand / Shale	Loss / Depletion
Skagerrak Fm.	2302.9 m	Interbedded Sand / Shale	Loss / Depletion
Kupferschiefer Fm.	2391.7 m	Interbedded Sand / Shale	Loss / Depletion

3. Casing Design & Mud Program Summary

--	--	--	--	--	--

36 in Hole	30 in Conductor	350 m	Spud Mud / Seawater	1.05 SG	FIT 1.25 SG
26 in Hole	20 in Surface	1,050 m	KCl / Polymer	1.12 SG	LOT 1.45 SG
17-1/2 in Hole	13-3/8 in Interm.	2,200 m	Low Solids Non-Dispersed	1.24 SG	LOT 1.62 SG
12-1/4 in Hole	9-5/8 in Prod.	2180 m	Oil Based / Synthetic Mud	1.32 SG	LOT 1.78 SG
8-1/2 in Hole	7 in Liner	2480 m	Synthetic Oil Based (SOBM)	1.38 SG	LOT 1.88 SG

4. Historical Operational Incidents, NPT & Mitigations (Well: 16/2-7)

This section constitutes the institutional memory log extracted by the NWIS knowledge engine. All alerts generated during active drilling cite these exact records.

INCIDENT #1: Lost Circulation / Mud Loss		
	Severity: HIGH	NPT Hours: 16.5 hrs
Depth Interval: 1450.2 m - 1503.5 m	Formation: Balder Fm.	Status: Resolved on Site
Event Occurrence Narrative: Experienced 45 bbl/hr mud loss at 1468.0m while drilling through permeable Balder Fm. section.		
Mitigation Action Applied: Pumped 45 bbl LCM pill with multi-modal calcium carbonate. Reduced flow rate by 15% and maintained backpressure.		
Offset Drilling Recommendation & Institutional Lesson: Pre-treat active system with bridging agents prior to drilling formation boundary.		

INCIDENT #2: Tight Hole / Stuck Pipe Risk		
	Severity: MEDIUM	NPT Hours: 10.0 hrs
Depth Interval: 1983.1 m - 2054.2 m	Formation: Vaale Fm.	Status: Resolved on Site
Event Occurrence Narrative: High torque and 45 klbs overpull on connections at 2018.6m due to reactive shale sloughing.		
Mitigation Action Applied: Conducted wiper trip, increased mud yield point to 20 lb/100ft2, and raised polymer encapsulator dosage.		
Offset Drilling Recommendation & Institutional Lesson: Do not let drillstring remain stationary for more than 4 minutes in this section.		