

OIL INDIA LIMITED - eRTMAC OPERATIONS

OFFICIAL WELL COMPLETION REPORT (WCR) & DRILLING HISTORY
WELL IDENTIFIER: 25/10-10

1. Well Location & Technical Header

Operator: Oil India Limited / Joint North Sea	Well Name: 25/10-10
UTM Easting (X): 459853.5 m	UTM Northing (Y): 6560992.9 m
Latitude: 59.186161° N	Longitude: 2.297416° E
Total Depth (MD): 2506.9 m	Spud Depth: 1090.4 m
Drilling Rig: eRTMAC Semi-Submersible Rig-07	Status: Plugged & Abandoned (P&A;) / Offset Reference

2. Stratigraphic Progression & Formation Tops

Formation / Stratum Name	Top Depth MD (m)	Lithology Characterization	Drillability / Risk Profile
Skade Fm.	1090.4 m	Interbedded Sand / Shale	Loss / Depletion
Grid Fm.	1208.4 m	Interbedded Sand / Shale	Loss / Depletion
Balder Fm.	1326.5 m	Interbedded Sand / Shale	Loss / Depletion
Intra Balder Fm. Sst.	1444.5 m	Interbedded Sand / Shale	Loss / Depletion
Sele Fm.	1562.6 m	Shale / Claystone with interbedded siltstone	Tight Hole / Swelling
Lista Fm.	1680.6 m	Interbedded Sand / Shale	Loss / Depletion
Heimdal Fm.	1798.7 m	Porous Turbidite Sandstone (Hydrocarbon Bearing)	Loss / Depletion
Ty Fm.	1916.7 m	Porous Turbidite Sandstone (Hydrocarbon Bearing)	Loss / Depletion
Tor Fm.	2034.7 m	Chalk / Hard Calcareous Limestone	Fractured / Losses
Staffjord Fm.	2152.8 m	Interbedded Sand / Shale	Loss / Depletion
Skagerrak Fm.	2270.8 m	Interbedded Sand / Shale	Loss / Depletion
Smith Bank Fm.	2388.9 m	Interbedded Sand / Shale	Loss / Depletion

3. Casing Design & Mud Program Summary

36 in Hole	30 in Conductor	350 m	Spud Mud / Seawater	1.05 SG	FIT 1.25 SG
26 in Hole	20 in Surface	1,050 m	KCl / Polymer	1.12 SG	LOT 1.45 SG
17-1/2 in Hole	13-3/8 in Interm.	2,200 m	Low Solids Non-Dispersed	1.24 SG	LOT 1.62 SG
12-1/4 in Hole	9-5/8 in Prod.	2207 m	Oil Based / Synthetic Mud	1.32 SG	LOT 1.78 SG
8-1/2 in Hole	7 in Liner	2507 m	Synthetic Oil Based (SOBM)	1.38 SG	LOT 1.88 SG

4. Historical Operational Incidents, NPT & Mitigations (Well: 25/10-10)

This section constitutes the institutional memory log extracted by the NWIS knowledge engine. All alerts generated during active drilling cite these exact records.

INCIDENT #1: Well Kick / Influx	Severity: HIGH	NPT Hours: 19.0 hrs
Depth Interval: 2180.0 m - 2220.0 m	Formation: HEIMDAL FM	Status: Resolved on Site
Event Occurrence Narrative: Encountered high pressure gas pocket in Heimdal turbidite sand at 2204m. Pit volume gain 14 bbls, background gas 22%. Mitigation Action Applied: Shut in well on annular preventer. SIDPP=280 psi, SICP=350 psi. Weighted mud from 1.19 SG to 1.28 SG using barite addition. Circulated bottom up cleanly. Offset Drilling Recommendation & Institutional Lesson: Heimdal sands in Block 25 are isolated pressure compartments. Ensure barite stock on rig exceeds 120 metric tons before drilling reservoir section.		