

OIL INDIA LIMITED - eRTMAC OPERATIONS

OFFICIAL WELL COMPLETION REPORT (WCR) & DRILLING HISTORY
WELL IDENTIFIER: 25/11-24

1. Well Location & Technical Header

Operator: Oil India Limited / Joint North Sea	Well Name: 25/11-24
UTM Easting (X): 462262.9 m	UTM Northing (Y): 6551906.2 m
Latitude: 59.104785° N	Longitude: 2.341148° E
Total Depth (MD): 2094.5 m	Spud Depth: 1457.0 m
Drilling Rig: eRTMAC Semi-Submersible Rig-07	Status: Plugged & Abandoned (P&A;) / Offset Reference

2. Stratigraphic Progression & Formation Tops

Formation / Stratum Name	Top Depth MD (m)	Lithology Characterization	Drillability / Risk Profile
Skade Fm.	1457.0 m	Interbedded Sand / Shale	Loss / Depletion
Grid Fm.	1506.0 m	Interbedded Sand / Shale	Loss / Depletion
Balder Fm.	1555.1 m	Interbedded Sand / Shale	Loss / Depletion
Sele Fm.	1604.1 m	Shale / Claystone with interbedded siltstone	Tight Hole / Swelling
Lista Fm.	1653.2 m	Interbedded Sand / Shale	Loss / Depletion
Heimdal Fm.	1702.2 m	Porous Turbidite Sandstone (Hydrocarbon Bearing)	Loss / Depletion
Vaale Fm.	1751.2 m	Interbedded Sand / Shale	Loss / Depletion
Tor Fm.	1800.3 m	Chalk / Hard Calcareous Limestone	Fractured / Losses
Roedby Fm.	1849.3 m	Interbedded Sand / Shale	Loss / Depletion
Sola Fm.	1898.3 m	Interbedded Sand / Shale	Loss / Depletion
Aasgard Fm.	1947.4 m	Interbedded Sand / Shale	Loss / Depletion
Draupne Fm.	1996.4 m	Interbedded Sand / Shale	Loss / Depletion
Statfjord Fm.	2045.5 m	Interbedded Sand / Shale	Loss / Depletion

3. Casing Design & Mud Program Summary

36 in Hole	30 in Conductor	350 m	Spud Mud / Seawater	1.05 SG	FIT 1.25 SG
26 in Hole	20 in Surface	1,050 m	KCl / Polymer	1.12 SG	LOT 1.45 SG
17-1/2 in Hole	13-3/8 in Interm.	2,200 m	Low Solids Non-Dispersed	1.24 SG	LOT 1.62 SG
12-1/4 in Hole	9-5/8 in Prod.	1794 m	Oil Based / Synthetic Mud	1.32 SG	LOT 1.78 SG
8-1/2 in Hole	7 in Liner	2094 m	Synthetic Oil Based (SOBM)	1.38 SG	LOT 1.88 SG

4. Historical Operational Incidents, NPT & Mitigations (Well: 25/11-24)

This section constitutes the institutional memory log extracted by the NWIS knowledge engine. All alerts generated during active drilling cite these exact records.

INCIDENT #1: Lost Circulation / Mud Loss		
	Severity: MEDIUM	NPT Hours: 14.0 hrs
Depth Interval: 1690.0 m - 1740.0 m	Formation: BALDER FM	Status: Resolved on Site
Event Occurrence Narrative: Partial mud loss of 25 bbl/hr in porous Balder tuff interval at 1712m. Total mud lost: 160 bbls.		
Mitigation Action Applied: Spotted 35 bbls coarse calcium carbonate LCM pill. Lowered pump rate to 600 gpm and adjusted mud weight to 1.16 SG. Losses stabilized.		
Offset Drilling Recommendation & Institutional Lesson: Volcanic tuffs in Balder formation possess low fracture threshold. Monitor ECD closely using PWD (pressure-while-drilling) sub.		