

OIL INDIA LIMITED - eRTMAC OPERATIONS

OFFICIAL WELL COMPLETION REPORT (WCR) & DRILLING HISTORY
WELL IDENTIFIER: 29/3-1

1. Well Location & Technical Header

Operator: Oil India Limited / Joint North Sea	Well Name: 29/3-1
UTM Easting (X): 442438.0 m	UTM Northing (Y): 6759358.7 m
Latitude: 60.965025° N	Longitude: 1.936866° E
Total Depth (MD): 4388.8 m	Spud Depth: 695.3 m
Drilling Rig: eRTMAC Semi-Submersible Rig-07	Status: Plugged & Abandoned (P&A;) / Offset Reference

2. Stratigraphic Progression & Formation Tops

Formation / Stratum Name	Top Depth MD (m)	Lithology Characterization	Drillability / Risk Profile
Utsira Fm.	695.3 m	Interbedded Sand / Shale	Loss / Depletion
Grid Fm.	871.2 m	Interbedded Sand / Shale	Loss / Depletion
Balder Fm.	1047.1 m	Interbedded Sand / Shale	Loss / Depletion
Sele Fm.	1222.9 m	Shale / Claystone with interbedded siltstone	Tight Hole / Swelling
Lista Fm.	1398.8 m	Interbedded Sand / Shale	Loss / Depletion
Vaale Fm.	1574.7 m	Interbedded Sand / Shale	Loss / Depletion
Jorsalfare Fm.	1750.6 m	Interbedded Sand / Shale	Loss / Depletion
Kyrre Fm.	1926.5 m	Interbedded Sand / Shale	Loss / Depletion
Tryggvason Fm.	2102.3 m	Interbedded Sand / Shale	Loss / Depletion
Blodoeks Fm.	2278.2 m	Interbedded Sand / Shale	Loss / Depletion
Svarte Fm.	2454.1 m	Interbedded Sand / Shale	Loss / Depletion
Roedby Fm.	2630.0 m	Interbedded Sand / Shale	Loss / Depletion
Heather Fm.	2805.9 m	Interbedded Sand / Shale	Loss / Depletion
Tarbert Fm.	2981.8 m	Interbedded Sand / Shale	Loss / Depletion
Ness Fm.	3157.6 m	Interbedded Sand / Shale	Loss / Depletion
Etive Fm.	3333.5 m	Interbedded Sand / Shale	Loss / Depletion
Rannoch Fm.	3509.4 m	Interbedded Sand / Shale	Loss / Depletion
Drake Fm.	3685.3 m	Interbedded Sand / Shale	Loss / Depletion
Cook Fm.	3861.2 m	Interbedded Sand / Shale	Loss / Depletion
Burton Fm.	4037.0 m	Interbedded Sand / Shale	Loss / Depletion
Amundsen Fm.	4212.9 m	Interbedded Sand / Shale	Loss / Depletion

3. Casing Design & Mud Program Summary

36 in Hole	30 in Conductor	350 m	Spud Mud / Seawater	1.05 SG	FIT 1.25 SG
26 in Hole	20 in Surface	1,050 m	KCl / Polymer	1.12 SG	LOT 1.45 SG
17-1/2 in Hole	13-3/8 in Interm.	2,200 m	Low Solids Non-Dispersed	1.24 SG	LOT 1.62 SG
12-1/4 in Hole	9-5/8 in Prod.	3100 m	Oil Based / Synthetic Mud	1.32 SG	LOT 1.78 SG
8-1/2 in Hole	7 in Liner	4389 m	Synthetic Oil Based (SOBM)	1.38 SG	LOT 1.88 SG

4. Historical Operational Incidents, NPT & Mitigations (Well: 29/3-1)

This section constitutes the institutional memory log extracted by the NWIS knowledge engine. All alerts generated during active drilling cite these exact records.

INCIDENT #1: Lost Circulation / Mud Loss		
	Severity: HIGH	NPT Hours: 16.5 hrs
Depth Interval: 2246.6 m - 2357.4 m	Formation: Balder Fm.	Status: Resolved on Site
Event Occurrence Narrative: Experienced 45 bbl/hr mud loss at 2283.5m while drilling through permeable Balder Fm. section.		
Mitigation Action Applied: Pumped 45 bbl LCM pill with multi-modal calcium carbonate. Reduced flow rate by 15% and maintained backpressure.		
Offset Drilling Recommendation & Institutional Lesson: Pre-treat active system with bridging agents prior to drilling formation boundary.		

INCIDENT #2: Tight Hole / Stuck Pipe Risk		
	Severity: MEDIUM	NPT Hours: 10.0 hrs
Depth Interval: 3354.6 m - 3502.4 m	Formation: Vaale Fm.	Status: Resolved on Site
Event Occurrence Narrative: High torque and 45 klbs overpull on connections at 3428.5m due to reactive shale sloughing.		
Mitigation Action Applied: Conducted wiper trip, increased mud yield point to 20 lb/100ft2, and raised polymer encapsulator dosage.		
Offset Drilling Recommendation & Institutional Lesson: Do not let drillstring remain stationary for more than 4 minutes in this section.		