

OIL INDIA LIMITED - eRTMAC OPERATIONS

OFFICIAL WELL COMPLETION REPORT (WCR) & DRILLING HISTORY
WELL IDENTIFIER: 34/3-3 A

1. Well Location & Technical Header

Operator: Oil India Limited / Joint North Sea	Well Name: 34/3-3 A
UTM Easting (X): 485609.1 m	UTM Northing (Y): 6852351.0 m
Latitude: 61.803775° N	Longitude: 2.726999° E
Total Depth (MD): 5007.4 m	Spud Depth: 2233.9 m
Drilling Rig: eRTMAC Semi-Submersible Rig-07	Status: Plugged & Abandoned (P&A;) / Offset Reference

2. Stratigraphic Progression & Formation Tops

Formation / Stratum Name	Top Depth MD (m)	Lithology Characterization	Drillability / Risk Profile
Jorsalfare Fm.	2233.9 m	Interbedded Sand / Shale	Loss / Depletion
Kyrre Fm.	2630.1 m	Interbedded Sand / Shale	Loss / Depletion
Tryggvason Fm.	3026.3 m	Interbedded Sand / Shale	Loss / Depletion
Mime Fm.	3422.5 m	Interbedded Sand / Shale	Loss / Depletion
Drake Fm.	3818.8 m	Interbedded Sand / Shale	Loss / Depletion
Cook Fm.	4215.0 m	Interbedded Sand / Shale	Loss / Depletion
Burton Fm.	4611.2 m	Interbedded Sand / Shale	Loss / Depletion

3. Casing Design & Mud Program Summary

36 in Hole	30 in Conductor	350 m	Spud Mud / Seawater	1.05 SG	FIT 1.25 SG
26 in Hole	20 in Surface	1,050 m	KCl / Polymer	1.12 SG	LOT 1.45 SG
17-1/2 in Hole	13-3/8 in Interm.	2,200 m	Low Solids Non-Dispersed	1.24 SG	LOT 1.62 SG
12-1/4 in Hole	9-5/8 in Prod.	3100 m	Oil Based / Synthetic Mud	1.32 SG	LOT 1.78 SG
8-1/2 in Hole	7 in Liner	5007 m	Synthetic Oil Based (SOBM)	1.38 SG	LOT 1.88 SG

4. Historical Operational Incidents, NPT & Mitigations (Well: 34/3-3 A)

This section constitutes the institutional memory log extracted by the NWIS knowledge engine. All alerts generated during active drilling cite these exact records.

INCIDENT #1: Lost Circulation / Mud Loss		
	Severity: HIGH	NPT Hours: 20.0 hrs
Depth Interval: 3120.0 m - 3170.0 m	Formation: SHETLAND GP	Status: Resolved on Site
Event Occurrence Narrative: Severe circulation losses of 75 bbl/hr encountered in fractured limestone streaks of Shetland Group at 3145m.		
Mitigation Action Applied: Pumped engineered LCM blend (fibers, mica, coarse carbonate). Squeezed 30 bbls into formation at 400 psi squeeze pressure. Full returns restored.		
Offset Drilling Recommendation & Institutional Lesson: Conduct LOT (Leak-Off Test) immediately upon drilling 5m out of 13-3/8 inch casing shoe in Shetland formation.		