

OIL INDIA LIMITED - eRTMAC OPERATIONS

OFFICIAL WELL COMPLETION REPORT (WCR) & DRILLING HISTORY
WELL IDENTIFIER: 35/9-7

1. Well Location & Technical Header

Operator: Oil India Limited / Joint North Sea	Well Name: 35/9-7
UTM Easting (X): 536108.6 m	UTM Northing (Y): 6793042.4 m
Latitude: 61.269952° N	Longitude: 3.673346° E
Total Depth (MD): 2973.9 m	Spud Depth: 1351.2 m
Drilling Rig: eRTMAC Semi-Submersible Rig-07	Status: Plugged & Abandoned (P&A;) / Offset Reference

2. Stratigraphic Progression & Formation Tops

Formation / Stratum Name	Top Depth MD (m)	Lithology Characterization	Drillability / Risk Profile
Sele Fm.	1351.2 m	Shale / Claystone with interbedded siltstone	Tight Hole / Swelling
Lista Fm.	1459.4 m	Interbedded Sand / Shale	Loss / Depletion
Vaale Fm.	1567.6 m	Interbedded Sand / Shale	Loss / Depletion
EGGA FM (INFORMAL).	1675.7 m	Interbedded Sand / Shale	Loss / Depletion
Jorsalfare Fm.	1783.9 m	Interbedded Sand / Shale	Loss / Depletion
Kyrre Fm.	1892.1 m	Interbedded Sand / Shale	Loss / Depletion
Tryggvason Fm.	2000.3 m	Interbedded Sand / Shale	Loss / Depletion
Blodoeks Fm.	2108.5 m	Interbedded Sand / Shale	Loss / Depletion
Roedby Fm.	2216.6 m	Interbedded Sand / Shale	Loss / Depletion
Draupne Fm.	2324.8 m	Interbedded Sand / Shale	Loss / Depletion
Heather Fm.	2433.0 m	Interbedded Sand / Shale	Loss / Depletion
Intra Heather Fm. Sst.	2541.2 m	Interbedded Sand / Shale	Loss / Depletion
Tarbert Fm.	2649.4 m	Interbedded Sand / Shale	Loss / Depletion
Ness Fm.	2757.5 m	Interbedded Sand / Shale	Loss / Depletion
Etive Fm.	2865.7 m	Interbedded Sand / Shale	Loss / Depletion

3. Casing Design & Mud Program Summary

36 in Hole	30 in Conductor	350 m	Spud Mud / Seawater	1.05 SG	FIT 1.25 SG
26 in Hole	20 in Surface	1,050 m	KCl / Polymer	1.12 SG	LOT 1.45 SG
17-1/2 in Hole	13-3/8 in Interm.	2,200 m	Low Solids Non-Dispersed	1.24 SG	LOT 1.62 SG
12-1/4 in Hole	9-5/8 in Prod.	2674 m	Oil Based / Synthetic Mud	1.32 SG	LOT 1.78 SG
8-1/2 in Hole	7 in Liner	2974 m	Synthetic Oil Based (SOBM)	1.38 SG	LOT 1.88 SG

4. Historical Operational Incidents, NPT & Mitigations (Well: 35/9-7)

This section constitutes the institutional memory log extracted by the NWIS knowledge engine. All alerts generated during active drilling cite these exact records.

INCIDENT #1: Overpressure / Tight Hole		
	Severity: HIGH	NPT Hours: 17.0 hrs
Depth Interval: 2650.0 m - 2710.0 m	Formation: VIKING GP	Status: Resolved on Site
Event Occurrence Narrative: Encountered high pore pressure transition zone in Viking organic shales at 2682m. Severe background gas (18%) and splitty shale cavings.		
Mitigation Action Applied: Increased active mud weight from 1.30 SG to 1.42 SG. Conducted short wiper trip to 9-5/8 inch shoe. Hole stabilized.		
Offset Drilling Recommendation & Institutional Lesson: Transition into Viking shales requires gradual density weighting. Use real-time PWD sonic porosity to track pore pressure ramp.		