

OIL INDIA LIMITED - eRTMAC OPERATIONS

OFFICIAL WELL COMPLETION REPORT (WCR) & DRILLING HISTORY
WELL IDENTIFIER: 35/9-8

1. Well Location & Technical Header

Operator: Oil India Limited / Joint North Sea	Well Name: 35/9-8
UTM Easting (X): 536233.1 m	UTM Northing (Y): 6794887.6 m
Latitude: 61.286504° N	Longitude: 3.676024° E
Total Depth (MD): 3225.0 m	Spud Depth: 2536.3 m
Drilling Rig: eRTMAC Semi-Submersible Rig-07	Status: Plugged & Abandoned (P&A;) / Offset Reference

2. Stratigraphic Progression & Formation Tops

Formation / Stratum Name	Top Depth MD (m)	Lithology Characterization	Drillability / Risk Profile
Kyrre Fm.	2536.3 m	Interbedded Sand / Shale	Loss / Depletion
Tryggvason Fm.	2593.7 m	Interbedded Sand / Shale	Loss / Depletion
Blodoeks Fm.	2651.1 m	Interbedded Sand / Shale	Loss / Depletion
Svarte Fm.	2708.5 m	Interbedded Sand / Shale	Loss / Depletion
Roedby Fm.	2765.9 m	Interbedded Sand / Shale	Loss / Depletion
Draupne Fm.	2823.3 m	Interbedded Sand / Shale	Loss / Depletion
Heather Fm.	2880.7 m	Interbedded Sand / Shale	Loss / Depletion
Intra Heather Fm. Sst.	2938.0 m	Interbedded Sand / Shale	Loss / Depletion
Tarbert Fm.	2995.4 m	Interbedded Sand / Shale	Loss / Depletion
Ness Fm.	3052.8 m	Interbedded Sand / Shale	Loss / Depletion
Etive Fm.	3110.2 m	Interbedded Sand / Shale	Loss / Depletion
Rannoch Fm.	3167.6 m	Interbedded Sand / Shale	Loss / Depletion

3. Casing Design & Mud Program Summary

36 in Hole	30 in Conductor	350 m	Spud Mud / Seawater	1.05 SG	FIT 1.25 SG
26 in Hole	20 in Surface	1,050 m	KCl / Polymer	1.12 SG	LOT 1.45 SG
17-1/2 in Hole	13-3/8 in Interm.	2,200 m	Low Solids Non-Dispersed	1.24 SG	LOT 1.62 SG
12-1/4 in Hole	9-5/8 in Prod.	2925 m	Oil Based / Synthetic Mud	1.32 SG	LOT 1.78 SG
8-1/2 in Hole	7 in Liner	3225 m	Synthetic Oil Based (SOBM)	1.38 SG	LOT 1.88 SG

4. Historical Operational Incidents, NPT & Mitigations (Well: 35/9-8)

This section constitutes the institutional memory log extracted by the NWIS knowledge engine. All alerts generated during active drilling cite these exact records.

INCIDENT #1: Lost Circulation / Induced Fracture			Severity: HIGH	NPT Hours: 25.0 hrs
Depth Interval: 2980.0 m - 3030.0 m		Formation: BRENT GP		Status: Resolved on Site
Event Occurrence Narrative: Encountered total mud loss (380 bbls) at 3010m when surge pressure during BHA trip fractured depleted Brent Tarbert sand.				
Mitigation Action Applied: Spotted 60 bbls high-squeeze thixotropic LCM pill. Maintained annular fluid level with seawater down annulus. Reduced trip-in speed to 8 m/min.				
Offset Drilling Recommendation & Institutional Lesson: Depleted Brent sandstones possess narrow drilling margins (< 0.08 SG window). Install continuous auto-trip tank monitoring.				

INCIDENT #2: Stuck Pipe / Differential			Severity: HIGH	NPT Hours: 21.0 hrs
Depth Interval: 3080.0 m - 3110.0 m		Formation: BRENT GP		Status: Resolved on Site
Event Occurrence Narrative: BHA stuck differentially across Ness sandstone at 3094m while taking MWD formation pressure test. 110 klbs overpull ineffective.				
Mitigation Action Applied: Soaked string in 50 bbls glycol-ester lubricant pill for 4 hours. Worked pipe with 130 klbs jar hits. Pipe freed without backing off.				
Offset Drilling Recommendation & Institutional Lesson: Minimize formation tester tool stationary time to under 12 minutes in Brent sands. Treat mud with 3% lubricity additive.				