

5.2.10. Scatter Plot for Age vs. Fare

00:41 AA ☾ ↻ -

Submit Debugger

Write a Python code to plot a scatter plot showing the relationship between the 'Age' and 'Fare' columns in the Titanic dataset. The scatter plot should display the following specifications:

1. Use the **Age** column for the x-axis and the **Fare** column for the y-axis.
2. Set the title of the plot to "**Age vs. Fare**".
3. Label the x-axis as '**Age**' and the y-axis as '**Fare**'.

The Titanic dataset contains columns as shown below,

Passe ngerId	Surviv ed	Pclass	Name	Sex	Age	SibSp	Parch	Ticket	Fare	Cabin	Embar ked

Sample Data:

```
PassengerId,Survived,Pclass,Name,Sex,Age,SibSp,Parch,Ticket,Fare,Cabin,Embarked
1,0,3,"Braund, Mr. Owen Harris",male,22,1,0,A/5 21171,7.25,,S
2,1,1,"Cumings, Mrs. John Bradley (Florence Briggs Thayer)",female,38,1,0,PC 17599,71.2833,C85,C
3,1,3,"Heikkinen, Miss. Laina",female,26,0,0,STON/O2. 3101282,7.925,,S
4,1,1,"Futrelle, Mrs. Jacques Heath (Lily May Peel)",female,35,1,0,113803,53.1,C123,S
5,0,3,"Allen, Mr. William Henry",male,35,0,0,373450,8.05,,S
6,0,3,"Moran, Mr. James",male,,0,0,330877,8.4583,,Q
7,0,1,"McCarthy, Mr. Timothy J",male,54,0,0,17463,51.8625,E46,S
8,0,3,"Palsson, Master. Gosta Leonard",male,2,3,1,349909,21.075,,S
9,1,3,"Johnson, Mrs. Oscar W (Elisabeth Vilhelmina Berg)",female,27,0,2,347742,11.1333,,S
10,1,2,"Nasser, Mrs. Nicholas (Adele Achem)",female,14,1,0,237736,30.0708,,C
```

Note: Refer to the visible test case for better reference.

Sample Test Cases

AgeFareS...

```
import pandas as pd
import matplotlib.pyplot as plt

# Load the Titanic dataset
data = pd.read_csv('Titanic-Dataset.csv')

# Data Cleaning
data['Age'].fillna(data['Age'].median(), inplace=True)
data['Embarked'].fillna(data['Embarked'].mode()[0], inplace=True)
data.drop('Cabin', axis=1, inplace=True)

# Convert categorical features to numeric
data['Sex'] = data['Sex'].map({'male': 0, 'female': 1})
data = pd.get_dummies(data, columns=['Embarked'], drop_first=True)

# Write your code here for Box Plot for Fare by Pclass
plt.figure(figsize=(6.4,4.8))
plt.scatter(data['Age'], data['Fare'])
plt.title('Age vs. Fare')
plt.xlabel('Age')
plt.ylabel('Fare')
plt.show()
```

Terminal Test cases

< Prev Reset Submit Next >

5.2.11. Scatter Plot for Age vs. Fare by Survived

04:14 AA ☾ ↻ -

Submit Debugger

Write a Python code to plot a scatter plot showing the relationship between the 'Age' and 'Fare' columns in the Titanic dataset, with points color-coded by survival status. The scatter plot should display the following specifications:

1. Use the **Age** column for the x-axis and the **Fare** column for the y-axis.
2. Color the points based on the **Survived** column: **Red** for passengers who did not survive (**Survived = 0**). **Blue** for passengers who survived (**Survived = 1**).
3. Set the title of the plot to "**Age vs. Fare by Survival**".
4. Label the x-axis as '**Age**' and the y-axis as '**Fare**'.

The Titanic dataset contains columns as shown below,

Passe ngerId	Surviv ed	Pclass	Name	Sex	Age	SibSp	Parch	Ticket	Fare	Cabin	Embar ked

Sample Data:

```
PassengerId,Survived,Pclass,Name,Sex,Age,SibSp,Parch,Ticket,Fare,Cabin,Embarked
1,0,3,"Braund, Mr. Owen Harris",male,22,1,0,A/5 21171,7.25,,S
2,1,1,"Cumings, Mrs. John Bradley (Florence Briggs Thayer)",female,38,1,0,PC 17599,71.2833,C85,C
3,1,3,"Heikkinen, Miss. Laina",female,26,0,0,STON/O2. 3101282,7.925,,S
4,1,1,"Futrelle, Mrs. Jacques Heath (Lily May Peel)",female,35,1,0,113803,53.1,C123,S
5,0,3,"Allen, Mr. William Henry",male,35,0,0,373450,8.05,,S
6,0,3,"Moran, Mr. James",male,,0,0,330877,8.4583,,Q
7,0,1,"McCarthy, Mr. Timothy J",male,54,0,0,17463,51.8625,E46,S
8,0,3,"Palsson, Master. Gosta Leonard",male,2,3,1,349909,21.075,,S
9,1,3,"Johnson, Mrs. Oscar W (Elisabeth Vilhelmina Berg)",female,27,0,2,347742,11.1333,,S
10,1,2,"Nasser, Mrs. Nicholas (Adele Achem)",female,14,1,0,237736,30.0708,,C
```

Note: Refer to the visible test case for better reference.

Sample Test Cases

AgeFareS...

```
# Convert categorical features to numeric
data['Sex'] = data['Sex'].map({'male': 0, 'female': 1})
data = pd.get_dummies(data, columns=['Embarked'], drop_first=True)

# Write your code here for Scatter Plot for Age vs. Fare by Survived

import pandas as pd
import matplotlib.pyplot as plt

# Load the Titanic dataset
data = pd.read_csv('Titanic-Dataset.csv')

# Data Cleaning
data['Age'].fillna(data['Age'].median(), inplace=True)
data['Embarked'].fillna(data['Embarked'].mode()[0], inplace=True)
data.drop('Cabin', axis=1, inplace=True)

# Convert categorical features to numeric
data['Sex'] = data['Sex'].map({0: 'red', 1: 'blue'})
data = pd.get_dummies(data, columns=['Embarked'], drop_first=True)

# Write your code here for Scatter Plot for Age vs. Fare by Survived

plt.figure()
colors = {0: 'red', 1: 'blue'}
plt.scatter(data['Age'], data['Fare'], c=data['Survived'].apply(lambda x: colors[x]))
plt.title('Age vs. Fare by Survival')
plt.xlabel('Age')
plt.ylabel('Fare')
plt.show()
```

Terminal Test cases

< Prev Reset Submit

adityabaste/EDS-Practical X Dashboard Course

mitaoe.codetantra.com/secure/course.jsp?euclid=6773e3f2f1f9c5320ca6bc85#/contents/6773e455f1f9c5320ca6bd19/6773e4d5f1f9c5320ca6bdc2/667a7e0428220463f6497a3c

202401090090@mitaoe.ac.in Support Logout

CODETANTRA

Home

4.1.1. Pandas - series creation and manipulation

12:07 AA ☾ ⚡ -

Write a Python program that takes a list of numbers from the user, creates a Pandas series from it, and then calculates the mean of even and odd numbers separately using the **groupby** and **mean()** operations.

Input Format:

- The user should enter a list of numbers separated by space when prompted.

Output Format:

- The program should display the mean of even and odd numbers separately.
- Each mean value should be displayed with a label indicating whether it corresponds to even or odd numbers.

Explorer seriesMa...

```
import pandas as pd

# Take inputs from the user to create a list of numbers
numbers = list(map(int, input().split()))

# Create a Pandas series from the list of numbers
series = pd.Series(numbers)

# Grouping by even and odd numbers and calculating the mean
grouped = series.groupby(series%2==0).mean()

# Display the mean of even and odd numbers with labels
grouped.index = ['Even' if is_even else 'Odd' for is_even in grouped.index]
print("Mean of even and odd numbers:")
print(grouped)
```

Sample Test Cases

Terminal Test cases

< Prev Reset Submit Next >

adityabaste/EDS-Practical X Dashboard Course

mitaoe.codetantra.com/secure/course.jsp?euclid=6773e3f2f1f9c5320ca6bc85#/contents/6773e455f1f9c5320ca6bd19/6773e4d5f1f9c5320ca6bdc2/667aa30728220463f649bb62

202401090090@mitaoe.ac.in Support Logout

CODETANTRA Home

4.1.2. Dictionary to dataframe

A dictionary of lists has been provided to you in the editor. Create a DataFrame from the dictionary of lists and perform the listed operations, then display the DataFrame before and after each manipulation.

Create the DataFrame:

- Convert the dictionary to a Pandas DataFrame.

Add a new row:

- Take inputs from the user for the new row data (name, age).
- Add the new row to the DataFrame.
- Display the DataFrame after adding the new row.

Modify a row:

- Modify a specific row by changing the age. Take the row index and new age value from the user.
- Display the DataFrame after modifying the row.

Delete a row:

- Take the row index to be deleted from the user.
- Remove the specified row.
- Display the DataFrame after deleting the row.

Add a new column:

- Add a column **Gender** with values taken from the user.
- Display the DataFrame after adding the new column.

Modify a column:

- Convert names to uppercase.
- Display the DataFrame after modifying the column.

Delete a column:

- Remove the **Age** column.

Sample Test Cases

50:56 A C E -

Explorer datafram...

```
import pandas as pd

# Provided dictionary of lists
data = {
    'Name': ['Alice', 'Bob', 'Charlie'],
    'Age': [25, 30, 35],
}

# Convert the dictionary to a DataFrame
df = pd.DataFrame(data)

# Display the original DataFrame
print("Original DataFrame:")
print(df)

# Adding a new row
new_name=input("New name: ")
new_age=int(input("New age: "))
new_row={'Name': new_name, 'Age':new_age}
df=pd.concat([df,pd.DataFrame([new_row])],ignore_index=True)

# Display the DataFrame after adding a new row
print("After adding a row:\n",df)

# Modifying a row
modify_index=int(input("Index of row to modify: "))
new_age_mod=int(input("New age: "))
df.loc[modify_index,"Age"]=new_age_mod

# Display the DataFrame after modifying a row
print("After modifying a row:")
print(df)

# Deleting a row
delete_index=int(input("Index of row to delete: "))
df=df.drop(delete_index).reset_index(drop=True)
```

Terminal Test cases

< Prev Reset Submit Next >

adityabaste/EDS-Practical X Dashboard Course

mitaoe.codetantra.com/secure/course.jsp?euclid=6773e3f2f1f9c5320ca6bc85#/contents/6773e455f1f9c5320ca6bd19/6773e4d5f1f9c5320ca6bdc2/667cf60f2365ba61af5a2ce7

202401090090@mitaoe.ac.in Support Logout

CODETANTRA Home

4.1.3. Student Information

37:21 AA ☾ ⏷ -

Write a program to read a text file containing student information (name, age, and grade) using Pandas. Perform the following tasks:

- Display the first five rows of the data frame.
- Calculate the average age of the students(limit the average age up to 2 decimal places).
- Filter out the students who have a grade above a certain threshold(consider the threshold grade is 'B').

Note:
Refer to the displayed test cases for better understanding.

Sample Test Cases

studentin... studentdat...

import pandas as pd
Read the text file into a DataFrame
file = input()
data = pd.read_csv(file, sep="\s+", header=None, names=["Name", "Age", "Grade"])
write your code here..

print("First five rows:")
print(data.head(5))
age = round(data['Age'].mean(), 2)
print("Average age:", age)
print("Students with a grade up to B")
df = pd.DataFrame(data)
a = df[df['Grade'] <= 'B']
print(a)

Terminal Test cases

< Prev Reset Submit Next >

adityabaste/EDS-Practical Dashboard Course mitaoe.codetantra.com/secure/course.jsp?euclid=6773e3f2f1f9c5320ca6bc85#/contents/6773e455f1f9c5320ca6bd19/6773e4e4f1f9c5320ca6bdce/67860994a50fe56b8dcf8747 Incognito Logout

202401090090@mitaoe.ac.in Support Logout

4.2.1. Month with the Highest Total Sales

01:36 A ☾ ⏺ ⏹ -

Write a Python program that takes the file name of a CSV file as input, reads the data, and performs the following operations:

- The CSV file contains the columns: Date, Product, Quantity, Price, and City.
- Group the data by Month and calculate the total sales for each month.
- Find the month with the highest total sales and display it.
- Also, display the total sales for the best month.

Sample Data:

```
Date,Product,Quantity,Price,City
2025-01-01,Product A,5,20,New York
2025-01-01,Product B,3,15,Los Angeles
2025-01-02,Product A,7,20,New York
2025-01-02,Product C,4,30,Chicago
2025-01-03,Product B,2,15,Chicago
2025-01-03,Product A,8,20,Los Angeles
2025-01-04,Product C,6,30,New York
2025-01-04,Product B,5,15,Los Angeles
2025-01-05,Product A,3,20,Chicago
2025-01-05,Product C,10,30,Los Angeles
```

Note:
The data cannot be displayed in the file. You can refer to the sample data provided for insights.

Sample Test Cases +

Explorer monthFor... sales_dat...

```
import pandas as pd

# Prompt the user for the file name
file_name = input()

# Load the data
df = pd.read_csv(file_name)
df['Date'] = pd.to_datetime(df['Date'])
#Extract the month from the Date column
df['Month'] = df['Date'].dt.to_period('M')
#Calculate the total sales for each row
df['Total_Sales'] = df['Quantity'] * df['Price']
#Group the data by Month and calculate the total sales for each month
monthly_sales = df.groupby('Month')['Total_Sales'].sum()
#Find the month with the highest total sales
best_month = monthly_sales.idxmax()
highest_sales = monthly_sales.max()

print(f"Best month: {best_month}")
print(f"Total sales: ${highest_sales:.2f}")
```

Terminal Test cases

< Prev Reset Submit Next >

adityabaste/EDS-Practical

Dashboard

Course

mitaoe.codetantra.com/secure/course.jsp?euclid=6773e3f2f1f9c5320ca6bc85#/contents/6773e455f1f9c5320ca6bd19/6773e4e4f1f9c5320ca6bdce/67861370a50fe56b8dcf9828

202401090090@mitaoe.ac.in

Support Logout

CODETANTRA Home

4.2.2. Best Selling Product

03:01

Submit

Debugger

Write a Python program that takes the file name of a CSV file as input, reads the data, and performs the following operations:

- The CSV file contains the columns: Date, Product, Quantity, Price, and City.
- Find the product that sold the most in terms of quantity sold.
- Display the product that sold the most and the total quantity sold for that product.

Sample Data:

```
Date,Product,Quantity,Price,City
2025-01-01,Product A,5,20,New York
2025-01-01,Product B,3,15,Los Angeles
2025-01-02,Product A,7,20,New York
2025-01-02,Product C,4,30,Chicago
2025-01-03,Product B,2,15,Chicago
2025-01-03,Product A,8,20,Los Angeles
2025-01-04,Product C,6,30,New York
2025-01-04,Product B,5,15,Los Angeles
2025-01-05,Product A,3,20,Chicago
2025-01-05,Product C,10,30,Los Angeles
```

Note:
The data cannot be displayed in the file. You can refer to the sample data provided for insights.

Sample Test Cases

Imported modules: pandas

File name: sales_data.csv

```
import pandas as pd

# Prompt the user for the file name
file_name = input()

# Load the data
df = pd.read_csv(file_name)

product_sales = df.groupby("Product")["Quantity"].sum()
best_product = product_sales.idxmax()
highest_quantity = product_sales.max()

# Display the result
print(f"Best selling product: {best_product}")
print(f"Total quantity sold: {highest_quantity}")
```

Terminal Test cases

< Prev Reset Submit Next >

adityabaste/EDS-Practical X Dashboard Course

mitaoe.codetantra.com/secure/course.jsp?euclid=6773e3f2f1f9c5320ca6bc85#/contents/6773e455f1f9c5320ca6bd19/6773e4e4f1f9c5320ca6bdce/67861553a50fe56b8dcf9a6e

202401090090@mitaoe.ac.in Support Logout

4.2.3. City that Sold the Most Products

01:50 AA ☾ ⏷ -

Write a Python program that takes the file name of a CSV file as input, reads the data, and performs the following operations:

- The CSV file contains the columns: Date, Product, Quantity, Price, and City.
- Group the data by City and calculate the total quantity of products sold for each city.
- Find the city that sold the most products (based on the total quantity sold).

Sample Data:

```
Date,Product,Quantity,Price,City
2025-01-01,Product A,5,20,New York
2025-01-01,Product B,3,15,Los Angeles
2025-01-02,Product A,7,20,New York
2025-01-02,Product C,4,30,Chicago
2025-01-03,Product B,2,15,Chicago
2025-01-03,Product A,8,20,Los Angeles
2025-01-04,Product C,6,30,New York
2025-01-04,Product B,5,15,Los Angeles
2025-01-05,Product A,3,20,Chicago
2025-01-05,Product C,10,30,Los Angeles
```

Note:
The data cannot be displayed in the file. You can refer to the sample data provided for insights.

Sample Test Cases

Explorer monthFor... sales_dat...

```
1 import pandas as pd
2
3 # Prompt the user for the file name
4 file_name = input()
5
6 # Load the data
7 df = pd.read_csv(file_name)
8
9 # write the code..
10 city_sales = df.groupby("City")["Quantity"].sum()
11 best_city = city_sales.idxmax()
12 # Display the result
13 print(f"City sold the most products: {best_city}")
14
```

Terminal Test cases

< Prev Reset Submit Next >

adityabaste/EDS-Practical Dashboard Course mitaoe.codetantra.com/secure/course.jsp?euclid=6773e3f2f1f9c5320ca6bc85#/contents/6773e455f1f9c5320ca6bd19/6773e4e4f1f9c5320ca6bdce/6788eea89ff79b6ea9e3ece1 Incognito Logout

202401090090@mitaoe.ac.in Support Logout

4.2.4. Most Frequently Sold Product Pairs

09:04 A ☾ ⏺ ⏹ -

Write a Python program that takes the file name of a CSV file as input, reads the data, and performs the following operations:

- The CSV file contains the following columns: Date, Product, Quantity, Price, and City.
- For each date, find all pairs of products that were sold together (i.e., two products sold on the same date).
- Output the product pair/s that was sold most frequently.

Sample Data:

```
Date,Product,Quantity,Price,City
2025-01-01,Product A,5,20>New York
2025-01-01,Product B,3,15>Los Angeles
2025-01-02,Product A,7,20>New York
2025-01-02,Product C,4,30>Chicago
2025-01-03,Product B,2,15>Chicago
2025-01-03,Product A,8,20>Los Angeles
2025-01-04,Product C,6,30>New York
2025-01-04,Product B,5,15>Los Angeles
2025-01-05,Product A,3,20>Chicago
2025-01-05,Product C,10,30>Los Angeles
```

Explanation:

Transactions:

- 2025-01-01: Product A, Product B
- 2025-01-02: Product A, Product C
- 2025-01-03: Product B, Product A
- 2025-01-04: Product C, Product B
- 2025-01-05: Product A, Product C

Now, let's count how often the pairs of products appear together:

- Product A and Product B:** Appear in transactions on 2025-01-01 and 2025-01-03.
- Product A and Product C:** Appear in transactions on 2025-01-02 and 2025-01-05.
- Product B and Product C:** Appears in transactions on 2025-01-04.

Most Frequent Product Combinations:

- Product A and Product B** (2 times)
- Product A and Product C** (2 times)

Code:

```
frequent... sales_dat...
1 import pandas as pd
2 from itertools import combinations
3 from collections import Counter
4
5 # Prompt user to input the file name
6 file_name = input()
7
8 # Read data from the specified CSV file
9 df = pd.read_csv(file_name)
10
11 date_products = {}
12 # Group products by date
13 for date, group in df.groupby('Date'):
14     products = group['Product'].unique()
15     if len(products) > 1:
16         date_products[date] = products
17
18 # Count product pairs
19 pair_counter = Counter()
20 for products in date_products.values():
21     pairs = combinations(sorted(products), 2)
22     pair_counter.update(pairs)
23
24 # Find the maximum-frequency
25 if pair_counter:
26     max_count = max(pair_counter.values())
27
28     # Output the most frequent product pairs
29     for pair, count in pair_counter.items():
30         if count == max_count:
31             print(f"{pair[0]} and {pair[1]}: {count} times")
32
33 # Output the most frequent product pairs
```

Explorer Terminal Test cases

< Prev Reset Submit Next >

4.2.5. Titanic Dataset Analysis and Data Cleaning

08:01 AA ☾ ⏺ ⏹ -

Submit Debugger

You are provided with the Titanic dataset containing information about passengers on the Titanic. Your task is to write Python code to answer the following questions based on the dataset. For each question, perform necessary data cleaning, transformations, and calculations as required.

1. Display the first 5 rows of the dataset.
2. Display the last 5 rows of the dataset.
3. Get the shape of the dataset (number of rows and columns).
4. Get a summary of the dataset (using .info()).
5. Get basic statistics (mean, standard deviation, etc.) of the dataset using .describe().
6. Check for missing values and display the count of missing values for each column.
7. Fill missing values in the 'Age' column with the median age.
8. Fill missing values in the 'Embarked' column with the most frequent value (mode).
9. Drop the 'Cabin' column due to many missing values.
10. Create a new column, 'FamilySize' by adding the 'SibSp' and 'Parch' columns.

The Titanic dataset contains columns as shown below,

Passe ngerId	Surviv ed	Pclass	Name	Sex	Age	SibSp	Parch	Ticket	Fare	Cabin	Embar ked

Sample Data:

```
PassengerId,Survived,Pclass,Name,Sex,Age,SibSp,Parch,Ticket,Fare,Cabin,Embarked
1,0,3,"Braund, Mr. Owen Harris",male,22,1,0,A/5 21171,7.25,,S
2,1,1,"Cumings, Mrs. John Bradley (Florence Briggs Thayer)",female,38,1,0,PC 17599,71.2833,C85,C
3,1,3,"Heikkinen, Miss. Laina",female,26,0,0,STON/O2. 3101282,7.925,,S
4,1,1,"Futrelle, Mrs. Jacques Heath (Lily May Peel)",female,35,1,0,113803,53.1,C123,S
5,0,3,"Allen, Mr. William Henry",male,35,0,0,373450,8.05,,S
6,0,3,"Moran, Mr. James",male,,0,0,330877,8.4583,,0
```

Sample Test Cases

titanicDat...

```
1 import pandas as pd
2 import numpy as np
3
4 # Load the Titanic dataset
5 data = pd.read_csv('Titanic-Dataset.csv')
6
7 print(data.head())
8 print(data.tail())
9 print(data.shape)
10 print(data.info())
11 print(data.describe())
12 print(data.isnull().sum())
13 median_age = data['Age'].median()
14 data['Age'].fillna(median_age, inplace=True)
15 mode_embarked = data['Embarked'].mode()[0]
16 data['Embarked'].fillna(mode_embarked, inplace=True)
17 data.drop('Cabin', axis=1, inplace=True)
18 data['FamilySize'] = data['SibSp'] + data['Parch']
```

Terminal Test cases

< Prev Reset Submit Next >

adityabaste/EDS-Practical

Dashboard

Course

mitaoe.codetantra.com/secure/course.jsp?euclid=6773e3f2f1f9c5320ca6bc85#/contents/6773e455f1f9c5320ca6bd19/6773e4e4f1f9c5320ca6bdce/67e378a17028471d94dad0a6

Incognito

Logout

CODETANTRA

Home

202401090090@mitaoe.ac.in

Support

Logout

4.2.6. Titanic Dataset Analysis and Data Cleaning - 2

33:08

A ⚡

Submit

Debugger

You are provided with the Titanic dataset containing information about passengers on the Titanic. Your task is to write Python code to answer the following questions based on the dataset.

1. Create a new column 'IsAlone' which is 1 if the passenger is alone (FamilySize = 0), otherwise 0.
2. Convert the 'Sex' column to numeric values (male: 0, female: 1).
3. One-hot encode the 'Embarked' column, dropping the first category.
4. Get the mean age of passengers.
5. Get the median fare of passengers.
6. Get the number of passengers by class.
7. Get the number of passengers by gender.
8. Get the number of passengers by survival status.
9. Calculate the survival rate of passengers.
10. Calculate the survival rate by gender.

The Titanic dataset contains columns as shown below,

Passe ngerId	Surviv ed	Pclass	Name	Sex	Age	SibSp	Parch	Ticket	Fare	Cabin	Embar ked

Sample Data:

```

PassengerId,Survived,Pclass,Name,Sex,Age,SibSp,Parch,Ticket,Fare,Cabin,Embarked
1,0,3,"Braund, Mr. Owen Harris",male,22,1,0,A/5 21171,7.25,,S
2,1,1,"Cumings, Mrs. John Bradley (Florence Briggs Thayer)",female,38,1,0,PC 17599,71.2833,C85,C
3,1,3,"Heikkinen, Miss. Laina",female,26,0,0,STON/O2. 3101282,7.925,,S
4,1,1,"Futrelle, Mrs. Jacques Heath (Lily May Peel)",female,35,1,0,113803,53.1,C123,S
5,0,3,"Allen, Mr. William Henry",male,35,0,0,373450,8.05,,S
6,0,3,"Moran, Mr. James",male,,0,0,330877,8.4583,,Q
7,0,1,"McCarthy, Mr. Timothy J",male,54,0,0,17463,51.8625,E46,S
8,0,3,"Palsson, Master. Gosta Leonard",male,2,3,1,349909,21.075,,S

```

Sample Test Cases

+

titanicDat...

```

import pandas as pd
import numpy as np

# Load the Titanic dataset
data = pd.read_csv('Titanic-Dataset.csv')
data['FamilySize'] = data['SibSp'] + data['Parch']

data['IsAlone'] = np.where(data['FamilySize'] == 0, 1, 0)
# 2-2. Convert-Sex-to-numeric (male: 0, forale: 1)
data['Sex'] = data['Sex'].map({'male': 0, 'female': 1})
# 3-3. One-hot-encode the Embarked column, dropping the first-category
data = pd.get_dummies(data, columns=['Embarked'], drop_first=True)
# 4-4. Get the mean-age-of-passengers
mean_age = data['Age'].mean()
print(mean_age)
# 5-5. Get the median-fare of passengers
median_fare = data['Fare'].median()
print(median_fare)
# 6-6. Get the number-of-passengers-by-class
passengers_by_class = data['Pclass'].value_counts()
print(passengers_by_class)
# 7-7. Get the number-of-passengers-by-gender
passengers_by_gender = data['Sex'].value_counts().sort_index()
print(passengers_by_gender)
# 8-8. Get the number-of-passengers-by-survival-status
passengers_by_survival = data['Survived'].value_counts().sort_index()
print(passengers_by_survival)
survival_rate = data['Survived'].mean()
print(survival_rate)
# 10-10. Calculate the survival-rate-by-gender
survival_rate_by_gender = data.groupby('Sex')[['Survived']].mean()
print(survival_rate_by_gender)

```

Terminal

Test cases

< Prev

Reset

Submit

Next >

4.2.7. Titanic Dataset Analysis and Data Cleaning - 3

You are provided with the Titanic dataset containing information about passengers on the Titanic. Your task is to write Python code to answer the following questions based on the dataset.

1. Calculate the survival rate by class.
2. Calculate the survival rate by embarkation location (Embarked_S).
3. Calculate the survival rate by family size (FamilySize).
4. Calculate the survival rate by being alone (IsAlone).
5. Get the average fare by passenger class (Pclass).
6. Get the average age by passenger class (Pclass).
7. Get the average age by survival status (Survived).
8. Get the average fare by survival status (Survived).
9. Get the number of survivors by class (Pclass).
10. Get the number of non-survivors by class (Pclass).

The Titanic dataset contains columns as shown below,

PasseengerId	Survived	Pclass	Name	Sex	Age	SibSp	Parch	Ticket	Fare	Cabin	Embar ked

Sample Data:

```
PassengerId,Survived,Pclass,Name,Sex,Age,SibSp,Parch,Ticket,Fare,Cabin,Embarked
1,0,3,"Braund, Mr. Owen Harris",male,22,1,0,A/5 21171,7.25,,S
2,1,1,"Cumings, Mrs. John Bradley (Florence Briggs Thayer)",female,38,1,0,PC 17599,71.2833,C85,C
3,1,3,"Heikkinen, Miss. Laina",female,26,0,0,STON/O2. 3101282,7.925,,S
4,1,1,"Futrelle, Mrs. Jacques Heath (Lily May Peel)",female,35,1,0,113803,53.1,C123,S
5,0,3,"Allen, Mr. William Henry",male,35,0,0,373450,8.05,,S
6,0,3,"Moran, Mr. James",male,,0,0,330877,8.4583,,Q
7,0,1,"McCarthy, Mr. Timothy J",male,54,0,0,17463,51.8625,E46,S
```

Sample Test Cases

titanicData...

```

1 import pandas as pd
2 import numpy as np
3
4 # Load the Titanic dataset
5 data = pd.read_csv('Titanic-Dataset.csv')
6 data['FamilySize'] = data['SibSp'] + data['Parch']
7 data['IsAlone'] = np.where(data['FamilySize'] > 0, 0, 1)
8 data = pd.get_dummies(data, columns=['Embarked'], drop_first=True)
9
10 # 1. Calculate the survival rate by class
11 print(data.groupby('Pclass')['Survived'].mean())
12 # 2. Calculate the survival rate by embarked location (Embarked_S)
13 print(data.groupby('Embarked_S')['Survived'].mean())
14 # 3. Calculate the survival rate by family size
15 print(data.groupby('FamilySize')['Survived'].mean())
16 # 4. Calculate the survival rate by being alone
17 print(data.groupby('IsAlone')['Survived'].mean())
18 # 5. Get the average fare by class
19 print(data.groupby('Pclass')['Fare'].mean())
20 # 6. Get the average age by class
21 print(data.groupby('Pclass')['Age'].mean())
22 # 7. Get the average age by survival status
23 print(data.groupby('Survived')['Age'].mean())
24 # 8. Get the average fare by survival status
25 print(data.groupby('Survived')['Fare'].mean())
26 # 9. Get the number of survivors by class (sort by values descending)
27 print(data[data['Survived']==1]['Pclass'].value_counts())
28 # 10. Get the number of non-survivors by class (sort by values descending)
29 print(data[data['Survived']==0]['Pclass'].value_counts())

```

Terminal Test cases

4.2.8. Titanic Dataset Analysis and Data Cleaning - 4

00:28 AA ☾ ⌂ ⌂ -

Submit

You are provided with the Titanic dataset containing information about passengers on the Titanic. Your task is to write Python code to answer the following questions based on the dataset.

1. Get the number of survivors by gender (Sex).
2. Get the number of non-survivors by gender (Sex).
3. Get the number of survivors by embarkation location (Embarked_S).
4. Get the number of non-survivors by embarkation location (Embarked_S).
5. Calculate the percentage of children (Age < 18) who survived.
6. Calculate the percentage of adults (Age >= 18) who survived.
7. Get the median age of survivors.
8. Get the median age of non-survivors.
9. Get the median fare of survivors.
10. Get the median fare of non-survivors.

The Titanic dataset contains columns as shown below,

Passe ngerId	Surviv ed	Pclass	Name	Sex	Age	SibSp	Parch	Ticket	Fare	Cabin	Embar ked

Sample Data:

```
PassengerId,Survived,Pclass,Name,Sex,Age,SibSp,Parch,Ticket,Fare,Cabin,Embarked
1,0,3,"Braund, Mr. Owen Harris",male,22,1,0,A/5 21171,7.25,,S
2,1,1,"Cumings, Mrs. John Bradley (Florence Briggs Thayer)",female,38,1,0,PC 17599,71.2833,C85,C
3,1,3,"Heikkinen, Miss. Laina",female,26,0,0,STON/O2. 3101282,7.925,,S
4,1,1,"Futrelle, Mrs. Jacques Heath (Lily May Peel)",female,35,1,0,113803,53.1,C123,S
5,0,3,"Allen, Mr. William Henry",male,35,0,0,373450,8.05,,S
6,0,3,"Moran, Mr. James",male,,0,0,330877,8.4583,,Q
7,0,1,"McCarthy, Mr. Timothy J",male,54,0,0,17463,51.8625,E46,S
```

Sample Test Cases

Explorer

titanicDat...

```
1 import pandas as pd
2 import numpy as np
3
4 # Load the Titanic dataset
5 data = pd.read_csv('Titanic-Dataset.csv')
6 data = pd.get_dummies(data, columns=['Embarked'], drop_first=True)
7
8
9 survivors_by_gender = data[data['Survived'] == 1]['Sex'].value_counts()
10 print(survivors_by_gender)
11
12 non_survivors_by_gender = data[data['Survived'] == 0]['Sex'].value_counts()
13 print(non_survivors_by_gender)
14
15 #3. Get the number of survivors by embarked location (Embarked_S)
16
17 survivors_by_embarked_s = data[data['Survived'] == 1]['Embarked_S'].value_counts()
18
19 print(survivors_by_embarked_s)
20
21 #4. Get the number of non-survivors by embarked location (Embarked_S)
22
23 non_survivors_by_embarked_s = data[data['Survived'] == 0]['Embarked_S'].value_counts()
24
25 print(non_survivors_by_embarked_s)
26
27 #5. Percentage of children (Age < 18) who survived
28
29 children = data[data['Age'] < 18]
30
31 children_survival_rate = children['Survived'].mean()
32
33 print(children_survival_rate)
34
35 #6. Percentage of adults (Age >= 18) who survived
```

Terminal Test cases

5.1.1. Stacked Plot

04:44 AA ☾ ⌂ ⌂ -

Submit Debugger

Create a stacked area plot to visualize the temperature variations for three different cities (City A, City B, and City C) across the months of the year. The temperature data is provided for each city in the editor.

Your task is to:

- Create a stacked area plot using the data.
- Label the x-axis as "Month", the y-axis as "Temperature", and provide the title "Temperature Variation" for the plot.
- Display the plot showing the temperature variation for each city throughout the months of the year.

Explorer stackedpl...

```
1 import matplotlib.pyplot as plt
2 import pandas as pd
3
4 # Data for Months and Temperature for three cities
5 data = {
6     'Month': ['January', 'February', 'March', 'April', 'May', 'June', 'July', 'August',
7               'September', 'October', 'November', 'December'],
8     'City_A_Temperature': [5, 7, 10, 13, 17, 20, 22, 21, 18, 12, 8, 6],
9     'City_B_Temperature': [2, 3, 5, 6, 10, 14, 16, 17, 12, 9, 5, 3],
10    'City_C_Temperature': [3, 4, 6, 8, 9, 12, 15, 14, 10, 7, 4, 2]
11 }
12 df = pd.DataFrame(data)
13 plt.stackplot(df['Month'], df['City_A_Temperature'],
14                df['City_B_Temperature'], df['City_C_Temperature'])
15 plt.title('Temperature Variation')
16 plt.xlabel('Month')
17 plt.ylabel('Temperature')
18 plt.show()
# Write your code...
```

Sample Test Cases

+ Terminal Test cases

< Prev Reset Submit Next >

adityabaste/EDS-Practical Dashboard Course mitaoe.codetantra.com/secure/course.jsp?euclid=6773e3f2f1f9c5320ca6bc85#/contents/6773e45af1f9c5320ca6bd1d/6773e4f1f1f9c5320ca6bdd5/677cbdd52372a2277b32ab1c Incognito

202401090090@mitaoe.ac.in Support Logout

CODETANTRA Home

5.2.1. Titanic Dataset

05:23 A ☾ ⏺ ⏹ -

Write a Python program to analyze and visualize data from the Titanic dataset based on the following instructions:

Dataset Information:

The dataset is stored in a CSV file named `titanic.csv` and has been loaded using the `pandas` library. It contains the following columns:

- Pclass: Passenger class (1 = First, 2 = Second, 3 = Third).
- Gender: Gender of the passenger (male/female).
- Age: Age of the passenger.
- Survived: Survival status (0 = Did not survive, 1 = Survived).
- Fare: Ticket fare paid by the passenger.

Visualization:

To represent these trends, you will create 5 visualizations using Matplotlib. The visualizations should be arranged in a 3x2 grid (3 rows and 2 columns).

Visualization Details:

Write the code to create a series of visualizations as follows:

Bar Plot (Pclass Distribution):

- Create a bar plot to show the distribution of passengers across the different passenger classes (Pclass).
- Use the color `skyblue` for the bars.
- Title the plot as "**Passenger Class Distribution**".
- Label the x-axis as "**Pclass**" and the y-axis as "**Count**".

Pie Chart (Gender Distribution):

- Create a pie chart to display the distribution of male and female passengers.
- Use `lightblue` for males and `lightcoral` for females.
- Include percentages on the slices (use `autopct='%.1f%%'`).
- Title the plot as "**Gender Distribution**".

Scatter Plot (Fare vs Age):

- Create a scatter plot showing the relationship between age and fare.
- Use `orange` for the scatter points.
- Title the plot as "**Fare vs Age**".
- Label the x-axis as "**Age**" and the y-axis as "**Fare**".

Sample Test Cases

+

Explorer titanicDat...

```
1 import pandas as pd
2 import matplotlib.pyplot as plt
3
4 # Load the Titanic dataset from the CSV file
5 df = pd.read_csv('titanic.csv')
6
7 # Set up the figure for 5 subplots
8 fig, axes = plt.subplots(3, 2, figsize=(12, 12))
9
10 # write the code..
11 pclass_counts=df['Pclass'].value_counts()
12 axes[0,0].bar(x=pclass_counts.index,height=pclass_counts.values,color='skyblue')
13 axes[0,0].set_title("Passenger Class Distribution")
14 axes[0,0].set_xlabel("Pclass")
15 axes[0,0].set_ylabel("Count")
16
17 axes[0,1].pie(df['Gender'].value_counts(),labels=df['Gender'].value_counts().index,autopct="%.1f%%",colors=['lightblue','lightcoral'])
18 axes[0,1].set_title('Gender Distribution')
19
20 axes[1,0].hist(df['Age'].dropna(),bins=8,color="lightgreen",edgecolor="black")
21 axes[1,0].set_title("Age Distribution")
22 axes[1,0].set_xlabel("Age")
23 axes[1,0].set_ylabel("Frequency")
24
25 axes[1,1].bar(df["Survived"].value_counts().index,df['Survived'].value_counts(),color=["lightblue","lightcoral"])
26 axes[1,1].set_title('Survival Count')
27 axes[1,1].set_xlabel("Survived(No=0,Yes=1)")
28 axes[1,1].set_ylabel("Count")
29
30 axes[2,0].scatter(df['Age'],df['Fare'],color='orange')
31 axes[2,0].set_title('Fare vs Age')
32 axes[2,0].set_xlabel("Age")
33 axes[2,0].set_ylabel("Fare")
```

Terminal Test cases

< Prev Reset Submit Next >

adityabaste/EDS-Practical Dashboard Course mitaoe.codetantra.com/secure/course.jsp?euclid=6773e3f2f1f9c5320ca6bc85#/contents/6773e45af1f9c5320ca6bd1d/6773e4f1f1f9c5320ca6bdd5/67e28a397c0b912d860e689c Incognito Logout

202401090090@mitaoe.ac.in Support Logout

CODETANTRA Home

5.2.2. Histogram of passenger information of Titanic

02:33 A ☾ ⏹ -

Write a Python code to plot a histogram for the distribution of the 'Age' column from the Titanic dataset. The histogram should display the frequency of different age ranges with the following specifications:

1. Use **30 bins** for the histogram.
2. Set the **edge color** of the bars to **black (k)**.
3. Label the x-axis as '**Age**' and the y-axis as '**Frequency**'.
4. Add the title "**Age Distribution**" to the histogram.

The Titanic dataset contains columns as shown below,

PasseengerId	Survived	Pclass	Name	Sex	Age	SibSp	Parch	Ticket	Fare	Cabin	Embarked

Sample Data:

```
PassengerId,Survived,Pclass,Name,Sex,Age,SibSp,Parch,Ticket,Fare,Cabin,Embarked
1,0,3,"Braund, Mr. Owen Harris",male,22,1,0,A/5 21171,7.25,,S
2,1,1,"Cumings, Mrs. John Bradley (Florence Briggs Thayer)",female,38,1,0,PC 17599,71.2833,C85,C
3,1,3,"Heikkinen, Miss. Laina",female,26,0,0,STON/O2. 3101282,7.925,,S
4,1,1,"Futrelle, Mrs. Jacques Heath (Lily May Peel)",female,35,1,0,113803,53.1,C123,S
5,0,3,"Allen, Mr. William Henry",male,35,0,0,373450,8.05,,S
6,0,3,"Moran, Mr. James",male,,0,0,330877,8.4583,,Q
7,0,1,"McCarthy, Mr. Timothy J",male,54,0,0,17463,51.8625,E46,S
8,0,3,"Palsson, Master. Gosta Leonard",male,2,3,1,349909,21.075,,S
9,1,3,"Johnson, Mrs. Oscar W (Elisabeth Vilhelmina Berg)",female,27,0,2,347742,11.1333,,S
10,1,2,"Nasser, Mrs. Nicholas (Adele Achem)",female,14,1,0,237736,30.0708,,C
```

Note: Refer to the visible test case for better reference.

Sample Test Cases +

Explorer Histogram

```
import pandas as pd
import matplotlib.pyplot as plt

# Load the Titanic dataset
data = pd.read_csv('Titanic-Dataset.csv')

# Data Cleaning
data['Age'].fillna(data['Age'].median(), inplace=True)
data['Embarked'].fillna(data['Embarked'].mode()[0], inplace=True)
data.drop('Cabin', axis=1, inplace=True)

# Convert categorical features to numeric
data['Sex'] = data['Sex'].map({'male': 0, 'female': 1})
data = pd.get_dummies(data, columns=['Embarked'], drop_first=True)

# Write your code here for Histogram
plt.hist(data['Age'], bins=30, edgecolor='k')
plt.xlabel('Age')
plt.ylabel('Frequency')
plt.title('Age Distribution')
plt.show()
```

Terminal Test cases

< Prev Reset Submit Next >

5.2.3. Bar plot of survival rate of passengers

01:08 AA ☾ ↻ -

Submit

Write a Python code to plot a bar chart that shows the count of passengers who survived and did not survive in the Titanic dataset.

The chart should display the following specifications:

1. Use the '**Survived**' column to show the count of survivors (0 = Did not survive, 1 = Survived).
2. Set the chart type to '**bar**'.
3. Add the title "**Survival Count**" to the chart.
4. Label the x-axis as '**Survived**' and the y-axis as '**Count**'.

The Titanic dataset contains columns as shown below,

Passe ngerId	Surviv ed	Pclass	Name	Sex	Age	SibSp	Parch	Ticket	Fare	Cabin	Embar ked

Sample Data:

```
PassengerId,Survived,Pclass,Name,Sex,Age,SibSp,Parch,Ticket,Fare,Cabin,Embarked
1,0,3,"Braund, Mr. Owen Harris",male,22,1,0,A/5 21171,7.25,,S
2,1,1,"Cumings, Mrs. John Bradley (Florence Briggs Thayer)",female,38,1,0,PC 17599,71.2833,C85,C
3,1,3,"Heikkinen, Miss. Laina",female,26,0,0,STON/O2. 3101282,7.925,,S
4,1,1,"Futrelle, Mrs. Jacques Heath (Lily May Peel)",female,35,1,0,113803,53.1,C123,S
5,0,3,"Allen, Mr. William Henry",male,35,0,0,373450,8.05,,S
6,0,3,"Moran, Mr. James",male,,0,0,330877,8.4583,,Q
7,0,1,"McCarthy, Mr. Timothy J",male,54,0,0,17463,51.8625,E46,S
8,0,3,"Palsson, Master. Gosta Leonard",male,2,3,1,349909,21.075,,S
9,1,3,"Johnson, Mrs. Oscar W (Elisabeth Vilhelmina Berg)",female,27,0,2,347742,11.1333,,S
10,1,2,"Nasser, Mrs. Nicholas (Adele Achem)",female,14,1,0,237736,30.0708,,C
```

Note: Refer to the visible test case for better reference.

Sample Test Cases

Explorer

BarPlotOf...

```
1 import pandas as pd
2 import matplotlib.pyplot as plt
3
4 # Load the Titanic dataset
5 data = pd.read_csv('Titanic-Dataset.csv')
6
7 # Data Cleaning
8 data['Age'].fillna(data['Age'].median(), inplace=True)
9 data['Embarked'].fillna(data['Embarked'].mode()[0], inplace=True)
10 data.drop('Cabin', axis=1, inplace=True)
11
12 # Convert categorical features to numeric
13 data['Sex'] = data['Sex'].map({'male': 0, 'female': 1})
14 data = pd.get_dummies(data, columns=['Embarked'], drop_first=True)
15
16 # Write your code here for Bar Plot for Survival Rate
17 survival_counts = data['Survived'].value_counts()
18 survival_counts.plot(kind='bar')
19 plt.title('Survival Count')
20 plt.xlabel('Survived')
21 plt.ylabel('Count')
22 plt.show()
```

Terminal

Test cases

< Prev Reset Submit Next >

adityabaste/EDS-Practical Dashboard Course

mitaoe.codetantra.com/secure/course.jsp?euclid=6773e3f2f1f9c5320ca6bc85#/contents/6773e45af1f9c5320ca6bd1d/6773e4f1f1f9c5320ca6bdd5/67e28fb27c0b912d860e7db4

202401090090@mitaoe.ac.in Support Logout

CODETANTRA Home

5.2.4. Bar Plot for Survival by Gender

02:26 AA ☾ ↻ -

Write a Python code to plot a stacked bar chart that shows the count of passengers who survived and did not survive, grouped by gender, in the Titanic dataset. The chart should display the following specifications:

1. Group the data by the 'Sex' column, then use the `value_counts()` function to count the occurrences of survivors (0 = Did not survive, 1 = Survived) for each gender.
2. Use a **stacked bar chart** to display the survival counts.
3. Add the title "**Survival by Gender**" to the chart.
4. Label the x-axis as '**Gender**' and the y-axis as '**Count**'.
5. The legend should indicate '**Not Survived**' and '**Survived**'.

The Titanic dataset contains columns as shown below,

Passe ngerId	Surviv ed	Pclass	Name	Sex	Age	SibSp	Parch	Ticket	Fare	Cabin	Embar ked

Sample Data:

```
PassengerId,Survived,Pclass,Name,Sex,Age,SibSp,Parch,Ticket,Fare,Cabin,Embarked
1,0,3,"Braund, Mr. Owen Harris",male,22,1,0,A/5 21171,7.25,,S
2,1,1,"Cumings, Mrs. John Bradley (Florence Briggs Thayer)",female,38,1,0,PC 17599,71.2833,C85,C
3,1,3,"Heikkinen, Miss. Laina",female,26,0,0,STON/O2. 3101282,7.925,,S
4,1,1,"Futrelle, Mrs. Jacques Heath (Lily May Peel)",female,35,1,0,113803,53.1,C123,S
5,0,3,"Allen, Mr. William Henry",male,35,0,0,373450,8.05,,S
6,0,3,"Moran, Mr. James",male,,0,0,330877,8.4583,,Q
7,0,1,"McCarthy, Mr. Timothy J",male,54,0,0,17463,51.8625,E46,S
8,0,3,"Palsson, Master. Gosta Leonard",male,2,3,1,349909,21.075,,S
9,1,3,"Johnson, Mrs. Oscar W (Elisabeth Vilhelmina Berg)",female,27,0,2,347742,11.1333,,S
10,1,2,"Nasser, Mrs. Nicholas (Adele Achen)",female,14,1,0,237736,30.0708,,C
```

Note: Refer to the visible test case for better reference

Sample Test Cases +

BarPlotOf...

```
import pandas as pd
import matplotlib.pyplot as plt

# Load the Titanic dataset
data = pd.read_csv('Titanic-Dataset.csv')

# Data Cleaning
data['Age'].fillna(data['Age'].median(), inplace=True)
data['Embarked'].fillna(data['Embarked'].mode()[0], inplace=True)
data.drop('Cabin', axis=1, inplace=True)

# Convert categorical features to numeric
data['Sex'] = data['Sex'].map({'male': 0, 'female': 1})
data = pd.get_dummies(data, columns=['Embarked'], drop_first=True)

# Write your code here for Bar Plot for Survival by Gender
import pandas as pd
import matplotlib.pyplot as plt

# Load the Titanic dataset
data = pd.read_csv('Titanic-Dataset.csv')

# Data Cleaning
data['Age'].fillna(data['Age'].median(), inplace=True)
data['Embarked'].fillna(data['Embarked'].mode()[0], inplace=True)
data.drop('Cabin', axis=1, inplace=True)

# Convert categorical features to numeric
data['Sex'] = data['Sex'].map({'male': 0, 'female': 1})
data = pd.get_dummies(data, columns=['Embarked'], drop_first=True)

# Write your code here for Bar Plot for Survival by Gender
survival_by_gender = data.groupby('Sex')['Survived'].value_counts().unstack().fillna(0)
survival_by_gender.columns = ['Not Survived', 'Survived']
survival_by_gender.index = ['0', '1']
```

Terminal Test cases

< Prev Reset Submit Next >

adityabaste/EDS-Practical Dashboard Course

mitaoe.codetantra.com/secure/course.jsp?euclid=6773e3f2f1f9c5320ca6bc85#/contents/6773e45af1f9c5320ca6bd1d/6773e4f1f1f9c5320ca6bdd5/67e291be7c0b912d860e876f

202401090090@mitaoe.ac.in Support Logout

CODETANTRA Home

5.2.5. Bar Plot for Survival by Pclass

02:29 A ☾ ↻ -

Write a Python code to plot a stacked bar chart that shows the count of passengers who survived and did not survive, grouped by passenger class (**Pclass**), in the Titanic dataset. The chart should display the following specifications:

1. Group the data by the **Pclass** column and count the number of survivors (0 = Did not survive, 1 = Survived) for each class using `value_counts()`.
2. Use a **stacked bar chart** to display the survival counts.
3. Add the title "**Survival by Pclass**" to the chart.
4. Label the x-axis as '**Pclass**' and the y-axis as '**Count**'.
5. The legend should indicate '**Not Survived**' and '**Survived**'.

The Titanic dataset contains columns as shown below,

Passe ngerId	Surviv ed	Pclass	Name	Sex	Age	SibSp	Parch	Ticket	Fare	Cabin	Embar ked

Sample Data:

```
PassengerId,Survived,Pclass,Name,Sex,Age,SibSp,Parch,Ticket,Fare,Cabin,Embarked
1,0,3,"Braund, Mr. Owen Harris",male,22,1,0,A/5 21171,7.25,,S
2,1,1,"Cumings, Mrs. John Bradley (Florence Briggs Thayer)",female,38,1,0,PC 17599,71.2833,C85,C
3,1,3,"Heikkinen, Miss. Laina",female,26,0,0,STON/O2. 3101282,7.925,,S
4,1,1,"Futrelle, Mrs. Jacques Heath (Lily May Peel)",female,35,1,0,113803,53.1,C123,S
5,0,3,"Allen, Mr. William Henry",male,35,0,0,373450,8.05,,S
6,0,3,"Moran, Mr. James",male,,0,0,330877,8.4583,,Q
7,0,1,"McCarthy, Mr. Timothy J",male,54,0,0,17463,51.8625,E46,S
8,0,3,"Palsson, Master. Gosta Leonard",male,2,3,1,349909,21.075,,S
9,1,3,"Johnson, Mrs. Oscar W (Elisabeth Vilhelmina Berg)",female,27,0,2,347742,11.1333,,S
10,1,2,"Nasser, Mrs. Nicholas (Adele Achem)",female,14,1,0,237736,30.0708,,C
```

Note:

Sample Test Cases +

BarPlotOf... 0 Submitter

```
import pandas as pd
import matplotlib.pyplot as plt

# Load the Titanic dataset
data = pd.read_csv('Titanic-Dataset.csv')

# Data Cleaning
data['Age'].fillna(data['Age'].median(), inplace=True)
data['Embarked'].fillna(data['Embarked'].mode()[0], inplace=True)
data.drop('Cabin', axis=1, inplace=True)

# Convert categorical features to numeric
data['Sex'] = data['Sex'].map({'male': 0, 'female': 1})
data = pd.get_dummies(data, columns=['Embarked'], drop_first=True)

# Write your code here for Bar Plot for Survival by Pclass
import pandas as pd
import matplotlib.pyplot as plt

# Load the Titanic dataset
data = pd.read_csv('Titanic-Dataset.csv')

# Data Cleaning
data['Age'].fillna(data['Age'].median(), inplace=True)
data['Embarked'].fillna(data['Embarked'].mode()[0], inplace=True)
data.drop('Cabin', axis=1, inplace=True)

# Convert categorical features to numeric
data['Sex'] = data['Sex'].map({'male': 0, 'female': 1})
data = pd.get_dummies(data, columns=['Embarked'], drop_first=True)

# Write your code here for Bar Plot for Survival by Pclass
survival_by_class = data.groupby('Pclass')['Survived'].value_counts().unstack().fillna(0)
survival_by_class.columns = ['Not Survived', 'Survived']
survival_by_class.plot(kind='bar', stacked=True)
```

Terminal Test cases

< Prev Reset Submit Next >

adityabaste/EDS-Practical Dashboard Course

mitaoe.codetantra.com/secure/course.jsp?euclid=6773e3f2f1f9c5320ca6bc85#/contents/6773e45af1f9c5320ca6bd1d/6773e4f1f1f9c5320ca6bdd5/67e297bf7c0b912d860e9c81

202401090090@mitaoe.ac.in Support Logout

CODETANTRA Home

5.2.6. Bar Plot for Survival by Embarked

01:48 A ☾ ↻ -

Write a Python code to plot a stacked bar chart showing the survival count for passengers based on their embarkation location in the Titanic dataset.

The chart should display the following specifications:

1. Use the **Embarked** column to determine the embarkation location. After converting this column into dummy variables (using `pd.get_dummies()`), plot the survival count based on the **Embarked_Q** column (representing passengers who embarked from Queenstown) in relation to survival.
2. Set the chart type to 'bar' and make it stacked.
3. Add the title "**Survival by Embarked**" to the chart.
4. Label the x-axis as '**Embarked**' and the y-axis as '**Count**'.
5. Include a legend to distinguish between survivors and non-survivors (label the legend as '**Survived**' and '**Not Survived**').

The Titanic dataset contains columns as shown below,

Passe ngerId	Surviv ed	Pclass	Name	Sex	Age	SibSp	Parch	Ticket	Fare	Cabin	Embar ked

Sample Data:

```
PassengerId,Survived,Pclass,Name,Sex,Age,SibSp,Parch,Ticket,Fare,Cabin,Embarked
1,0,3,"Braund, Mr. Owen Harris",male,22,1,0,A/5 21171,7.25,,S
2,1,1,"Cumings, Mrs. John Bradley (Florence Briggs Thayer)",female,38,1,0,PC 17599,71.2833,C85,C
3,1,3,"Heikkinen, Miss. Laina",female,26,0,0,STON/O2. 3101282,7.925,,S
4,1,1,"Futrelle, Mrs. Jacques Heath (Lily May Peel)",female,35,1,0,113803,53.1,C123,S
5,0,3,"Allen, Mr. William Henry",male,35,0,0,373450,8.05,,S
6,0,3,"Moran, Mr. James",male,,0,0,330877,8.4583,,Q
7,0,1,"McCarthy, Mr. Timothy J",male,54,0,0,17463,51.8625,E46,S
8,0,3,"Palsson, Master. Gosta Leonard",male,2,3,1,349909,21.075,,S
9,1,3,"Johnson, Mrs. Oscar W (Elisabeth Vilhelmina Berg)",female,27,0,2,347742,11.1333,,S
10,1,2,"Nasser, Mrs. Nicholas (Adele Achem)",female,14,1,0,237736,30.0708,,C
```

Sample Test Cases +

BarPlotOf... 0 Submitter Debugger

```
8 data['Age'].fillna(data['Age'].median(), inplace=True)
9 data['Embarked'].fillna(data['Embarked'].mode()[0], inplace=True)
10 data.drop('Cabin', axis=1, inplace=True)

12 # Convert categorical features to numeric
13 data['Sex'] = data['Sex'].map({'male': 0, 'female': 1})
14 data = pd.get_dummies(data, columns=['Embarked'], drop_first=True)

16 import pandas as pd
17 import matplotlib.pyplot as plt

19 # Load the Titanic dataset
20 data = pd.read_csv('Titanic-Dataset.csv')

22 # Data Cleaning
23 data['Age'].fillna(data['Age'].median(), inplace=True)
24 data['Embarked'].fillna(data['Embarked'].mode()[0], inplace=True)
25 data.drop('Cabin', axis=1, inplace=True)

27 # Convert categorical features to numeric
28 data['Sex'] = data['Sex'].map({'male': 0, 'female': 1})
29 data = pd.get_dummies(data, columns=['Embarked'], drop_first=True)

31 # Write your code here for Bar Plot for Survival by Embarked
32 grouped = data.groupby('Embarked_Q')['Survived'].value_counts().unstack().fillna(0)
33 grouped.columns = ['Not Survived', 'Survived']
34 grouped.plot(kind='bar', stacked=True)
35 plt.title('Survival by Embarked')
36 plt.xlabel('Embarked')
37 plt.ylabel('Count')
38 plt.legend(title=None)
39 plt.show()
```

Terminal Test cases

< Prev Reset Submit Next >

adityabaste/EDS-Practical Dashboard Course mitaoe.codetantra.com/secure/course.jsp?euclid=6773e3f2f1f9c5320ca6bc85#/contents/6773e45af1f9c5320ca6bd1d/6773e4f1f1f9c5320ca6bdd5/67e2992e7c0b912d860ea071 Incognito Logout

202401090090@mitaoe.ac.in Support Logout

CODETANTRA Home

5.2.7. Box plot for Age Distribution

01:41 A ☾ ⚡ -

Write a Python code to plot a boxplot that shows the distribution of the 'Age' column from the Titanic dataset across different passenger classes. The boxplot should display the following specifications:

1. Use the **Pclass** column to group the data for the boxplot.
2. Set the title of the plot to "**Age by Pclass**".
3. Remove the default subtitle with **plt.suptitle("")**.
4. Label the x-axis as '**Pclass**' and the y-axis as '**Age**'.

The Titanic dataset contains columns as shown below,

Passe ngerId	Surviv ed	Pclass	Name	Sex	Age	SibSp	Parch	Ticket	Fare	Cabin	Embar ked

Sample Data:

```
PassengerId,Survived,Pclass,Name,Sex,Age,SibSp,Parch,Ticket,Fare,Cabin,Embarked
1,0,3,"Braund, Mr. Owen Harris",male,22,1,0,A/5 21171,7.25,,S
2,1,1,"Cumings, Mrs. John Bradley (Florence Briggs Thayer)",female,38,1,0,PC 17599,71.2833,C85,C
3,1,3,"Heikkinen, Miss. Laina",female,26,0,0,STON/O2. 3101282,7.925,,S
4,1,1,"Futrelle, Mrs. Jacques Heath (Lily May Peel)",female,35,1,0,113803,53.1,C123,S
5,0,3,"Allen, Mr. William Henry",male,35,0,0,373450,8.05,,S
6,0,3,"Moran, Mr. James",male,,0,0,330877,8.4583,,Q
7,0,1,"McCarthy, Mr. Timothy J",male,54,0,0,17463,51.8625,E46,S
8,0,3,"Palsson, Master. Gosta Leonard",male,2,3,1,349909,21.075,,S
9,1,3,"Johnson, Mrs. Oscar W (Elisabeth Vilhelmina Berg)",female,27,0,2,347742,11.1333,,S
10,1,2,"Nasser, Mrs. Nicholas (Adele Achem)",female,14,1,0,237736,30.0708,,C
```

Note: Refer to the visible test case for better reference.

Sample Test Cases +

BoxPlotF...

```
import pandas as pd
import matplotlib.pyplot as plt

# Load the Titanic dataset
data = pd.read_csv('Titanic-Dataset.csv')

# Data Cleaning
data['Age'].fillna(data['Age'].median(), inplace=True)
data['Embarked'].fillna(data['Embarked'].mode()[0], inplace=True)
data.drop('Cabin', axis=1, inplace=True)

# Convert categorical features to numeric
data['Sex'] = data['Sex'].map({'male': 0, 'female': 1})
data = pd.get_dummies(data, columns=['Embarked'], drop_first=True)

# Write your code here for Box Plot for Age by Pclass
plt.figure(figsize=(8, 6))
data.boxplot(column='Age', by='Pclass')
plt.suptitle('')
plt.title('Age by Pclass')
plt.xlabel('Pclass')
plt.ylabel('Age')
plt.show()
```

Terminal Test cases

< Prev Reset Submit Next >

5.2.8. Box Plot for Age by Survived

02:33 AA ☾ ↻ -

Submit

Write a Python code to plot a boxplot that shows the distribution of the 'Age' column from the Titanic dataset based on whether passengers survived or not. The boxplot should display the following specifications:

1. Use the **Survived** column to group the data for the boxplot (0 = Did not survive, 1 = Survived).
2. Set the title of the plot to "**Age by Survival**".
3. Remove the default subtitle with `plt.suptitle("")`.
4. Label the x-axis as '**Survived**' and the y-axis as '**Age**'.

The Titanic dataset contains columns as shown below,

Passe ngerId	Surviv ed	Pclass	Name	Sex	Age	SibSp	Parch	Ticket	Fare	Cabin	Embar ked

Sample Data:

```
PassengerId,Survived,Pclass,Name,Sex,Age,SibSp,Parch,Ticket,Fare,Cabin,Embarked
1,0,3,"Braund, Mr. Owen Harris",male,22,1,0,A/5 21171,7.25,,S
2,1,1,"Cumings, Mrs. John Bradley (Florence Briggs Thayer)",female,38,1,0,PC 17599,71.2833,C85,C
3,1,3,"Heikkinen, Miss. Laina",female,26,0,0,STON/O2. 3101282,7.925,,S
4,1,1,"Futrelle, Mrs. Jacques Heath (Lily May Peel)",female,35,1,0,113803,53.1,C123,S
5,0,3,"Allen, Mr. William Henry",male,35,0,0,373450,8.05,,S
6,0,3,"Moran, Mr. James",male,,0,0,330877,8.4583,,Q
7,0,1,"McCarthy, Mr. Timothy J",male,54,0,0,17463,51.8625,E46,S
8,0,3,"Palsson, Master. Gosta Leonard",male,2,3,1,349909,21.075,,S
9,1,3,"Johnson, Mrs. Oscar W (Elisabeth Vilhelmina Berg)",female,27,0,2,347742,11.1333,,S
10,1,2,"Nasser, Mrs. Nicholas (Adele Achem)",female,14,1,0,237736,30.0708,,C
```

Note: Refer to the visible test case for better reference.

Sample Test Cases

Explorer

BoxPlotF...

```
1 import pandas as pd
2 import matplotlib.pyplot as plt
3
4 # Load the Titanic dataset
5 data = pd.read_csv('Titanic-Dataset.csv')
6
7 # Data Cleaning
8 data['Age'].fillna(data['Age'].median(), inplace=True)
9 data['Embarked'].fillna(data['Embarked'].mode()[0], inplace=True)
10 data.drop('Cabin', axis=1, inplace=True)
11
12 # Convert categorical features to numeric
13 data['Sex'] = data['Sex'].map({'male': 0, 'female': 1})
14 data = pd.get_dummies(data, columns=['Embarked'], drop_first=True)
15
16 # Write your code here for Box Plot for Age by Survived
17 plt.figure(figsize=(8, 6))
18 data.boxplot(column='Age', by='Survived')
19 plt.suptitle('')
20 plt.title('Age by Survival')
21 plt.xlabel('Survived')
22 plt.ylabel('Age')
23 plt.show()
```

Terminal

Test cases

< Prev Reset Submit Next >

5.2.9. Box Plot for Fare by Pclass

01:32 AA ☾ ↻ -

Submit Debugger

Write a Python code to plot a boxplot that shows the distribution of the 'Fare' column from the Titanic dataset based on the passenger class (Pclass). The boxplot should display the following specifications:

1. Use the **Pclass** column to group the data for the boxplot.
2. Set the title of the plot to "**Fare by Pclass**".
3. Remove the default subtitle with **plt.suptitle("")**.
4. Label the x-axis as '**Pclass**' and the y-axis as '**Fare**'.

The Titanic dataset contains columns as shown below,

Passe ngerId	Surviv ed	Pclass	Name	Sex	Age	SibSp	Parch	Ticket	Fare	Cabin	Embar ked

Sample Data:

```
PassengerId,Survived,Pclass,Name,Sex,Age,SibSp,Parch,Ticket,Fare,Cabin,Embarked
1,0,3,"Braund, Mr. Owen Harris",male,22,1,0,A/5 21171,7.25,,S
2,1,1,"Cumings, Mrs. John Bradley (Florence Briggs Thayer)",female,38,1,0,PC 17599,71.2833,C85,C
3,1,3,"Heikkinen, Miss. Laina",female,26,0,0,STON/O2. 3101282,7.925,,S
4,1,1,"Futrelle, Mrs. Jacques Heath (Lily May Peel)",female,35,1,0,113803,53.1,C123,S
5,0,3,"Allen, Mr. William Henry",male,35,0,0,373450,8.05,,S
6,0,3,"Moran, Mr. James",male,,0,0,330877,8.4583,,Q
7,0,1,"McCarthy, Mr. Timothy J",male,54,0,0,17463,51.8625,E46,S
8,0,3,"Palsson, Master. Gosta Leonard",male,2,3,1,349909,21.075,,S
9,1,3,"Johnson, Mrs. Oscar W (Elisabeth Vilhelmina Berg)",female,27,0,2,347742,11.1333,,S
10,1,2,"Nasser, Mrs. Nicholas (Adele Achem)",female,14,1,0,237736,30.0708,,C
```

Note: Refer to the visible test case for better reference.

Sample Test Cases

BoxPlotF...

```
import pandas as pd
import matplotlib.pyplot as plt

# Load the Titanic dataset
data = pd.read_csv('Titanic-Dataset.csv')

# Data Cleaning
data['Age'].fillna(data['Age'].median(), inplace=True)
data['Embarked'].fillna(data['Embarked'].mode()[0], inplace=True)
data.drop('Cabin', axis=1, inplace=True)

# Convert categorical features to numeric
data['Sex'] = data['Sex'].map({'male': 0, 'female': 1})
data = pd.get_dummies(data, columns=['Embarked'], drop_first=True)

# Write your code here for Box Plot for Fare by Pclass
plt.figure(figsize=(8, 6))
data.boxplot(column='Fare', by='Pclass')
plt.suptitle('')
plt.title('Fare by Pclass')
plt.xlabel('Pclass')
plt.ylabel('Fare')
plt.show()
```

Terminal Test cases

< Prev Reset Submit Next >

adityabaste/EDS-Practical

Dashboard

Course

mitaoe.codetantra.com/secure/course.jsp?euclid=6773e3f2f1f9c5320ca6bc85#/contents/6773e447f1f9c5320ca6bce4/6773e494f1f9c5320ca6bd76/6773e9c2f4ab787eca9d09e4

Incognito

Logout

CODETANTRA Home

202401090090@mitaoe.ac.in Support Logout

1.1.1. Calculate Momentum

09:35

A -

Write a program that accepts the mass of an object (in kilograms) and its velocity (in meters per second), then calculates and displays the momentum of the object. The momentum p is calculated using the formula:

$$p = m \times v$$

where:

m is the mass of the object (in kilograms).

v is the velocity of the object (in meters per second).

Input Format:

A single floating-point number representing the mass of the object in kilograms.

A single floating-point number representing the velocity of the object in meters per second.

Output Format:

The output will display calculated momentum with appropriate units (kgm/s) (rounded up to 2 decimal places).

Sample Test Cases

+

calculate...

Explorer

```
1 mass = float(input())
2 velocity = float(input())
3 momentum = mass * velocity
4 print('%.2f' % momentum, end=' ')
5 print("kgm/s")
```

Terminal Test cases

< Prev Reset Submit Next >

adityabaste/EDS-Practical X Dashboard X Course X +

mitaoe.codetantra.com/secure/course.jsp?euclid=6773e3f2f1f9c5320ca6bc85#/contents/6773e447f1f9c5320ca6bce4/6773e494f1f9c5320ca6bd76/6773eb5df4ab787eca9d0bf7

202401090090@mitaoe.ac.in Support Logout

CODETANTRA

Home

1.1.2. Conditional Calculation Based on the Number of Digits

16:54 AA ☾ ⚙ -

Write a Python program that accepts an integer n as input. Depending on the number of digits in n .

Constraints:
 $1 \leq n \leq 999$

Input Format:
The input consists of a single integer n .

Output Format:
If n is a single-digit number, print its square.
If n is a two-digit number, print its square root (rounded to two decimal places).
If n is a three-digit number, print its cube root (rounded to two decimal places).
Else print "Invalid".

Sample Test Cases

condition...

```
1 num = int(input())
2 if num >= 1 and num < 10:
3     p = num * num
4     print('%.0f' % p)
5 elif num >= 10 and num < 100:
6     q = num ** (0.5)
7     print('%.2f' % q)
8 elif num >= 100 and num <= 999:
9     r = num ** (1/3)
10    print('%.2f' % r)
11 else:
12     print("Invalid")
```

Terminal Test cases

< Prev Reset Submit Next >

adityabaste/EDS-Practical X Dashboard Course

mitaoe.codetantra.com/secure/course.jsp?euclid=6773e3f2f1f9c5320ca6bc85#/contents/6773e447f1f9c5320ca6bce4/6773e494f1f9c5320ca6bd76/6773ef42f4ab787eca9d11f7

202401090090@mitaoe.ac.in Support Logout

CODETANTRA Home

1.1.3. Age and Salary Calculation

43:24 A C D E -

Write a Python program that reads the birth date and salary of employees.

Input Format:
The input consists of:
A string representing the birth date of the employee in the format *DD – MM – YYYY*.
A floating-point number representing the salary of the employee in rupees.

Output Format:
The output should include:
The age of the employee.
The salary of the employee in dollars.

Note:
1INR=0.012USD

Sample Test Cases

Explorer birthDate...

```
1 from datetime import datetime
2
3 def calculate_age(birthdate):
4     date_object = datetime.strptime(birthdate, "%d-%m-%Y")
5     today = datetime.today()
6     if((today.month, today.day) < (date_object.month, date_object.day)):
7         age = today.year - date_object.year - ((today.month, today.day) < (date_object.month, date_object.day))
8     else:
9         age = today.year - date_object.year - ((today.month, today.day) > (date_object.month, date_object.day))
10    return age
11
12 def convert_salary_to_dollars(salary_in_rupees):
13     salary = salary_in_rupees * 0.012
14     return salary
15 birthdate = input()
16 salary_in_rupees = float(input())
17 age = calculate_age(birthdate)
18 salary_in_dollars = convert_salary_to_dollars(salary_in_rupees)
19 print(f"Age: {age}")
20 print(f"Salary in dollars: {salary_in_dollars:.2f}")
21
```

Terminal Test cases

< Prev Reset Submit Next >

adityabaste/EDS-Practical

Dashboard

Course

mitaoe.codetantra.com/secure/course.jsp?euclid=6773e3f2f1f9c5320ca6bc85#/contents/6773e447f1f9c5320ca6bce4/6773e494f1f9c5320ca6bd76/6774c276f4ab787eca9d88e3

202401090090@mitaoe.ac.in

Support Logout

CODETANTRA

Home

1.1.4. Reverse a Number

08:27

You are given an integer number. Your task is to reverse the digits of the number and print the reversed number.

Input Format
The input is an integer.

Output Format
Print a single integer which is the reversed number.

Sample Test Cases

reverseN...

```
1 num=int(input())
2 n1=str(num)
3 print(n1[::-1])
```

Submit

Debugger

adityabaste/EDS-Practical X Dashboard Course

mitaoe.codetantra.com/secure/course.jsp?euclid=6773e3f2f1f9c5320ca6bc85#/contents/6773e447f1f9c5320ca6bce4/6773e494f1f9c5320ca6bd76/678dd2f0fa4f5e20f6fc1dc1a

202401090090@mitaoe.ac.in Support Logout

CODETANTRA Home

1.1.5. Multiplication Table

06:48 AA ☾ ⚡ -

Write a Python program that takes an integer as input and prints the multiplication table for that integer from 1 to 10.

Input Format:
The first line of input contains an integer that represents the number for which the multiplication table is to be printed.

Output Format:
Print the multiplication table for the given number .

Sample Test Cases

Explorer multiplica...

```
i=int(input())
n=1
while n<=10:
    print(i,"x",n,"=",i*n)
    n=n+1
```

Terminal Test cases

< Prev Reset Submit Next >

adityabaste/EDS-Practical X Dashboard Course

mitaoe.codetantra.com/secure/course.jsp?euclid=6773e3f2f1f9c5320ca6bc85#/contents/6773e447f1f9c5320ca6bce4/6773e49af1f9c5320ca6bd79/6773f211f4ab787eca9d15d0

202401090090@mitaoe.ac.in Support Logout

CODETANTRA Home

1.2.1. Pass or Fail

02:21 A ⚡ -

Write a Python program that accepts the number of courses and the marks of a student in those courses. The grade is determined based on the aggregate percentage:

- If the aggregate percentage is greater than 75, the grade is Distinction.
- If the aggregate percentage is greater than or equal to 60 but less than 75, the grade is First Division.
- If the aggregate percentage is greater than or equal to 50 but less than 60, the grade is Second Division.
- If the aggregate percentage is greater than or equal to 40 but less than 50, the grade is Third Division.

Input Format:
The first input will be an integer n , the number of courses.
The second input will be n integers representing the marks of the student in each of the n courses, separated by a space.

Output Format:
If the student passes all courses:

- Print the aggregate percentage (rounded to two decimal places).
- Print the grade based on the aggregate percentage.

If the student fails any course (marks < 40 in any course), print:

- "Fail".

Explorer passorFa...

```
1 def calculate_grade(num_courses,marks):
2     total_marks = sum(marks)
3     aggregate_percentage = (total_marks / (num_courses * 100)) * 100
4     if aggregate_percentage > 75:
5         grade = "Distinction"
6     elif aggregate_percentage >= 60:
7         grade = "First Division"
8     elif aggregate_percentage >= 50:
9         grade = "Second Division"
10    elif aggregate_percentage >= 40:
11        grade = "Third Division"
12    else:
13        grade = "Fail"
14    return aggregate_percentage,grade
15 num_courses = int(input(""))
16 marks = list(map(int, input().split()))
17
18 if any(mark < 40 for mark in marks):
19     print("Fail")
20 else:
21     aggregate_percentage, grade = calculate_grade(num_courses, marks)
22     print(f"Aggregate Percentage: {aggregate_percentage:.2f}")
23     print(f"Grade: {grade}")
```

Sample Test Cases

Terminal Test cases

< Prev Reset Submit Next >

adityabaste/EDS-Practical X Dashboard Course

mitaoe.codetantra.com/secure/course.jsp?euclid=6773e3f2f1f9c5320ca6bc85#/contents/6773e447f1f9c5320ca6bce4/6773e49af1f9c5320ca6bd79/65f7d776bfe2dc3ed510ca60

202401090090@mitaoe.ac.in Support Logout

CODETANTRA Home

1.2.2. Fibonacci series using Recursive Function

02:26 AA ☾ ⚙ -

Write a Python program to find the Fibonacci series of a given number of terms using recursive function calls.

Expected Output-1:
Enter terms for Fibonacci series: 5
0 1 1 2 3

Expected Output-2:
Enter terms for Fibonacci series: 9
0 1 1 2 3 5 8 13 21

Instructions:

- Your input and output must follow the input and output layout mentioned in the visible sample test case.
- Hidden test cases will only pass when users' input and output match the expected input and output.

fib.py

```
1 def fib(n):
2     if n<=1:
3         return n
4
5     else:
6         return fib(n-1)+fib(n-2)
7
8
9 # n=int(input("Enter terms for Fibonacci series:"))
10 # for i in range (n):
11 #     print(fib(i),end=" ")
12 #
13 #
14
15 n=int(input("Enter terms for Fibonacci series:"))
16 for i in range (n):
17     print(fib(i),end=" ")
18 #
19 #
20 #
21 #
22 #
23 #
24 #
25 #
26 #
27 #
28
29 # n=int(input("Enter terms for Fibonacci series:"))
30 # for i in range (n):
31 #     print(fib(i),end=" ")
```

Sample Test Cases

Terminal Test cases

< Prev Reset Submit Next >

adityabaste/EDS-Practical X Dashboard Course

mitaoe.codetantra.com/secure/course.jsp?euclid=6773e3f2f1f9c5320ca6bc85#/contents/6773e447f1f9c5320ca6bce4/6773e49af1f9c5320ca6bd79/6774c521f4ab787eca9d8a75

202401090090@mitaoe.ac.in Support Logout

CODETANTRA

1.2.3. Pattern - 1

01:26 AA ☾ ⚡ -

Write a Python program to print a pattern of asterisks in the form of a right-angled triangle.

Input Format:
The input is an integer, representing the number of rows in the pattern.

Output Format
The output should display the pattern of asterisks (*), with each row containing an increasing number of asterisks.

Note:
Refer to the displayed test cases for the sample pattern.

Sample Test Cases

rightangl...

```
1 n=int(input())
2 i=1
3 v while(i<=n):
4     print("*"*i)
5     i+=1
```

Terminal Test cases

< Prev Reset Submit Next >

adityabaste/EDS-Practical X Dashboard Course

mitaoe.codetantra.com/secure/course.jsp?euclid=6773e3f2f1f9c5320ca6bc85#/contents/6773e447f1f9c5320ca6bce4/6773e49af1f9c5320ca6bd79/6774cc86f4ab787eca9d8f99

202401090090@mitaoe.ac.in Support Logout

CODETANTRA Home

1.2.4. Pattern - 2

02:10 AA ☾ ⚡ -

Write a Python program to print a right-angled triangle pattern of numbers.

Input Format:
The input is an integer, representing the number of rows in the pattern.

Output Format:
The output should display the pattern of numbers, with each row containing increasing numbers starting from 1 up to the row number.

Note:
Refer to the displayed test cases for the sample pattern.

Sample Test Cases

numberP...

```
a = int(input())
for i in range(1, a+1):
    for j in range(1, i+1):
        print(j, end=" ")
    print()
```

Explorer Terminal Test cases

Submit Debugger

adityabaste/EDS-Practical

Dashboard

Course

mitaoe.codetantra.com/secure/course.jsp?euclid=6773e3f2f1f9c5320ca6bc85#/contents/6773e44bf1f9c5320ca6bce8/6773e49ef1f9c5320ca6bd7d/667bbd7f01060f3d690f3f83

202401090090@mitaoe.ac.in

Support Logout

CODETANTRA Home

2.1.1. List operations

01:53

Submit

Debugger

Write a Python program that implements a menu-driven interface for managing a list of integers. The program should have the following menu options:

1. Add
2. Remove
3. Display
4. Quit

The program should repeatedly prompt the user to enter a choice from the menu. Depending on the choice selected, the program should perform the following actions:

- **Add:** Prompts the user to enter an integer and add it to the integer list. If the input is not a valid integer, display "Invalid input".
- **Remove:** Prompts the user to enter an integer to remove from the list. If the integer is found in the list, remove it; otherwise, display "Element not found". If the list is empty, display "List is empty".
- **Display:** Displays the current list of integers. If the list is empty, display "List is empty".
- **Quit:** Exits the program.
- The program should handle invalid menu choices by displaying "Invalid choice". Ensure that the program continues to prompt the user until they choose to quit (option 4).

Sample Test Cases

```
listOps.py
```

```
1 def display_menu():
2     print("1. Add")
3     print("2. Remove")
4     print("3. Display")
5     print("4. Quit")
6
7     int_list = []
8
9     while True:
10        display_menu()
11        choice = input("Enter choice: ")
12
13        if choice == '1':
14            num = int(input("Integer: "))
15            int_list.append(num)
16            print(f"List after adding: {int_list}")
17
18
19        elif choice == '2':
20            if len(int_list) == 0:
21                print("List is empty")
22            else:
23
24                num = int(input("Integer: "))
25                if num in int_list:
26                    int_list.remove(num)
27                    print(f"List after removing: {int_list}")
28                else:
29                    print("Element not found")
30
31
32        elif choice == '3':
33            if len(int_list) == 0:
34                print("List is empty")
35            else:
```

< Prev Reset Submit Next >

adityabaste/EDS-Practical Dashboard Course

mitaoe.codetantra.com/secure/course.jsp?euclid=6773e3f2f1f9c5320ca6bc85#/contents/6773e44bf1f9c5320ca6bce8/6773e49ef1f9c5320ca6bd7d/677bb1ca63fd602f55ad634f

202401090090@mitaoe.ac.in Support Logout

CODETANTRA Home

2.1.2. Dictionary Operations

02:15 A ⚡ -

Write a Python program to perform the following dictionary operations:

- Create an empty dictionary and display it.
- Ask the user how many items to add, then input key-value pairs.
- Show the dictionary after adding items.
- Ask the user to update a key's value. Print "Value updated" if the key exists, otherwise print "Key not found".
- Retrieve and print a value using a key. If not found, print "Key not found".
- Use get() to retrieve a value. If the key doesn't exist, print "Key not found".
- Delete a key-value pair. If the key exists, delete and print "Deleted". If not, print "Key not found".
- Display the updated dictionary.

Note: Refer to visible test cases.

dictOpera...

```
41 num_items = int(input("Number of items: "))
42
43 for _ in range(num_items):
44     key = input("key: ")
45     value = input("value: ")
46     my_dict[key] = value
47
48
49 print("Dictionary:", my_dict)
50
51 update_key = input("Enter the key to update: ")
52 if update_key in my_dict:
53     new_value = input("Enter the new value: ")
54     my_dict[update_key] = new_value
55     print("Value updated")
56 else:
57     print("Key not found")
58
59 retrieve_key = input("Enter the key to retrieve: ")
60 if retrieve_key in my_dict:
61     print(f"Key: {retrieve_key}, Value: {my_dict[retrieve_key]}")
62 else:
63     print("Key not found")
64
65
66 get_key = input("Enter the key to get using the get() method: ")
67 value = my_dict.get(get_key)
68 if value is None:
69     print("Key not found")
70 else:
71     print(f"Key: {get_key}, Value: {value}")
72
73
74 delete_key = input("Enter the key to delete: ")
75 if delete_key in my_dict:
```

Sample Test Cases +

Terminal Test cases

< Prev Reset Submit Next >

adityabaste/EDS-Practical

Dashboard

Course

mitaoe.codetantra.com/secure/course.jsp?euclid=6773e3f2f1f9c5320ca6bc85#/contents/6773e44bf1f9c5320ca6bce8/6773e4b0f1f9c5320ca6bd85/64ac0cb9b4547106899a4e1b

202401090090@mitaoe.ac.in

Support Logout

CODETANTRA

Home

2.2.1. Linear search Technique

01:29

Submit

Debugger

Write a program to check whether the given element is present or not in the array of elements using linear search.

Input format:

- The first line of input contains the array of integers which are separated by space
- The last line of input contains the key element to be searched

Output format:

- If the element is found, print the index.
- If the element is not found, print **Not found**.

Sample Test Case:

Input:

```
1 2 3 4 3 5 6
3
```

Output:

```
2
```

Sample Test Cases

CTP1709...

```
1 # Function to implement linear search
2 def linear_search(arr, key):
3     for index in range(len(arr)):
4         if arr[index] == key:
5             return index # Return the index if the element is found
6     return "Not found" # Return "Not found" if the element is not found
7
8 # Input: Array of integers
9 arr = list(map(int, input().split()))
10
11 # Input: Key element to search for
12 key = int(input())
13
14 # Call the linear_search function and print the result
15 result = linear_search(arr, key)
16 print(result)
17
18
```

Terminal Test cases

< Prev Reset Submit Next >

adityabaste/EDS-Practical

Dashboard

Course

mitaoe.codetantra.com/secure/course.jsp?euclid=6773e3f2f1f9c5320ca6bc85#/contents/6773e44bf1f9c5320ca6bce8/6773e4b0f1f9c5320ca6bd85/6774d0abf4ab787eca9d9230

202401090090@mitaoe.ac.in

Support Logout

CODETANTRA Home

2.2.2. Captain of the Team

01:26

You are provided with the heights of 11 cricket players (in centimeters). Your task is to identify the tallest player, who will be selected as the captain of the team.

Input Format:
The first line of input will contain 11 integers, each representing the height of a player (in centimeters), each separated by a space.

Output Format
The output should be the height (in centimeters) of the tallest player.

Sample Test Cases

Explorer

captainof...

```
heights = list(map(int, input().split()))
max = 0
for i in heights:
    if max < i:
        max = i
print(max)
```

Terminal

Test cases

< Prev

Reset

Submit

Next >

adityabaste/EDS-Practical

Dashboard

Course

mitaoe.codetantra.com/secure/course.jsp?euclid=6773e3f2f1f9c5320ca6bc85#/contents/6773e451f1f9c5320ca6bd17/6773e4ccf1f9c5320ca6bdb2/6684d40e5d95376955a73c1d

Incognito

CODETANTRA [Home](#)

202401090090@mitaoe.ac.in [Support](#) [Logout](#)

3.1.1. Numpy array operations

00:48 [A](#) [M](#) [D](#) [P](#) -

Write a python program to demonstrate the usage of ndim, shape and size for a Numpy Array. The program should create a NumPy array using the entered elements and display it. Assume all input elements are valid numeric values.

Input Format:

- User inputs the number of rows and columns with space separated values.
- User inputs elements of the array row-wise followed line by line, separated by spaces.

Output Format:

- The created NumPy array based on the input dimensions and elements.
- Dimensions (ndim): Number of dimensions of the array.
- Shape: Tuple representing the shape of the array (number of rows, number of columns).
- Size: Total number of elements in the array.

Note: Use reshape() function to reshape the input array with the specified number of rows and columns.

Sample Test Cases +

numpyarr...

1 `#import numpy as np`
2 `import numpy as np`
3
4 `# Read number of rows and columns`
5 `rows, cols = map(int, input().split())`
6
7 `# Read elements row-wise`
8 `elements = []`
9 `for _ in range(rows):`
10 `... elements.extend(map(int, input().split())) # use int, not float`
11
12 `# Create numpy array and reshape`
13 `arr = np.array(elements, dtype=int).reshape(rows, cols)`
14
15 `# Display the array`
16 `print(arr)`
17
18 `# Display properties`
19 `print(arr.ndim)`
20 `print(arr.shape)`
21 `print(arr.size)`
22
23
24

Terminal Test cases

< Prev Reset Submit Next >

adityabaste/EDS-Practical X Dashboard Course

mitaoe.codetantra.com/secure/course.jsp?euclid=6773e3f2f1f9c5320ca6bc85#/contents/6773e451f1f9c5320ca6bd17/6773e4d1f1f9c5320ca6bdb8/6774e3fff4ab787eca9da092

202401090090@mitaoe.ac.in Support Logout

CODETANTRA

3.2.1. Numpy: Matrix Operations

The given code takes two 3×3 matrices, `matrix_a`, and `matrix_b`, as input from the user and converts them into NumPy arrays.

Task:

You are required to compute and display the results of the following matrix operations:

1. **Addition** (`matrix_a + matrix_b`)
2. **Subtraction** (`matrix_a - matrix_b`)
3. **Element-wise Multiplication** (`matrix_a * matrix_b`)
4. **Matrix Multiplication** (`matrix_a . matrix_b`)
5. **Transpose of Matrix A**

Input Format:

- The user will input 3 rows for `matrix_a`, each containing 3 integers separated by spaces.
- Similarly, the user will input 3 rows for `matrix_b`, each containing 3 integers separated by spaces.

Output Format:

The program should display the results of the operations in the following order:

1. The result of Addition.
2. The result of Subtraction.
3. The result of Element-wise Multiplication.
4. The result of Matrix Multiplication.
5. The Transpose of Matrix A.

Sample Test Cases

matrixOp...

```
15 # print("Subtraction (A - B):")
16
17 # # Multiplication (element-wise)
18 # print("Element-wise Multiplication (A * B):")
19
20 # # Matrix multiplication (dot product)
21 # print("A dot B:")
22
23 # # Transpose
24 # print("Transpose of A:")
25 import numpy as np
26
27 # Input matrices
28 print("Enter Matrix A:")
29 matrix_a = np.array([list(map(int, input().split())) for i in range(3)])
30
31 print("Enter Matrix B:")
32 matrix_b = np.array([list(map(int, input().split())) for i in range(3)])
33
34
35 # Addition
36 print("Addition (A+B):")
37 print(matrix_a + matrix_b)
38 # Subtraction
39 print("Subtraction (A-B):")
40 print(matrix_a - matrix_b)
41 # Multiplication (element-wise)
42 print("Element-wise Multiplication (A*B):")
43 print(matrix_a * matrix_b)
44 # Matrix multiplication (dot product)
45 print("A dot B:")
46 print(np.dot(matrix_a, matrix_b))
47 # Transpose
48 print("Transpose of A:")
49 print(np.transpose(matrix_a))
```

Terminal Test cases

< Prev Reset Submit Next >

adityabaste/EDS-Practical Dashboard Course mitaoe.codetantra.com/secure/course.jsp?euclid=6773e3f2f1f9c5320ca6bc85#/contents/6773e451f1f9c5320ca6bd17/6773e4d1f1f9c5320ca6bdb8/6774ee19f4ab787eca9da7fe Incognito Logout

CODETANTRA Home

3.2.2. Numpy: Horizontal and Vertical Stacking of Arrays

You are given two arrays `arr1` and `arr2`. You need to perform horizontal and vertical stacking operations on them using NumPy.

- **Horizontal Stacking:** Stack the two matrices horizontally (side by side).
- **Vertical Stacking:** Stack the two matrices vertically (one below the other).

Input Format:

- The program should first prompt the user to input two 3x3 arrays.
- Each array consists of 3 rows, and each row contains 3 space-separated integers.
- The user will input the two arrays row by row.

Output Format:

- The program should display the result of the Horizontal Stack (side-by-side stacking) of the two arrays.
- The program should then display the result of the Vertical Stack (one below the other) of the two arrays.

stacking.py

```
1 # import numpy as np
2
3 # # Input matrices
4 # print("Enter Array1:")
5 # arr1 = np.array([list(map(int, input().split())) for i in range(3)])
6
7 # print("Enter Array2:")
8 # arr2 = np.array([list(map(int, input().split())) for i in range(3)])
9
10 # # Perform horizontal stacking (hstack)
11
12
13
14 import numpy as np
15
16 # Input matrices
17 print("Enter Array1:")
18 arr1 = np.array([list(map(int, input().split())) for i in range(3)])
19
20 print("Enter Array2:")
21 arr2 = np.array([list(map(int, input().split())) for i in range(3)])
22 s1=np.hstack((arr1,arr2))
23 s2=np.vstack((arr1,arr2))
24 print("Horizontal Stack:")
25 print(s1)
26 print("Vertical Stack:")
27 print(s2)
```

Sample Test Cases

+

Terminal Test cases

< Prev Reset Submit Next >

adityabaste/EDS-Practical

Dashboard

Course

mitaoe.codetantra.com/secure/course.jsp?euclid=6773e3f2f1f9c5320ca6bc85#/contents/6773e451f1f9c5320ca6bd17/6773e4d1f1f9c5320ca6bdb8/6774ee9df4ab787eca9da869

202401090090@mitaoe.ac.in

Support Logout

CODETANTRA

Home

3.2.3. Numpy: Custom Sequence Generation

01:48

Submit

Debugger

Write a Python program that takes the following inputs from the user:

- Start value: The starting point of the sequence.
- Stop value: The sequence should end before this value.
- Step value: The increment between each number in the sequence.

The program should then generate a sequence using numpy based on these inputs and print the generated sequence.

Input Format:

- The user will input three integer values: start, stop, and step, each on a new line.

Output Format:

- The program should print the generated sequence based on the input values.

customS...

```
1 # import numpy as np
2
3 # # Take user input for the start, stop, and step of the sequence
4 # start = int(input())
5 # stop = int(input())
6 # step = int(input())
7
8 # # Generate the sequence using np.arange()
9
10 import numpy as np
11
12 # Take user input for the start, stop, and step of the sequence
13 start = int(input())
14 stop = int(input())
15 step = int(input())
16
17 # Generate the sequence using np.arange()
18 sequence=np.arange(start,stop,step)
19 # Print the generated sequence
20 print(sequence)
```

Sample Test Cases

+

Terminal Test cases

< Prev Reset Submit Next >

3.2.4. Numpy: Arithmetic and Statistical Operations, Mathematical Operations, Bitwise Operators

01:32 AA ☾ ⏺ ⏹ -

Submit Debugger

You are given two arrays A and B. Your task is to complete the function array_operations, which will convert these lists into NumPy arrays and perform the following operations:

1. Arithmetic Operations:

- Compute the element-wise sum, difference, and product of the two arrays.

2. Statistical Operations:

- Calculate the mean, median, and standard deviation of array A.

3. Bitwise Operations:

- Perform bitwise AND, bitwise OR, and bitwise XOR on the arrays (ex: $A_i \text{ OR } B_i$).

Input Format:

- The first line contains space-separated integers representing the elements of array A.
- The second line contains space-separated integers representing the elements of array B.

Output Format:

- For each operation (arithmetic, statistical, and bitwise), print the results in the specified format as shown in sample test cases.

Sample Test Cases +

different...

```
38 import numpy as np
39
40 def array_operations(A, B):
41     # Convert A and B to NumPy arrays
42     A=np.array(A)
43     B=np.array(B)
44
45     # Arithmetic Operations
46     sum_result = A+B
47     diff_result = A-B
48     prod_result = A*B
49
50     # Statistical Operations
51     mean_A = np.mean(A)
52     median_A = np.median(A)
53     std_dev_A = np.std(A)
54
55     # Bitwise Operations
56     and_result = np.bitwise_and(A,B)
57     or_result = np.bitwise_or(A,B)
58     xor_result = np.bitwise_xor(A,B)
59
60     # Output results with one space between each element
61     print("Element-wise Sum:", ''.join(map(str, sum_result)))
62     print("Element-wise Difference:", ''.join(map(str, diff_result)))
63     print("Element-wise Product:", ''.join(map(str, prod_result)))
64
65     # Mean, Median, and Standard Deviation of A
66     print(f"Mean of A: {mean_A}")
67     print(f"Median of A: {median_A}")
68     print(f"Standard Deviation of A: {std_dev_A}")
69
70     # Bitwise AND and OR
71     print("Bitwise AND:", ''.join(map(str, and_result)))
72     print("Bitwise OR:", ''.join(map(str, or_result)))
```

Terminal Test cases

adityabaste/EDS-Practical X | Dashboard X | Course X | +

mitaoe.codetantra.com/secure/course.jsp?euclid=6773e3f2f1f9c5320ca6bc85#/contents/6773e451f1f9c5320ca6bd17/6773e4d1f1f9c5320ca6bdb8/6774efaaf4ab787eca9da91e

202401090090@mitaoe.ac.in ▾ Support Logout

CODETANTRA

Home

3.2.5. Numpy: Copying and Viewing Arrays

01:26 A ⚡ -

The given code takes a list of integers as input and converts it into a NumPy array. Your task is to complete the code by:

- Creating a view of the `original_array` and assigning it to `view_array`.
- Creating a copy of the `original_array` and assigning it to `copy_array`.

After completing these steps, observe how modifying the view affects the `original_array`, while modifying the copy does not.

Input Format:

- A single line of space-separated integers.

Output Format:

- After modifying the view:

```
Original array after modifying view: <original_array>
View array: <view_array>
```

- After modifying the copy:

```
Original array after modifying copy: <original_array>
Copy array: <copy_array>
```

Sample Test Cases +

copyAnd... Submit

import numpy as np

inputlist = list(map(int,input().split(" ")))

Original array

original_array = np.array(inputlist)

Create a view

view_array = original_array.view()

Create a copy

copy_array = original_array.copy()

Modify the view

view_array[0] = 99

print("Original array after modifying view:", original_array)

print("View array:", view_array)

Modify the copy

copy_array[1] = 88

print("Original array after modifying copy:", original_array)

print("Copy array:", copy_array)

Terminal Test cases

< Prev Reset Submit Next >

adityabaste/EDS-Practical Dashboard Course mitaoe.codetantra.com/secure/course.jsp?euclid=6773e3f2f1f9c5320ca6bc85#/contents/6773e451f1f9c5320ca6bd17/6773e4d1f1f9c5320ca6bdb8/6774f064f4ab787eca9da9b0 Incognito Logout

CODETANTRA Home

3.2.6. Numpy: Searching, Sorting, Counting, Broadcasting

The given code in the editor takes a single array, `array1`, as space-separated integers as input from the user. Additionally, it takes the following inputs:

- `search_value`: The value to search for in the array.
- `count_value`: The value to count its occurrences in the array.
- `broadcast_value`: The value to add for broadcasting across the array.

You need to complete the code to perform the following operations:

1. **Searching**: Find the indices where `search_value` appears in `array1` and print these indices.
2. **Counting**: Count how many times `count_value` appears in `array1` and print the count.
3. **Broadcasting**: Add `broadcast_value` to each element of `array1` using broadcasting, and print the resulting array.
4. **Sorting**: Sort `array1` in ascending order and print the sorted array.

Input Format:

1. A single line containing space-separated integers representing `array1`.
2. An integer `search_value` represents the value to search for in the array.
3. An integer `count_value` represents the value to count in the array.
4. An integer `broadcast_value` represents the value to add to each element of the array.

Output Format:

1. The indices where `search_value` occurs in `array1`.
2. The count of occurrences of `count_value` in `array1`.
3. The array after adding the `broadcast_value` to each element.
4. The sorted array.

Sample Test Cases +

arrayOp...

```
1 # import numpy as np
2
3 # # Input array from the user
4 array1 = np.array(list(map(int, input().split())))
5
6 # # Searching
7 # search_value = int(input("Value to search: "))
8 # count_value = int(input("Value to count: "))
9 # broadcast_value = int(input("Value to add: "))
10
11
12 # # Sort the first array
13 import numpy as np
14
15
16 # Input array from the user
17 array1 = np.array(list(map(int, input().split())))
18
19 # Searching
20 search_value = int(input("Value to search: "))
21 count_value = int(input("Value to count: "))
22 broadcast_value = int(input("Value to add: "))
23
24 # Find indices where value matches in array1
25 a = np.where(array1 == search_value)[0]
26 print(a)
27 # Count occurrences in array1
28 b = np.count_nonzero(array1 == count_value)
29 print(b)
30 # Broadcasting addition
31 c = array1 + broadcast_value
32 print(c)
33 # Sort the first array
34 d = np.sort(array1)
35 print(d)
```

Terminal Test cases

< Prev Reset Submit Next >

3.2.7. Student Data Analysis and Operations

03:13 AA ☾ ↻ -

Write a Python program that takes the file name of a CSV file containing student details, including roll numbers and their marks in three subjects as input, reads the data, and performs the following operations:

- **Print all student details:** Display the complete details of all students, including roll numbers and marks for all subjects.
- **Find total students:** Determine the total number of students in the dataset.
- **Print all student roll numbers:** Extract and print the roll numbers of all students.
- **Print Subject 1 marks:** Extract and print the marks of all students in Subject 1.
- **Find minimum marks in Subject 2:** Identify the lowest marks in Subject 2.
- **Find maximum marks in Subject 3:** Identify the highest marks in Subject 3.
- **Print all subject marks:** Display the marks of all students for each subject.
- **Find total marks of students:** Compute the total marks for each student across all subjects.
- **Find the average marks of each student:** Compute the average marks for each student.
- **Find average marks of each subject:** Compute the average marks for all students in each subject.
- **Find average marks of Subject 1 and Subject 2:** Compute the average marks for Subject 1 and Subject 2.
- **Find average marks of Subject 1 and Subject 3:** Compute the average marks for Subject 1 and Subject 3.
- **Find the roll number of the student with maximum marks in Subject 3:** Identify the student with the highest marks in Subject 3 and print their roll number.
- **Find the roll number of the student with minimum marks in Subject 2:** Identify the student with the lowest marks in Subject 2 and print their roll number.
- **Find the roll number of students who scored 24 marks in Subject 2:** Identify students who obtained exactly 24 marks in Subject 2 and print their roll numbers.
- **Find the count of students who got less than 40 marks in Subject 1:** Count the number of students who scored less than 40 marks in Subject 1.
- **Find the count of students who got more than 90 marks in Subject 2:** Count the number of students who scored more than 90 marks in Subject 2.
- **Find the count of students who scored >=90 in each subject:** Count the number of students who scored 90 or more marks in each subject.
- **Find the count of subjects in which each student scored >=90:** Determine how many subjects each student scored 90 or more marks in.
- **Print Subject 1 marks in ascending order:** Sort and print the marks of students in Subject 1 in ascending order.
- **Print students who scored between 50 and 90 in Subject 1:** Display students who scored marks between 50 and 90 in Subject 1.

Sample Test Cases +

Explorer Operations

```
import numpy as np
a = np.loadtxt("Sample.csv", delimiter=',', skiprows=1)
# 1. Print all student details
print("All student Details:\n", a)
# 2. print total students
print("Total Students:", len(a))
# 3. Print all student Roll numbers
print("All Student Roll Nos", a[:, 0])
# 4. Print subject 1 marks
print("Subject 1 Marks", a[:, 1])
# 5. print minimum marks of Subject 2
print("Min marks in Subject 2", np.min(a[:, 2]))
# 6. print maximum marks of Subject 3
print("Max marks in Subject 3", np.max(a[:, 3]))
# 7. Print All subject marks
print("All subject marks:", a[:, 1:])
# 8. print Total marks of students
total = np.sum(a[:, 1:], axis=1)
print("Total Marks", total)
# 9. print average marks of each student
average = np.mean(a[:, 1:], axis=1)
print(np.round(average, 1))
# 10. printt average marks of each subject
avg = np.round(np.mean(a[:, 1:], axis=0), 2)
```

Terminal Test cases