

A PROJECT REPORT ON

Phishing Website Detection using Machine Learning

SUBMITTED TO THE SAVITRIBAI PHULE UNIVERSITY, PUNE
IN THE PARTIAL FULFILLMENT OF THE REQUIREMENTS
FOR THE AWARD OF THE DEGREE

OF

**BACHELOR OF ENGINEERING
(COMPUTER ENGINEERING)**

SUBMITTED BY

Atharva Dharrao
Divya Khandare
Akash Jadhav
Gaurav Mahadik

Exam No: B400050375
Exam No: B400050382
Exam No: B400050416
Exam No: B400050483



DEPARTMENT OF COMPUTER ENGINEERING
Pune Institute of Computer Technology
Dhankawadi, Pune - 411043

SAVITRIBAI PHULE PUNE UNIVERSITY
2024-2025



CERTIFICATE

This is to certify that the project report entitled
Phishing Website Detection using Machine Learning

Submitted by

Atharva Dharrao
Divya Khandare
Akash Jadhav
Gaurav Mahadik

Exam No: B400050375
Exam No: B400050382
Exam No: B400050416
Exam No: B400050483

is a bonafide student of this institute and the work has been carried out by him/her under the supervision of **Prof. Dipika Raigar** and it is approved for the partial fulfillment of the requirement of Savitribai Phule Pune University, for the award of the degree of **Bachelor of Engineering** (Computer Engineering).

Prof. Dipika Raigar
Internal Guide
Dept. of Computer Engg.

Dr. G.V. Kale
Head
Dept. of Computer Engg.

Dr. S.T. Gandhe
Principal
Pune Institute of Computer Technology

Place: Pune
Date:

ACKNOWLEDGEMENT

It gives us great pleasure in presenting the project report on '**Phishing Website Detection using Machine Learning**'.

We would like to express our sincere gratitude to our project guide, **Prof. Dipika Raigar**, for her valuable guidance, consistent support, and encouragement throughout the development of our project. Their timely feedback and technical expertise played a crucial role in shaping the direction of our work.

We extend our heartfelt thanks to **Dr. G.V. Kale**, Head of the Department, and to all faculty members and technical staff of the Computer Engineering Department at PICT for their assistance and motivation during various phases of the project.

We are also thankful to the project review panel for their insightful feedback and constructive suggestions, which helped us refine our system and improve the overall quality of our work. Their observations pushed us to explore better approaches and polish our implementation.

Lastly, we would like to thank our families and friends for their constant encouragement, patience, and moral support throughout this journey. Their unwavering support kept us motivated and focused, even during challenging phases of the project.

Atharva Dharrao
Divya Khandare
Akash Jadhav
Gaurav Mahadik
(B.E. Computer Engg.)

ABSTRACT

Phishing remains a pervasive cybersecurity threat that significantly impacts both individuals and organizations, including targeted brands. Over time, phishing tactics have evolved to become more sophisticated, making detection and prevention crucial in mitigating the damage caused by such attacks. Despite years of advancements in cybersecurity, phishing continues to be successful, necessitating more effective and adaptive detection solutions. This report provides a thorough examination of the current landscape of phishing detection, underscoring the continued relevance and urgency of addressing this threat.

The literature presents a variety of approaches to phishing detection, which can broadly be categorized into three main methods: list-based, similarity-based, and machine learning-based approaches. List-based techniques rely on maintaining up-to-date blacklists or whitelists of phishing URLs, while similarity-based methods detect phishing by comparing suspicious websites to legitimate ones based on features such as URL structure, visual appearance, or content. Machine learning-based solutions have gained significant attention in recent years due to their ability to automatically identify phishing attempts by learning from patterns in large datasets. This report examines each approach, highlighting key studies and the datasets used for their validation.

In addition to reviewing the existing solutions, this report identifies several research gaps that need to be addressed to enhance phishing detection systems. Despite the progress made in the field, challenges such as the adaptability of phishing tactics and the limitations of datasets remain obstacles to fully effective detection. This report discusses these gaps and provides insights into potential directions for future research to improve the reliability and robustness of phishing detection techniques.

Contents

1	Introduction	1
1.1	Overview	2
1.2	Motivation	2
1.3	Problem Definition and Objectives	3
1.3.1	Problem	3
1.3.2	Objectives	3
1.4	Project Scope and Limitations	3
1.4.1	Scope	3
1.4.2	Limitations	4
1.5	Methodologies of Problem Solving	4
2	Literature Survey	5
3	Software Requirements Specification	9
3.1	Assumptions and Dependencies	10
3.1.1	Assumptions	10
3.1.2	Dependencies	10
3.2	Functional Requirements	11
3.3	External Interface Requirements	12
3.3.1	User Interfaces	12
3.3.2	Hardware Interfaces	12
3.3.3	Software Interfaces	12
3.4	Nonfunctional Requirements	12
3.4.1	Performance Requirements	12
3.4.2	Safety Requirements	12
3.4.3	Security Requirements	13
3.4.4	Software Quality Attributes	13
3.5	System Requirements	13
3.5.1	Dataset and Storage Requirements	13
3.5.2	Software Requirements	13
3.5.3	Hardware Requirements	14

3.6	Development Methodology	14
3.6.1	Database Requirements	14
3.7	Analysis Models: SDLC Model to be applied	15
4	System Design	16
4.1	System Architecture	17
4.1.1	Layers in the System	17
4.2	Mathematical Model	18
4.3	Data Flow Diagram (DFD)	18
4.4	Class Diagram	19
4.5	Sequence Diagram	20
5	Project Estimate	21
5.1	Reconciled Estimates	22
5.1.1	Development Phase (Estimated Duration: 15-20 Weeks)	22
5.1.2	Deployment Phase (Estimated Duration: 2-3 Weeks)	23
5.2	Project Resources	24
5.3	Risk Management	25
5.3.1	Risk Analysis	25
5.3.2	Overview of Risk Mitigation, Monitoring, Management	25
6	Project Implementation	26
6.1	Overview of Project Modules	27
6.2	Tools and Technologies Used	27
6.3	Algorithm Details	28
6.3.1	XGBoost Algorithm	28
6.3.2	Random Forest Algorithm	28
7	Software Testing	29
7.1	Type of Testing	30
7.2	Test Cases & Test Results	30
8	Results	32
8.1	Outcomes	33
8.2	Screen Shots	33
9	Conclusions	36
9.0.1	Future Work	37
9.1	Applications	38

10 Appendix	39
10.1 Appendix A	40
10.2 Appendix B	41
10.3 Appendix C	42
11 References	43

LIST OF ABBREVIATIONS

ABBREVIATION	ILLUSTRATION
SVM	Support Vector Machine
API	Application Programming Interface
ROUGE	Recall-Oriented Understudy for Gisting Evaluation
BLEU	Bilingual Evaluation Understudy
TF-IDF	Term Frequency-Inverse Document Frequency
RNN	Recurrent Neural Network

List of Figures

3.1	Iterative Waterfall Model Applied in the Project	15
4.1	Architecture Diagram	17
4.2	Data Flow Diagram	18
4.3	Class Diagram	19
4.4	Sequence Diagram	20
8.1	Home Page	33
8.2	SignUP Page	34
8.3	Login Page	34
8.4	Legitimate URL	35
8.5	Phishing URL	35

CHAPTER 1

INTRODUCTION

1.1 Overview

With the increasing number of online services, phishing attacks have become one of the most common and dangerous cyber threats. Phishing websites are crafted to mimic legitimate ones to deceive users and extract sensitive data such as usernames, passwords, or credit card details. Traditional blacklist-based and rule-based detection methods fall short in detecting new and evolving phishing attacks. This project proposes a machine learning-based approach to detect phishing websites by analyzing URL features, domain information, and content-based indicators. Multiple ML models are explored and integrated into a real-time detection system that classifies URLs as legitimate or phishing.

1.2 Motivation

Phishing attacks continue to pose a serious and evolving threat in today's digital world, targeting both individuals and organizations. As technology advances, cybercriminals are employing more sophisticated tactics, making phishing schemes increasingly difficult to detect. The potential consequences of successful phishing attack—ranging from financial loss and data breaches to reputational damage—underscore the critical need for robust detection and prevention mechanisms. This ever-growing threat requires heightened attention, as it not only impacts the security of personal and corporate information but also challenges the trust that users place in online interactions. Given the dynamic nature of phishing tactics, it is essential to stay ahead by continuously refining detection strategies. This report aims to motivate a deeper exploration of existing approaches to phishing detection, with a focus on developing more resilient, adaptive solutions. By understanding the strengths and limitations of current methods, as well as identifying gaps in the research, we can enhance our ability to combat phishing attacks and better protect users in an increasingly digital world.

1.3 Problem Definition and Objectives

1.3.1 Problem

Despite the availability of various phishing detection methods, the evolving nature of phishing tactics presents substantial challenges in effectively identifying and mitigating these threats. Current solutions can be categorized into list-based, similarity-based, and machine learning-based approaches, each with its own advantages and limitations. However, many existing methods rely on outdated datasets, lack real-time detection capabilities, or fail to address the dynamic strategies employed by attackers. Furthermore, there are significant research gaps regarding the integration of different detection methodologies and the exploration of user behaviour analytics. This paper aims to address these issues by reviewing the state of the art in phishing detection, assessing the effectiveness of current approaches, and identifying key areas for future research.

1.3.2 Objectives

- Develop a phishing detection system using machine learning.
- Extract relevant URL-based, domain-based, and content-based features.
- Compare various ML models (e.g., Random Forest, XGBoost, SVM, Neural Networks).
- Build a web-based interface for real-time URL classification.
- Address challenges such as class imbalance and adversarial evasion.

1.4 Project Scope and Limitations

1.4.1 Scope

- Collection and preprocessing of phishing and legitimate URLs.

- Feature extraction from URLs, WHOIS data, and webpage content.
- Model training, evaluation, and deployment using Flask and React.
- Integration with real-time systems for detection and alert generation.

1.4.2 Limitations

- Some content-based features require webpage rendering, increasing latency.
- Adversarial attacks may still bypass the model.
- Real-time detection models must balance speed and accuracy.

1.5 Methodologies of Problem Solving

- **Data Collection:** Gathering datasets from PhishTank, OpenPhish, Alexa Top Sites, etc.
- **Preprocessing:** Cleaning URLs, extracting domain and content features.
- **Feature Engineering:** Selection of relevant features including length, symbols, presence of HTTPS, domain age, etc.
- **Model Training:** Evaluating ML algorithms like XGBoost, SVM, and Neural Networks.
- **Real-Time Deployment:** Flask API integrated with a React frontend for user input and model predictions.
- **Evaluation:** Using metrics like accuracy, precision, recall, F1-score, and AUC-ROC to measure model performance.

CHAPTER 2

LITERATURE SURVEY

1.1 Phishing Website Detection Techniques

Phishing website detection is an essential task in cybersecurity, aimed at identifying malicious websites designed to deceive users into disclosing sensitive information. Three primary approaches are commonly used for detecting phishing websites: Feature-Based Analysis, Machine Learning Algorithms, and Hybrid Approaches.

- **Feature-Based Analysis:** This approach involves identifying specific URL and webpage features that are characteristic of phishing sites, such as URL length, use of special symbols, redirection, and HTTPS protocols. These features help differentiate legitimate sites from phishing ones.
- **Examples of Feature Extraction Techniques:**
 - **Keyword-Based Analysis:** Extract keywords or patterns often found in phishing URLs.
 - **URL Structure Analysis:** Analyze the URL structure to identify suspicious patterns.
- **Machine Learning Algorithms:** Using machine learning techniques, phishing websites can be detected by training models on large datasets containing both phishing and legitimate URLs. Common algorithms used include Random Forest, Decision Tree, SVM, and XGBoost, which can efficiently classify websites based on extracted features.
- **Examples of Machine Learning Algorithms:**
 - **Random Forest:** These models, based on Recurrent Neural Networks (RNNs), generate text by learning sentence structures.
 - **XGBoost:** A powerful boosting algorithm effective in phishing detection tasks.

2.2 Phishing Website Detection Challenges

Phishing website detection presents several challenges due to the constantly evolving nature of phishing tactics and the variety of techniques used by attackers:

- **Data Quality:** Inconsistent or limited data can affect the reliability of machine learning models. Access to extensive, up-to-date datasets is crucial for accurate detection.
- **Feature Selection:** Selecting the right features is critical for model accuracy. However, phishing websites may use diverse techniques, making it challenging to identify effective, universal features.
- **Class Imbalance:** Phishing datasets are often imbalanced, with legitimate URLs outnumbering phishing URLs, which can impact model performance.
- **Real-Time Detection:** Phishing attacks are time-sensitive, so efficient and fast processing is needed for real-time protection.

2.3 Existing Systems and Models

Several tools and frameworks have been developed to detect phishing websites, utilizing various machine learning models and techniques:

- **PhishTank API:** An open-source platform for detecting phishing sites, providing a constantly updated database of known phishing URLs that can be used for model training and validation.
- **URLNet:** A neural network-based approach that detects phishing websites by analyzing URLs and extracting meaningful features, showing high accuracy in phishing detection.

2.4 Key Research Studies

- **“Machine Learning Approaches to Phishing Detection”:** This study compares different machine learning algorithms (SVM, Decision Tree, Random Forest) in phishing detection, demonstrating the high accuracy of ensemble methods like Random Forest.
- **“A Survey on Phishing Detection Techniques Using URL Features”:** This survey reviews various feature-based techniques for phishing detection, emphasizing URL features and their importance in identifying malicious sites.
- **“Evaluating Phishing Detection Models in Real-World Scenarios”:** This paper investigates how well different models perform under real-world conditions, highlighting the need for robust testing methods. Data is obtained by scraping websites like TOS-Dr and TL:DR Legal, which provide datasets as text-summary pairs.
- **PhishNet: A Hybrid Approach for Phishing Detection:** PhishNet integrates feature extraction with machine learning for efficient phishing detection, demonstrating the effectiveness of hybrid models.

2.5 Gaps in Current Research

- Selecting features that generalize well across all phishing tactics remains a challenge. Research is needed on adaptive feature selection techniques.
- The class imbalance in phishing datasets affects model accuracy. Techniques such as data augmentation and synthetic data generation could help.
- Existing models often lack the efficiency needed for real-time phishing detection. Further research on optimizing model speed is necessary.

CHAPTER 3

**SOFTWARE REQUIREMENTS
SPECIFICATION**

3.1 Assumptions and Dependencies

3.1.1 Assumptions

- The URLs provided for analysis are valid and accessible.
- The system assumes that users have an internet connection to input URLs and receive results.
- The tool assumes URLs are in the public domain and do not require authentication or special permissions to access.

3.1.2 Dependencies

- The system relies on third-party libraries and APIs (e.g., machine learning frameworks like TensorFlow, Scikit-learn, NLP libraries like SpaCy, URL analysis APIs).
- Cloud infrastructure is required for model training and storage of phishing detection results.

3.2 Functional Requirements

Table 3.1: System Features Table

System Feature	Description	Input	Output	Criticality
URL and Website Content Analysis	The system should analyze the URL and website content for patterns often found in phishing sites, such as suspicious keywords and unusual URL structures.	URL or website content provided by the user.	A risk score or classification indicating whether the website is likely to be phishing.	High
Machine Learning-Based Detection	The system applies machine learning models trained on features of phishing and legitimate websites to detect phishing attempts.	Website features extracted from the URL and content.	A prediction of whether the website is phishing based on model analysis.	High
Real-Time Detection	The system should detect phishing websites in real time to prevent user access to malicious sites.	URL accessed by the user in real time.	Immediate notification or blocking of access if the website is suspected to be phishing.	High
User Feedback and Reporting	Users should be able to report suspicious websites to improve detection accuracy over time.	User-submitted URL or feedback.	Enhanced detection accuracy and updates to the model with user-reported phishing data.	Medium

3.3 External Interface Requirements

3.3.1 User Interfaces

The application will feature a web-based user interface with a responsive design for both desktop and mobile devices, allowing users to submit URLs for phishing detection and view prediction results.

3.3.2 Hardware Interfaces

The system will be hosted on cloud platforms (Render for backend, Vercel for frontend). It does not require specialized hardware but will need a basic system with at least a 4-core CPU and 8GB RAM for efficient model hosting and real-time prediction.

3.3.3 Software Interfaces

Integration with third-party APIs for additional features, such as WHOIS API for domain information. The system will also use machine learning libraries (scikit-learn, XGBoost) for model training, and MongoDB for optional logging of URLs and prediction results.

3.4 Nonfunctional Requirements

3.4.1 Performance Requirements

- The API should respond within 1 second under normal load.
- Feature extraction and phishing URL prediction must be optimized for real-time response.

3.4.2 Safety Requirements

- URLs submitted should be sandboxed to prevent the execution of malicious content.
- Input validation checks must be in place to prevent script injections and malicious payloads.

3.4.3 Security Requirements

- Use of HTTPS for secure communication between frontend and back-end.
- Input sanitization to prevent XSS, SQL injection, and other security vulnerabilities.
- Optional integration of reCAPTCHA to prevent bot submissions.

3.4.4 Software Quality Attributes

- **Scalability:** The system can scale by hosting APIs on cloud platforms like Render and Vercel.
- **Maintainability:** The codebase is modular, with clear separation between frontend and backend, and well-documented for ease of updates.
- **Usability:** The user interface is simple, intuitive, and provides immediate feedback on URL status.
- **Portability:** The system is portable across platforms supporting Python (Flask) and JavaScript (React).

3.5 System Requirements

3.5.1 Dataset and Storage Requirements

- **Datasets:** PhishTank, Kaggle-based datasets.
- Storage of ML model file (.pkl or .joblib).
- Optional logging of user predictions in MongoDB.

3.5.2 Software Requirements

- **Frontend:** ReactJS, Vercel (UI for URL submission and results)
- **Backend:** Flask, scikit-learn, pandas, XGBoost, joblib, Render (API for prediction and classification)
- **Tools:** VS Code/PyCharm, Git/GitHub, Postman
- **OS:** Windows 10/11 or Ubuntu Linux

3.5.3 Hardware Requirements

A system with an Intel i5 processor, 8 GB RAM, and 256 GB SSD is sufficient for development and testing.

3.6 Development Methodology

Agile methodology was followed with iterative sprints. Each sprint delivered a working module:

- **Sprint 1:** Dataset collection and preprocessing.
- **Sprint 2:** Feature extraction and model training.
- **Sprint 3:** API development and integration.
- **Sprint 4:** Frontend development.
- **Sprint 5:** Testing and deployment.

3.6.1 Database Requirements

While persistent storage is optional, a database can be integrated for logging predictions and user activity.

Recommended Database: MongoDB

- **Type:** NoSQL document database
- **Usage:**
 - Store URLs, predictions, timestamps, and user sessions
- **Advantages:**
 - Schema-less, flexible structure
 - Fast I/O for real-time logging
 - Scalable and easy integration with Flask

3.7 Analysis Models: SDLC Model to be applied




Figure 3.1: Iterative Waterfall Model Applied in the Project

CHAPTER 4

SYSTEM DESIGN

4.1 System Architecture

The architecture of the phishing detection system is divided into several layers to support modularity, real-time prediction, and maintainability.




Figure 4.1: Architecture Diagram

4.1.1 Layers in the System

- **Input Layer:** Users input URLs through the frontend interface.
- **Feature Extraction Layer:** Extracts features from the URL such as:
 - Length, use of HTTPS, special characters.
 - Domain-related features like age, WHOIS info.
 - Content-based (optional): e.g., JavaScript usage, form actions.
- **Machine Learning Layer:** Preprocessed features are passed to an ML model (Random Forest/XGBoost/SVM) for prediction.
- **API Layer:** Flask API receives features, passes them to the model, and returns results to the frontend.
- **Output Layer:** Frontend displays result to the user as “Phishing” or “Legitimate”, with additional risk insights if enabled.

4.2 Mathematical Model

Let the system be modeled as a function:

$$f(x) \rightarrow y$$

Where:

- x = vector of extracted features (URL length, domain age, etc.)
- y = output class $\in \{0 : \text{Legitimate}, 1 : \text{Phishing}\}$

The ML model (Random Forest and XGBoost) is trained to minimize loss:

$$L(y, \hat{y}) = \frac{1}{n} \sum_{i=1}^n \text{Loss}(y_i, \hat{y}_i)$$

Where $\hat{y}$ is the predicted label and y is the ground truth.

4.3 Data Flow Diagram (DFD)




Figure 4.2: Data Flow Diagram

4.4 Class Diagram




Figure 4.3: Class Diagram

4.5 Sequence Diagram




Figure 4.4: Sequence Diagram

CHAPTER 5

PROJECT ESTIMATE

5.1 Reconciled Estimates

The development and deployment timelines are based on available resources and technologies, with inherent uncertainties. Below is the estimated timeline for the different phases of the project.

5.1.1 Development Phase (Estimated Duration: 15-20 Weeks)

- **Requirement Analysis & Research (2-3 weeks):**
 - Gathering data on phishing URL patterns, domain features, and malicious indicators.
 - Understanding the key objectives for phishing website detection using machine learning.
- **System Architecture Design (2-3 weeks):**
 - Designing the system architecture, including backend integration (Flask), frontend development (React), and database setup (MongoDB).
 - Defining how machine learning models (e.g., Random Forest, XG-Boost) will be integrated with the backend.
- **Data Collection & Preprocessing (3-4 weeks):**
 - Collecting labeled datasets of phishing and legitimate URLs.
 - Cleaning, tokenizing, and preprocessing the data, including handling class imbalance.
- **Model Development & Testing (4-6 weeks):**
 - Developing machine learning models for phishing detection and evaluating them using metrics like accuracy, precision, and recall.
 - Testing models on validation datasets and fine-tuning for better performance.
- **Frontend & Backend Development (4-5 weeks):**
 - Developing the React-based frontend for user interaction (URL input and phishing classification results).

- Integrating the trained machine learning model into the Flask backend for real-time classification.

- **Integration & Testing (2-3 weeks):**

- Integrating all components (frontend, backend, machine learning model) and performing end-to-end testing.
- Conducting stress testing and performance benchmarking.

5.1.2 Deployment Phase (Estimated Duration: 2-3 Weeks)

- **Local Server Setup (1 week):**

- Setting up a local or on-premises server to host the application.
- Configuring the environment to run the Flask backend, React frontend, and MongoDB database.
- Ensuring that all dependencies (e.g., Python libraries, Node.js) are properly installed and configured.

- **Application Deployment & Configuration (3-5 days):**

- Deploying the Flask backend and React frontend on the local server or on-premises infrastructure.
- Configuring the necessary environment variables, ensuring the communication between the frontend, backend, and database is secure and functional.
- Ensuring proper routing and load handling for efficient data processing.

- **Post-Deployment Testing & Monitoring (2-3 days):**

- Running final end-to-end tests to ensure that the entire system works as expected after deployment.
- Setting up local monitoring tools (e.g., logging, error tracking) to detect issues and ensure the system performs as required.
- Verifying the application's stability and scaling capabilities on the local setup under real-time traffic conditions.

5.2 Project Resources

The project will be carried out by a small team, utilizing personal and laboratory resources.

- **Personnel:**
 - Machine Learning Engineer (to handle model development and testing).
 - Backend Developer (to integrate the model with Flask).
 - Frontend Developer (to design and implement the React-based interface).
 - Database Administrator (for managing MongoDB).
- **Tools/Technologies:**
 - Python, Flask, React, MongoDB, scikit-learn, TensorFlow/PyTorch.
- **Hardware:**
 - GPU-enabled systems for model training and development.
- **Software:**
 - Git for version control, Jupyter Notebooks for experimentation.

5.3 Risk Management

- Risk Identification: Data quality issues, false negatives, model overfitting, evolving phishing techniques.

5.3.1 Risk Analysis

- False negatives can lead to severe security breaches.
- Data imbalance may affect model performance, requiring techniques like SMOTE.

5.3.2 Overview of Risk Mitigation, Monitoring, Management

- Data validation and preprocessing.
- Threshold tuning and regular model evaluation to minimize false negatives.
- Continuous monitoring and retraining with updated data.
- Backtesting predictions against real-world phishing sites.

CHAPTER 6

PROJECT IMPLEMENTATION

6.1 Overview of Project Modules

- **Data Collection and Preprocessing:** Gather and clean labeled URL datasets, extract features like URL length, domain age, and suspicious keywords.
- **Feature Engineering:** Select relevant features from raw URLs for model input.
- **Model Training and Evaluation:** Train models (e.g., Random Forest, SVM) and evaluate using metrics like accuracy and F1-score.
- **Backend Integration:** Integrate the trained model with Flask for real-time URL classification.
- **Frontend Development:** Develop a React-based UI for user URL input and phishing detection results.
- **Database Integration:** Use MongoDB to store URLs and results for future analysis.

6.2 Tools and Technologies Used

- **Python:** Used for implementing machine learning and preprocessing.
- **scikit-learn, TensorFlow/PyTorch:** Libraries for training machine learning models.
- **Flask:** Backend framework for URL classification.
- **MongoDB:** NoSQL database for storing URL data.
- **React:** Used to build the frontend interface.
- **Jupyter Notebooks:** For model experimentation and analysis.
- **Git:** Version control for code management.

6.3 Algorithm Details

6.3.1 XGBoost Algorithm

XGBoost (Extreme Gradient Boosting) is a powerful ensemble learning algorithm that builds a sequence of decision trees where each new tree tries to correct the errors made by the previous ones. It is based on the gradient boosting framework and uses second-order derivatives for better optimization and convergence. XGBoost is highly efficient, scalable, and includes regularization techniques to reduce overfitting, making it suitable for handling complex, high-dimensional phishing data. In this project, XGBoost is used to classify URLs by learning patterns from various features like URL length, presence of symbols, domain info, and keyword usage.

6.3.2 Random Forest Algorithm

Random Forest is an ensemble learning method that constructs multiple decision trees during training and outputs the class that is the mode of the classes predicted by individual trees. It operates by randomly selecting subsets of data and features, which promotes model diversity and reduces overfitting. The randomness and majority voting mechanism make Random Forest robust and accurate, even on noisy or imbalanced datasets. In the context of phishing detection, it helps capture various patterns and anomalies in URLs through a collection of diverse decision trees, enhancing the reliability of classification.

CHAPTER 7

SOFTWARE TESTING

7.1 Type of Testing

- **Unit Testing:** Testing individual components like data preprocessing functions, URL feature extraction, and machine learning model training to ensure correctness.
- **Integration Testing:** Verifying that the integration between the back-end (Flask), database (MongoDB), and machine learning model works smoothly, including data flow and retrieval.
- **Functional Testing:** Testing the functionality of the web application by ensuring the phishing detection system classifies URLs correctly.
- **Performance Testing:** Measuring the performance of the model, especially its speed and accuracy when processing large datasets of URLs.
- **Security Testing:** Ensuring that the application is resistant to common web application vulnerabilities, especially to prevent malicious attacks targeting the detection system.

7.2 Test Cases & Test Results

- **Test Case 1: Model Classification Accuracy**
 - **Description:** Test the classification accuracy of the model on a validation dataset.
 - **Expected Result:** The model should correctly classify phishing URLs with at least 90
 - **Test Result:** 92
- **Test Case 2: False Positives and False Negatives**
 - **Description:** Evaluate the false positive and false negative rates of the model.
 - **Expected Result:** The false positive rate should be below 5
 - **Test Result:** False positive rate of 4.5
- **Test Case 3: URL Feature Extraction**
 - **Description:** Verify the feature extraction process for URLs.

- **Expected Result:** The correct features (e.g., URL length, domain age, etc.) are extracted and passed to the model.
- **Test Result:** All features were correctly extracted from a sample set of URLs.
- **Test Case 4: Web Application Functionality**
 - **Description:** Test the functionality of the web interface for inputting URLs and receiving phishing classification results.
 - **Expected Result:** The user should be able to input a URL, and the system should display whether the URL is phishing or not.
 - **Test Result:** The web interface functions correctly with no errors.
- **Test Case 5: Load Testing for Model Response Time**
 - **Description:** Measure the response time of the model when processing a batch of URLs.
 - **Expected Result:** The model should respond within 2 seconds for each URL.
 - **Test Result:** The model responded within 1.5 seconds for each URL, ensuring fast performance.

CHAPTER 8

RESULTS

8.1 Outcomes

The successful implementation of the project resulted in a robust system capable of accurately detecting phishing websites using machine learning techniques. It provides users with real-time predictions based on URL features, helping prevent access to malicious sites. The system enhances cybersecurity awareness, minimizes the risk of phishing attacks, and demonstrates the effectiveness of ML algorithms like XGBoost and Random Forest in detecting online threats.

8.2 Screen Shots






Figure 8.1: Home Page



A sign-up form titled "Sign Up" is centered on a light blue background. The form is a light gray rounded rectangle containing three input fields: "Full Name", "Email", and "Password". Below these fields is a green "Register" button. At the bottom of the form, it says "Already have an account? [Login](#)".

Figure 8.2: SignUP Page



A login form titled "Login" is centered on a light blue background. The form is a light gray rounded rectangle containing two input fields: "Email" and "Password". Below these fields is a green "Login" button. At the bottom of the form, it says "Don't have an account? [Sign up](#)".

Figure 8.3: Login Page




Figure 8.4: Legitimate URL




Figure 8.5: Phishing URL

CHAPTER 9

CONCLUSIONS

The project "*Phishing Website Detection Using Machine Learning*" addresses the rising threat of phishing attacks by utilizing data-driven models to classify URLs as either legitimate or phishing. By employing algorithms like XGBoost and Random Forest, the system achieves efficient and accurate classification based on multiple extracted features. The project demonstrates the effectiveness of machine learning in cybersecurity, particularly for real-time phishing detection in web applications.

The developed solution offers the following benefits:

- **High Detection Accuracy:** Machine learning models provide reliable detection performance using extracted URL features.
- **Real-Time Prediction:** The system enables instant prediction and feedback to users.
- **Scalability:** The cloud-deployed architecture supports scalability for widespread use.
- **Security Enhancement:** Early phishing detection helps protect users from credential theft and financial loss.
- **User-Friendly Interface:** A clean, responsive frontend allows easy URL submission and results visualization.

9.0.1 Future Work

Future scope of the project includes:

- Integration of deep learning models (e.g., LSTM or BERT) for improved detection from URL and textual content.
- Expansion to multilingual phishing detection by analyzing website content.
- Real-time threat intelligence by integrating data from WHOIS, blacklist APIs, and domain registrars.
- User account system for tracking predictions and maintaining history.
- Browser extension for on-the-fly phishing detection while browsing.

9.1 Applications

The system has wide applicability across various domains:

- **Email Security:** Can be integrated into email gateways for phishing email filtering.
- **Browser Extensions:** Useful as an extension to detect phishing URLs in real time.
- **Enterprise Security:** Corporates can integrate the system into internal networks to block suspicious URLs.
- **Educational Institutions:** Helps educate students and staff about phishing and test awareness.
- **Cybersecurity Research:** Serves as a base model for experimenting with advanced phishing detection techniques.

CHAPTER 10

APPENDIX

10.1 Appendix A

Problem Statement Feasibility Assessment:

The core objective of this project is to classify a given URL as either phishing or legitimate using machine learning models. From a theoretical standpoint in computational complexity:

- **P Class:** The problem of classifying URLs using trained models (like Random Forest or XGBoost) lies in the class P, as both feature extraction and prediction can be performed in polynomial time with respect to the size of the input (number of URLs and their features).
- **NP Class:** NP problems are those for which a proposed solution can be verified in polynomial time. If we consider a heuristic rule-based phishing detection system, verifying whether a specific rule-set correctly classifies a URL could fall under NP. However, in practice, machine learning avoids explicit search over all possible rules.
- **NP-Complete:** Problems in NP-Complete are both in NP and as hard as any problem in NP. Designing an optimal rule-based phishing detection mechanism or finding the smallest subset of features that guarantees the highest accuracy may be NP-Complete, especially when modeled as optimization problems (e.g., feature subset selection).
- **NP-Hard:** These problems are at least as hard as the hardest problems in NP, but not necessarily verifiable in polynomial time. Certain generalized formulations, like finding the globally optimal decision tree or modeling phishing detection as a SAT problem, may fall under NP-Hard. However, such formulations are not practically implemented due to complexity and scalability constraints.

10.2 Appendix B

Paper Publication Details:

- **Title:** Phishing Website Detection Using Machine Learning
- **Published In:** International Journal of Scientific Research in Engineering and Management (IJSREM)
- **Volume/Issue:** Volume 09, Issue 03 — March 2025
- **ISSN:** 2582-3930

10.3 Appendix C

Plagiarism Report of project report.

CHAPTER 11

REFERENCES

- [1] Ali, S., et al. "Phishing Detection Using Machine Learning: An Experimental Study." *Journal of Cyber Security*, 2020.
- [2] - Abdelhamid, N., et al. "Phishing Detection Based on Machine Learning Algorithms." *Neural Computing and Applications*, 2017.
- [3] Prof. Dipika Raigar, Divya Khandare, Atharva Dharrao, Akash Jadhav, Gaurav Mahadik "Phishing Website Detection Using ML"
- [4] Dheeru, D., Karra Taniskidou, E. "UCI Machine Learning Repository: Phishing Websites Data Set." *University of California, Irvine*, 2017.
- [5] El, A. K., et al. "Phishing Website Detection Using Machine Learning." *Mendeley Data*, 2020.
- [6] PhishTank. "PhishTank Real-Time Phishing Data." *PhishTank*, 2021.
- [7] Mohaisen, A., Alrawi, O. "Heuristic Methods for Phishing Detection: A Survey." *IEEE Transactions on Cybersecurity*, 2020.
- [8] Gupta, A., Patel, V. "A Study on Phishing Detection Using Decision Trees." *Journal of Cybersecurity*, 2020.
- [9] Panwar, S., Sharma, N. "Ensemble Learning for Phishing Detection: A Comprehensive Study." *Journal of Internet Services*, 2020.
- [10] Patil, K., et al. "SVM for Phishing Website Detection." *Journal of Information Security*, 2019.
- [11] Huang, Y., et al. "Deep Learning for Phishing Detection: A Comparative Study." *IEEE Access*, 2020.
- [12] Yadav, N., et al. "Phishing Website Detection Using Neural Networks." *Journal of Computer Security*, 2019.
- [13] Jain, A., et al. "A Study on Ensemble Methods for Phishing Detection." *Computer Networks*, 2020.
- [14] Chawla, N. V., et al. "SMOTE: Synthetic Minority Over-sampling Technique." *Journal of Artificial Intelligence Research*, 2019.
- [15] - Goodfellow, I., et al. "Adversarial Attacks and Defenses in Machine Learning." *Journal of Cybersecurity*, 2019.

- [16] Verma, R., et al. "Real-Time Phishing Detection: Challenges and Opportunities." *IEEE Transactions on Information Forensics and Security*, 2018.
- [17] A. Mukherjee, B. Bhattacharya, and A. Bandyopadhyay, "A Survey of Machine Learning Techniques for Phishing Detection," *International Journal of Computer Applications*, vol. 975, no. 8887, 2019.
- [18] R. Verma and A. Das, "Phish-Alert: A Machine Learning Based Approach for Phishing URL Detection," in *Proceedings of the 2017 IEEE International Conference on Big Data (Big Data)*, pp. 1173-1182, 2017, IEEE. doi: 10.1109/BigData.2017.8258034.

LIST OF ABBREVIATIONS

Abbreviation	Illustration
VPN	Virtual Private Network
IP	Internet Protocol
IDS	Intrusion Detection System
TCP	Transmission Control Protocol