

K.G. feature test cases

Contribution for J.L. to merge into TP1 Test Cases.pdf; not the full team catalog

Executed 17 September 2026: 193 checks passed, 0 failed: 35 K.G. database checks, 19 controller/view checks, 7 invitation-boundary checks, plus the existing six-class team regression suite (132 checks). The entire supplied application compiles with these changes.

Environment: Windows, JDK 25 compiling for Java 22, JavaFX 21.0.8 (Windows), H2 2.3.232. Tests use isolated in-memory H2 databases and offscreen JavaFX scene renders. No personal or production database was used.

Database tests: confirmation and authorization

IDs	Setup / action	Expected result
D01-D02	Register users, then authenticate an admin.	Registration alone has no authority; correct admin credentials establish it.
D03	Pass confirmed=false for an existing member.	CANCELLED; all three records remain.
D04	Pass target ID 0.	NO_SELECTION; no deletion.
D05-D06	Delete the actor ID, before/after reading member details.	SELF_PROTECTED; details cache cannot replace session identity.
D07-D09	Try deletion/listing as member or logged-out caller.	Unauthorized actions do not mutate accounts.
D10	Delete an unknown positive ID.	NOT_FOUND.
D11	Confirm a real member account.	Only the selected row is removed.
D12-D14	Use removed credentials and fetch removed details.	Authentication, all role logins and lookup return false.
D15-D16	Repeat delete, then recreate same username and use old ID.	Old ID cannot remove any replacement record.
D17-D18	Delete another admin; then try to delete the remaining actor.	Other admin is removed; sole actor is protected.

Failure, boundaries and UI tests

The code includes explicit assertions and exits unsuccessfully if a check fails

IDs	Setup / action	Expected result
D19-D20	Close and reopen connection to retained in-memory test DB.	Deletion remains; authorization is cleared.
D21	Authenticate, then enter a wrong password.	Failed login clears prior authority.
D22-D25	Use length 33 username, length 65 password, nulls and SQL-like username.	Inputs rejected before unauthorized access; accounts remain.
D26	Revoke actor admin role through another connection.	Role is reread; deletion denied.
D27-D28	Add FK dependency so DELETE fails; remove FK and retry.	Failure rolls back; next transaction works.
D30-D32	Rename the authenticated admin and update the password.	Stable ID still prevents self-deletion; new credentials work and old ones fail.
D29	Release two threads to delete one another's admin accounts.	Exactly one deletion succeeds; an admin remains.

Controller and JavaFX checks

IDs	What is checked
V01-V02	Null selection does not prompt. No preserves the account.
V03-V05	Delete starts disabled; selector is not editable; selecting an account enables Delete.
V06-V08	Dialog says Are you sure? and names target/ID. Yes is not default. No is default and cancel.
V09-V10	Confirmed controller action removes the captured account; clearing selection disables Delete.
V11 (7 outcomes)	Each database outcome maps to a nonblank explanatory message.
D33-D35	Legacy deletion rejects logged-out/self calls; deleting an OTP-enabled user removes OTP access.
V13	Selected account details from the team interface remain visible.
V12	The implemented login scene has the shared stylesheet attached.
I1-I7	Invitation input: null, empty and whitespace rejected; lengths 1, 6 and 10 accepted by the size guard; length 11 rejected. Existence is checked separately by the existing workflow.

Run evidence and final checks

Executable scripts, raw results and a manual integration checklist

Reproduce the automated run

From TP1 in PowerShell, run `.\test.ps1`. It compiles the application and tests, then runs `database.DeletionTests`, `guiDeleteUser.DeletionViewTests` and `guiUserLogin.LoginInputTests`, then the existing `testingAutomation.TP1RegressionSuite`. Use a JDK version 22 or newer. The bundled dependency JARs target Windows.

Raw output is in `TP1/build/reports/database-tests.txt`, `view-tests.txt` and `invitation-tests.txt`, plus `team-regression.txt`. Scene renders are in the same folder. The script regenerates all of these. A pre-existing module-name warning and JavaFX/JDK native/deprecation warnings do not cause test failures.

Manual checks still required before the team submission

Check	Steps / expected evidence
M01 Actual desktop dialog	Run the app, open Delete a User, select a disposable member and choose No. Repeat with Escape and window close. Confirm the account and count remain unchanged.
M02 Confirmed removal	Choose Yes. Verify the success message, refreshed selector and lower Admin Home count. Log out and confirm the removed credentials fail.
M03 Self-protection	Select the signed-in admin and choose Yes. Verify the protection message and continued access. Repeat when another admin also exists.
M04 Existing flows	Create the first admin; create an invited account; log out/in; switch roles; open account details; visit role-management and other merged screens. Check layout, keyboard focus and unchanged expected behavior.
M05 Team regression	The latest teammate features are merged and all 132 team checks pass. Perform the desktop OTP/reset and list-user workflows together before recording the final demonstration.

Evidence boundary: these automated checks do not claim a human desktop walkthrough, full application security review, persistent-file restart test, recorded screencast, or successful Canvas submission. D19 verifies reconnect against an H2 database kept alive in memory; the application's run script uses a separate persistent project-local file database.

Input-validation contribution

Deletion introduces no free-text field: it uses a read-only database selection and rejects absent/invalid IDs. Login fields redesigned by K.G. are bounded before use (username 32, password 64, invitation 10). Full password policy, all other field rules and the team-wide coverage map remain with their assigned owners.