Name - Vipin Rawat University Roll No - 1121169 Subject Code - PBC-602
Subject Name - Computer Graphics and Animation

Ans:1-

```
#include <stdio.h>
#include <graphics.h>
int main()
{
int round (float num)
{
return num<0 ? num-0.5 : num+0.5;
}
int x1=100, x2=300, y1=100, y2=200;
int gd = DETECT, gm;
float pk, pk, x, y, step;
int dx = x2-x1;
int dy = y2-y1;
pk = 2*dx-dy;
if (dx>dy)
step = dx;
else
step = dy;
initgraph (&gd,&gm,"");
outtextxy (x1,y2, "A");
outtextxy (x2,y2, "B");
putpixel (x1,y1, WHITE);
x=x1, y=y1;
while (step>0)
{
```

```
if(pk<0)
{
pkk=pk+2*dy;
}
else
{
pkk = pk+2*dy-2*dx;
 y++;
}
putpixel(sou(x),sou(y), WHITE);
 x++;
step--;
 }
getch();
return 0;
}
```

```
@gehu-HP-EliteDesk-800-G2-SFF:~/Desktop/Vatsal_G$ gcc bres_line.c -o bres
ph
@gehu-HP-EliteDesk-800-G2-SFF:~/Desktop/Vatsal_G$ ./bress
inates of first point:
the value of x1: 100
the value of y1: 100
inates of second point:
the value of x2: 265
the value of y2: 275
```

SDL-libgraph -- Graphics on GNU/Linux



Ag Bresenham's line Algorithm :-

Step1: Start algorithm

Step2: Declare variable $x_1, x_2, y_1, y_2, i_1, i_2, dx, dy$

Step3: Enter value of x_1, y_1, y_2, x_2

where x_1, y_1 are coordinates of starting point

and x_2, y_2 are coordinates of ending point

Step4: Calculate $dx = x_2 - x_1$

Calculate $dy = y_2 - y_1$

Calculate $i_1 = 2 * dy$

Calculate $i_2 = 2 * (dy - dx)$

Calculate $d = i_1 - dx$

Step5: Consider (x,y) as starting point and x_end as maximum possible value of x

If $dx < 0$

then $x = x_2$

$y = y_2$

$x_{end} = x_1$

If $dx > 0$

then $x = x_1$

$y = y_1$

$x_{end} = x_2$

Step6: Generate point at (x,y) coordinates.

Step7: check if whole line is generated.

If $x >= x\_end$

Stop.

Step8: calculate coordinates of the next pixel

If $d < 0$

then $d = d + i_1$

If $d > 0$

then $d = d + i_2$

increment $y = y + 1$

Step9: Increment $x = x + 1$

Step10: Draw a point of latest (x,y) coordinates

Step11: go to Step 7

Step12: end of algorithm