

Spring Data JPA - Quick Example

Mentioning only those programs where changes are made inside them from the code given in the Hands on.

Country.java:

```
package com.cognizant.ormlearn.model;

import javax.persistence.Column;
import javax.persistence.Entity;
import javax.persistence.Id;
import javax.persistence.Table;

@Entity
@Table(name="country")
public class Country {

    @Id
    @Column(name="co_code")
    private String code;

    @Column(name="co_name")
    private String name;

    public String getCode() {
        return code;
    }

    public void setCode(String code) {
        this.code = code;
    }

    public String getName() {
        return name;
    }

    public void setName(String name) {
        this.name = name;
    }

    @Override
    public String toString() {
        return "Country [code=" + code + ", name=" + name + "]";
    }
}
```

CountryService.java:

```
package com.cognizant.ormlearn.service;

import java.util.List;
import org.springframework.beans.factory.annotation.Autowired;
import org.springframework.stereotype.Service;
import org.springframework.transaction.annotation.Transactional;
import com.cognizant.ormlearn.model.Country;
import com.cognizant.ormlearn.repository.CountryRepository;

@Service
public class CountryService {

    @Autowired
    private CountryRepository countryRepository;

    @Transactional(readOnly = true)
    public List<Country> getAllCountries() {
        return countryRepository.findAll();
    }
}
```

OrmLearnApplication.java:

```
package com.cognizant.ormlearn;

import java.util.List;
import org.slf4j.Logger;
import org.slf4j.LoggerFactory;
import org.springframework.boot.SpringApplication;
import org.springframework.boot.autoconfigure.SpringBootApplication;
import org.springframework.context.ApplicationContext;
import com.cognizant.ormlearn.model.Country;
import com.cognizant.ormlearn.service.CountryService;

@SpringBootApplication
public class OrmLearnApplication {

    private static final Logger LOGGER = LoggerFactory.getLogger(OrmLearnApplication.class);
    private static CountryService countryService;

    public static void main(String[] args) {
        ApplicationContext context = SpringApplication.run(OrmLearnApplication.class, args);
        countryService = context.getBean(CountryService.class);

        LOGGER.info("Inside main");
        testGetAllCountries();
    }

    private static void testGetAllCountries() {
        LOGGER.info("Start");
        List<Country> countries = countryService.getAllCountries();
        LOGGER.debug("countries={}", countries);
    }
}
```

```
    LOGGER.info("End");  
  }  
}
```

Output:

```
[INFO] -----  
[INFO] BUILD SUCCESS  
[INFO] -----  
[INFO] Total time: 3.108 s  
[INFO] Finished at: 2026-06-25T17:11:56+05:30  
[INFO] -----
```