
```
% =====
% ass3_q2.m
% =====
%
% This assignment will introduce you to the idea of first building an
% occupancy grid then using that grid to estimate a robot's motion
% using a
% particle filter.
%
% There are three questions to complete (5 marks each):
%
%   Question 1: see ass3_q1.m
%   Question 2: code particle filter to localize from known map
%
% Fill in the required sections of this script with your code, run it
% to
% generate the requested plot/movie, then paste the plots into a short
% report
% that includes a few comments about what you've observed.  Append
% your
% version of this script to the report.  Hand in the report as a PDF
% file
% and the two resulting AVI files from Questions 1 and 2.
%
% requires: basic Matlab, 'gazebo.mat', 'occmmap.mat'
%
% T D Barfoot, January 2016
%
clear;
clc;
close all

% set random seed for repeatability
rng(1);

% =====
% load the dataset from file
% =====
%
%   ground truth poses: t_true x_true y_true theta_true
%   odometry measurements: t_odom v_odom omega_odom
%   laser scans: t_laser y_laser
%   laser range limits: r_min_laser r_max_laser
%   laser angle limits: phi_min_laser phi_max_laser
%
load gazebo.mat;

% =====
% load the occupancy map from question 1 from file
% =====
%   ogres: resolution of occ grid
%   ogxmin: minimum x value
```

```

% ogxmax: maximum x value
% ogymin: minimum y value
% ogymax: maximum y value
% ognx: number of cells in x direction
% ognx: number of cells in y direction
% oglo: occupancy grid in log-odds format
% ogp: occupancy grid in probability format
load occmap.mat;

%
=====
% Question 2: localization from an occupancy grid map using particle
filter
%
=====
%
% Write a particle filter localization algorithm to localize from the
laser
% rangefinder readings, wheel odometry, and the occupancy grid map you
built in Question 1. We will only use two laser scan lines at the
% extreme left and right of the field of view, to demonstrate that the
algorithm does not need a lot of information to localize fairly
well. To
% make the problem harder, the below lines add noise to the wheel
odometry
% and to the laser scans. You can watch the movie "ass2_q2_soln.mp4"
to
% see what the results should look like. The plot "ass2_q2_soln.png"
shows
% the errors in the estimates produced by wheel odometry alone and by
the
% particle filter look like as compared to ground truth; we can see
that
% the errors are much lower when we use the particle filter.

% interpolate the noise-free ground-truth at the laser timestamps
numodom = size(t_odom,1);
t_interp = linspace(t_true(1),t_true(numodom),numodom);
x_interp = interp1(t_interp,x_true,t_laser);
y_interp = interp1(t_interp,y_true,t_laser);
theta_interp = interp1(t_interp,theta_true,t_laser);
omega_interp = interp1(t_interp,omega_odom,t_laser);

% interpolate the wheel odometry at the laser timestamps and
% add noise to measurements (yes, on purpose to see effect)
v_interp = interp1(t_interp,v_odom,t_laser) +
    0.2*randn(size(t_laser,1),1);
omega_interp = interp1(t_interp,omega_odom,t_laser) +
    0.04*randn(size(t_laser,1),1);

% add noise to the laser range measurements (yes, on purpose to see
effect)
% and precompute some quantities useful to the laser
y_laser = y_laser + 0.1*randn(size(y_laser));

```

```

npoints = size(y_laser,2);
angles = linspace(phi_min_laser, phi_max_laser,npoints);
dx = ogres*cos(angles);
dy = ogres*sin(angles);
y_laser_max = 5;    % don't use laser measurements beyond this distance

% particle filter tuning parameters (yours may be different)
nparticles = 200;    % number of particles
v_noise = 0.2;       % noise on longitudinal speed for propagating
    particle
u_noise = 0.2;       % noise on lateral speed for propagating
    particle
omega_noise = 0.04;  % noise on rotational speed for propagating
    particle
laser_var = 0.5^2;    % variance on laser range distribution
w_gain = 10*sqrt( 2 * pi * laser_var );    % gain on particle weight

% generate an initial cloud of particles
x_particle = x_true(1) + 0.5*randn(nparticles,1);
y_particle = y_true(1) + 0.3*randn(nparticles,1);
theta_particle = theta_true(1) + 0.1*randn(nparticles,1);

% compute a wheel odometry only estimate for comparison to particle
% filter
x_odom_only = x_true(1);
y_odom_only = y_true(1);
theta_odom_only = theta_true(1);

% error variables for final error plots - set the errors to zero at
    the start
pf_err(1) = 0;
wo_err(1) = 0;

% set up the plotting/movie recording
vid = VideoWriter('ass2_q2.avi');
open(vid);
figure(2);
clf;
hold on;
pcolor(ogp);
set(plot( (x_particle-ogxmin)/ogres, (y_particle-ogymin)/ogres, 'g.'
    ), 'MarkerSize',10, 'Color',[0 0.6 0]);
set(plot( (x_odom_only-ogxmin)/ogres, (y_odom_only-ogymin)/ogres, 'r.'
    ), 'MarkerSize',20);
x = (x_interp(1)-ogxmin)/ogres;
y = (y_interp(1)-ogymin)/ogres;
th = theta_interp(1);
r = 0.15/ogres;
set(rectangle( 'Position', [x-r y-r 2*r 2*r], 'Curvature', [1
    1]), 'LineWidth',2, 'FaceColor',[0.35 0.35 0.75]);
set(plot([x x+r*cos(th)], [y y+r*sin(th)]), 'k-','LineWidth',2);
set(plot( (mean(x_particle)-ogxmin)/ogres, (mean(y_particle)-ogymin)/
    ogres, 'g.' ), 'MarkerSize',20);
colormap(1-gray);

```

```

shading('flat');
axis equal;
axis off;
M = getframe;
writeVideo(vid,M);

% loop over laser scans
for i=2:size(t_laser,1)

    % update the wheel-odometry-only algorithm
    dt = t_laser(i) - t_laser(i-1);
    v = v_interp(i);
    omega = omega_interp(i);
    x_odom_only = x_odom_only + dt*v*cos( theta_odom_only );
    y_odom_only = y_odom_only + dt*v*sin( theta_odom_only );
    phi = theta_odom_only + dt*omega;
    while phi > pi
        phi = phi - 2*pi;
    end
    while phi < -pi
        phi = phi + 2*pi;
    end
    theta_odom_only = phi;

    % loop over the particles
    for n=1:nparticles

        % propagate the particle forward in time using wheel odometry
        % (remember to add some unique noise to each particle so they
        % spread out over time)
        v = v_interp(i) + v_noise*randn(1);
        u = u_noise*randn(1);
        omega = omega_interp(i) + omega_noise*randn(1);
        x_particle(n) = x_particle(n) + dt*(v*cos( theta_particle(n) )
- u*sin( theta_particle(n) ));
        y_particle(n) = y_particle(n) + dt*(v*sin( theta_particle(n) )
+ u*cos( theta_particle(n) ));
        phi = theta_particle(n) + dt*omega;
        while phi > pi
            phi = phi - 2*pi;
        end
        while phi < -pi
            phi = phi + 2*pi;
        end
        theta_particle(n) = phi;

        % pose of particle in initial frame
        T = [cos(theta_particle(n)) -sin(theta_particle(n))
x_particle(n); ...
            sin(theta_particle(n)) cos(theta_particle(n))
y_particle(n); ...
0 0 1];

```

```

    % compute the weight for each particle using only 2 laser rays
    % (right=beam 1 and left=beam 640)
    w_particle(n) = 1.0;
    for beam=1:2

        % we will only use the first and last laser ray for
        % localization
        if beam==1 % rightmost beam
            j = 1;
            beam_angle = phi_min_laser;
        elseif beam==2 % leftmost beam
            j = 640;
            beam_angle = phi_max_laser;
        end

        % -----insert your particle filter weight calculation
here -----
        threshold = 0.5;
        if ~isnan(y_laser(i,j))
            row_pos = max(1,round((y_particle(n)-ogymin)/ogres));
            col_pos = max(1,round((x_particle(n)-ogxmin)/ogres));

            y_measurement = y_laser(i,j);
            y_expected     = exp_meas(row_pos, col_pos,
theta_particle(n)...
                , beam_angle, ogp, ogres, threshold, y_laser_max);

            w_particle(n) =
w_gain*w_particle(n)*normpdf(y_measurement,...
                y_expected, sqrt(laser_var));

            end % -----end of your particle filter weight
calculation-----
        end

    end

    % resample the particles using Madow systematic resampling
    w_bounds = cumsum(w_particle)/sum(w_particle);
    w_target = rand(1);
    j = 1;
    for n=1:nparticles
        while w_bounds(j) < w_target
            j = mod(j,nparticles) + 1;
        end
        x_particle_new(n) = x_particle(j);
        y_particle_new(n) = y_particle(j);
        theta_particle_new(n) = theta_particle(j);
        w_target = w_target + 1/nparticles;
        if w_target > 1
            w_target = w_target - 1.0;
            j = 1;
        end
    end
end

```

```

x_particle = x_particle_new;
y_particle = y_particle_new;
theta_particle = theta_particle_new;

% save the translational error for later plotting
pf_err(i) = sqrt( (mean(x_particle) - x_interp(i))^2 +
(mean(y_particle) - y_interp(i))^2 );
wo_err(i) = sqrt( (x_odom_only - x_interp(i))^2 + (y_odom_only -
y_interp(i))^2 );

% plotting
figure(2);
clf;
hold on;
pcolor(ogp);
set(plot( (x_particle-ogxmin)/ogres, (y_particle-ogymin)/
ogres, 'g.' ), 'MarkerSize',10, 'Color',[0 0.6 0]);
set(plot( (x_odom_only-ogxmin)/ogres, (y_odom_only-ogymin)/
ogres, 'r.' ), 'MarkerSize',20);
x = (x_interp(i)-ogxmin)/ogres;
y = (y_interp(i)-ogymin)/ogres;
th = theta_interp(i);
if ~isnan(y_laser(i,1)) & y_laser(i,1) <= y_laser_max
    set(plot([x x+y_laser(i,1)/ogres*cos(th+angles(1))]', [y y
+y_laser(i,1)/ogres*sin(th+angles(1))]', 'm-'), 'LineWidth',1);
end
if ~isnan(y_laser(i,640)) & y_laser(i,640) <= y_laser_max
    set(plot([x x+y_laser(i,640)/ogres*cos(th+angles(640))]', [y y
+y_laser(i,640)/ogres*sin(th+angles(640))]', 'm-'), 'LineWidth',1);
end
r = 0.15/ogres;
set(rectangle( 'Position', [x-r y-r 2*r 2*r], 'Curvature', [1
1]), 'LineWidth',2, 'FaceColor',[0.35 0.35 0.75]);
set(plot([x x+r*cos(th)]', [y y+r*sin(th)]', 'k-'), 'LineWidth',2);
set(plot( (mean(x_particle)-ogxmin)/ogres, (mean(y_particle)-
ogymin)/ogres, 'g.' ), 'MarkerSize',20);
colormap(1-gray);
shading('flat');
axis equal;
axis off;

% save the video frame
M = getframe;
M.cdata = M.cdata(1:343, 1:434, :);
writeVideo(vid,M);

pause(0.01);

end

close(vid);

% final error plots
figure(3);

```

```

clf;
hold on;
plot( t_laser, pf_err, 'g-' );
plot( t_laser, wo_err, 'r-' );
xlabel('t [s]');
ylabel('error [m]');
legend('particle filter', 'odom', 'Location', 'NorthWest');
title('error (estimate-true)');
print -dpng ass2_q2.png

```

custom function definitions

```

% returns the expected laser measurement given the particle's
% position and map
function y_exp = exp_meas(row, col, theta, beam_angle, map, ogres,
    thresh, y_max)

    new_angle = atan2(sin(theta+beam_angle), cos(theta+beam_angle));
    incr = 0;
    r_p = row;
    c_p = col;

    % angle is between -pi/4 and pi/4
    if -pi/4<=new_angle && new_angle<=pi/4
        while r_p>0 && c_p>0 && r_p<=180 && c_p<=300 && map(r_p,
c_p)<thresh
            incr = incr + 1;
            c_p = col + incr;
            r_p = row + round(incr*tan(new_angle));

        end
        y_exp = abs((incr/cos(new_angle))*ogres);

    % angle is between -3pi/4 and 3pi/4
    elseif 3*pi/4<=new_angle || new_angle<=-3*pi/4
        while r_p>0 && c_p>0 && r_p<=180 && c_p<=300 && map(r_p,
c_p)<thresh
            incr = incr + 1;
            c_p = col - incr;
            r_p = row - round(incr*tan(new_angle));

        end
        y_exp = abs((incr/cos(new_angle))*ogres);

    % angle is between pi/4 and 3pi/4
    elseif pi/4<new_angle && new_angle<3*pi/4
        while r_p>0 && c_p>0 && r_p<=180 && c_p<=300 && map(r_p,
c_p)<thresh
            incr = incr + 1;
            r_p = row + incr;
            c_p = col + round(incr/tan(new_angle));

        end
    end

```

```
        y_exp = abs((incr/sin(new_angle))*ogres);

        % angle is between -pi/4 and -3pi/4
    else
        while r_p>0 && c_p>0 && r_p<=180 && c_p<=300 && map(r_p,
c_p)<thresh
            incr = incr + 1;
            r_p = row - incr;
            c_p = col - round(incr/tan(new_angle));
        end
        y_exp = abs((incr/sin(new_angle))*ogres);

    end

end
```

Published with MATLAB® R2020a