Assignment No : 2

//Creating a department tablewithnamebranch.

```
SQL> create table branch(no number(2) PRIMARY KEY, name varchar(10), hod
varchar(10));

Table created.

SQL> desc branch;

 Name                                      Null? Type
 ----------------------------------------- -------- ----------------------------
 NO                                        NOT NULL NUMBER(2)
 NAME                                               VARCHAR2(10)
 HOD                                                VARCHAR2(10)
```

//Entered Values in the branch table.

```
SQL> insert into branch values(&dept_no,'&name','&hod');
Enter value for dept_no: 1
Enter value for name: Computer
Enter value for hod: XYZ
old 1: insert into branch values(&dept_no,'&name','&hod')
new 1: insert into branch values(1,'Computer','XYZ')

1 row created.

SQL> /
Enter value for dept_no: 2
Enter value for name: AiMl
Enter value for hod: ABC
old 1: insert into branch values(&dept_no,'&name','&hod')
new 1: insert into branch values(2,'AiMl','ABC')

1 row created.

SQL> /
Enter value for dept_no: 3
Enter value for name: ENTC
Enter value for hod: QPR
old 1: insert into branch values(&dept_no,'&name','&hod')
new 1: insert into branch values(3,'ENTC','QPR')

1 row created.

SQL> /
Enter value for dept_no: 4
Enter value for name: Mechanical
Enter value for hod: TSD
```

```
old 1: insert into branch values(&dept_no,'&name','&hod')
new 1: insert into branch values(4,'Mechanical','TSD')

1 row created.

SQL> /
Enter value for dept_no: 5
Enter value for name: Electrical
Enter value for hod: TGC
old 1: insert into branch values(&dept_no,'&name','&hod')
new 1: insert into branch values(5,'Electrical','TGC')

1 row created.


SQL> SELECT * FROM branch;


     NO NAME            HOD
---------- --------------- ----------
         1 Computer        XYZ
         2 AiMl            ABC
         3 ENTC            QPR
         4 Mechanical      TSD
         5 Electrical      TGC
```

//Created a student table with name stud22528to store student data.

```
SQL> create table stud22528(rno Number(5) Primary key, name varchar2(20) Not Null,
email varchar(30) UNIQUE,admission_date DATE default sysdate, marks Number(3) default
0,dept_no number(2));

Table created.

SQL> alter table stud22528 add foreign key(dept_no) references branch(dept_no);

Table altered.

SQL> desc stud22528;

 Name                                      Null? Type
 ----------------------------------------- -------- ----------------------------
 RNO                                       NOT NULL NUMBER(5)
 NAME                                      NOT NULL VARCHAR2(20)
 EMAIL                                              VARCHAR2(30)
 ADMISSION_DATE                                     DATE
 MARKS                                              NUMBER(3)
 DEPT_NO                                            NUMBER(2)
```

//Entering values into the student table.
SQL> INSERT INTO stud22528 VALUES (&rno, '&name', '&email', TO_DATE('&admission_date','DD-MM-YYYY'), &marks, &dept_no);
Enter value for rno: 20

Enter value for name: sorab

Enter value for email: sorab@gmail.com

Enter value for admission_date: 10-01-2026

Enter value for marks: 78

Enter value for dept_no: 1

old 1: INSERT INTO stud22528 VALUES (&rno, '&name', '&email', TO_DATE('&admission_date','DD-MM-YYYY'), &marks, &dept_no)

new 1: INSERT INTO stud22528 VALUES (20, 'sorab', 'sorab@gmail.com', TO_DATE('10-01-2026','DD-MM-YYYY'), 78, 1)

1 row created.

SQL>/

Enter value for rno: 21

Enter value for name: anjali

Enter value for email: anjali@gmail.com

Enter value for admission_date: 15-01-2026

Enter value for marks: 85

Enter value for dept_no: 2

old 1: INSERT INTO stud22528 VALUES (&rno, '&name', '&email', TO_DATE('&admission_date','DD-MM-YYYY'), &marks, &dept_no)

new 1: INSERT INTO stud22528 VALUES (21, 'anjali', 'anjali@gmail.com', TO_DATE('15-01-2026','DD-MM-YYYY'), 85, 2)

1 row created.

SQL>/

Enter value for rno: 22

Enter value for name: Arushi

Enter value for email: arushi@gmail.com

Enter value for admission_date: 20-01-2026

Enter value for marks: 91

Enter value for dept_no: 1

old 1: INSERT INTO stud22528 VALUES (&rno, '&name', '&email', TO_DATE('&admission_date','DD-MM-YYYY'), &marks, &dept_no)

new 1: INSERT INTO stud22528 VALUES (22, 'arushi', 'arushi@gmail.com', TO_DATE('20-01-2026','DD-MM-YYYY'), 91, 1)

1 row created.

SQL>/

Enter value for rno: 23

Enter value for name: Prerna

Enter value for email: prerna@gmail.com

Enter value for admission_date: 25-01-2026

Enter value for marks: 69

Enter value for dept_no: 3

old 1: INSERT INTO stud22528 VALUES (&rno, '&name', '&email', TO_DATE('&admission_date','DD-MM-YYYY'), &marks, &dept_no)

new 1: INSERT INTO stud22528 VALUES (23, 'Prerna', 'prerna@gmail.com', TO_DATE('25-01-2026','DD-MM-YYYY'), 69, 3)

1 row created.

SQL>/

Enter value for rno: 24

Enter value for name: suhani

Enter value for email: suhani@gmail.com

Enter value for admission_date: 30-01-2026

Enter value for marks: 88

Enter value for dept_no: 2

old 1: INSERT INTO stud22528 VALUES (&rno, '&name', '&email', TO_DATE('&admission_date','DD-MM-YYYY'), &marks, &dept_no)

new 1: INSERT INTO stud22528 VALUES (24, 'suhani', 'suhani@gmail.com', TO_DATE('30-01-2026','DD-MM-YYYY'), 88, 2)

1 row created.

SQL> SELECT * FROM stud22528;

RNO	NAME	EMAIL	ADMISSION_DATE	MARKS	DEPT_NO
21	sorab	sorab@gmail.com	10-JAN-26	78	1
22	anjali	anjali@gmail.com	15-JAN-26	85	2
23	arushi	arushi@gmail.com	20-JAN-26	91	1
24	Prerna	prerna@gmail.com	25-JAN-26	69	3
25	suhani	suhani@gmail.com	30-JAN-26	88	2

//Performing operations on the data

SQL> SELECT rno, name, marks FROM stud22528;

RNO	NAME	MARKS
20	sorab	78
21	anjali	85
22	arushi	91
23	Prerna	69
24	suhani	88

SQL> SELECT * FROM stud22528 WHERE marks > 90;

RNO	NAME	EMAIL	ADMISSION_DATE	MARKS	DEPT_NO
22	arushi	arushi@gmail.com	20-JAN-26	91	1

SQL> SELECT SUM(marks) FROM stud22528;

```
SUM(MARKS)
----------
      411
SQL> SELECT AVG(marks) FROM stud22528;


AVG(MARKS)
----------
     82.2
SQL>
```