




Mean-field games between teams

Jayakumar Subramanian^a, Akshat Kumar^b, Aditya Mahajan^a

^a McGill University and GERAD, ^b Singapore Management University

11th Workshop on Dynamic Games in Management Science
25 Oct 2019


DARPA Spectrum Collaboration Challenge (SC2)



Source: <https://www.spectrumcollaborationchallenge.com/media/>

Mean-field games between teams-(Subramanian, Kumar, and Mahajan)

Multiple aggregators in energy markets



Source: https://en.wikipedia.org/wiki/Smart_grid#/media/File:Staying_big_or_getting_smaller.jpg

Salient Features

- ▷ Each “player” is a collection of multiple agents (i.e., a team).
- ▷ All agents in a team are exchangeable.
- ▷ Agents within a team only care about the utility of the team and don’t have an individual utility.
- ▷ Teams are competing with one another.
- ▷ Information is decentralized and asymmetric.

Salient Features

- ▷ Each “player” is a collection of multiple agents (i.e., a team).
 - ▷ All agents in a team are exchangeable.
 - ▷ Agents within a team only care about the utility of the team and don't have an individual utility.
 - ▷ Teams are competing with one another.
 - ▷ **Information is decentralized and asymmetric.**
- ▷ What is the right solution concept for games between teams?
 - ▷ How do find a solution in the dynamic case?
Note that agents within a team as well as within the entire population have asymmetric information.

What are games between teams?

Preliminaries: Static Bayesian Games

- ▶ N players.
- ▶ Uncertainty lies in a probability space (Ω, \mathcal{F}, P) .
- ▶ Player i receives a signal $t_i = t_i(\omega)$ and takes an action $a_i \in A_i$ using a STRATEGY $s_i: t_i \mapsto a_i$.
- ▶ Utility of player i is $u_i: A_1 \times \cdots \times A_n \rightarrow \mathbb{R}$.

Preliminaries: Static Bayesian Games

- ▶ N players.
- ▶ Uncertainty lies in a probability space (Ω, \mathcal{F}, P) .
- ▶ Player i receives a signal $t_i = t_i(\omega)$ and takes an action $a_i \in A_i$ using a STRATEGY $s_i: t_i \mapsto a_i$.
- ▶ Utility of player i is $u_i: A_1 \times \cdots \times A_n \rightarrow \mathbb{R}$.

EX-ANTE UTILITY

$$U_i(s_i, s_{-i}) = \sum_{\omega \in \Omega} P(\omega) u_i(s_i(t_i(\omega)), s_{-i}(t_{-i}(\omega)))$$

INTERIM UTILITY

$$U_i(a_i, s_{-i} \mid t_i) = \sum_{\omega \in \Omega} P(\omega \mid t_i) u_i(a_i, s_{-i}(t_{-i}(\omega)))$$

Preliminaries: Static Bayesian Games

- ▶ N players.
- ▶ Uncertainty lies in a probability space (Ω, \mathcal{F}, P) .
- ▶ Player i receives a signal $t_i = t_i(\omega)$ and takes an action $a_i \in A_i$ using a STRATEGY $s_i: t_i \mapsto a_i$.
- ▶ Utility of player i is $u_i: A_1 \times \cdots \times A_n \rightarrow \mathbb{R}$.

EX-ANTE UTILITY

$$U_i(s_i, s_{-i}) = \sum_{\omega \in \Omega} P(\omega) u_i(s_i(t_i(\omega)), s_{-i}(t_{-i}(\omega)))$$

INTERIM UTILITY

$$U_i(a_i, s_{-i} \mid t_i) = \sum_{\omega \in \Omega} P(\omega \mid t_i) u_i(a_i, s_{-i}(t_{-i}(\omega)))$$

BAYESIAN NASH EQUILIBRIUM (EX-ANTE)

A strategy $s = (s_1, \dots, s_n)$ is BNE if:

$$U_i(s_i, s_{-i}) \geq U_i(s'_i, s_{-i}), \quad \forall s'_i, \forall i.$$

Preliminaries: Static Bayesian Games

- ▶ N players.
- ▶ Uncertainty lies in a probability space (Ω, \mathcal{F}, P) .
- ▶ Player i receives a signal $t_i = t_i(\omega)$ and takes an action $a_i \in A_i$ using a STRATEGY $s_i: t_i \mapsto a_i$.
- ▶ Utility of player i is $u_i: A_1 \times \cdots \times A_n \rightarrow \mathbb{R}$.

EX-ANTE UTILITY

$$U_i(s_i, s_{-i}) = \sum_{\omega \in \Omega} P(\omega) u_i(s_i(t_i(\omega)), s_{-i}(t_{-i}(\omega)))$$

INTERIM UTILITY

$$U_i(a_i, s_{-i} \mid t_i) = \sum_{\omega \in \Omega} P(\omega \mid t_i) u_i(a_i, s_{-i}(t_{-i}(\omega)))$$

BAYESIAN NASH EQUILIBRIUM (EX-ANTE)

A strategy $s = (s_1, \dots, s_n)$ is BNE if:

$$U_i(s_i, s_{-i}) \geq U_i(s'_i, s_{-i}), \quad \forall s'_i, \forall i.$$

BAYESIAN NASH EQUILIBRIUM (INTERIM)

A strategy $s = (s_1, \dots, s_n)$ is BNE if:

$$U_i(s_i(t_i), s_{-i} \mid t_i) \geq U_i(a'_i, s_{-i} \mid t_i), \quad \forall a'_i, \forall t_i, \forall i.$$

Preliminaries: Static Bayesian Teams

- ▷ N agents.
- ▷ Uncertainty lies in a probability space (Ω, \mathcal{F}, P) .
- ▷ Agent i receives a signal $t_i = t_i(\omega)$ and takes an action $a_i \in A_i$ using a STRATEGY $s_i: t_i \mapsto a_i$.
- ▷ Utility of TEAM is $u: A_1 \times \cdots \times A_n \rightarrow \mathbb{R}$.

Preliminaries: Static Bayesian Teams

- ▶ N agents.
- ▶ Uncertainty lies in a probability space (Ω, \mathcal{F}, P) .
- ▶ Agent i receives a signal $t_i = t_i(\omega)$ and takes an action $a_i \in A_i$ using a STRATEGY $s_i: t_i \mapsto a_i$.
- ▶ Utility of TEAM is $u: A_1 \times \cdots \times A_n \rightarrow \mathbb{R}$.

EX-ANTE UTILITY

$$U(s_i, s_{-i}) = \sum_{\omega \in \Omega} P(\omega) u(s_i(t_i(\omega)), s_{-i}(t_{-i}(\omega)))$$

INTERIM UTILITY (WRT AGENT i)

$$U_i(a_i, s_{-i} \mid t_i) = \sum_{\omega \in \Omega} P(\omega \mid t_i) u(a_i, s_{-i}(t_{-i}(\omega)))$$

Preliminaries: Static Bayesian Teams

- ▶ N agents.
- ▶ Uncertainty lies in a probability space (Ω, \mathcal{F}, P) .
- ▶ Agent i receives a signal $t_i = t_i(\omega)$ and takes an action $a_i \in A_i$ using a STRATEGY $s_i: t_i \mapsto a_i$.
- ▶ Utility of TEAM is $u: A_1 \times \cdots \times A_n \rightarrow \mathbb{R}$.

EX-ANTE UTILITY

$$U(s_i, s_{-i}) = \sum_{\omega \in \Omega} P(\omega) u(s_i(t_i(\omega)), s_{-i}(t_{-i}(\omega)))$$

INTERIM UTILITY (WRT AGENT i)

$$U_i(a_i, s_{-i} \mid t_i) = \sum_{\omega \in \Omega} P(\omega \mid t_i) u(a_i, s_{-i}(t_{-i}(\omega)))$$

Globally Optimal Strategy

A strategy $s = (s_1, \dots, s_n)$ is GO if:

$$U(s) \geq U(s'), \quad \forall s' = (s'_1, \dots, s'_n).$$

Preliminaries: Static Bayesian Teams

- ▶ N agents.
- ▶ Uncertainty lies in a probability space (Ω, \mathcal{F}, P) .
- ▶ Agent i receives a signal $t_i = t_i(\omega)$ and takes an action $a_i \in A_i$ using a STRATEGY $s_i: t_i \mapsto a_i$.
- ▶ Utility of TEAM is $u: A_1 \times \cdots \times A_n \rightarrow \mathbb{R}$.

EX-ANTE UTILITY

$$U(s_i, s_{-i}) = \sum_{\omega \in \Omega} P(\omega) u(s_i(t_i(\omega)), s_{-i}(t_{-i}(\omega)))$$

INTERIM UTILITY (WRT AGENT i)

$$U_i(a_i, s_{-i} \mid t_i) = \sum_{\omega \in \Omega} P(\omega \mid t_i) u(a_i, s_{-i}(t_{-i}(\omega)))$$

GLOBALLY OPTIMAL STRATEGY

A strategy $s = (s_1, \dots, s_n)$ is GO if:

$$U(s) \geq U_i(s'), \quad \forall s' = (s'_1, \dots, s'_n).$$

PERSON BY PERSON OPTIMAL STRATEGY

A strategy $s = (s_1, \dots, s_n)$ is PBPO if:

$$U_i(s_i(t_i), s_{-i} \mid t_i) \geq U_i(a'_i, s_{-i} \mid t_i), \quad \forall a'_i, \forall t_i, \forall i.$$

Preliminaries: Static Games between Teams

- ▷ K teams. Team k has $N^{(k)}$ agents.
- ▷ Uncertainty lies in a probability space (Ω, \mathcal{F}, P) .
- ▷ Agent i receives a signal $t_i = t_i(\omega)$ and takes an action $a_i \in A_i$ using a STRATEGY $s_i: t_i \mapsto a_i$.
- ▷ $s^{(k)} = (s_i)_{i \in N^{(k)}}$ is the strategy of team k .
- ▷ $a^{(k)} = (a_i)_{i \in N^{(k)}}$ is the action profile of team k .
- ▷ Utility of team k is $u^{(k)}: A^{(1)} \times \cdots \times A^{(k)} \rightarrow \mathbb{R}$.

Preliminaries: Static Games between Teams

- ▷ K teams. Team k has $N^{(k)}$ agents.
- ▷ Uncertainty lies in a probability space (Ω, \mathcal{F}, P) .
- ▷ Agent i receives a signal $t_i = t_i(\omega)$ and takes an action $a_i \in A_i$ using a STRATEGY $s_i: t_i \mapsto a_i$.
- ▷ $s^{(k)} = (s_i)_{i \in N^{(k)}}$ is the strategy of team k .
- ▷ $a^{(k)} = (a_i)_{i \in N^{(k)}}$ is the action profile of team k .
- ▷ Utility of team k is $u^{(k)}: A^{(1)} \times \dots \times A^{(k)} \rightarrow \mathbb{R}$.

EX-ANTE UTILITY OF TEAM k

$$U^{(k)}(s^{(k)}, s^{(-k)}) = \sum_{\omega \in \Omega} P(\omega) u^{(k)}(s^{(k)}(t^{(k)}(\omega)), s^{(-k)}(t^{(-k)}(\omega)))$$

Not possible to define interim utility wrt to team k , because the agents in a team receive different signals.

Preliminaries: Static Games between Teams

- ▶ K teams. Team k has $N^{(k)}$ agents.
- ▶ Uncertainty lies in a probability space (Ω, \mathcal{F}, P) .
- ▶ Agent i receives a signal $t_i = t_i(\omega)$ and takes an action $a_i \in A_i$ using a STRATEGY $s_i: t_i \mapsto a_i$.
- ▶ $s^{(k)} = (s_i)_{i \in N^{(k)}}$ is the strategy of team k .
- ▶ $a^{(k)} = (a_i)_{i \in N^{(k)}}$ is the action profile of team k .
- ▶ Utility of team k is $u^{(k)}: A^{(1)} \times \dots \times A^{(k)} \rightarrow \mathbb{R}$.

EX-ANTE UTILITY OF TEAM k

$$U^{(k)}(s^{(k)}, s^{(-k)}) = \sum_{\omega \in \Omega} P(\omega) u^{(k)}(s^{(k)}(t^{(k)}(\omega)), s^{(-k)}(t^{(-k)}(\omega)))$$

Not possible to define interim utility wrt to team k , because the agents in a team receive different signals.

TEAM GAME EQUILIBRIUM

A strategy $s = (s^{(1)}, \dots, s^{(n)})$ is TGE if:

$$U^{(k)}(s^{(k)}, s^{(-k)}) \geq U^{(k)}(s'^{(k)}, s^{(-k)}), \quad \forall s'^{(k)}, \forall k.$$

Preliminaries: Static Games between Teams

- ▶ K teams. Team k has $N^{(k)}$ agents.
- ▶ Uncertainty lies in a probability space (Ω, \mathcal{F}, P) .
- ▶ Agent i receives a signal $t_i = t_i(\omega)$ and takes an action $a_i \in A_i$ using a STRATEGY $s_i: t_i \mapsto a_i$.
- ▶ $s^{(k)} = (s_i)_{i \in N^{(k)}}$ is the strategy of team k .
- ▶ $a^{(k)} = (a_i)_{i \in N^{(k)}}$ is the action profile of team k .
- ▶ Utility of team k is $u^{(k)}: A^{(1)} \times \dots \times A^{(k)} \rightarrow \mathbb{R}$.

EX-ANTE UTILITY OF TEAM k

$$U^{(k)}(s^{(k)}, s^{(-k)}) = \sum_{\omega \in \Omega} P(\omega) u^{(k)}(s^{(k)}(t^{(k)}(\omega)), s^{(-k)}(t^{(-k)}(\omega)))$$

Not possible to define interim utility wrt to team k , because the agents in a team receive different signals.

TEAM GAME EQUILIBRIUM

A strategy $s = (s^{(1)}, \dots, s^{(n)})$ is TGE if:

$$U^{(k)}(s^{(k)}, s^{(-k)}) \geq U^{(k)}(s'^{(k)}, s^{(-k)}), \quad \forall s'^{(k)}, \forall k.$$

- ▶ Note that in the definition of TGE, all agents in a team are allowed to deviate together!
- ▶ Therefore, game between teams are different than games in which subsets of agents have identical interests.

Exchangeable Markov processes and their mean-field projection

Notation: Mean-field of a sequence

Given a finite set \mathcal{X} and a positive integer n , let Δ_n denote the set of probability distributions on \mathcal{X} with denominator n .

Note that $|\Delta_n| \leq (n+1)^{|\mathcal{X}|}$.

EXAMPLE: Let $\mathcal{X} = \{0, 1\}$ and $n = 3$. Then

$$\Delta_n = \left\{ \begin{bmatrix} 0 & 1 \end{bmatrix}, \begin{bmatrix} \frac{1}{3} & \frac{2}{3} \end{bmatrix}, \begin{bmatrix} \frac{2}{3} & \frac{1}{3} \end{bmatrix}, \begin{bmatrix} 1 & 0 \end{bmatrix} \right\}.$$

Notation: Mean-field of a sequence

Given a finite set \mathcal{X} and a positive integer n , let Δ_n denote the set of probability distributions on \mathcal{X} with denominator n .

Note that $|\Delta_n| \leq (n+1)^{|\mathcal{X}|}$.

EXAMPLE: Let $\mathcal{X} = \{0, 1\}$ and $n = 3$. Then

$$\Delta_n = \left\{ \begin{bmatrix} 0 & 1 \end{bmatrix}, \begin{bmatrix} 1 & 2 \\ 3 & 3 \end{bmatrix}, \begin{bmatrix} 2 & 1 \\ 3 & 3 \end{bmatrix}, \begin{bmatrix} 1 & 0 \end{bmatrix} \right\}.$$

For a sequence $x \in \mathcal{X}^n$, let $\xi(x) \in \Delta_n$ denote the empirical distribution of x . We call $\xi(x)$ as the (empirical) MEAN-FIELD of a sequence.

EXAMPLE: Let $\mathcal{X} = \{0, 1\}$, $n = 3$, and $x = (0, 0, 1)$. Then,

$$\xi(x) = \begin{bmatrix} 2 & 1 \\ 3 & 3 \end{bmatrix}.$$

Notation: Mean-field of a sequence

Given a finite set \mathcal{X} and a positive integer n , let Δ_n denote the set of probability distributions on \mathcal{X} with denominator n .

Note that $|\Delta_n| \leq (n+1)^{|\mathcal{X}|}$.

EXAMPLE: Let $\mathcal{X} = \{0, 1\}$ and $n = 3$. Then

$$\Delta_n = \left\{ \begin{bmatrix} 0 & 1 \end{bmatrix}, \begin{bmatrix} 1 & 2 \\ 3 & 3 \end{bmatrix}, \begin{bmatrix} 2 & 1 \\ 3 & 3 \end{bmatrix}, \begin{bmatrix} 1 & 0 \end{bmatrix} \right\}.$$

For a sequence $x \in \mathcal{X}^n$, let $\xi(x) \in \Delta_n$ denote the empirical distribution of x . We call $\xi(x)$ as the (empirical) MEAN-FIELD of a sequence.

EXAMPLE: Let $\mathcal{X} = \{0, 1\}$, $n = 3$, and $x = (0, 0, 1)$. Then,

$$\xi(x) = \begin{bmatrix} 2 & 1 \\ 3 & 3 \end{bmatrix}.$$

For a distribution $z \in \Delta_n$, let $\Xi(z) \subset \mathcal{X}^n$ denote all sequences with mean-field z . We refer to $\Xi(z)$ as the MEAN-FIELD CLASS of a distribution.

EXAMPLE: Let $\mathcal{X} = \{0, 1\}$, $n = 3$, and $z = \begin{bmatrix} 2 & 1 \\ 3 & 3 \end{bmatrix}$. Then,

$$\Xi(z) = \{(0, 0, 1), (0, 1, 0), (1, 0, 0)\}$$

Notation: Mean-field of a sequence

Given a finite set \mathcal{X} and a positive integer n , let Δ_n denote the set of probability distributions on \mathcal{X} with denominator n .

Note that $|\Delta_n| \leq (n+1)^{|\mathcal{X}|}$.

EXAMPLE: Let $\mathcal{X} = \{0, 1\}$ and $n = 3$. Then

$$\Delta_n = \left\{ \begin{bmatrix} 0 & 1 \end{bmatrix}, \begin{bmatrix} \frac{1}{3} & \frac{2}{3} \end{bmatrix}, \begin{bmatrix} \frac{2}{3} & \frac{1}{3} \end{bmatrix}, \begin{bmatrix} 1 & 0 \end{bmatrix} \right\}.$$

For a sequence $x \in \mathcal{X}^n$, let $\xi(x) \in \Delta_n$ denote the empirical distribution of x . We call $\xi(x)$ as the (empirical) MEAN-FIELD of a sequence.


EXAMPLE: Let $\mathcal{X} = \{0, 1\}$, $n = 3$, and $x = (0, 0, 1)$. Then,

$$\xi(x) = \begin{bmatrix} \frac{2}{3} & \frac{1}{3} \end{bmatrix}.$$

For a distribution $z \in \Delta_n$, let $\Xi(z) \subset \mathcal{X}^n$ denote all sequences with mean-field z . We refer to $\Xi(z)$ as the MEAN-FIELD CLASS of a distribution.

EXAMPLE: Let $\mathcal{X} = \{0, 1\}$, $n = 3$, and $z = \begin{bmatrix} \frac{2}{3} & \frac{1}{3} \end{bmatrix}$. Then,

$$\Xi(z) = \{(0, 0, 1), (0, 1, 0), (1, 0, 0)\}$$



Exchangeable random vector

Given a sequence x , let σx denote a permutation of x . Note that $\xi(\sigma x) = \xi(x)$.

Exchangeable random vector

Given a sequence x , let σx denote a permutation of x . Note that $\xi(\sigma x) = \xi(x)$.

A random vector $X \in \mathcal{X}^n$ is called **exchangeable** if for any permutation σ :

$$\mathbb{P}(X = \sigma x) = \mathbb{P}(X = x).$$

EXAMPLE: Let $\mathcal{X} = \{0, 1\}$, $n = 3$, and p_{ijk} denotes $\mathbb{P}(X = (i, j, k))$. Then X is exchangeable if

$$p_{001} = p_{010} = p_{100} \quad \text{and} \quad p_{110} = p_{101} = p_{011}.$$

Exchangeable random vector

Given a sequence x , let σx denote a permutation of x . Note that $\xi(\sigma x) = \xi(x)$.

A random vector $X \in \mathcal{X}^n$ is called **exchangeable** if for any permutation σ :

$$\mathbb{P}(X = \sigma x) = \mathbb{P}(X = x).$$

EXAMPLE: Let $\mathcal{X} = \{0, 1\}$, $n = 3$, and p_{ijk} denotes $\mathbb{P}(X = (i, j, k))$. Then X is exchangeable if

$$p_{001} = p_{010} = p_{100} \quad \text{and} \quad p_{110} = p_{101} = p_{011}.$$


A Markov process $\{X_t\}_{t \geq 1}$, $X_t \in \mathcal{X}^n$ is called **exchangeable** if

- ▶ The initial state X_1 is exchangeable
- ▶ The transition matrix is invariant under permutations, i.e., for any permutation σ ,
$$\mathbb{P}(X_{t+1} = \sigma y | X_t = \sigma x) = \mathbb{P}(X_{t+1} = y | X_t = x)$$

Note that if $\{X_t\}_{t \geq 1}$ is an exchangeable Markov process, then X_t is an exchangeable random vector.

Mean-field projection of exchangeable Markov processes

Let $\{X_t\}_{t \geq 1}$, $X_t \in \mathcal{X}^n$ be an exchangeable Markov process. Its **mean-field projection** is the process $\{Z_t\}_{t \geq 1}$, where $Z_t = \xi(X_t)$.



Mean-field projection of exchangeable Markov processes

Let $\{X_t\}_{t \geq 1}$, $X_t \in \mathcal{X}^n$ be an exchangeable Markov process. Its **mean-field projection** is the process $\{Z_t\}_{t \geq 1}$, where $Z_t = \xi(X_t)$.


PROPOSITION:

- ▶ The mean-field projection is a Markov process, i.e.,

$$\mathbb{P}(Z_{t+1} \mid Z_{1:t}) = \mathbb{P}(Z_{t+1} \mid Z_t)$$

- ▶ The mean-field is a sufficient statistic for predicting mean-field projection, i.e.,

$$\mathbb{P}(Z_{t+1} \mid X_{1:t}) = \mathbb{P}(Z_{t+1} \mid Z_t = \xi(X_t)).$$



Mean-field projection of exchangeable Markov processes

Let $\{X_t\}_{t \geq 1}$, $X_t \in \mathcal{X}^n$ be an exchangeable Markov process. Its **mean-field projection** is the process $\{Z_t\}_{t \geq 1}$, where $Z_t = \xi(X_t)$.

PROPOSITION:

- ▶ The mean-field projection is a Markov process, i.e.,


$$\mathbb{P}(Z_{t+1} \mid Z_{1:t}) = \mathbb{P}(Z_{t+1} \mid Z_t)$$

- ▶ The mean-field is a sufficient statistic for predicting mean-field projection, i.e.,

$$\mathbb{P}(Z_{t+1} \mid X_{1:t}) = \mathbb{P}(Z_{t+1} \mid Z_t = \xi(X_t)).$$

THEOREM: Conditioned on the mean-field, all feasible realizations are equally likely, i.e.,

$$\begin{aligned} \mathbb{P}(X_t \mid Z_{1:t}) &= \mathbb{P}(X_t \mid Z_t) \\ &= \mathbb{P}(\sigma X_t \mid Z_t) \\ &= \frac{\mathbb{1}\{\xi(X_t) = Z_t\}}{|\Xi(Z_t)|}. \end{aligned}$$



Mean-field games between teams

System Model: States, actions, and dynamics

- ▶ K teams. Team k has $N^{(k)}$ exchangeable agents indexed by the set $\mathcal{N}^{(k)}$.

System Model: States, actions, and dynamics

- ▶ K teams. Team k has $N^{(k)}$ exchangeable agents indexed by the set $\mathcal{N}^{(k)}$.
- ▶ $X_t^i \in \mathcal{X}^{(k)}$: State of agent i in team k .
- ▶ $U_t^i \in \mathcal{U}^{(k)}$: Action of agent i in team k .

System Model: States, actions, and dynamics

- ▷ K teams. Team k has $N^{(k)}$ exchangeable agents indexed by the set $\mathcal{N}^{(k)}$.
- ▷ $X_t^i \in \mathcal{X}^{(k)}$: State of agent i in team k .
- ▷ $U_t^i \in \mathcal{U}^{(k)}$: Action of agent i in team k .
- ▷ $X_t^{(k)} = (X_t^i)_{i \in \mathcal{N}^{(k)}}$ is the state profile of team k .
- ▷ $X_t = (X_t^{(k)})_{k \in \mathcal{K}}$ is the state profile of entire population.
- ▷ Similar interpretation holds of $U_t^{(k)}$ and U_t .

System Model: States, actions, and dynamics

- ▷ K teams. Team k has $N^{(k)}$ exchangeable agents indexed by the set $\mathcal{N}^{(k)}$.
- ▷ $X_t^i \in \mathcal{X}^{(k)}$: State of agent i in team k .
- ▷ $U_t^i \in \mathcal{U}^{(k)}$: Action of agent i in team k .
- ▷ $X_t^{(k)} = (X_t^i)_{i \in \mathcal{N}^{(k)}}$ is the state profile of team k .
- ▷ $X_t = (X_t^{(k)})_{k \in \mathcal{K}}$ is the state profile of entire population.
- ▷ Similar interpretation holds of $U_t^{(k)}$ and U_t .
- ▷ $Z_t^{(k)} = \xi(X_t^{(k)})$ is the (empirical) mean-field of team k .
- ▷ $Z_t = (Z_t^{(k)})_{k \in \mathcal{K}}$ is the mean-field profile of all teams.

System Model: States, actions, and dynamics

- ▶ K teams. Team k has $N^{(k)}$ exchangeable agents indexed by the set $\mathcal{N}^{(k)}$.
- ▶ $X_t^i \in \mathcal{X}^{(k)}$: State of agent i in team k .
- ▶ $U_t^i \in \mathcal{U}^{(k)}$: Action of agent i in team k .
- ▶ $X_t^{(k)} = (X_t^i)_{i \in \mathcal{N}^{(k)}}$ is the state profile of team k .
- ▶ $X_t = (X_t^{(k)})_{k \in \mathcal{K}}$ is the state profile of entire population.
- ▶ Similar interpretation holds of $U_t^{(k)}$ and U_t .
- ▶ $Z_t^{(k)} = \xi(X_t^{(k)})$ is the (empirical) mean-field of team k .
- ▶ $Z_t = (Z_t^{(k)})_{k \in \mathcal{K}}$ is the mean-field profile of all teams.

- ▶ Initial states are independent across all agents

$$\mathbb{P}(X_1 = (x_1^i)_{i \in \mathcal{N}}) = \prod_{k \in \mathcal{K}} \prod_{i \in \mathcal{N}^{(k)}} p_0^{(k)}(x_1^i)$$

System Model: States, actions, and dynamics

- ▶ K teams. Team k has $N^{(k)}$ exchangeable agents indexed by the set $\mathcal{N}^{(k)}$.
- ▶ $X_t^i \in \mathcal{X}^{(k)}$: State of agent i in team k .
- ▶ $U_t^i \in \mathcal{U}^{(k)}$: Action of agent i in team k .
- ▶ $X_t^{(k)} = (X_t^i)_{i \in \mathcal{N}^{(k)}}$ is the state profile of team k .
- ▶ $X_t = (X_t^{(k)})_{k \in \mathcal{K}}$ is the state profile of entire population.
- ▶ Similar interpretation holds of $U_t^{(k)}$ and U_t .
- ▶ $Z_t^{(k)} = \xi(X_t^{(k)})$ is the (empirical) mean-field of team k .
- ▶ $Z_t = (Z_t^{(k)})_{k \in \mathcal{K}}$ is the mean-field profile of all teams.

- ▶ Initial states are independent across all agents

$$\mathbb{P}(X_1 = (x_1^i)_{i \in \mathcal{N}}) = \prod_{k \in \mathcal{K}} \prod_{i \in \mathcal{N}^{(k)}} p_0^{(k)}(x_1^i)$$

- ▶ The population state evolves in a controlled Markov manner.
- ▶ Agents within a team are exchangeable and, therefore, are only coupled through the mean-field.

$$\mathbb{P}(X_{t+1} \mid X_{1:t}, U_{1:t}) = \prod_{k \in \mathcal{K}} \prod_{i \in \mathcal{N}^{(k)}} p^{(k)}(X_{t+1}^i \mid X_t^i, U_t^i, Z_t)$$

System Model: Information structure and cost

- ▶ Mean-field sharing information structure

$$I_t^i = \{X_t^i, Z_t\}.$$

Note that agents have asymmetric information (also called non-classical information structure in the team theory literature).

System Model: Information structure and cost

- ▷ Mean-field sharing information structure

$$I_t^i = \{X_t^i, Z_t\}.$$

Note that agents have asymmetric information (also called non-classical information structure in the team theory literature).

- ▷ Agents in a team are exchangeable. So, we assume that all agents in a team use identical control laws

$$u_t^i \sim g_t^{(k)}(X_t^i, Z_t)$$

where $g^{(k)} = (g_1^{(k)}, \dots, g_T^{(k)})$ is called the strategy of team k .

System Model: Information structure and cost

- ▶ Mean-field sharing information structure

$$I_t^i = \{X_t^i, Z_t\}.$$

Note that agents have asymmetric information (also called non-classical information structure in the team theory literature).

- ▶ Agents in a team are exchangeable. So, we assume that all agents in a team use identical control laws

$$U_t^i \sim g_t^{(k)}(X_t^i, Z_t)$$

where $g^{(k)} = (g_1^{(k)}, \dots, g_T^{(k)})$ is called the strategy of team k .

- ▶ Average cost incurred by team k

$$C^{(k)} = \frac{1}{N^{(k)}} \sum_{i \in \mathcal{N}^{(k)}} c_t^{(k)}(X_t^i, U_t^i, Z_t).$$

- ▶ Cost incurred by team k :

$$J^{(k)}(g^{(k)}, g^{(-k)}) = \mathbb{E}^{(g^{(k)}, g^{(-k)})} \left[\sum_{t=1}^T C_t^{(k)} \right]$$

System Model: Information structure and cost

- ▶ Mean-field sharing information structure

$$I_t^i = \{X_t^i, Z_t\}.$$

Note that agents have asymmetric information (also called non-classical information structure in the team theory literature).

- ▶ Agents in a team are exchangeable. So, we assume that all agents in a team use identical control laws

$$U_t^i \sim g_t^{(k)}(X_t^i, Z_t)$$

where $g^{(k)} = (g_1^{(k)}, \dots, g_T^{(k)})$ is called the strategy of team k .

- ▶ Average cost incurred by team k

$$C^{(k)} = \frac{1}{N^{(k)}} \sum_{i \in \mathcal{N}^{(k)}} c_t^{(k)}(X_t^i, U_t^i, Z_t).$$

- ▶ Cost incurred by team k :

$$J^{(k)}(g^{(k)}, g^{(-k)}) = \mathbb{E}^{(g^{(k)}, g^{(-k)})} \left[\sum_{t=1}^T C_t^{(k)} \right]$$

GAME 1: Identify a TGE $g = (g^{(k)})_{k \in \mathcal{K}}$ of the game between teams formulated above.

Such a (mixed-strategy) equilibrium always exists because each “player” has a finite number of strategies.



Conceptual difficulties

- ▶ The game formulated above is a dynamic game with asymmetric information. So, the TGE must satisfy **sequential rationality** and **consistency**. Such equilibrium are call Perfect Bayesian Equilibrium.
- ▶ However, there is no general methodology to identify PBE in dynamic games.

Conceptual difficulties

- ▶ The game formulated above is a dynamic game with asymmetric information. So, the TGE must satisfy **sequential rationality** and **consistency**. Such equilibrium are call Perfect Bayesian Equilibrium.
- ▶ However, there is no general methodology to identify PBE in dynamic games.
- ▶ In recent years, there are some results that propose a common information based refinement of Nash Equilibrium for dynamic games with asymmetric information.
- ▶ These may be viewed as the extension of the common information approach [Nayyar, Mahajan, Teneketzis 2013] for teams with non-classical information to games with asymmetric information.

Common information based refinements of Nash equilibrium

- ▶ [Nayyar, Gupta, Langbort, Başar 2014] propose a common information based refinement of Markov perfect equilibrium for a subclass of dynamic games with asymmetric information.
- ▶ The key assumption is that the common information based beliefs are **strategy independent**. This may be viewed as games where there is **no signalling effect**.
- ▶ The CIB-MPE can be computed using dynamic programming for a game with function valued actions.

Common information based refinements of Nash equilibrium

- ▶ [Nayyar, Gupta, Langbort, Başar 2014] propose a common information based refinement of Markov perfect equilibrium for a subclass of dynamic games with asymmetric information.
 - ▶ The key assumption is that the common information based beliefs are **strategy independent**. This may be viewed as games where there is **no signalling effect**.
 - ▶ The CIB-MPE can be computed using dynamic programming for a game with function valued actions.
- ▶ [Ouyang, Tavafoghi, Tenketzis, 2017] propose a common information based refined for Perfect Bayesian equilibrium for general dynamic games with asymmetric information (under some technical assumptions).
 - ▶ Works for games with signaling.
 - ▶ The CIB-MPE can be computed using dynamic programming for a game with function valued actions. But the information state of the DP is more elaborate.

Common information based refinements of Nash equilibrium

- ▶ [Nayyar, Gupta, Langbort, Başar 2014] propose a common information based refinement of Markov perfect equilibrium for a subclass of dynamic games with asymmetric information.
- ▶ The key assumption is that the common information based beliefs are **strategy independent**. This may be viewed as games where there is **no signalling effect**.
- ▶ The CIB-MPE can be computed using dynamic programming for a game with function valued actions.
- ▶ [Ouyang, Tavafoghi, Tenketzis, 2017] propose a common information based refined for Perfect Bayesian equilibrium for general dynamic games with asymmetric information (under some technical assumptions).
- ▶ Works for games with signaling.
- ▶ The CIB-MPE can be computed using dynamic programming for a game with function valued actions. But the information state of the DP is more elaborate.
- ▶ We effectively show that mean-field games have **no signalling effect**.
- ▶ Following [NGLB 2014], we propose a common information based MPE for our model.

Preliminary results

For any strategy $g = (g^{(1)}, \dots, g^{(K)})$ and any realization $z_{1:T}$ of the mean-field $Z_{1:T}$, define the following partial functions, which we call **prescriptions**:

$$\gamma_t^{(k)} = g_t^{(k)}(\cdot, z_t), \quad \forall k \in \mathcal{K}.$$

- ▶ When the realization z_t of the mean-field is given, $\gamma_t^{(k)}$ is a function from $\mathcal{X}^{(k)}$ to $\mathcal{U}_t^{(k)}$.
- ▶ When the mean-field Z_t is a random variable, $\gamma_t^{(k)}$ is a random function from $\mathcal{X}^{(k)}$ to $\mathcal{U}_t^{(k)}$. We denote this by $\Gamma^{(k)}$.

Preliminary results

For any strategy $g = (g^{(1)}, \dots, g^{(K)})$ and any realization $z_{1:T}$ of the mean-field $Z_{1:T}$, define the following partial functions, which we call

prescriptions:

$$\gamma_t^{(k)} = g_t^{(k)}(\cdot, z_t), \quad \forall k \in \mathcal{K}.$$

- ▶ When the realization z_t of the mean-field is given, $\gamma_t^{(k)}$ is a function from $\mathcal{X}^{(k)}$ to $\mathcal{U}^{(k)}$.
- ▶ When the mean-field Z_t is a random variable, $\gamma_t^{(k)}$ is a random function from $\mathcal{X}^{(k)}$ to $\mathcal{U}^{(k)}$. We denote this by $\Gamma^{(k)}$.

LEMMA: The mean-field process $\{Z_t\}_{t \geq 1}$ is a controlled Markov process that evolves conditionally independently across teams:

$$\mathbb{P}(Z_{t+1} \mid Z_{1:t}, \Gamma_{1:t}) = \prod_{k \in \mathcal{K}} Q^{(k)}(z_{t+1}^{(k)} \mid z_t, \Gamma_t^{(k)})$$

where $Q^{(k)}(z_{t+1}^{(k)} \mid z_t, \gamma_t^{(k)})$ can be computed by picking any $x_{t+1}^{(k)} \in \Xi(z_{t+1}^{(k)})$ and $x_t \in \Xi(z_t)$ and setting

$$\begin{aligned} & Q^{(k)}(z_{t+1}^{(k)} \mid z_t, \gamma_t^{(k)}) \\ &= \prod_{i \in \mathcal{N}^{(k)}} p^{(k)}(x_{t+1}^i \mid x_t^i, \gamma_t^{(k)}(x_t^i), z_t) \end{aligned}$$

Preliminary results

For any strategy $g = (g^{(1)}, \dots, g^{(K)})$ and any realization $z_{1:T}$ of the mean-field $Z_{1:T}$, define the following partial functions, which we call

prescriptions:

$$\gamma_t^{(k)} = g_t^{(k)}(\cdot, z_t), \quad \forall k \in \mathcal{K}.$$

- ▶ When the realization z_t of the mean-field is given, $\gamma_t^{(k)}$ is a function from $\mathcal{X}^{(k)}$ to $\mathcal{U}^{(k)}$.
- ▶ When the mean-field Z_t is a random variable, $\gamma_t^{(k)}$ is a random function from $\mathcal{X}^{(k)}$ to $\mathcal{U}^{(k)}$. We denote this by $\Gamma^{(k)}$.

LEMMA: The mean-field process $\{Z_t\}_{t \geq 1}$ is a controlled Markov process that evolves conditionally independently across teams:

$$\mathbb{P}(Z_{t+1} \mid Z_{1:t}, \Gamma_{1:t}) = \prod_{k \in \mathcal{K}} Q^{(k)}(Z_{t+1}^{(k)} \mid Z_t, \Gamma_t^{(k)})$$

where $Q^{(k)}(z_{t+1}^{(k)} \mid z_t, \gamma_t^{(k)})$ can be computed by picking any $x_{t+1}^{(k)} \in \Xi(z_{t+1}^{(k)})$ and $x_t \in \Xi(z_t)$ and setting

$$\begin{aligned} & Q^{(k)}(z_{t+1}^{(k)} \mid z_t, \gamma_t^{(k)}) \\ &= \prod_{i \in \mathcal{N}^{(k)}} p^{(k)}(x_{t+1}^i \mid x_t^i, \gamma_t^{(k)}(x_t^i), z_t) \end{aligned}$$

LEMMA: The mean-field is a sufficient statistic to predict the population state

$$\mathbb{P}(X_t \mid Z_{1:t}, \Gamma_{1:t}) = \prod_{k \in \mathcal{K}} \frac{\mathbb{1}\{\xi(X_t^{(k)}) = Z_t^{(k)}\}}{|\Xi^{(k)}(Z_t^{(k)})|}$$

**Common information based
Markov perfect equilibrium (CIB-MPE)**

A virtual game between virtual players

- ▶ Consider a virtual Markov game between K virtual players with symmetric information.
- ▶ The state is $Z_t = (Z_t^{(k)})_{k \in \mathcal{K}}$.
- ▶ Player k 's action is a function $\gamma_t^{(k)}: \mathcal{X}^{(k)} \rightarrow \mathcal{U}^{(k)}$.
To avoid confusion, we call this a **prescription**.

A virtual game between virtual players

- ▶ Consider a virtual Markov game between K virtual players with symmetric information.
- ▶ The state is $Z_t = (Z_t^{(k)})_{k \in \mathcal{K}}$.
- ▶ Player k 's action is a function $\gamma_t^{(k)}: \mathcal{X}^{(k)} \rightarrow \mathcal{U}^{(k)}$.
To avoid confusion, we call this a **prescription**.
- ▶ Distribution of initial state

$$\mathbb{P}(Z_1) = \prod_{k \in \mathcal{K}} \sum_{\mathbf{x}^{(k)}} \prod_{i \in \mathcal{N}^{(k)}} p^{(k)}(x^i).$$

- ▶ Dynamics of the state

$$\mathbb{P}(Z_{t+1} \mid Z_t, \gamma_t) = \prod_{k \in \mathcal{K}} Q^{(k)}(Z_{t+1}^{(k)} \mid Z_t, \gamma_t^{(k)})$$

A virtual game between virtual players

- ▶ Consider a virtual Markov game between K virtual players with symmetric information.
- ▶ The state is $Z_t = (Z_t^{(k)})_{k \in \mathcal{K}}$.
- ▶ Player k 's action is a function $\gamma_t^{(k)}: \mathcal{X}^{(k)} \rightarrow \mathcal{U}^{(k)}$.
To avoid confusion, we call this a **prescription**.
- ▶ Distribution of initial state

$$\mathbb{P}(Z_1) = \prod_{k \in \mathcal{K}} \sum_{\mathbf{x}^{(k)}} \prod_{i \in \mathcal{N}^{(k)}} p^{(k)}(x^i).$$

- ▶ Dynamics of the state

$$\mathbb{P}(Z_{t+1} \mid Z_t, \gamma_t) = \prod_{k \in \mathcal{K}} Q^{(k)}(Z_{t+1}^{(k)} \mid Z_t, \gamma_t^{(k)})$$

- ▶ Per-step cost function of player k is

$$\begin{aligned} \ell^{(k)}(Z_t, \gamma_t^{(k)}) \\ = \frac{1}{N^{(k)}} \sum_{i \in \mathcal{N}^{(k)}} \mathbb{E}[c^{(k)}(X_t^i, \gamma^{(k)}(X_t^i), Z_t) \mid Z_t] \end{aligned}$$

Note that the cost does not depend on the action of other players!

A virtual game between virtual players

- ▶ Consider a virtual Markov game between K virtual players with symmetric information.
- ▶ The state is $Z_t = (Z_t^{(k)})_{k \in \mathcal{K}}$.
- ▶ Player k 's action is a function $\gamma_t^{(k)}: \mathcal{X}^{(k)} \rightarrow \mathcal{U}^{(k)}$.
To avoid confusion, we call this a **prescription**.

- ▶ Distribution of initial state

$$\mathbb{P}(Z_1) = \prod_{k \in \mathcal{K}} \sum_{\mathbf{x}^{(k)}} \prod_{i \in \mathcal{N}^{(k)}} p^{(k)}(x^i).$$

- ▶ Dynamics of the state

$$\mathbb{P}(Z_{t+1} \mid Z_t, \gamma_t) = \prod_{k \in \mathcal{K}} Q^{(k)}(Z_{t+1}^{(k)} \mid Z_t, \gamma_t^{(k)})$$

- ▶ Per-step cost function of player k is

$$\begin{aligned} \ell^{(k)}(Z_t, \gamma_t^{(k)}) \\ = \frac{1}{N^{(k)}} \sum_{i \in \mathcal{N}^{(k)}} \mathbb{E}[c^{(k)}(X_t^i, \gamma^{(k)}(X_t^i), Z_t) \mid Z_t] \end{aligned}$$

Note that the cost does not depend on the action of other players!

- ▶ All players observe the state Z_t .

- ▶ Player k uses a Markov strategy $\psi^{(k)}$:

$$\gamma_t^{(k)} \sim \psi_t^{(k)}(Z_t)$$

A virtual game between virtual players

- ▶ Consider a virtual Markov game between K virtual players with symmetric information.
- ▶ The state is $Z_t = (Z_t^{(k)})_{k \in \mathcal{K}}$.
- ▶ Player k 's action is a function $\gamma_t^{(k)}: \mathcal{X}^{(k)} \rightarrow \mathcal{U}^{(k)}$.
To avoid confusion, we call this a **prescription**.
- ▶ Distribution of initial state

$$\mathbb{P}(Z_1) = \prod_{k \in \mathcal{K}} \sum_{\mathbf{x}^{(k)}} \prod_{i \in \mathcal{N}^{(k)}} p^{(k)}(x^i).$$

- ▶ Dynamics of the state

$$\mathbb{P}(Z_{t+1} \mid Z_t, \gamma_t) = \prod_{k \in \mathcal{K}} Q^{(k)}(Z_{t+1}^{(k)} \mid Z_t, \gamma_t^{(k)})$$

- ▶ Per-step cost function of player k is

$$\begin{aligned} \ell^{(k)}(Z_t, \gamma_t^{(k)}) \\ = \frac{1}{N^{(k)}} \sum_{i \in \mathcal{N}^{(k)}} \mathbb{E}[c^{(k)}(X_t^i, \gamma^{(k)}(X_t^i), Z_t) \mid Z_t] \end{aligned}$$

Note that the cost does not depend on the action of other players!

- ▶ All players observe the state Z_t .
- ▶ Player k uses a Markov strategy $\psi^{(k)}$:

$$\gamma_t^{(k)} \sim \psi_t^{(k)}(Z_t)$$

GAME 2: Identify a MPE $\psi = (\psi^{(k)})_{k \in \mathcal{K}}$ of the virtual game formulated above.

Such a MPE can be identified using dynamic programming.



Equivalence between Game 1 and Game 2

THEOREM (GAME 1 TO GAME 2)

Let $g = (g^{(k)})_{k \in \mathcal{K}}$ be a TGE of Game 1. Define a strategy $\psi = (\psi^{(k)})_{k \in \mathcal{K}}$ for Game 2 as follows:

$$\psi_t^{(k)}(z) = g_t^{(k)}(\cdot, z), \quad \forall z.$$

Then $\psi = (\psi^{(k)})_{k \in \mathcal{K}}$ is a MPE of Game 2.

Equivalence between Game 1 and Game 2

THEOREM (GAME 1 TO GAME 2)

Let $g = (g^{(k)})_{k \in \mathcal{K}}$ be a TGE of Game 1. Define a strategy $\psi = (\psi^{(k)})_{k \in \mathcal{K}}$ for Game 2 as follows:

$$\psi_t^{(k)}(z) = g_t^{(k)}(\cdot, z), \quad \forall z.$$

Then $\psi = (\psi^{(k)})_{k \in \mathcal{K}}$ is a MPE of Game 2.

THEOREM (GAME 2 TO GAME 1)

Let $\psi = (\psi^{(k)})_{k \in \mathcal{K}}$ be a MPE of Game 2. Define a strategy $g = (g^{(k)})_{k \in \mathcal{K}}$ for Game 1 as follows:

$$g_t^{(k)}(x, z) = \psi_t^{(k)}(z)(x), \quad \forall x \in \mathcal{X}^{(k)}, \forall z.$$

Then $g = (g^{(k)})_{k \in \mathcal{K}}$ is a TGE of Game 1.

We call this the **common information based MPE** of Game 1.

Conclusion

SOLUTION IDEA

- ▷ Formulate a Markov game between virtual players.
- ▷ The virtual players represent the entire team and decide the prescription for all members of the team.
- ▷ Find an MPE of the virtual game using DP
- ▷ Any MPE of the virtual game is a TGE of the game between teams (called CIB-MPE).
- ▷ Thus, we obtain a dynamic program to find a refinement of equilibrium for a dynamic game between teams

Conclusion

SOLUTION IDEA

- ▶ Formulate a Markov game between virtual players.
- ▶ The virtual players represent the entire team and decide the prescription for all members of the team.
- ▶ Find an MPE of the virtual game using DP
- ▶ Any MPE of the virtual game is a TGE of the game between teams (called CIB-MPE).
- ▶ Thus, we obtain a dynamic program to find a refinement of equilibrium for a dynamic game between teams

FUTURE WORK

- ▶ Zero-sum games
- ▶ LQG models
- ▶ Mean-field limits for large populations in each team ($N^{(k)} \rightarrow \infty$) and also for large number of teams ($K \rightarrow \infty$).
- ▶ ...