

Experiment - 03

AIM:-

1. List all employees and jobs in Department 30 in descending order by salary.
2. List job and Department Number of employees whose name are five letters long begin with "A" and end with "N".
3. Display the name of employees whose name start with alphabet S.
4. Display the names of employees whose name ends with alphabet S.
5. Display the names of employees working in department number 10 or 20 or 40 or employees working as clerks, salesman or analyst.
6. Display employee number and names for employees who earn commission.
7. Display employee number and total salary for each employee.
8. Display employee number and annual salary for each employee.
9. Display the names of all employees working as clerks and drawing a salary more than 3,000.
10. Display the names of employees who are working as clerk, salesman or analyst and drawing a salary more than 3,000.

PROCEDURE:-

- SELECT – Retrieve data from table
- WHERE – Filter records
- LIKE – Pattern matching
- IN – Multiple value condition
- ORDER BY – Sort results
- AND / OR – Combine conditions
- IS NOT NULL – Check non-null values
- Arithmetic Operators – Perform calculations (+, *)

Perform Following Query using Employee Table:-

1. List all employees and jobs in Department 30 in descending order by salary.

Ans-

Experiment - 03

SELECT ename, job FROM Employee WHERE deptno = 30 ORDER BY sal DESC;

```
MariaDB [2cse25_1650]> SELECT ename, job
-> FROM Employee
-> WHERE deptno = 30
-> ORDER BY sal DESC;
+-----+-----+
| ename  | job      |
+-----+-----+
| BLAKE  | MANAGER  |
| ALLEN  | SALESMAN |
| TURNER | SALESMAN |
| WARD   | SALESMAN |
| MARTIN | SALESMAN |
| JAMES  | CLERK    |
+-----+-----+
6 rows in set (0.004 sec)
```

2. List job and Department Number of employees whose name are five letters long begin with "A" and end with "N".

Ans-

SELECT job, deptno FROM Employee WHERE ename LIKE 'A___N';

```
MariaDB [2cse25_1650]> SELECT job, deptno
-> FROM Employee
-> WHERE ename LIKE 'A___N';
+-----+-----+
| job      | deptno |
+-----+-----+
| SALESMAN | 30     |
+-----+-----+
1 row in set (0.001 sec)
```

3. Display the name of employees whose name start with alphabet S.

Ans-

Experiment - 03

SELECT ename FROM Employee WHERE ename LIKE 'S%'

```
MariaDB [2cse25_1650]> SELECT ename
-> FROM Employee
-> WHERE ename LIKE 'S%';
+-----+
| ename |
+-----+
| SMITH |
| SCOTT |
+-----+
2 rows in set (0.001 sec)
```

4. Display the names of employees whose name ends with alphabet S.

Ans-

SELECT ename FROM Employee WHERE ename LIKE '%S';

```
MariaDB [2cse25_1650]> SELECT ename
-> FROM Employee
-> WHERE ename LIKE '%S';
+-----+
| ename |
+-----+
| JONES |
| ADAMS |
| JAMES |
+-----+
3 rows in set (0.001 sec)
```

5. Display the names of employees working in department number 10 or 20 or 40 or employees working as clerks, salesman or analyst.

Ans-

SELECT * FROM Employee WHERE deptno IN (10,20,40) OR job IN ('CLERK','SALESMAN','ANALYST');

Experiment - 03

```
MariaDB [2cse25_1650]> SELECT *  
  -> FROM Employee  
  -> WHERE deptno IN (10,20,40)  
  -> OR job IN ('CLERK','SALESMAN','ANALYST');
```

EMPNO	ENAME	JOB	MGR	HIREDATE	SAL	COMM	DEPTNO
7369	SMITH	CLERK	7902	1980-12-17	880.00	NULL	20
7499	ALLEN	SALESMAN	7698	1981-02-20	1600.00	300.00	30
7521	WARD	SALESMAN	7698	1981-02-22	1250.00	300.00	30
7566	JONES	MANAGER	7839	1981-04-02	3272.50	NULL	20
7654	MARTIN	SALESMAN	7698	1981-09-28	1250.00	1400.00	30
7782	CLARK	MANAGER	7839	1981-06-09	2695.00	NULL	20
7788	SCOTT	ANALYST	7566	1982-12-09	3300.00	NULL	40
7839	KING	PRESIDENT	NULL	1981-11-17	5500.00	NULL	20
7844	TURNER	SALESMAN	7698	1981-09-08	1500.00	0.00	30
7876	ADAMS	CLERK	7788	1983-01-12	1210.00	NULL	20
7900	JAMES	CLERK	7698	1981-12-03	1045.00	NULL	30
7902	FORD	ANALYST	7566	1981-12-03	3300.00	NULL	20
7934	MILLER	CLERK	7782	1982-01-23	1430.00	NULL	10

13 rows in set (0.001 sec)

6. Display employee number and names for employees who earn commission.

Ans-

SELECT empno, ename FROM Employee WHERE comm IS NOT NULL;

```
MariaDB [2cse25_1650]> SELECT empno, ename  
  -> FROM Employee  
  -> WHERE comm IS NOT NULL;
```

empno	ename
7499	ALLEN
7521	WARD
7654	MARTIN
7844	TURNER

4 rows in set (0.001 sec)

7. Display employee number and total salary for each employee.

Ans-

SELECT empno, sal + IFNULL(comm,0) AS total_salary FROM Employee;

Experiment - 03

```
MariaDB [2cse25_1650]> SELECT empno, sal + IFNULL(comm,0) AS total_salary  
-> FROM Employee;
```

empno	total_salary
7369	880.00
7499	1900.00
7521	1550.00
7566	3272.50
7654	2650.00
7698	3135.00
7782	2695.00
7788	3300.00
7839	5500.00
7844	1500.00
7876	1210.00
7900	1045.00
7902	3300.00
7934	1430.00

```
14 rows in set (0.001 sec)
```

8. Display employee number and annual salary for each employee.

Ans-

```
SELECT empno, sal*12 AS annual_salary FROM Employee;
```

Experiment - 03

```
MariaDB [2cse25_1650]> SELECT empno, sal*12 AS annual_salary
-> FROM Employee;
+-----+-----+
| empno | annual_salary |
+-----+-----+
| 7369  | 10560.00     |
| 7499  | 19200.00     |
| 7521  | 15000.00     |
| 7566  | 39270.00     |
| 7654  | 15000.00     |
| 7698  | 37620.00     |
| 7782  | 32340.00     |
| 7788  | 39600.00     |
| 7839  | 66000.00     |
| 7844  | 18000.00     |
| 7876  | 14520.00     |
| 7900  | 12540.00     |
| 7902  | 39600.00     |
| 7934  | 17160.00     |
+-----+-----+
14 rows in set (0.001 sec)
```

9. Display the names of all employees working as clerks and drawing a salary more than 3,000.

Ans-

```
SELECT ename FROM Employee WHERE job = 'CLERK' AND sal > 3000;
```

```
MariaDB [2cse25_1650]> SELECT ename
-> FROM Employee
-> WHERE job = 'CLERK'
-> AND sal > 3000;
Empty set (0.001 sec)
```

10. Display the names of employees who are working as clerk, salesman or analyst and drawing a salary more than 3,000.

Ans-

Experiment - 03

SELECT ename FROM Employee WHERE job IN ('CLERK','SALESMAN','ANALYST') AND sal > 3000;

```
MariaDB [2cse25_1650]> SELECT ename  
-> FROM Employee  
-> WHERE job IN ('CLERK','SALESMAN','ANALYST')  
-> AND sal > 3000;
```

ename
SCOTT
FORD

2 rows in set (0.001 sec)