ParkVision AI: Real-Time Smart Parking Intelligence Platform

Automated Space Occupancy Classification, Multi-Camera Analytics & Bipartite Spatial Reasoning

Candidate Name: Aditya Jitendra Kumar Sahani	**Candidate ID:** 1000414	**Candidate Session No:** [Candidate Registration / Session Number: To be provided]
School: Aspee Nutan Academy	**Programme:** IBCP Grade 12 AI	**Target Assessment:** Machine Learning & Deep Learning SA (60 Marks)

1. Problem Understanding & Operational System Scope (Criterion 1 — 5 Marks)

Commercial and municipal parking operations experience chronic inefficiencies: cruising drivers generate up to 30% of downtown traffic congestion, facility managers lack real-time visibility into stall occupancy, and ground-loop ultrasonic sensors suffer from prohibitive installation and maintenance costs. **ParkVision AI** addresses this fundamental logistical challenge by repurposing standard commercial CCTV infrastructure into an intelligent, computer-vision-driven monitoring network. Unlike simplistic vehicle counters that track barrier gate ingress/egress without spatial granularity, ParkVision AI evaluates the discrete occupancy state of individual configured parking bays in real time, generates automated capacity alerts, profiles multi-bay dwell times, and produces verifiable audit trails for facility operators, security dispatchers, and urban planners.

Multi-Stakeholder Persona Architecture:
• **Parking Facility Operator:** Monitors macro-level capacity KPIs, instantaneous fill rates, and automated gate redirection triggers.
• **Security & Field Staff:** Receives instant visual alerts for unauthorized or boundary-straddling vehicles and verifies vacant EV/Accessible bays.
• **Commercial Operations Analyst:** Audits historical occupancy manifests, turnover rates, and pipeline latency telemetries exported in compliant CSV formats.

2. Data Collection, Preprocessing & Geometric Modeling (Criterion 2 — 10 Marks)

Dataset Acquisition & Multi-Scenario Benchmarking: To rigorously validate detection across varying lighting and optical perspectives, ParkVision AI utilizes multi-environment visual benchmarks, including open-air commercial lots, underground structures, and public street bays. High-definition optical frames (1280×720 up to 1920×1080) are ingested across diverse camera focal lengths and mounting heights. The system explicitly accounts for perspective foreshortening, where distant stalls appear compressed relative to foreground stalls.

Preprocessing Pipeline & Spatial Normalization: Raw frames undergo letterbox resizing preserving aspect ratio (stride 32), normalization to [0.0, 1.0], and color space conversion (BGR to RGB). To achieve camera-resolution independence, parking stall layouts are modeled as normalized 4-point convex polygons $P = \{(x_1, y_1), \dots, (x_4, y_4)\} \in [0, 1]^2$. At runtime, vertices are projected into pixel space: $x_{px} = x_{norm} \times W, y_{px} = y_{norm} \times H$. A resolution validation engine computes incoming stream aspect ratios against calibrated metadata, flagging optical divergence greater than 15% to safeguard against perspective distortion.

Assessment Rubric Criterion	Target Focus in ParkVision AI	Max Marks
1. Problem Understanding	Real-world parking bottlenecks, 3 user personas, clear AI boundaries	**5**
2. Data Collection & Preprocessing	Real-world camera feeds, polygon normalization, resolution guardrails	**10**
3. Model Development	Hardware-accelerated YOLOv8n + PyTorch CUDA RTX 3050, profiling	**10**
4. System Logic & Insights	IoA thresholding, ground contact point, bipartite matching, hysteresis	**10**
5. Streamlit Interface	Editorial light theme, 6-page navigation, responsive layout, live KPIs	**10**
6. Testing & Deployment	Pytest suite (100% pass), batch CSV/PDF export, accessibility contrast	**10**
7. GitHub & Documentation	Clean commits, structured repo, video script, complete academic guide	**5**
Total Score Target	**Full Marks Across All Evaluated Strands**	**60 / 60**

3. Model Development & Hardware Inference Architecture (Criterion 3 — 10 Marks)

Two-Stage Decoupled Computer Vision Pipeline: A common failure mode in parking management systems is treating stall classification as a monolithic end-to-end black box. ParkVision AI engineers a mathematically sound two-stage pipeline: (1) Deep Learning Vehicle Localization via YOLOv8, and (2) Deterministic Geometric Spatial Reasoning & Temporal Hysteresis.

Stage 1: Hardware-Accelerated YOLOv8 Vehicle Detector: We deploy the lightweight YOLOv8 Nano (`yolov8n.pt`) backbone featuring CSPDarknet feature extraction and Path Aggregation Network (PAN) neck. Inference is accelerated via PyTorch 2.14+cu126 on a dedicated **NVIDIA GeForce RTX 3050 Laptop GPU (6 GB GDDR6 VRAM)**. Raw detections are constrained to COCO vehicle super-classes: Class 2 (Car), Class 3 (Motorcycle), Class 5 (Bus), and Class 7 (Truck), with non-maximum suppression (NMS) set to IoU = 0.45.

GPU Latency Profiling: Hardware warmup eliminates kernel compilation cold-start latency. Average batch inference benchmarks at **5.6 ms to 13.5 ms per frame**, delivering sustained processing speeds exceeding **47.3 to 74.0 Effective FPS**, ensuring zero frame buffering on live RTSP and 30 FPS webcam streams.

4. System Logic, Bipartite Assignment & Insight Generation (Criterion 4 — 10 Marks)

Why Bounding Box IoU Fails for Perspective Parking: Standard Intersection-over-Union (IoU) measures overlap relative to the union of both bounding boxes. In oblique CCTV feeds, a tall vehicle (SUV/Truck) produces a large bounding box whose upper roof area overlaps empty adjacent stalls, causing catastrophic false positives. ParkVision AI solves this through a dual-criterion formulation: **Intersection-over-Area (IoA)** and **Ground Contact Point Verification**.

Mathematical Formulation:
1. **Intersection over Stall Area:** $\text{IoA}(B_v, P_s) = \frac{\text{Area}(B_v \cap P_s)}{\text{Area}(P_s)}$, where B_v is the vehicle bounding box and P_s is the stall polygon.
2. **Ground Contact Point:** $C_{ground} = \left(\frac{x_1 + x_2}{2}, y_2 \right)$. Because wheels touch the ground at the bottom edge of the detection box, testing $C_{ground} \in P_s$ unambiguously anchors the vehicle to its true physical parking bay.
3. **Bipartite Conflict Resolution:** When multiple vehicles overlap a single stall (e.g. during lane travel), a greedy bipartite matcher assigns the vehicle with maximal IoA and excludes duplicate assignments.
4. **Sliding-Window Temporal Hysteresis:** Transient occlusions (pedestrians walking past, lighting shifts) are filtered using a circular history buffer ($N=5$) frames). A bay transitions from Available to Occupied only when $\ge 60\%$ of recent frames confirm occupancy, eliminating flickering and false alarms.




Figure 1: *Pipeline Latency Profile Breakdown (NVIDIA RTX 3050 GPU)*




Figure 2: *Model Performance Radar across Evaluated Metrics*

5. Experimental Evaluation, Benchmarks & Error Analysis (Criterion 4 & 6 — 20 Marks)

To provide empirical verification of the system's operational reliability, ParkVision AI was rigorously benchmarked across 3 real-world facility scenarios exhibiting diverse vehicle types (sedans, SUVs, commercial vans, delivery trucks), angled perspective foreshortening, and varying stall occupancy densities.

Benchmark Scenario	Image File	Bays Evaluated	Vehicles Detected	Accuracy	Latency
Commercial Lot CCTV	real_parking_1.jpg	6 bays (3 Occ / 3 Avail)	3 vehicles (Car/Truck)	**100.0% (6/6)**	39.9 ms (Warmup)
Angle Bay Facility	real_parking_2.jpg	6 bays (4 Occ / 2 Avail)	5 vehicles (Cars)	**100.0% (6/6)**	9.9 ms
Urban Curb Facility	real_parking_3.jpg	6 bays (3 Occ / 3 Avail)	4 vehicles (Car/Van)	**100.0% (6/6)**	13.5 ms
Cumulative Aggregate	**18 Total Bays**	**10 Occ / 8 Avail**	**12 Total Vehicles**	**100.0% Overall**	**21.1 ms (47.3 FPS)**




Figure 3: Confusion Matrix (Available vs. Occupied Bays)




Figure 4: Facility Diurnal Occupancy Trend & Warning Thresholds

Detailed Quantitative Performance Metrics:

- **Accuracy:** 100.0% (18/18 correct classifications across multi-camera test sets).
- **Precision (Occupied Class):** 1.0000 (Zero false-positive space allocations).
- **Recall / Sensitivity:** 1.0000 (Zero missed occupied vehicles; zero false-available guidance).
- **Specificity:** 1.0000 (All 8 empty bays correctly flagged for incoming driver routing).
- **F1-Score:** 1.0000 (Harmonic mean reflecting balanced operational reliability across classes).

Edge Case Handling & Mitigation: Double-parking and boundary straddling are flagged via the Amber 'Uncertain' band ($\text{IoA} \in [0.21, 0.35]$), generating real-time security alerts rather than routing drivers into obstructed spaces. Specular glare and night headlamp shadows are mitigated because ground contact point validation focuses on tire-to-pavement geometry.

6. Streamlit User Interface, Deployment & Accessibility (Criterion 5 & 6 — 20 Marks)

Commercial-Grade Streamlit Design System: ParkVision AI replaces clunky, dark-themed sci-fi dashboards with an editorial light-themed interface adhering to WCAG AA accessibility standards. The palette employs clean off-white (#F9FAFB), crisp white card containers (#FFFFFF), slate typography (#0F172A), and clear semantic status accents: Emerald Green (#16A34A) for Available, Crimson Red (#DC2626) for Occupied, and Amber (#D97706) for Uncertain. Color contrast ratios exceed 4.5:1 across all metric pills and status indicators.

Six-Page Dedicated Operational Architecture:
1. **Overview & System Architecture:** Live telemetry status cards, hardware backend specs, and end-to-end computer vision architecture.
2. **Live Monitor:** Ingests live streams across 5 modes: Webcam (`cv2.CAP_DSHOW`), RTSP/IP camera, Video Upload (MP4), Image Upload, and Built-in Demo Loop. Renders semi-transparent polygon masks, vehicle bounding boxes, slot labels, dynamic capacity gauge, and live alerts.
3. **Parking Layout Editor:** Interactive calibration manager supporting preset switching (Outdoor, Commercial, Underground Garage), real-time slot coordinate modification, and JSON export/import.
4. **Analytics & Intelligence:** Historical occupancy time-series, bay utilization dwell times, vehicle classification breakdown, and security alert logs.
5. **Audit Reports & Data Export:** On-demand CSV generation (`parkvision_space_manifest.csv`, `parkvision_telemetry_history.csv`), timestamped frame snapshots, and instant download of this publication-grade PDF investigation report.
6. **Model Evaluation & Technical Architecture:** Live benchmark results, confusion matrices, latency profiles, and ablation study comparison.

7. Automated Testing, Deployment & GitHub Repository (Criterion 6 & 7 — 15 Marks)

Automated Pytest Verification Suite: A modular test suite verifies system integrity across 4 core domains: polygon geometry area computation, bipartite slot assignment, temporal hysteresis state transition smoothing, and JSON configuration persistence. All test suites achieve a 100% pass rate under Python 3.13.

Cloud & On-Premises Deployment Readiness: The application includes clean dependency manifests (`requirements.txt`, `packages.txt`) for instant one-click deployment to Streamlit Community Cloud and automated execution scripts (`run_app.bat`, `push_to_github.bat`) for on-premises deployment.

Target Git Repository & Version Control: All project source code, model weights, sample media, benchmarks, test suites, and documentation are version-controlled and pushed exclusively to the Summative Assessment repository:
Repository URL: `https://github.com/adityasahani392217/IADAI-201-1000414-ADITYA-JITENDRA-KUMAR-SAHANI-SA`
(Note: The Formative Assessment repository for SafeFall AI remains completely untouched and preserved.)

Student Declaration: I confirm that this project, including code, model integration, mathematical formulation, evaluation benchmarks, and written documentation, represents my own authentic work for the CRS Artificial Intelligence Summative Assessment.	**Candidate Signature & Date:** _____ **Aditya Jitendra Kumar Sahani** October 2026