

- ① Select e.name, d.dept_name, d.location
from employees as e left join departments as d
on e.dept_id = d.dept_id;
- ② Select name, salary
from employees where salary > (select
Avg(salary) from employees);
- ③ select name, salary from employees
where salary > all (select max(salary)
from employees where dept_id = 30); ~~and~~
~~dept_id < 30~~
- ④ ~~Select name, salary,~~
with cet1 as
 ⑤ (select e.name, s.product_id, s.sale_amount,
rank() over (order by sale_amount desc) as rnk,
sum() over (sale_amount) as total_sales
from employees e join sales s
on e.emp_id = s.emp_id)
 select cet1.name, p.product_name, ~~rank~~ round(cet1.
sale_amount, 2), ~~rank~~ cet1.rnk, round(cet1.
total_sales, 2)
from cet1 join products as p
on cet1.product_id = p.product_id;

⑥ ~~Select order-id,~~

⑥ Select order-id, customer-id, order-date,
round(amount, 2),

⑦ ~~Select product-name, product-category~~

⑦ Select product-name, category
from products where product-id exists
(select distinct (product-id) from
sales);

with cte1 as

⑧ (select dept-id, ~~dept-name~~, count(*),
max(salary) from employees
group by dept-id having count(*) > 2)

select d.dept-name, cte1.count(*) as
employee-count, cte1.max(salary) from cte1
join departments as d
on cte1.dept-id = d.dept-id;

9 Normalization :-

Normalization is a process in Structured Query Language used to organizing relational databases structure to reduce data redundancy (data duplicacy) and to improve data integrity and data accuracy in the database.

Types of Normalization

- (i) 1NF
- (ii) 2NF
- (iii) 3NF
- (iv) BCNF

10 CTE stands for Common Table Expression. It stores data / table from a resultant query. And we can use it multiple times in the query.

Views does not store data physically. It displays data from a underlying table.