

```

#include <stdio.h>
int main()
{
    int num1,num2,optn,x;
    while(1)
    {

        printf("Enter the first Integer :");
        scanf("%d",&num1);
        printf("\nEnter the second Integer :");
        scanf("%d",&num2);

        printf("\nEnter the option :\n");
        printf("\n1-Addition\n");
        printf("\n2-Subtraction\n");
        printf("\n3-Multiplication\n");
        printf("\n4-Division\n");
        printf("\n5-Greater than\n");
        printf("\n6-Less than\n");
        printf("\n7-Equal to\n");
        printf("\n8-Not equal to\n");
        printf("\n9-Modulus\n");
        printf("\n10-Decrement\n");
        scanf("%d",&optn);

        double div=((double)num1)/num2;

        printf("\n\n");

        switch(optn)
        {
            case 1:
                printf("The Addition of %d and %d is: %d\n", num1, num2, num1+num2);
                break;

            case 2:
                printf("\nThe Substraction of %d and %d is: %d\n", num1, num2, num1-num2);
                break;

            case 3:
                printf("\nThe Multiplication of %d and %d is: %d\n", num1, num2, num1*num2);
                break;

            case 4:
                printf("\nThe Division of %d and %d is : %.2f \n", num1, num2, div);
                break;

            case 5:
                if(num1>num2)
                    printf("\nThe number %d is greater than the number %d\n", num1, num2);

```

```

        else
        {
            printf("\nThe number %d is greater than %d\n", num2, num1);
        }
        break;

    case 6:

        if(num1<num2)
            printf("\nThe number %d is less than the number %d\n", num1, num2);

        else
        {
            printf("\nThe number %d is less than the number %d", num2, num1);
        }
        break;

    case 7:

        if(num1==num2)
            printf("\nBoth the numbers are equal\n");

        else
        {
            printf("\nThe numbers are not equal\n");
        }
        break;

    case 8:

        if(num1!=num2)
            printf("\nBoth the numbers are not equal\n");

        else
        {
            printf("\nThe numbers are equal\n");
        }
        break;

    case 9:
        printf("\n%d mod %d = %d\n", num1, num2, num1%num2);
        break;

    case 10:
        printf("\n%d-- = %d", num1, num1-1);
        printf("\n%d-- = %d", num2, num2-1);
        break;

    default:
        printf("Input correct option\n");

}

printf("\nTo exit press any other key");
printf("\n\nTo continue press 0\n\n");
scanf("%d", &x);

```

```
        if(x!=0)
        {
            break;
        }
    }
}
```