PYTORCH CHEAT SHEET

Imports

General

```
import torch
from torch.utils.data import Dataset, DataLoader
# root package
# dataset representation and loading
```

Neural Network API

```
import torch.autograd as autograd  # computation graph
from torch import Tensor  # tensor node in the computation graph
import torch.nn as nn  # neural networks
import torch.nn.functional as F  # layers, activations and more
import torch.optim as optim  # optimizers e.g. gradient descent, ADAM, etc.
from torch.jit import script, trace  # hybrid frontend decorator and tracing jit
```

See autograd, nn, functional and optim

Torchscript and JIT

See Torchscript

ONNX

```
torch.onnx.export(model, dummy data, xxxx.proto)  # exports an ONNX formatted
# model using a trained model, dummy
# data and the desired file name

model = onnx.load("alexnet.proto")  # load an ONNX model
onnx.checker.check_model(model)  # check that the model
# IR is well formed

onnx.helper.printable_graph(model.graph)  # print a human readable
# representation of the graph
```

See onnx

Vision

```
from torchvision import datasets, models, transforms # vision datasets,
# architectures &
# transforms

import torchvision.transforms as transforms # composable transforms
```

See torchvision

Distributed Training

```
import torch.distributed as dist  # distributed communication
from torch.multiprocessing import Process  # memory sharing processes
```

Tensors

Creation

See tensor

Dimensionality

```
x.size()
                                           # return tuple-like object of dimensions
x = torch.cat(tensor_seq, dim=0)
                                           # concatenates tensors along dim
y = x.view(a,b,...)
                                           # reshapes x into size (a,b,...)
y = x.view(-1,a)
                                           # reshapes x into size (b,a) for some b
                                           # swaps dimensions a and b
y = x.transpose(a,b)
y = x.permute(*dims)
                                          # permutes dimensions
y = x.unsqueeze(dim)
                                          # tensor with added axis
y = x.unsqueeze(dim=2)
                                          # (a,b,c) tensor -> (a,b,1,c) tensor
                                           \# removes all dimensions of size 1 (a,1,b,1) \rightarrow (a,b)
y = x.squeeze()
y = x.squeeze(dim=1)
                                           \# removes specified dimension of size 1 (a,1,b,1) -> (a,b,1)
```

See tensor

Algebra

```
ret = A.mm(B)  # matrix multiplication
ret = A.mv(x)  # matrix-vector multiplication
x = x.t()  # matrix transpose
```

See math operations

GPU Usage

```
torch.cuda.is_available
                                                            # check for cuda
x = x.cuda()
                                                            # move x's data from
                                                            # CPU to GPU and return new object
                                                            # move x's data from GPU to CPU
x = x.cpu()
                                                            # and return new object
if not args.disable_cuda and torch.cuda.is_available():
                                                            # device agnostic code
    args.device = torch.device('cuda')
                                                            # and modularity
    args.device = torch.device('cpu')
                                                            #
net.to(device)
                                                            # recursively convert their
                                                            # parameters and buffers to
                                                            # device specific tensors
x = x.to(device)
                                                            # copy your tensors to a device
                                                            # (gpu, cpu)
```

See cuda

Deep Learning

```
nn.Linear(m,n)
                                                 # fully connected layer from
                                                 # m to n units
nn.ConvXd(m,n,s)
                                                 # X dimensional conv layer from
                                                 # m to n channels where X \in \{1, 2, 3\}
                                                 # and the kernel size is s
nn.MaxPoolXd(s)
                                                 # X dimension pooling layer
                                                 # (notation as above)
nn.BatchNormXd
                                                 # batch norm layer
                                                 # recurrent layers
nn.RNN/LSTM/GRU
nn.Dropout(p=0.5, inplace=False)
                                                 # dropout layer for any dimensional input
nn.Dropout2d(p=0.5, inplace=False)
                                                 # 2-dimensional channel-wise dropout
\textbf{nn.Embedding(num\_embeddings, embedding\_dim)} \qquad \textit{\# (tensor-wise) mapping from}
                                                 # indices to embedding vectors
```

See nn

Loss Functions

```
nn.X

# where X is L1Loss, MSELoss, CrossEntropyLoss

# CTCLoss, NLLLoss, PoissonNLLLoss,

# KLDivLoss, BCELoss, BCEWithLogitsLoss,

# MarginRankingLoss, HingeEmbeddingLoss,

# MultiLabelMarginLoss, SmoothL1Loss,

# SoftMarginLoss, MultiLabelSoftMarginLoss,

# CosineEmbeddingLoss, MultiMarginLoss,

# or TripletMarginLoss
```

See loss functions

Activation Functions

```
nn.X

# where X is ReLU, ReLU6, ELU, SELU, PReLU, LeakyReLU,

# RReLu, CELU, GELU, Threshold, Hardshrink, HardTanh,

# Sigmoid, LogSigmoid, Softplus, SoftShrink,

# Softsign, Tanh, TanhShrink, Softmin, Softmax,

# Softmax2d, LogSoftmax or AdaptiveSoftmaxWithLoss
```

See activation functions

Optimizers

```
opt = optim.x(model.parameters(), ...)  # create optimizer
opt.step()  # update weights
optim.X  # where X is SGD, Adadelta, Adagrad, Adam,
# AdamW, SparseAdam, Adamax, ASGD,
# LBFGS, RMSprop or Rprop
```

See optimizers

Learning rate scheduling

See learning rate scheduler

Data Utilities

Datasets

```
Dataset  # abstract class representing dataset

TensorDataset  # labelled dataset in the form of tensors

Concat Dataset  # concatenation of Datasets
```

Dataloaders and DataSamplers

DataLoader(dataset, batch_size=1, ...) # loads data batches agnostic

of structure of individual data points

sampler.Sampler(dataset,...) # abstract class dealing with

ways to sample from dataset

sampler.XSampler where ... # Sequential, Random, SubsetRandom,

WeightedRandom, Batch, Distributed

See dataloader

Also see

- Deep Learning with PyTorch: A 60 Minute Blitz (pytorch.org)
- PyTorch Forums (discuss.pytorch.org)
- PyTorch for Numpy users (github.com/wkentaro/pytorch-for-numpy-users)

Rate this Tutorial



© Copyright 2022, PyTorch.

Built with Sphinx using a theme provided by Read the Docs.

Docs

Access comprehensive developer documentation for ${\bf PyTorch}$

View Docs

Tutorials

Get in-depth tutorials for beginners and advanced developers

View Tutorials

Resources

Find development resources and get your questions answered

View Resources

PyTorch Resources Stay Connected

Get Started Tutorials

Features Docs

Ecosystem Discuss

Blog Github Issues

Contributing Brand Guidelines