

Fifteen hard questions and honest answers

1. The PS explicitly says RoadRunner. Where are those scenes?

We lack that licence. We propose two detailed **CARLA 0.9.15** village and junction scenes connected to the Simulink ego stack. This is a disclosed **literal deviation**, not a waiver. [P14](#)

2. Is the complete Simulink system working today?

No. The MATLAB 2D planner and some sensor tracking run; the Simulink bicycle model is a side model, and camera inference is outside the driving loop. [P2](#)

3. Why claim real-time replanning when you measured 735.8 ms?

We do **not** claim it today. The build gate replaces the collision-check hotspot, compiles planner and verifier kernels, and reports full-loop p50/p95/p99 plus 100 ms deadline misses. [P15](#)

4. Can your camera currently identify an auto or a cow in CARLA?

Not reliably: YOLOX produced zero render boxes at the audited default threshold. Offline auto and cow AP are 38.2% and 16.3%; labelled in-loop recall is a required gate. [P2](#)

5. Does your yield model give the car permission to cross?

No. Its dangerous-error rate is 2.089% against its $\leq 1\%$ gate, so its output is disabled. The planned model predicts occupied regions; only the separate geometric/braking checker may permit movement. [P2](#), [P13](#)

6. What prevents the independent checker from freezing the car forever?

Nothing can guarantee progress in a truly blocked road. We fix today's S2/S3 stall bugs, record **false** stalls when a feasible gap existed, and permit only a freshly checked, stoppable creep. [P3](#)

7. What is new if learned proposals and separate verification already exist?

Those mechanisms are prior art, including Mosaic. The proposed contribution is an **India-calibrated, measured** closed loop with responsive traffic, false-stall accounting and held-out baselines; its benefit is not proved yet. R20–R23.

8. Fourteen AI models with two builders in ten weeks?

Fourteen is the **design inventory**. Five form the target core; only YOLOX and DeepLab exist offline today. Nine are later extensions, and the RL policy is a comparison, not the driving authority. [P15](#)

9. How will you obtain authentic autos and cattle in CARLA?

A custom driveable vehicle needs a Windows UE4 source build; W2 must spawn one vehicle and one prop. If it fails, we disclose blueprint/prop surrogates and withdraw claims of realistic auto pixels or physics. R31.

10. Will SUMO and CARLA both control the same actor?

No. SUMO owns reactive traffic state; the bridge mirrors it into CARLA, while Simulink controls ego. Timestamp, actor-ID and pose assertions must pass before a run counts. [P13](#)

11. How do hand gestures and horns affect right of way?

They raise caution or change an intent hypothesis. A police "proceed" gesture, horn, or siren cannot itself open the verifier; a siren triggers only a checked yield or stop. [P15](#)

12. Does a real dashcam replay prove the car can drive on a real road?

No. It is open-loop evidence for perception and tracking transfer. We report per-class recall on held-out real versus rendered frames; road-driving safety still needs much more evidence. [P15](#)

13. How do you predict a cow's sudden motion without a cattle-trajectory dataset?

We do not claim a learned cattle-intent model. Cattle remain detected obstacles with conservative reachable regions, tested against sudden-onset scenarios. [P4–P5](#)

14. What do the large crash numbers prove about your expected impact?

They establish the **problem's scale**, not lives saved by our system. MoRTH totals are national 2023 counts; the cattle-crash count is Haryana-only over five years. We give no projected reduction. R03–R05.

15. What will you hand over if the finale gates fail or data access is denied?

The same model, scenario manifests, raw logs, failure reasons, measured PS metrics and a plainly marked partial result. Dataset access is checked before use; missing classes and the RoadRunner deviation remain visible. [P14](#), [P15](#)