

assignment12

November 17, 2021

```
[1]: from keras.datasets import mnist
from keras.models import Model
import keras
from keras import layers
from keras import backend as K
from keras.models import Model
#from tensorflow.keras.models import Model
import tensorflow.compat.v1.keras.backend as K
import tensorflow as tf
tf.compat.v1.disable_eager_execution()
from pathlib import Path
```

```
[2]: results_dir = Path('results').joinpath('vae')
results_dir.mkdir(parents=True, exist_ok=True)
```

```
[3]: import numpy as np
img_shape = (28, 28, 1)
batch_size = 16
latent_dim = 2
input_img = keras.Input(shape=img_shape)
x = layers.Conv2D(32, 3,
padding='same', activation='relu')(input_img)
x = layers.Conv2D(64, 3,
padding='same', activation='relu',
strides=(2, 2))(x)
x = layers.Conv2D(64, 3,padding='same', activation='relu')(x)
x = layers.Conv2D(64, 3,padding='same', activation='relu')(x)
shape_before_flattening = K.int_shape(x)
x = layers.Flatten()(x)
x = layers.Dense(32, activation='relu')(x)
z_mean = layers.Dense(latent_dim)(x)
z_log_var = layers.Dense(latent_dim)(x)
```

```
[4]: def sampling(args):
    z_mean, z_log_var = args
    epsilon = K.random_normal(shape=(K.shape(z_mean)[0], latent_dim),
    mean=0., stddev=1.)
    return z_mean + K.exp(z_log_var) * epsilon
```

```

z = layers.Lambda(sampling)([z_mean, z_log_var])
decoder_input = layers.Input(K.int_shape(z)[1:])
x = layers.Dense(np.prod(shape_before_flattening[1:]),
activation='relu')(decoder_input)
x = layers.Reshape(shape_before_flattening[1:])(x)
x = layers.Conv2DTranspose(32, 3,
padding='same',
activation='relu',
strides=(2, 2))(x)

x = layers.Conv2D(1, 3,
padding='same',
activation='sigmoid')(x)
decoder = Model(decoder_input, x)
z_decoded = decoder(z)

```

```

[5]: class CustomVariationalLayer(keras.layers.Layer):
    def vae_loss(self, x, z_decoded):
        x = K.flatten(x)
        z_decoded = K.flatten(z_decoded)
        xent_loss = keras.metrics.binary_crossentropy(x, z_decoded)
        kl_loss = -5e-4 * K.mean(
            1 + z_log_var - K.square(z_mean) - K.exp(z_log_var), axis=-1)
        return K.mean(xent_loss + kl_loss)
    def call(self, inputs):
        x = inputs[0]
        z_decoded = inputs[1]
        loss = self.vae_loss(x, z_decoded)
        self.add_loss(loss, inputs=inputs)
        return x

```

```

[6]: y = CustomVariationalLayer()([input_img, z_decoded])

```

```

[7]: vae = Model(input_img, y)
vae.compile(optimizer='rmsprop', loss=None)
vae.summary()
(x_train, _), (x_test, y_test) = mnist.load_data()
x_train = x_train.astype('float32') / 255.
x_train = x_train.reshape(x_train.shape + (1,))
x_test = x_test.astype('float32') / 255.
x_test = x_test.reshape(x_test.shape + (1,))
vae.fit(x=x_train, y=None,
shuffle=True,
epochs=10,
batch_size=batch_size,
validation_data=(x_test, None))

```

WARNING:tensorflow:Output custom_variational_layer missing from loss dictionary.

We assume this was done on purpose. The fit and evaluate APIs will not be expecting any data to be passed to custom_variational_layer.

Model: "model_1"

Layer (type)	Output Shape	Param #	Connected to
input_1 (InputLayer)	[(None, 28, 28, 1)]	0	[]
conv2d (Conv2D) ['input_1[0][0]']	(None, 28, 28, 32)	320	
conv2d_1 (Conv2D) ['conv2d[0][0]']	(None, 14, 14, 64)	18496	
conv2d_2 (Conv2D) ['conv2d_1[0][0]']	(None, 14, 14, 64)	36928	
conv2d_3 (Conv2D) ['conv2d_2[0][0]']	(None, 14, 14, 64)	36928	
flatten (Flatten) ['conv2d_3[0][0]']	(None, 12544)	0	
dense (Dense) ['flatten[0][0]']	(None, 32)	401440	
dense_1 (Dense)	(None, 2)	66	['dense[0][0]']
dense_2 (Dense)	(None, 2)	66	['dense[0][0]']
lambda (Lambda) ['dense_1[0][0]', 'dense_2[0][0]']	(None, 2)	0	
model (Functional) ['lambda[0][0]']	(None, 28, 28, 1)	56385	
custom_variational_layer (CustomVariationalLayer)	(None, 28, 28, 1)	0	'model[0][0]'
Total params: 550,629			
Trainable params: 550,629			
Non-trainable params: 0			

```
-----  
-----  
Train on 60000 samples, validate on 10000 samples
```

```
Epoch 1/10
```

```
60000/60000 [=====] - ETA: 0s - loss: 0.2230
```

```
C:\Users\aditya.sumbaraju\Anaconda3\lib\site-  
packages\keras\engine\training_v1.py:2057: UserWarning: `Model.state_updates`  
will be removed in a future version. This property should not be used in  
TensorFlow 2.0, as `updates` are applied automatically.
```

```
updates = self.state_updates
```

```
60000/60000 [=====] - 218s 4ms/sample - loss: 0.2230 -  
val_loss: 0.1989
```

```
Epoch 2/10
```

```
60000/60000 [=====] - 208s 3ms/sample - loss: 0.1961 -  
val_loss: 0.1926
```

```
Epoch 3/10
```

```
60000/60000 [=====] - 208s 3ms/sample - loss: 0.1909 -  
val_loss: 0.1899
```

```
Epoch 4/10
```

```
60000/60000 [=====] - 204s 3ms/sample - loss: 0.1881 -  
val_loss: 0.1865
```

```
Epoch 5/10
```

```
60000/60000 [=====] - 213s 4ms/sample - loss: 0.1861 -  
val_loss: 0.1844
```

```
Epoch 6/10
```

```
60000/60000 [=====] - 206s 3ms/sample - loss: 0.1846 -  
val_loss: 0.1834
```

```
Epoch 7/10
```

```
60000/60000 [=====] - 211s 4ms/sample - loss: 0.1834 -  
val_loss: 0.1830
```

```
Epoch 8/10
```

```
60000/60000 [=====] - 212s 4ms/sample - loss: 0.1825 -  
val_loss: 0.1816
```

```
Epoch 9/10
```

```
60000/60000 [=====] - 209s 3ms/sample - loss: 0.1817 -  
val_loss: 0.1819
```

```
Epoch 10/10
```

```
60000/60000 [=====] - 210s 3ms/sample - loss: 0.1810 -  
val_loss: 0.1813
```

```
[7]: <keras.callbacks.History at 0x2869196da90>
```

```
[8]: import matplotlib.pyplot as plt  
from scipy.stats import norm  
n = 15  
digit_size = 28
```

```

figure = np.zeros((digit_size * n, digit_size * n))
grid_x = norm.ppf(np.linspace(0.05, 0.95, n))
grid_y = norm.ppf(np.linspace(0.05, 0.95, n))
for i, yi in enumerate(grid_x):
    for j, xi in enumerate(grid_y):
        z_sample = np.array([[xi, yi]])
        z_sample = np.tile(z_sample, batch_size).reshape(batch_size, 2)
        x_decoded = decoder.predict(z_sample, batch_size=batch_size)
        digit = x_decoded[0].reshape(digit_size, digit_size)
        figure[i * digit_size: (i + 1) * digit_size,
              j * digit_size: (j + 1) * digit_size] = digit

plt.figure(figsize=(10, 10))
plt.imshow(figure, cmap='Greys_r')
img_file = results_dir.joinpath('Assignment_12_15x15_Grid.png')
plt.savefig(img_file)
plt.show()


```

C:\Users\aditya.sumbaraju\Anaconda3\lib\site-packages\keras\engine\training_v1.py:2079: UserWarning: `Model.state_updates` will be removed in a future version. This property should not be used in TensorFlow 2.0, as `updates` are applied automatically.

```

updates=self.state_updates,

```



[]: