

Solution Code - Spring Core and Maven - Bean_Scopes

Below is the complete functional source code implementation for this assignment. All logic, validation rules, and structural requirements have been satisfied.

Source File: src\main\java\com\library\BookService.java

```
1 | package com.library;
2 |
3 | public class BookService {}
```

Source File: src\main\java\com\library\LibraryApp.java

```
1 | package com.library;
2 |
3 | import org.springframework.context.ApplicationContext;
4 | import org.springframework.context.support.ClassPathXmlApplicationContext;
5 |
6 | public class LibraryApp {
7 |     public static void main(String[] args) {
8 |         ApplicationContext context = new ClassPathXmlApplicationContext("applicationContext.xml");
9 |         BookService singleton1 = (BookService) context.getBean("singletonService");
10 |        BookService singleton2 = (BookService) context.getBean("singletonService");
11 |        System.out.println("Singleton Identity Match: " + (singleton1 == singleton2)); // true
12 |
13 |        BookService prototype1 = (BookService) context.getBean("prototypeService");
14 |        BookService prototype2 = (BookService) context.getBean("prototypeService");
15 |        System.out.println("Prototype Identity Match: " + (prototype1 == prototype2)); // false
16 |    }
17 | }
```

Source File: src\main\resources\applicationContext.xml

```
1 | <beans xmlns="http://www.springframework.org/schema/beans"
2 |       xmlns:xsi="http://www.w3.org/2001/XMLSchema-instance"
3 |       xsi:schemaLocation="http://www.springframework.org/schema/beans
4 |       http://www.springframework.org/schema/beans/spring-beans.xsd">
5 |
6 |     <bean id="singletonService" class="com.library.BookService" scope="singleton" />
7 |     <bean id="prototypeService" class="com.library.BookService" scope="prototype" />
8 | </beans>
```