

# Deep Learning

## - Recurrent Neural Network -

Aug. 2019

Ando Ki, Ph.D.


[adki@future-ds.com](mailto:adki@future-ds.com)

## Contents

- Recurrent Neural Network
- Predicting last word
- RNN applications and type of sequences
- Variants of RNN
- RNN examples

# Recurrent Neural Network

- RNN: neural network with loop
  - ▶ A RNN can be thought of as multiple copies of the same network, each passing a message to a successor
- It is called “recurrent” because it performs the same task for every element of a sequence, with the output being depended on the previous computations.
- It also can be seen as it has a “memory” which captures information about what has been calculated so far.




3


## Predicting last word

- Short term relationship

- ▶ “the clouds are in the (       )”
- ☞ → “sky”




- Long term relationship: “I grew up in France..... I speak fluent (       )”
- ☞ → “French”



4

## RNN applications and type of sequences



- (1) Vanilla mode of processing without RNN, from fixed-sized input to fixed-sized output (e.g. image classification). → traditional neural network, e.g., MLP, CNN, ...
- (2) Sequence output (e.g. image captioning takes an image and outputs a sentence of words; music generation).
- (3) Sequence input (e.g. sentiment analysis where a given sentence is classified as expressing positive or negative sentiment).
- (4) Sequence input and sequence output (e.g. Machine Translation: an RNN reads a sentence in English and then outputs a sentence in French).
- (5) Synced sequence input and output (e.g. video classification where we wish to label each frame of the video).


<http://karpathy.github.io/2015/05/21/rnn-effectiveness/>

5


## Variants of RNN: BRNN and DRNN

### ■ Bidirectional (BRNN)

- the output at time  $t$  may not only depend on the previous elements in the sequence, but also future elements.



### ■ Deep (DRNN)



6

## Variants of RNN: LSTM

### ■ LSTM

- ▶ Long Short Term Memory network is a special kind of RNN, capable of learning long-term dependencies.
- ▶ It fixes vanishing gradient problem of the original RNN






Figure 6.15 Anatomy of an LSTM


7

## Variants of RNN: LSTM

- It runs straight down the entire chain, with only some minor linear interactions.




- Gate using Sigmoid (0 ~ 1)



8

# RNN



- ▶  $x_t$ : input at time  $t$
- ▶  $z_t$ : output of time  $t$
- ▶  $y_t$ : output at time  $t$
- ▶  $e_t$ : cost or error at time  $t$
- ▶  $h_t$ : internal (hidden) state at time  $t$
- ▶  $W_{hh}$ : weight for hidden state ( $W$ )
- ▶  $W_{xh}$ : weight for input ( $U$ )
- ▶  $W_{hy}$ : weight for output ( $V$ )
- ▶  $f_W$ : function with weight  $W$

$$h_t = f_W(h_{t-1}, x_t)$$

$$h_t = \tanh(W_{hh} \cdot h_{t-1} + W_{xh} x_t)$$


$$z_t = W_{hy} \cdot h_t$$

$$e_t = \text{loss}(z_t, y_t)$$

9

## BPTT: backpropagation through time

### Forward




### Backpropagation on hidden to output

### Backpropagation on input to hidden

### Backpropagation on hidden to hidden

### Backward



10

(주)퓨처디자인시스템

34051 대전광역시 유성구 문지로 193, KAIST 문지캠퍼스, F723호  
(042) 864-0211~0212 / [contact@future-ds.com](mailto:contact@future-ds.com) / [www.future-ds.com](http://www.future-ds.com)

Future Design Systems, Inc.

Faculty Wing F723, KAIST Munji Campus, 193 Munji-ro, Yuseong-gu, Daejeon 34051, Korea  
+82-042-864-0211~0212 / [contact@future-ds.com](mailto:contact@future-ds.com) / [www.future-ds.com](http://www.future-ds.com)



**FUTURE**  
Design Systems