

Bioinformatyka 2

ZBOiB WBBiB UJ
Adrian Kania

28 października 2025

- ❶ **NCBI** – National Center for Biotechnology Information
- ❷ **NCBI Entrez** – zintegrowany system ponad 30 baz danych gromadzących informację z nauk biomedycznych, głównie w postaci sekwencji i literatury naukowej. Obejmuje m.in Pubmed (streszczenia publikacji), Nucleotide (sekwencje nukleotydowe), Protein (sekwencje aminokwasowe).
- ❸ **Entrez Programming Utilities** – oprogramowanie umożliwiające dostęp do danych zintegrowanych w ramach systemu Entrez bez konieczności obsługi formularzy na stronach WWW
 - ❶ **ESearch** – wyszukiwanie identyfikatorów/kodów dostępu rekordów wybranej bazy danych,
 - ❷ **EFetch** – pobieranie rekordów o wskazanych identyfikatorach lub wyników wskazanego wyszukiwania

NCBI Home

Resource List (A-Z)

All Resources

Chemicals & Bioassays

Data & Software

DNA & RNA

Domains & Structures

Genes & Expression

Genetics & Medicine

Genomes & Maps

Homology

Literature

Proteins

Sequence Analysis

Taxonomy

Training & Tutorials

Variation

Welcome to NCBI

The National Center for Biotechnology Information advances science and health by providing access to biomedical and genomic information.

[About the NCBI](#) | [Mission](#) | [Organization](#) | [NCBI News & Blog](#)

Submit

Deposit data or manuscripts
into NCBI databases



Download

Transfer NCBI data to your
computer



Learn

Find help documents, attend
a class or watch a tutorial



Develop

Use NCBI APIs and code
libraries to build applications



Analyze

Identify an NCBI tool for your
data analysis task




Research


Explore NCBI research and
collaborative projects



Popular Resources

[PubMed](#)[Bookshelf](#)[PubMed Central](#)[BLAST](#)[Nucleotide](#)[Genome](#)[SNP](#)[Gene](#)[Protein](#)[PubMed](#)


[Resources](#)
[How To](#)



National Center for Biotechnology Information

[All Databases](#)

[All Databases](#)

- Assembly
- Biocollections
- BioProject
- BioSample
- BioSystems
- Books
- ClinVar
- Conserved Domains
- dbGaP
- dbVar
- Gene
- Genome
- GEO DataSets
- GEO Profiles
- GTR
- HomoloGene
- Identical Protein Groups
- MedGen
- MeSH

NCBI

er for Biotechnology Information advances science and health by providing access to nomic information.


[Mission](#) | [Organization](#) | [NCBI News & Blog](#)

Submit

manuscripts
ases


Download

Transfer NCBI data to your computer



Learn

Find help documents, attend a class or watch a tutorial




Develop

and code
applications


Analyze

Identify an NCBI tool for your data analysis task



Research

Explore NCBI research and collaborative projects



Popular Resources

- [PubMed](#)
- [Bookshelf](#)
- [PubMed Central](#)
- [BLAST](#)
- [Nucleotide](#)
- [Genome](#)
- [SNP](#)
- [Gene](#)
- [Protein](#)
- [PubChem](#)

EFetch

EFetch (efetch.fcgi) returns full data records for a list of unique identifiers (UIDs) in a format specified in the parameters. The list of UIDs is either provided in the parameters, or is retrieved from the [History server](#).

EFetch Parameters

EFetch Required Parameters

- db** (required): Database containing the unique identifiers (UIDs) for which you wish to retrieve records. You can see NCBI's [table of Entrez Unique Identifiers \(UIDs\)](#) for a complete list of allowable database names, but some example values include:
 - pubmed**: PubMed
 - pmc**: PubMed Central
 - nlmcatalog**: NLM Catalog
- id** (required): Either a single unique identifier (UID) or a comma-delimited list of UIDs. All of the UIDs must be from the database specified by the **db** parameter.

EFetch Optional Parameters

- retstart** (optional): Setting this parameter helps limit which records will be shown in the output, as it determines whether the record for the first input unique identifier (UID) is retrieved, or whether to skip to a later UID in the input list. For example, if **retstart** is set to **10**, the output will begin with the record for the tenth UID. The default of this parameter is **1**, corresponding to the first UID in the input list. This parameter can be used in conjunction with **retmax** to download an arbitrary subset of records.
- retmax** (optional): Total number of records to be shown in the output, up to a maximum of 10,000. If the set of records you are trying to retrieve is larger than 10,000, you can submit multiple EFetch requests, and increase the **retstart** parameter each time.
- retmode**/**rettype**: These two parameters determine how your results will be displayed. **retmode** determines the data format your records will be returned in (e.g. XML, plain text, etc.). **rettype** determines the specific view your records will be returned in (e.g. MEDLINE, Abstract, list of PMIDs, etc.). Different databases have different allowable data formats and record views, and not all **retmode** data formats are compatible with all **rettype** record views, and vice versa.


The table below shows the allowable combinations of **retmode** and **rettype** for some of the databases. **Bold** **retmode** values are the default data format for the specified database. **Bold** **rettype** parameters are the default record view for the specified data format and database.

EFetch Examples

- Retrieve the abstract view (text format) of two PubMed records.
 - <https://eutils.ncbi.nlm.nih.gov/entrez/eutils/efetch.fcgi?db=pubmed&id=17284678,9997&retmode=text&rettype=abstract>
- Retrieve two PubMed records in XML format.
 - <https://eutils.ncbi.nlm.nih.gov/entrez/eutils/efetch.fcgi?db=pubmed&id=11748933,11700088&retmode=xml>

ESearch Formatting Parameters

- **retstart** (optional): Setting this parameter helps limit which of the unique identifiers (UIDs) in the results set will be shown in the output, as it determines whether the output begins at the first retrieved UID, or with a UID that is later in the results set. For example, if **retstart** is set to **10**, the first ten UIDs in the results set will be skipped, and the output will begin with the eleventh UID. The default of this parameter is **0**, corresponding to the first record in the entire set. This parameter can be used in conjunction with **retmax** to download an arbitrary subset of UIDs retrieved from a search.
- **retmax** (optional): Total number of unique identifiers (UIDs) from the retrieved set to be shown in the output (default=20). Increasing **retmax** allows more of the retrieved UIDs to be included in the output, up to a maximum of 100,000 UIDs. If you need to retrieve more than 100,000 UIDs, you can submit multiple ESearch requests, and increase the **retstart** parameter each time. For example:
 - <https://eutils.ncbi.nlm.nih.gov/entrez/eutils/esearch.fcgi?db=pubmed&term=cancer&retmax=100>: This URL will return results 1 through 100 of a search for "Cancer".
 - <https://eutils.ncbi.nlm.nih.gov/entrez/eutils/esearch.fcgi?db=pubmed&term=cancer&retstart=100&retmax=100>: This URL will return results 101 through 200 of the same search for "Cancer".
- **rettype** (optional): Retrieval type. There are two supported values:
 - **uilist** (default): Displays the standard XML output, including a list of unique identifiers (UIDs), the total number of results, and the query translation for the search.
 - **count**: Displays only the total number of results, without the list of UIDs or query translation.
- **retmode** (optional): Determines the format of the returned output. The default value is **xml**, but **json** is also supported.



https://www.rcsb.org 80%

RCSB PDB Deposit Search Visualize Analyze Download Learn More MyPDB

RCSB PDB PROTEIN DATA BANK

161757 Biological Macromolecular Structures Enabling Breakthroughs in Research and Education

Search by PDB ID, author, macromolecule, sequence, or ligands **Go**

Advanced Search | Browse by Annotations

PDB-101 EMBL-EBI Protein Data Bank EMDB Resource Worldwide Protein Data Bank Foundation

f t y d

Welcome

Deposit

Search

Visualize

Analyze

Download


Learn

A Structural View of Biology


This resource is powered by the Protein Data Bank archive—information about the 3D shapes of proteins, nucleic acids, and complex assemblies that helps students and researchers understand all aspects of biomedicine and agriculture, from protein synthesis to health and disease.

As a member of the wwPDB, the RCSB PDB curates and annotates PDB data.

The RCSB PDB builds upon the data by creating tools and resources for research and education in molecular biology, structural biology, computational biology, and beyond.




March Molecule of the Month



Voltage-gated Sodium Channels

- ❶ **XML** – Extensible Markup Language – rozszerzalny język znakowania przeznaczony do reprezentowania różnych danych w ustrukturalizowany sposób
 - ❶ **znacznik** – ciąg liter, cyfr i innych znaków (bez spacji i zaczynający się od litery) ograniczony znakami `<` i `>`. Tagowi (znacznikowi) otwierającemu zawsze towarzyszy tag zamykający zaczynający się od znaków `</` i kończący się znakiem `>`.
 - ❷ **atrybut** – definiowany w obrębie znacznika, składa się zwykle pary *nazwa = wartość*, przy czym wartość zwykle podawana jest w cudzysłowach,
 - ❸ **encja** – jest elementem treści dokumentu i reprezentuje pojedynczy symbol, encje definiuje się podając po znaku `&` numer symbolu i kończąc znakiem średnika, np `<`;



```

<eInfoResult>
  <DbInfo>
    <DbName>pubmed</DbName>
    <MenuName>PubMed</MenuName>
    <Description>PubMed bibliographic record</Description>
    <Count>22595116</Count>
    <LastUpdate>2013/03/19 03:50</LastUpdate>
    <FieldList>
      <Field>
        <Name>ALL</Name>
        <FullName>All Fields</FullName>
        <Description>All terms from all searchable fields</Description>
        <TermCount>139835112</TermCount>
        <IsDate>N</IsDate>
        <IsNumerical>N</IsNumerical>
        <SingleToken>N</SingleToken>
        <Hierarchy>N</Hierarchy>
        <IsHidden>N</IsHidden>
      </Field>
      <Field>
        ...
      </Field>
    </eInfoResult>

```

Niech dane są $v = (1, 2)$ oraz $w = (4, 0)$. Wtedy:

- ❶ **suma wektorów** v i w wynosi:

$$v + w = (1 + 4, 2 + 0) = (5, 2),$$

- ❷ **iloczyn skalarny wektorów** v i w wynosi:

$$\langle v, w \rangle = 1 \cdot 4 + 2 \cdot 0 = 4 + 0 = 4$$

- ❸ **długość wektora** v wynosi:

$$\|v\| = \sqrt{\langle v, v \rangle} = \sqrt{1 \cdot 1 + 2 \cdot 2} = \sqrt{5}.$$

Niech dane są $v = (1, 2, 3)$ oraz $w = (4, 0, -2)$. Wtedy:

- ❶ **suma wektorów** v i w wynosi:

$$v + w = (1 + 4, 2 + 0, 3 + (-2)) = (5, 2, 1),$$

- ❷ **iloczyn skalarny wektorów** v i w wynosi:

$$\langle v, w \rangle = 1 \cdot 4 + 2 \cdot 0 + 3 \cdot (-2) = 4 + 0 - 6 = -2,$$

- ❸ **długość wektora** v wynosi:

$$\|v\| = \sqrt{\langle v, v \rangle} = \sqrt{1 \cdot 1 + 2 \cdot 2 + 3 \cdot 3} = \sqrt{14}.$$

Niech dane są $v = (v_1, v_2, \dots, v_n)$ oraz $w = (w_1, w_2, \dots, w_n)$. Wtedy:

- ❶ **suma wektorów** v i w wynosi:

$$v + w = (v_1 + w_1, v_2 + w_2, \dots, v_n + w_n),$$

- ❷ **iloczyn skalarny wektorów** v i w wynosi:

$$\langle v, w \rangle = v_1 w_1 + v_2 w_2 + \dots + v_n w_n,$$

- ❸ **długość wektora** v wynosi:

$$\|v\| = \sqrt{\langle v, v \rangle} = \sqrt{v_1 v_1 + v_2 v_2 + \dots + v_n v_n} = \sqrt{v_1^2 + v_2^2 + \dots + v_n^2}.$$

Zdanie1: new york times

Zdanie2: new york post

Zdanie3: los angeles times

Dokument1: new york times

Dokument2: new york post

Dokument3: los angeles times

Występujące słowa : angeles, los, new, post, times, york

Dokument1: new york times

Dokument2: new york post

Dokument3: los angeles times

Występujące słowa (w ilu tekstach): angeles (1), los (1), new (2), post (1), times (2), york (2)

IDF (Inverse Document Frequency)

Liczba zdań $N = 3$.

Występujące słowa (w ilu tekstach): angeles (1), los (1), new (2), post (1), times (2), york (2)

$$idf_i = \log_2\left(\frac{N}{df_i}\right)$$

gdzie df_i - liczba dokumentów zawierających i -te słowo. Wtedy:

- angles, $\log_2\left(\frac{3}{1}\right) = 1.584$,
- los, $\log_2\left(\frac{3}{1}\right) = 1.584$,
- new, $\log_2\left(\frac{3}{2}\right) = 0.584$,
- post, $\log_2\left(\frac{3}{1}\right) = 1.584$,
- times, $\log_2\left(\frac{3}{2}\right) = 0.584$,
- york, $\log_2\left(\frac{3}{2}\right) = 0.584$.

TF (Term Frequency)

Niech:

f_{ij} - częstość i - tego słowa w dokumencie j .

Wtedy:

$$tf_{ij} = \frac{f_{ij}}{\max\{f_{ij}\}}.$$

W naszym przypadku:

| | angeles | los | new | post | times | york |
|----|---------|-----|-----|------|-------|------|
| d1 | 0 | 0 | 1 | 0 | 1 | 1 |
| d2 | 0 | 0 | 1 | 1 | 0 | 1 |
| d3 | 1 | 1 | 0 | 0 | 1 | 0 |

Definiujemy:

$$w_{ij} = tf_{ij}idf_i = tf_{ij} \log_2\left(\frac{N}{df_i}\right).$$

Uwaga:

- słowa występujące często w jakimś dokumencie, ale rzadko w pozostałych dokumentach będą miały wysoką wagę
- eksperymentalnie takie ważenie się sprawdza

Ważenie TF-IDF

Definiujemy:

$$w_{ij} = tf_{ij}idf_i = tf_{ij} \log_2\left(\frac{N}{df_i}\right).$$

W naszym przypadku:

| | angeles | los | new | post | times | york |
|----|---------|-------|-------|-------|-------|-------|
| d1 | 0 | 0 | 0.584 | 0 | 0.584 | 0.584 |
| d2 | 0 | 0 | 0.584 | 1.584 | 0 | 0.584 |
| d3 | 1.584 | 1.584 | 0 | 0 | 0.584 | 0 |

Powiedzmy, że mamy nowy dokument:

new new times

Pytanie: Który dokument najbardziej przypomina?

Powiedzmy, że mamy nowy dokument:

new new times

Pytanie: Który dokument najbardziej przypomina? Należy obliczyć ważenie $TD - IDF$ dla zapytania.

Powiedzmy, że mamy nowy dokument:

new new times

Pytanie: Który dokument najbardziej przypomina? Należy obliczyć ważenie $TD - IDF$ dla zapytania.

| | | | | | | |
|---|---|---|---------------------|---|---------------------|---|
| q | 0 | 0 | $(2/2)*0.584=0.584$ | 0 | $(1/2)*0.584=0.292$ | 0 |
|---|---|---|---------------------|---|---------------------|---|

Mamy:

- $\|d1\| = \sqrt{0.584^2 + 0.584^2 + 0.584^2} = 1.011,$
- $\|d2\| = \sqrt{0.584^2 + 1.584^2 + 0.584^2} = 1.786,$
- $\|d3\| = \sqrt{1.584^2 + 1.584^2 + 0.584^2} = 2.316,$
- $\|q\| = \sqrt{0.584^2 + 0.292^2} = 0.652.$

Podobieństwo pomiędzy wektorami

Mamy:

$$\cos(d, q) = \frac{\langle d, q \rangle}{\|d\| \cdot \|q\|}$$

Zadanie:

Wyznaczy miarę kosinus pomiędzy sekwencjami $d1$, $d2$, $d3$ a q .

Mamy:

$$\cos(d, q) = \frac{\langle d, q \rangle}{\|d\| \cdot \|q\|}$$

- $\cos(d1, q) = \frac{0 \cdot 0 + 0 \cdot 0 + 0.584 \cdot 0.584 + 0 \cdot 0 + 0.584 \cdot 0.292 + 0.584 \cdot 0}{1.011 \cdot 0.652} = 0.776$
- $\cos(d2, q) = \frac{0 \cdot 0 + 0 \cdot 0 + 0.584 \cdot 0.584 + 1.584 \cdot 0 + 0 \cdot 0.292 + 0.584 \cdot 0}{1.786 \cdot 0.652} = 0.292$
- $\cos(d3, q) = \frac{1.584 \cdot 0 + 1.584 \cdot 0 + 0 \cdot 0.584 + 0 \cdot 0 + 0.584 \cdot 0.292 + 0 \cdot 0}{2.316 \cdot 0.652} = 0.112$

W jakiej kolejności należałoby zwrócić dokumenty na podane zapytanie?