School of Computer Science and Engineering

Department of Artificial Intelligence and Machine Learning

M.Tech (Computer Science and Engineering / Artificial Intelligence and Machine Learning)

Fall Semester 2026

Course Title: Visual Analytics Lab | **Course Code:** MACSE603

Slot: VL2026270106590 (PRP135)

COMPREHENSIVE CAPSTONE PROJECT REPORT

SMART ENERGY CONSUMPTION VISUALIZATION DASHBOARD USING POWER BI & IoT PIPELINES

An Integrated Multi-Tier Visual Analytics Framework with Kimball Star Schema Warehouse, Machine Learning Demand Forecasting, Shewhart Statistical Quality Control, Apache ECharts, and Cloud-Native Telemetry Analytics

---

SUBMITTED TO

Dr. Mary Jennifer J

Assistant Professor (Senior)

School of Social Sciences and Languages (SSL) / Faculty Evaluator

School of Computer Science and Engineering (SCOPE)

Vellore Institute of Technology, Vellore - 632014

SUBMITTED BY: PROJECT TEAM

Student Name	Registration Number	Program & Branch	Project Role
Vedant Nimkar	26MML0045	M.Tech CSE / AI & ML	Team Leader (Lead Architect & Power BI Dev)
Jitesh Bobde	26MML0025	M.Tech CSE / AI & ML	Team Member (ETL & Dimensional Modeling)
Ayush Sharma	26MML0043	M.Tech CSE / AI & ML	Team Member (IoT Telemetry & Literature Review)

Vellore Institute of Technology, Vellore - 632014, Tamil Nadu, India

October 2026

Abstract

Large institutional campuses and modern commercial building complexes face escalating electrical utility expenditures governed by multi-tier Time-of-Use (ToU) tariffs, high peak contract demand charges, and distributed sub-facility operations. Traditional monitoring methods rely on monthly aggregated billing statements that conceal instantaneous load spikes, overnight baseload leaks, and uncorrected low power-factor penalties. This project engineers an end-to-end, publication-grade Smart Energy Consumption Visual Analytics platform that unifies IoT sensor edge ingestion, automated ETL normalization, a 52,560-record Star Schema warehouse (FY 2025 across 6 facilities), machine learning demand forecasting, Shewhart statistical anomaly detection, and dual-track presentation serving.

The diagnostic and predictive core features a Fourier-expanded Ridge regression engine achieving an exceptional accuracy of $R^2 = 0.996$ *(MAE = 270.1 kWh, MAPE = 0.61%) across a 30-day holdout validation, and a rolling Shewhart +/-3sigma control limit algorithm that successfully flags 196 operational breaches, including a high-severity weekend chiller runaway that wasted INR 64,400. In the serving tier, we engineer a modern Microsoft Fabric Power BI Project (.pbip) using clean Tabular Model Definition Language (TMDL) and Power BI Report (PBIR) multi-page layouts alongside an interactive, responsive cyber-glassmorphism Web Application built with Apache ECharts and deployed globally to Vercel (https://webdashboard-eta.vercel.app). The system demonstrates an actionable annual cost-saving potential of* ***INR 21.34 Lakhs*** *through automated peak shaving and anomaly curtailment.*

1. Introduction & Background

Modern university campuses operate as self-contained micro-cities comprising diverse facilities: academic lecture halls, intensive research laboratories, high-density residential dormitories, 24x7 computing server wings, sports complexes, and central administrative infrastructure. Managing the electrical demand of such heterogeneous complexes is exceptionally challenging due to disjointed operating hours, localized climatic variances, and differing equipment loads. Without granular, time-synchronized telemetry, facilities managers are forced into a reactive posture - receiving electricity bills weeks after consumption has occurred, with no ability to pinpoint the root cause of billing surges.

Visual Analytics bridges this cognitive and operational divide. By combining automated data transformation pipelines, dimensional modeling, predictive machine learning, and interactive visual encodings, Visual Analytics enables stakeholders to move seamlessly from high-level executive KPIs down to root-cause submetered appliance telemetry. Following Ben Shneiderman's Visual Information Seeking Mantra - *'Overview first, zoom and filter, then details-on-demand'* - this platform empowers energy managers to eliminate unmonitored equipment runaways, optimize contract maximum demand thresholds, and coordinate rooftop solar photovoltaic (PV) generation with peak commercial tariff windows.

Key Research & Engineering Objectives:

- **Granular Temporal Ingestion:** Capture 52,560 hourly metered intervals spanning all 8,760 hours of FY 2025 across 6 diverse campus facilities.
- **Dimensional Data Warehouse:** Construct a robust Kimball-style Star Schema with 1 central fact, 4 derived analytical facts, and 6 dimension tables.
- **Predictive Demand Modeling:** Implement regularized machine learning time-series forecasting capturing diurnal, intra-week, and weather cooling-degree dynamics.
- **Statistical Quality Control:** Formulate rolling Shewhart +/-3sigma control charts to isolate operational anomalies, baseline drift, and equipment leaks.
- **Dual-Platform Enterprise Serving:** Deploy both a native Power BI Project (.pbip with TMDL/PBIR) and an open-access cloud Web Dashboard on Vercel.

2. System Model & Pipeline Architecture

The platform architecture follows a decoupled, five-tier pipeline designed for high resilience, analytical reproducibility, and sub-second interactive query response times across millions of metered data points.




Figure 1: *End-to-End Five-Tier Smart Energy Visual Analytics Pipeline Architecture*

Tier 1: Telemetry Ingestion Gate: Collects raw electrical measurements (active power kW, reactive power kVARh, voltage V, power factor) and environmental sensors (ambient temperature °C, solar irradiance W/m^2). Features automated schema verification, range clipping, and null imputation.

Tier 2: Automated ETL & Feature Engineering: Executes Cooling Degree Hours (CDH = max(0, Temp - 24.0°C)) integration, solar self-consumption ratio calculations, time-of-use tariff matching, and carbon emission footprint quantification (0.82 kg CO_2e / kWh grid factor).

Tier 3: Kimball Star Schema Warehouse: Relational persistence across 11 synchronized CSV tables organized into core facts (hourly readings, submetering, ML forecasts, anomalies, load clusters) and denormalized dimensions (facilities, date, time, tariffs, weather, appliances).

Tier 4: Predictive & Diagnostic Analytics Engine: Python-powered analytics executing Ridge Fourier demand forecasting, Shewhart statistical quality control limits, Barnes-Hut t-SNE dimensionality reduction, and K-Means load-shape archetype clustering.

Tier 5: Presentation & Interactive Serving Layer: Dual presentation interfaces: (a) Native Power BI Project (.pbip) with TMDL definitions and 12 DAX measures; (b) Cloud Web Dashboard deployed on Vercel with responsive Apache ECharts and real-time MQTT simulator.

3. Literature Review & Synthesis of Core Research Papers

This project directly synthesizes and builds upon six foundational research papers from smart energy monitoring, big data visualization, business intelligence, and machine learning literature:

No.	Study / Reference	Methodological Core	Key Finding	Implementation in Our Project
1	Portugal BI Solution (2024)	Design Science Research (DSRM) over national grid data	Proved that star schemas and drill-throughs dramatically reduce analytical query latency	Engineered Kimball star schema warehouse and multi-pa
2	Awate et al. (IJARSCT 2023)	Big data analytics on 500 residential meters over 24 months	Peak-demand forecasting and consumer ranking exposed high-load households	Scaled high-granularity consumption to hourly (52.5k rows)
3	Energy Calc. in Power BI (2023)	End-to-end Power BI workflow from collection to visualization	Demonstrated the criticality of reusable DAX measures for time-intelligenc	Engineered 12 enterprise DAX measures including time-intelligenc
4	Soliman & Fetais (IEEE 2017)	Big data visualization of Qatar smart meter network	Identified data inconsistency, outlier pollution, and slow ETL as primary barriers	Built robust ETL quality gates with hard-limit validation, physi
5	IoT Smart Energy (IJIRT 2026)	ESP32 voltage/current sensing, MQTT broker, cloud database	Demonstrated hardware-to-cloud telemetry pipelines for real-time monitoring	Designed MQTT-ready IoT telemetry simulator pushing liv
6	Interactive ML (ESANN 2024)	2D manifold mapping of load profiles using t-SNE and clustering	Revealed that dimensional reduction uncovers hidden behavioral archetypes	Implemented t-SNE visualization for project use

4. Existing Approaches & Methodological Limitations

Commercial and institutional energy monitoring has historically relied on three prevailing approaches, each characterized by severe architectural and operational deficiencies:

- **1. Monthly Utility Invoices & Manual Spreadsheets:** Aggregates total kilowatt-hours into a single billing figure weeks after consumption. Completely obscures peak demand spikes, provides zero temporal granularity, and prevents timely root-cause investigation.

• **2. Closed SCADA / Building Management Systems (BMS):** Highly proprietary industrial hardware installations (e.g., Siemens, Honeywell). While providing millisecond sensor polling, they suffer from extreme vendor lock-in, high licensing costs, rigid user interfaces, and an utter lack of executive visual storytelling or modern machine learning forecasting.

• **3. Standalone Python / Jupyter Notebook Workflows:** Data scientists frequently perform ad-hoc analysis in isolated notebooks. While algorithmically sophisticated, these pipelines are entirely detached from operational facility managers, lack automated refresh schedules, and provide no persistent visual interface.

5. Proposed Design & Star Schema Warehouse

To resolve these limitations, we formulate a Kimball Star Schema specifically optimized for time-series energy analytics. The relational schema separates highly transactional fact tables from contextual dimensions, ensuring efficient analytical query execution in both Power BI's in-memory VertiPaq engine and relational SQL databases.

Table Name	Type	Row Count	Primary Keys / Foreign Keys	Analytical Grain & Core Attributes
Fact_EnergyConsumption	Fact	52,560	Timestamp, FacilityID, TariffID	Hourly facility readings: ActivePower_kWh, ReactivePower_kVARh, Cost_INR, Anor
Fact_ApplianceSubmeter	Fact	60,480	Date, Hour, FacilityID, ApplianceID	Hourly end-use disaggregation: HVAC, Servers/IT, Lighting, Motors, Auxiliary Plug.
Fact_DemandForecast	Fact	395	Date	Daily campus demand: Actual_kWh, Forecast_kWh, Lower95_kWh, Upper95_kWh.
Fact_Anomalies_Detailed	Fact	196	Timestamp, FacilityID	Operational breaches: RollingMean_kWh, Excess_kWh, WastedCost_INR, Anomaly
Fact_LoadClusters	Fact	2,190	Date, FacilityID	Dimensional manifold: tSNE_1, tSNE_2, ClusterID, ClusterName.
Dim_Facility	Dim	6	FacilityID (PK)	Facility metadata: FacilityName, Category, Area_SqFt, Baseline_kW, Solar_kWp.
Dim_Tariff	Dim	3	TariffID (PK)	ToU tariff schedule: PeakRate_INR, ShoulderRate_INR, OffPeakRate_INR, Demand
Dim_Date	Dim	731	Date (PK)	Calendar dimensions: Year, Quarter, Month, WeekNum, DayOfWeek, IsWeekend, S
Dim_Time	Dim	24	Hour (PK)	Intra-day temporal grain: HourFormatted, PeriodOfDay, TariffBand, PeakTariffFlag.
Dim_Weather	Dim	17,544	Date, Hour (PK)	Climatic context: AmbientTemp_C, SolarIrradiance_W_m2, CoolingDegreeHours.
Dim_Appliance	Dim	5	ApplianceID (PK)	Equipment taxonomy: ApplianceName, PowerRating_kW, Category, EfficiencyRatin

Enterprise DAX Measure Formulations:

• **Total Active Consumption (GWh)**: DIVIDE(SUM(Fact_EnergyConsumption[ActivePower_kWh]), 1000000)
Total electrical energy utilized across all campus facilities in Gigawatt-hours.

• **Total Electricity Spend (Cr)**: DIVIDE(SUM(Fact_EnergyConsumption[Cost_INR]), 10000000)
Cumulative tariff expenditure formatted in Indian Crores (INR).

• **Campus Peak Demand (kW)**: MAXX(VALUES(Fact_EnergyConsumption[Timestamp]), CALCULATE(SUM(Fact_EnergyConsumption[ActivePower_kWh])))
Coincident instantaneous peak demand across campus for contract demand billing.

• **Solar Penetration %**: DIVIDE(SUM(Fact_EnergyConsumption[SolarGeneration_kWh]), SUM(Fact_EnergyConsumption[ActivePower_kWh]), 0)
Proportion of total electrical demand offset directly by on-site clean solar PV generation.

• **Carbon Footprint (tCO_2e)**: DIVIDE(SUM(Fact_EnergyConsumption[Carbon_kgCO_2]), 1000)
Total Scope 2 greenhouse gas emissions using CEA grid emission factor (0.82 kg CO_2e / kWh).

• **Clean Energy Offset (tCO_2e)**: DIVIDE(SUM(Fact_EnergyConsumption[SolarGeneration_kWh]) * 0.82, 1000)
Direct carbon emissions abated through solar self-consumption (equivalent to ~42,500 trees).

• **Operational Anomaly Count**: CALCULATE(COUNTROWS(Fact_EnergyConsumption), Fact_EnergyConsumption[AnomalyFlag] = 1)
Total number of hourly intervals breaching statistical control limits.

6. Implementation & Technical Realization

Implementation spanned four tightly integrated technical workstreams: automated data pipelines, machine learning algorithms, modern Microsoft Power BI Project (.pbip) assembly, and cloud deployment.

A. Machine Learning Analytics Engines

1. Prophet-Style Ridge Demand Forecasting: We implement regularized Ridge regression (alpha = 1.0) incorporating dual Fourier harmonic terms to model diurnal (P = 24h) and intra-week (P = 168h) periodicity alongside weather interactions:

ActivePower(t) = beta0 + SUM [alphak sin(2pikt/P) + gammak cos(2pikt/P)] + beta_cdh CDH(t) + beta_occ Occupancy(t) + epsilon

On a 30-day holdout validation dataset, the model achieved an **R^2 score of 0.996**, a Mean Absolute Error of 270.1 kWh, and a Mean Absolute Percentage Error of 0.61%.

2. Shewhart +/-3sigma Statistical Process Control: Rolling 24-hour mean (mu_24) and standard deviation (sigma_24) limits dynamically track baseline variations. Operational anomalies are flagged whenever: ActivePower(t) > mu_24(t) + 3*sigma_24(t). Across FY 2025, exactly 196 hourly anomalies were isolated, categorizing weekend equipment leaks, HVAC override breaches, and sensor faults.

3. 24-Dimensional t-SNE Load-Shape Manifold: Daily 24-hour load profiles were normalized into unit vectors and mapped onto a two-dimensional manifold using Barnes-Hut t-SNE (perplexity = 30, iterations = 1000). K-Means clustering (k = 4) isolates four distinct operational archetypes: (1) Commercial Day-Shift Heavy, (2) Continuous 24x7 Server Baseload, (3) Evening Residential Peak, and (4) Weekend Idle Curtailment.

B. Modern Power BI Architecture (.pbip, TMDL & PBIR)

Rather than relying on legacy, brittle binary .pbix packages, this project adopts Microsoft's official Fabric **Power BI Project (.pbip)** format. The semantic model is defined entirely in Tabular Model Definition Language (TMDL) files (in SemanticModel/definition/tables/), enabling full Git version control, branch merging, and collaborative schema evolution. Report pages and visuals are defined in structured Power BI Report (PBIR) JSON schemas (in Report/definition/pages/). Furthermore, our generator resolves the classic PowerBIFileSerializer UTF-16LE Byte Order Mark (BOM) parsing exception by serializing diagram layouts without BOM, ensuring instant, error-free loading in Power BI Desktop v2.157+.




Figure 2: *Native Microsoft Fabric Power BI Desktop Multi-Page Report & Star Schema Analytics Interface (Dark Executive Theme)*

Figure 2 captures the operational Power BI Desktop application running the Smart Energy Dashboard. The executive view delivers six high-visibility KPI indicator cards (Active Consumption 19.35 GWh, Total Electricity Spend INR 13.20 Cr, Campus Peak Demand 2,840 kW, Solar Carbon Offset 936.8 tCO_2e, 196 Operational Breaches, and 0.94 Power Factor), dynamic facility slicers, calendar date filtering, diurnal active load area profiles, facility consumption comparisons, and a cross-filtering benchmark matrix.

C. Cloud Web Dashboard & Telemetry Streaming

To provide universally accessible analytics without requiring proprietary desktop installations, we built a responsive, cyber-glassmorphism Web Dashboard using Vanilla JavaScript and Apache ECharts. The web application is deployed to production on the Vercel Edge Serverless Network (https://webdashboard-eta.vercel.app) with automated CI/CD continuous deployment connected to our GitHub repository (adminsharpcode/visual-analytics-lab). It includes a live ESP32 IoT sensor simulator emitting 3-phase telemetry packets over MQTT every 1.5 seconds with real-time waveform oscilloscopes.




Figure 3: *Cloud-Native Cyber-Executive Apache ECharts Real-Time Telemetry HUD Deployed Globally on Vercel (https://webdashboard-eta.vercel.app)*

Figure 3 illustrates the production Cloud Web Dashboard rendering in Apache ECharts (v5.4.3). The cyber-slate dark interface features real-time KPI telemetry ribbons, interactive multi-facility slicers, animated solar self-consumption gauges, and high-frequency IoT streaming charts rendered smoothly at 60 FPS via hardware-accelerated canvas.

7. Comprehensive Result Analysis & Visual Findings

We evaluate the operational, visual, and financial performance of the platform across seven dedicated visual analytic modules powered by interactive Apache ECharts rendering:



Figure 4: Interactive Apache ECharts 24x7 Campus Load Intensity Heatmap Matrix (Hourly Demand in kW across Days & Hours)

Finding 1: 24x7 Operational Regime Segmentation: The hour-of-day versus day-of-week intensity matrix in Figure 4 exposes distinct operational regimes through continuous visual color ramps: sharp morning demand ramps at 08:30 (escalating from 950 kW to 2,200 kW), coincident afternoon peaks (14:00 - 17:00) driven by thermal cooling inertia, and a sustained overnight baseload of ~820 kW primarily driven by Computing Wing C server clusters and continuous ventilation chillers.



Figure 5: Apache ECharts 30-Day Ahead Fourier Ridge Demand Forecast with Dynamic 95% Confidence Prediction Bands (R^2 = 0.996)

Finding 2: High-Fidelity Machine Learning Forecasting: Figure 5 demonstrates the predictive performance of the Fourier-expanded Ridge regression engine across a 30-day unseen holdout validation horizon. The model achieves an outstanding **R^2 score of 0.996**, a Mean Absolute Error (MAE) of **270.1 kWh**, and a Mean Absolute Percentage Error (MAPE) of **0.61%**. The interactive visual encoding clearly delineates historical training observations, holdout actuals, predicted trajectory, and 95% expanding confidence bounds.



Figure 6: *Interactive Shewhart 3-Sigma Rolling Statistical Process Control Chart Highlighting Equipment Operational Runaway Breaches & Audit Log*

Finding 3: Automated Detection of Equipment Runaways & Baseload Leaks: Figure 6 isolates an acute operational fault where Academic Block A chillers remained energized at 100% load across an entire summer weekend. The dynamic Shewhart +/-3sigma control limit chart flagged the breach immediately as active power exceeded upper control bounds (+280 kWh/h above threshold for 46 consecutive hours). The automated diagnostic module calculated the avoidable financial waste at **INR 64,400**, contributing to a total of 196 isolated anomalies saving **INR 2.84 Lakhs** across FY 2025.




Figure 7: *24-Dimensional Barnes-Hut t-SNE Manifold Projection & K-Means Clustering of 2,190 Daily Load Archetypes in Apache ECharts*

Finding 4: Behavioral Archetype Isolation via Manifold Learning: Figure 7 presents the 2D non-linear manifold projection of 2,190 daily load vectors normalized into unit profiles. K-Means clustering (k = 4) isolates four distinct operational archetypes: (1) Commercial Day-Shift Heavy (38.2%), (2) Continuous 24x7 Server Baseload (22.1%), (3) Evening Residential Peak (24.5%), and (4) Low Weekend Idle Curtailment (15.2%). Interactive tooltip inspections allow facilities operators to classify daily operating schedules instantaneously.




Figure 8: Campus End-Use Submetering Category Disaggregation & Polar Load Distribution in Apache ECharts

Finding 5: End-Use Submetered Attribution & Polar Distribution: Figure 8 displays the disaggregation of total electrical demand into five functional circuits via an interactive donut and polar coordinate radar encoding. HVAC and thermal comfort dominate campus demand at **42.1%** (8.15 GWh), followed by Computing & Server IT infrastructure at **22.4%** (4.34 GWh), architectural lighting at **18.2%** (3.52 GWh), heavy induction pumps/motors at **11.8%** (2.28 GWh), and auxiliary plug loads at **5.5%**.




Figure 9: Facility Consumption Benchmark & Top-N Ranking with Monthly Sparklines

Finding 6: Facility Energy Intensity Disparity: Benchmarking across facilities in Figure 9 reveals that Computing Wing C (4.88 GWh) and Research Complex B (4.21 GWh) consume 46.9% of campus energy despite occupying only 28.5% of total floor area, identifying them as prime candidates for targeted solar carport installations.




Figure 10: *Diurnal Power Flow - Solar PV Generation vs. Net Grid Import Load Curve*

Finding 7: Solar PV Self-Consumption & Peak Coincidence: Figure 10 contrasts campus total load against on-site rooftop solar PV generation (590 kWp installed capacity). Solar generation crests at 420 kW during mid-day hours (11:30-13:30), coinciding with peak air-conditioning draw. The solar self-consumption ratio reaches **94.2%**, eliminating grid backfeeding and abating **936.8 tCO_2e** in annual Scope 2 emissions.

Annual Quantitative Performance Summary (FY 2025):

Key Metric Description	Annual Metric Value	Unit of Measure	Operational Significance & Impact
Total Active Energy Consumption	19,352,396	kWh (19.35 GWh)	Comprehensive campus baseline for carbon accounting.
Total Annual Electricity Spend	13.20	Crores INR (INR)	Governed by Time-of-Use tariff structure with peak penalties.
Solar PV Self-Generation	1,142,435	kWh (1.14 GWh)	5.90% Renewable penetration from 590 kWp installed PV.
Campus Peak Coincident Demand	2,840.0	kW	Contract demand threshold recorded during June cooling peak.
Total Campus Carbon Footprint	15,868.9	tCO₂e	Quantified using Central Electricity Authority grid factor.
Clean Solar Carbon Offset	936.8	tCO₂e	Equivalent to environmental benefit of ~42,500 mature trees.
Operational Anomalies Flagged	196	Events	Prevented avoidable equipment waste of ~INR 2.84 Lakhs.
Forecasting Model Accuracy	R² = 0.996	Validation Holdout	MAPE = 0.61%, MAE = 270.1 kWh on 30-day unseen test.

8. Conclusion & Strategic Recommendations

This project successfully conceptualized, validated, and deployed a production-grade Smart Energy Consumption Visual Analytics platform. By synthesizing the core methodologies of six foundational research papers - Kimball star schemas, Prophet/Ridge machine learning forecasting, Shewhart statistical anomaly detection, and t-SNE manifold clustering - we have demonstrated that Visual Analytics transforms raw electrical telemetry into strategic, actionable business value.

Actionable Campus Energy Strategies:

*1. Peak Shaving via HVAC Pre-Cooling: Pre-cooling Academic Complex A and Research Wing B between 11:00 and 13:00 utilizes surplus rooftop solar power and flattens the 14:00-17:00 commercial peak demand, saving an estimated **INR 18.5 Lakhs annually** in demand charges.*

*2. Automated Shewhart Weekend Shutdowns: Connecting Shewhart +/-3sigma alerts to automated building management relays prevents chiller runaways during non-occupancy hours, eliminating **INR 2.84 Lakhs** in avoidable waste.*

3. Targeted Solar PV Expansion: Prioritizing a 350 kWp carport solar installation on Computing Wing C directly offsets the continuous 24x7 IT server baseload.

9. Future Scope & Research Extensions

• **Reinforcement Learning BESS Dispatch:** Train Deep Q-Network (DQN) agents to dynamically charge and discharge battery energy storage systems (BESS) based on real-time solar irradiance and day-ahead electricity spot tariffs.

• **Edge AI Microcontroller Deployment:** Compile lightweight TinyML neural networks directly onto ESP32-S3 edge microcontrollers for sub-second anomaly detection at the circuit-breaker level without cloud latency.

• **Automated OpenADR Demand Response:** Integrate OpenADR 2.0b compliance protocols to allow the campus microgrid to participate in utility automated demand response programs and frequency regulation markets.

• **3D Spatial Digital Twin Analytics:** Develop a WebGL/Three.js 3D digital twin of the campus integrating building thermal envelopes, solar shading models, and real-time indoor air quality sensors.

10. Bibliographic References

1. NOVA IMS, 'Energy Consumption Distribution in Portugal: A Business Intelligence Solution,' Master's Dissertation, NOVA Information Management School, Universidade Nova de Lisboa, 2024.

2. S. A. Awate, R. Chaurasia, P. Kirolkar, M. More, and P. Ingale, 'Electricity Consumption using Big Data Analytics,' International Journal of Advanced Research in Science, Communication and Technology (IJARSCT), vol. 3, no. 2, pp. 245-252, 2023. DOI: 10.48175/IJARSCT-9099.

3. R. Sharma and K. Patel, 'Energy Calculation Using Power BI: A Practical Implementation Framework for Commercial Facilities,' International Journal of Research Publication and Reviews (IJRPR), vol. 4, no. 8, pp. 1120-1128, 2023.

4. E. Soliman and N. Fetais, 'Visualization as a Means of Big Data Management: Using Qatar's Electricity Consumption Data,' in Proc. IEEE GCC Conference and Exhibition (GCCCE), Manama, Bahrain, 2017, pp. 1-9. DOI: 10.1109/GCCCE.2017.8080512.

5. A. K. Verma, P. Singh, and M. Thomas, 'An IoT-Enabled Smart Energy Monitoring and Fault Prediction System Using ESP32 and Cloud Analytics,' International Journal of Innovative Research in Technology (IJIRT), vol. 12, no. 4, pp. 410-418, 2026.

6. F. Rossi, M. Verleysen, and H. Bourlard, 'Interactive Machine Learning-Powered Dashboard for Smart Meter Load Analytics,' in Proc. European Symposium on Artificial Neural Networks, Computational Intelligence and Machine Learning (ESANN), Bruges, Belgium, 2024, pp. 315-320.

7. R. Kimball and M. Ross, The Data Warehouse Toolkit: The Definitive Guide to Dimensional Modeling, 3rd ed. Hoboken, NJ: John Wiley & Sons, 2013.

8. S. J. Taylor and B. Letham, 'Forecasting at scale,' The American Statistician, vol. 72, no. 1, pp. 37-45, 2018. DOI: 10.1080/00031305.2017.1380080.

9. D. C. Montgomery, Introduction to Statistical Quality Control, 8th ed. New York, NY: John Wiley & Sons, 2019.

10. L. van der Maaten and G. Hinton, 'Visualizing data using t-SNE,' Journal of Machine Learning Research, vol. 9, pp. 2579-2605, 2008.

11. Central Electricity Authority (CEA), 'CO_2 Baseline Database for the Indian Power Sector, User Guide Version 19.0,' Ministry of Power, Government of India, New Delhi, 2024.

12. B. Shneiderman, 'The eyes have it: A task by data type taxonomy for information visualizations,' in Proc. IEEE Symposium on Visual Languages, Boulder, CO, 1996, pp. 336-343.