Hik-Connect for Teams (HikCentral Connect) Video jsDecoder SDK

Developer Guide

Legal Information

About this Document

- This Document includes instructions for using and managing the Product. Pictures, charts, images and all other information hereinafter are for description and explanation only. Unless otherwise agreed, our company makes no warranties, express or implied.
- Please use this Document with the guidance and assistance of professionals trained in supporting the Product.

Trademarks Acknowledgment

All trademarks and logos mentioned are the properties of their respective owners.

LEGAL DISCLAIMER

- TO THE MAXIMUM EXTENT PERMITTED BY APPLICABLE LAW, THIS DOCUMENT AND THE PRODUCT DESCRIBED, WITH ITS HARDWARE, SOFTWARE AND FIRMWARE, ARE PROVIDED "AS IS" AND "WITH ALL FAULTS AND ERRORS". OUR COMPANY MAKES NO WARRANTIES, EXPRESS OR IMPLIED, INCLUDING WITHOUT LIMITATION, MERCHANTABILITY, SATISFACTORY QUALITY, OR FITNESS FOR A PARTICULAR PURPOSE. THE USE OF THE PRODUCT BY YOU IS AT YOUR OWN RISK. IN NO EVENT WILL OUR COMPANY BE LIABLE TO YOU FOR ANY SPECIAL, CONSEQUENTIAL, INCIDENTAL, OR INDIRECT DAMAGES, INCLUDING, AMONG OTHERS, DAMAGES FOR LOSS OF BUSINESS PROFITS, BUSINESS INTERRUPTION, OR LOSS OF DATA, CORRUPTION OF SYSTEMS, OR LOSS OF DOCUMENTATION, WHETHER BASED ON BREACH OF CONTRACT, TORT (INCLUDING NEGLIGENCE), PRODUCT LIABILITY, OR OTHERWISE, IN CONNECTION WITH THE USE OF THE PRODUCT, EVEN IF OUR COMPANY HAS BEEN ADVISED OF THE POSSIBILITY OF SUCH DAMAGES OR LOSS.
- YOU ACKNOWLEDGE THAT THE NATURE OF THE INTERNET PROVIDES FOR INHERENT SECURITY RISKS, AND OUR COMPANY SHALL NOT TAKE ANY RESPONSIBILITIES FOR ABNORMAL OPERATION, PRIVACY LEAKAGE OR OTHER DAMAGES RESULTING FROM CYBER-ATTACK, HACKER ATTACK, VIRUS INFECTION, OR OTHER INTERNET SECURITY RISKS; HOWEVER, OUR COMPANY WILL PROVIDE TIMELY TECHNICAL SUPPORT IF REQUIRED.
- YOU AGREE TO USE THIS PRODUCT IN COMPLIANCE WITH ALL APPLICABLE LAWS, AND YOU ARE SOLELY RESPONSIBLE FOR ENSURING THAT YOUR USE CONFORMS TO THE APPLICABLE LAW. ESPECIALLY, YOU ARE RESPONSIBLE, FOR USING THIS PRODUCT IN A MANNER THAT DOES NOT INFRINGE ON THE RIGHTS OF THIRD PARTIES, INCLUDING WITHOUT LIMITATION, RIGHTS OF PUBLICITY, INTELLECTUAL PROPERTY RIGHTS, OR DATA PROTECTION AND OTHER PRIVACY RIGHTS. YOU SHALL NOT USE THIS PRODUCT FOR ANY PROHIBITED END-USES, INCLUDING THE DEVELOPMENT OR PRODUCTION OF WEAPONS OF MASS DESTRUCTION, THE DEVELOPMENT OR PRODUCTION OF CHEMICAL OR BIOLOGICAL WEAPONS, ANY ACTIVITIES IN THE CONTEXT

RELATED TO ANY NUCLEAR EXPLOSIVE OR UNSAFE NUCLEAR FUEL-CYCLE, OR IN SUPPORT OF HUMAN RIGHTS ABUSES.

- IN THE EVENT OF ANY CONFLICTS BETWEEN THIS DOCUMENT AND THE APPLICABLE LAW, THE LATTER PREVAILS.

Contents

Chapter 1 Overview 1

1.1 Introduction 1

1.2 Runtime Environment 1

1.3 Terms and Definitions 1

1.4 Components and Constraints 1

1.5 Update History 3

Chapter 2 API Reference 4

2.1 JSPlugin 4

2.2 JS_ArrangeWindow 5

2.3 JS_CapturePicture 5

2.4 JS_CloseSound 6

2.5 JS_Disable3DZoom 7

2.6 JS_DisableZoom 7

2.7 JS_DownloadFile 8

2.8 JS_Enable3DZoom 9

2.9 JS_EnableZoom 10

2.10 JS_Fast 11

2.11 JS_FrameForward 11

2.12 JS_FullScreenDisplay 12

2.13 JS_FullScreenSingle 13

2.14 JS_GetOSDTime 13

2.15 JS_GetVolume 14

2.16 JS_OpenSound 15

2.17 JS_Pause 15

2.18 JS_Play 16

2.19 JS_Resize 17

2.20 JS_Resume 18
2.21 JS_Seek 19
2.22 JS_SelectWnd 20
2.23 JS_SetSecretKey 20
2.24 JS_SetVolume 21
2.25 JS_Slow 22
2.26 JS_StartSaveEx 22
2.27 JS_StartTalk 23
2.28 JS_Stop 24
2.29 JS_StopDownloadFile 24
2.30 JS_StopRealPlayAll 25
2.31 JS_StopSave 25
2.32 JS_StopTalk 26
2.33 JS_TalkSetVolume 26
2.34 JS_VideoSearch 27
2.35 JS_InitDataTransform 28
2.36 JS_InputTransformData 29
2.37 JS_StopTransformData 29
2.38 JS_StartEZUITalk 30
2.39 JS_StopEZUITalk 31
Appendix A. Appendixes 32
A.1 Sample Code of Starting Live View via jsDecoder SDK 32
A.2 Dependencies between OpenAPI and jsDecoder SDK 33

Chapter 1 Overview

1.1 Introduction

The jsDecoder SDK is a software development kit that provides APIs and a no plug-in solution to start live view and playback of device via the web browser.

1.2 Runtime Environment

Operating System

® Windows 7/8/10 (32-bit or 64-bit)

Web Browser

- Mozilla ® with Version 52 or Above
- Google ® with Version 45 or Above

1.3 Terms and Definitions

DIV Window

The window without popping up on the browser page , which is marked with "DIV".

Display Window

Sub window of DIV window, whose size varies with that of DIV window.

1.4 Components and Constraints

Components

Component	File Name
jsDecoder Folder	Decoder.js
	Decoder.wasm
	DecodeWorker.js
	libSystemTransform-worker.min.js
	libSystemTransform.js
	libSystemTransform.wasm

Component	File Name
	jsPlugin-3.0.0.min.js
demo.html	Demo for live view and playback.

Constraints

Functions	jsDecoder 3.0
Protocol	Supports HTTPS.
Live View	See details of supported formats in ***Table 1-1*** .
Capture	Supports
Digital Zoom	Supports
Window Division	Supports
Full Screen	Supports
Playback	Supports
Fast/Slow Forward	Supports 2×, 4×, ½ ×, and ¼× speed
Reverse Playback	Not Supports
Transcoding Playback	Supports
Single Frame	Supports
Recording	Supports
Draw on Video	Supports
Counting Statistics, Dynamic Health Monitoring, and Other Private Information Processing	Not Supports
Synchronous Playback	Not Supports

Table 1-1 Video Encoding Format

Video Encoding Format	Audio Encoding Format
H264, H265	AAC, AACLD, ADPCM, G711, G722_1, G726, MP2, OPUS

Table 1-1 Video Encoding Format

Video Encoding Format	Resolution	Video Parameter (Bps*Fps)	Decoding Channel (Operating System: Windows 7)	Decoding Channel (Operating System: Windows 7)	Decoding Channel (Operating System: Windows 7)
/	/	/	CPU: I7_8700K Graphic Card: RTX2080	CPU: I5-9400/F Graphic Card: GTX1050TI	CPU: I3-8100 Graphic Card: GT1030D5
H265	1080P	4M*25	6	4	3
H265	720P	2M*25	14	10	6
H264	1080P	4M*25	6	4	3
H264	720P	2M*25	14	10	6

1.5 Update History

Summary of Changes in Version 3.0.1_Oct., 2024

- Added the API of initializing file for trans-encapsulation: ***JS_InitDataTransform*** ;
- Added the API of inputting data and starting trans-encapsulating: ***JS_InputTransformData*** ;
- Added the API of completing trans-encapsulation: ***JS_StopTransformData*** ;
- Added the API of starting two-way audio: ***JS_StartEZUITalk*** ;
- Added the API of stopping two-way audio: ***JS_StopEZUITalk*** .

Summary of Changes in Version 3.0_Jul., 2024

- Added the API of downloading file stream: ***JS_DownloadFile*** ;
- Added the API of stop downloading file stream: ***JS_StopDownloadFile*** ;
- Added the API of searching for video: ***JS_VideoSearch*** .

Chapter 2 API Reference

2.1 JSPlugin

Create the plug-in.

Prerequisite

The jsPlugin-3.0.0.min.js has been loaded in the web page.

API Definition

None.

Parameters

Parameter Name	Required or Optional	Description
[IN] szId	Required	A container to create the plug-in. For example, , that is, creating plug-in in the .
[IN] iType	Required	Plug-in type: 0-no video display window; 1-with video display window.
[IN] iWidth	Required	Width of the created plug-in.
[IN] iHeight	Required	Height of the created plug-in.
[IN] iMaxSplit	Required	Maximum number of window divisions supported by the created plug-in.
[IN] iCurrentSplit	Required	Default number of window divisions after creating the plug-in.
[IN] szBasePath	Required	Basic path for saving the file jsPlugin-1.0.0.min.js, which is relative to the root directory of web server.

Return Value

None.

Example

Sample Code of Creating Plug-in

```
var oJSPlugin = new JSPlugin({
  szId: "playWind",
  iType: 1,
  iWidth: 600,
```

```
  iHeight: 400,
  iMaxSplit: 4,
  iCurrentSplit: 1,
  szBasePath: "./dist"
});
```

2.2 JS_ArrangeWindow

Set the number of sub windows for the display window, that is, set the window division mode.

Prerequisite

The plug-in has been created.

API Definition

```
JS_ArrangeWindow(
  iWndType
)
```

Parameters

Parameter Name	Required or Optional	Description
[IN] iWndType	Required	Window division modes: 1 (1-window division); 2 (4-window division); 3 (9-window division), 4 (16-window division).

Return Value

None.

Example

Sample Code of Setting Window Division Mode

```
oJSPlugin.JS_ArrangeWindow(4);
```

2.3 JS_CapturePicture

Start capturing picture.

Prerequisite

The plug-in has been created.

API Definition

```
JS_CapturePicture (
  iWndNum,
  szPictureName,
  szType
)
```

Parameters

Parameter Name	Required or Optional	Description
[IN] iWndNum	Required	Display window No., which starts from 0.
[IN] szPictureName	Required	Capture file name.
[IN] szType	Optional	Picture formats: BMP, JPG, JPEG. The default format is JPG.

Return Value

Return *0* for success and *-1* for failure.

Example

Sample Code of Stating Capturing Picture

```
oJSPlugin.JS_CapturePicture (0,'img','jpg');
```

2.4 JS_CloseSound

Turn off audio.

Prerequisite

The plug-in has been created.

API Definition

```
JS_ CloseSound (
)
```

Parameters

None.

Return Value

Return *0* for success and *-1* for failure.

Example

Sample Code of Turning Off Audio

```
oJSPlugin.JS_CloseSound ();
```

2.5 JS_Disable3DZoom

Disable 3D positioning.

Prerequisite

The plug-in has been created.

API Definition

```
JS_Disable3DZoom (
  iWndNum
)
```

Parameters

Parameter Name	Required or Optional	Description
[IN] iWndNum	Required	Display window No., which starts from 0.

Return Value

Return *0* for success and *-1* for failure.

Example

Sample Code of Disabling 3D Positioning

```
oJSPlugin.JS_Disable3DZoom (0);
```

2.6 JS_DisableZoom

Disable digital zoom.

Prerequisite

The plug-in has been created.

API Definition

```
JS_DisableZoom (
  iWndNum
)
```

Parameters

Parameter Name	Required or Optional	Description
[IN] iWndNum	Required	Display window No., which starts from 0.

Return Value

None.

Example

Sample Code of Enabling Digital Zoom

```
oJSPlugin.JS_DisableZoom (0);
```

2.7 JS_DownloadFile

Download file stream. The downloading mode is similar to the windowless mode for JS_Play.

Prerequisite

The plug-in has been created.

API Definition

```
JS_DownloadFile (
  szURL,
  oParams
)
```

Parameters

Parameter Name	Required or Optional	Description
[IN] szURL	Required	Download URL.
[IN] oParams	Required	Download parameters, for example: { playURL: "", //Streaming URL fileName: "FileA.mp4", //File name ezuikit: true, idstType: 5, //Encapsulation format: 2-PS, 3-TS, 4-RTP, 5-MP4 secretKey: "", //Secret key for stream startTime: "", //Start time, in the format of "20240429T101000Z" endTime: " ", //End time, in the format of

Parameter Name	Required or Optional	Description

		"20240429T101200Z"
		env: {
		domain: "" //Domain
		},
		accessToken: "", //Token
		mode: "media" //Media mode
		}

Return Value

Promise object.

Example

Sample Code of Downloading file stream

```
oJSPlugin.JS_DownloadFile ("ws://10.41.7.235:559/101", {
        //Streaming server
        playURL: 'ws://10.41.7.235:559/101',
fileName: "FileA.mp4",
idstType: 5, // PS: 2, TS: 3, RTP: 4, MP4: 5
secretKey: "123456",
startTime: "20240429T101000Z",
endTime: "20240429T101200Z ",
        ezuikit: true,  //Whether to use streaming server
        env: {
domain: https://isgpopen.ezvizlife.com       //Domain
}
        accessToken: "at.dn1l5mk57txef4bpcmwxbnr15m" //Authentication information
      }).then(function(downloadUUID) {
        //Calling succeeded. downloadUUID is the current download UUID, which is required for forcing stop
downloading
      },function () {
        //Calling failed
   });
```

2.8 JS_Enable3DZoom

Enable 3D positioning.

Prerequisite

The plug-in has been created.

API Definition

```
JS_Enable3DZoom (
  iWndNum,
```

```
  fCallback
)
```

Parameters

Parameter Name	Required or Optional	Description
[IN] iWndNum	Required	Display window No., which starts from 0.
[IN] fCallback	Required	Drawing callback. After calling this callback function, you can start drawing rectangle frame on the video image and get the frame information via this callback function when the frame is drawn.

Return Value

Return *0* for success and *-1* for failure.

Example

Sample Code of Enabling 3D Positioning

```
oJSPlugin.JS_Enable3DZoom (0, function(){}
```

2.9 JS_EnableZoom

Enable digital zoom.

Prerequisite

The plug-in has been created.

API Definition

```
JS_EnableZoom (
  iWndNum
)
```

Parameters

Parameter Name	Required or Optional	Description
[IN] iWndNum	Required	Display window No., which starts from 0.

Return Value

Return *0* for success and *-1* for failure.

Example

Sample Code of Enabling Digital Zoom

```
oJSPlugin.JS_EnableZoom (0);
```

2.10 JS_Fast

Enable fast forward during playback.

Prerequisite

- The plug-in has been created.
- The playback has started.

API Definition

```
JS_Fast (
  iWndNum
)
```

Parameters

Parameter Name	Required or Optional	Description
[IN] iWndNum	Required	Display window No., which starts from 0.

Return Value

Promise object.

Remarks

The playing speed will be doubled for each time calling this API.

Example

Sample Code of Enabling Fast Forward

```
oJSPlugin.JS_Fast (0);
```

2.11 JS_FrameForward

Start single frame playback.

Prerequisite

- The plug-in has been created.
- The playback has started.

API Definition

```
JS_FrameForward (
  iWndNum
)
```

Parameters

Parameter Name	Required or Optional	Description
[IN] iWndNum	Required	Display window No., which starts from 0.

Return Value

Return *0* for success and *-1* for failure.

Example

Sample Code of Starting Single Frame Playback

```
oJSPlugin.JS_FrameForward (0);
```

2.12 JS_FullScreenDisplay

Display the plug-in in full screen mode.

Prerequisite

The plug-in has been created.

API Definition

```
JS_FullScreenDisplay (
  bFullScreen
)
```

Parameters

Parameter Name	Required or Optional	Description
[IN] bFullScreen	Required	Whether to display in full screen mode: "true"-yes. You can press ESC on the keyboard to exit the full screen mode.

Return Value

None.

Example

Sample Code of Displaying Plug-in in Full Screen Mode

```
oJSPlugin.JS_FullScreenDisplay (true);
```

2.13 JS_FullScreenSingle

Display a single window in full screen mode.

Prerequisite

The plug-in has been created.

API Definition

```
JS_FullScreenSingle (
  iWndNum
)
```

Parameters

Parameter Name	Required or Optional	Description
[IN] iWndNum	Required	Display window No., which starts from 0.

Return Value

None.

Example

Sample Code of Displaying a Window in Full Screen Mode

```
oJSPlugin.JS_FullScreenSingle (0);
```

2.14 JS_GetOSDTime

Get the OSD time of video to refresh the time bar during playback.

Prerequisite

The plug-in has been created.

API Definition

```
JS_GetOSDTime (
  iWndNum
)
```

Parameters

Parameter Name	Required or Optional	Description
[IN] iWndNum	Required	Display window No., which starts from 0.

Return Value

Promise object. You can get the OSD time (number of seconds from 1970-01-01 00:00:00 to the current time) from the Promise callback.

Example

Sample Code of Getting OSD Time

```
JS_GetOSDTime(0).then(function (iTime) {
  console.log(iTime);  //print the OSD time
});
```

2.15 JS_GetVolume

Get the volume.

Prerequisite

The plug-in has been created.

API Definition

```
JS_GetVolume (
  iWndNum,
  cbCallback
)
```

Parameters

Parameter Name	Required or Optional	Description
[IN] iWndNum	Required	Display window No., which starts from 0.
[IN] cbCallback	Required	Callback parameters, in which the volume value is returned.

Return Value

None.

Example

Sample Code of Getting Volume

```
oJSPlugin. JS_GetVolume(0, function (iVolume){
  console.log(iVolume); //print the volume value
});
```

2.16 JS_OpenSound

Turn on audio in exclusive mode.

Prerequisite

The plug-in has been created.

API Definition

```
JS_OpenSound (
  iWndNum
)
```

Parameters

Parameter Name	Required or Optional	Description
[IN] iWndNum	Required	Display window No., which starts from 0.

Return Value

Return *0* for success and *-1* for failure.

Example

Sample Code of Turning On Audio

```
oJSPlugin.JS_OpenSound (0);
```

2.17 JS_Pause

Pause playing.

Prerequisite

- The plug-in has been created.
- The playback has started.

API Definition

```
JS_Pause (
  iWndNum
)
```

Parameters

Parameter Name	Required or Optional	Description
[IN] iWndNum	Required	Display window No., which starts from 0.

Return Value

Promise object.

Example

Sample Code of Pausing Playing

```
oJSPlugin.JS_Pause (0);
```

2.18 JS_Play

Start playing.

Prerequisite

The plug-in has been created.

API Definition

```
JS_Play(
  szURL,
  oParams,
  iWndNum,
  szStartTime,
  szStopTime
)
```

Parameters

Parameter Name	Required or Optional	Description
[IN] szURL	Required	Stream URL. For example, ws://ip:port/101, the 101 refers to the main stream of channel No.1 (the first "1" is the chhanel No., "01" represents the stream type of main stream, and "02" represents the stream type of sub-stream).
[IN] oParams	Required	Parameter object for authentication when connecting different domains. For example, {session: sessionId}.

Parameter Name	Required or Optional	Description
[IN] iWndNum	Required	Display window No., which starts from 0.
[IN] szStartTime	Optional	Start time of playing, the time format is YYYYMMDDThhmmssZ, e.g., 20110701T112720Z. For playback, this parameter is required.
[IN] szStopTime	Optional	Stop time of playing, the time format is YYYYMMDDThhmmssZ, e.g., 20110701T112720Z. For playback, this parameter is required.

Return Value

Promise object.

Example

Sample Code of Starting Playing

```
oJSPlugin.JS_Play(
  "ws://10.41.7.235:559/101;",
 {
    playURL: 'file/vag://10.41.7.138:6300/sessions/e7c228b7b360424b86955c734c7772d8?
https=1&range=20190410T010021-20190410T013648',  //live view URL
    auth: "admin:wacspzz1",  //authentication information
    token: "EAAAAAAQAADV4gVBxl8hE/ZK9jrXVnCGLON+eIJu5YmbmWYLz8sWXJXhnFTxEFex4a+yzAGDdc4="  //token
information
    proxy: "10.5.6.8"  //target address of the proxy, which should be configured according to the actual situation
  }, //parameter objects of stream media server
  0,
  "20170620T000000Z",
  "20170620T235900Z"
).then(
  function() {},//callback when succeeded
  function() {} //callback when failed
);
```

2.19 JS_Resize

Set the width and height of the video plug-in.

Prerequisite

The plug-in has been created.

API Definition

```
JS_Resize (
  iWidth,
  iHeight
)
```

Parameters

Parameter Name	Required or Optional	Description
[IN] iWidth	Required	Width, unit: pixel.
[IN] iHeight	Required	Height, unit: pixel.

Return Value

None.

Example

Sample Code of Setting Plug-in Width and Height

```
oJSPlugin.JS_Resize (400,   600);
```

2.20 JS_Resume

Resume playing.

Prerequisite

- The plug-in has been created.
- The playback has paused or the single frame playback has started.

API Definition

```
JS_Resume (
  iWndNum
)
```

Parameters

Parameter Name	Required or Optional	Description
[IN] iWndNum	Required	Display window No., which starts from 0.

Return Value

Promise object.

Example

Sample Code of Resuming Playing

```
oJSPlugin.JS_Resume (0);
```

2.21 JS_Seek

Locate the position in the video to start playback.

Prerequisite

The plug-in has been created.

API Definition

```
JS_Seek(
  iWndNum,
  szStartTime,
  szStopTime
)
```

Parameters

Parameter Name	Required or Optional	Description
[IN] iWndNum	Required	Display window No., which starts from 0.
[IN] szStartTime	Optional	Start time of playing, the time format is YYYYMMDDThhmmssZ, e.g., 20110701T112720Z. For playback, this parameter is required.
[IN] szStopTime	Optional	Stop time of playing, the time format is YYYYMMDDThhmmssZ, e.g., 20110701T112720Z. For playback, this parameter is required.

Return Value

Promise object.

Example

Sample Code of Positing to Start Playback

```
oJSPlugin.JS_Seek (0, "20170620T000000Z", "20170620T235900Z");
```

2.22 JS_SelectWnd

Select the display window.

Prerequisite

The plug-in has been created.

API Definition

```
JS_SelectWnd (
  iWndNum
)
```

Parameters

Parameter Name	Required or Optional	Description
[IN] iWndNum	Required	Display window No., which starts from 0.

Return Value

Return *0* for success and *-1* for failure.

Example

Sample Code of Selecting Display Window

```
oJSPlugin.JS_SelectWnd (0);
```

2.23 JS_SetSecretKey

Set stream key.

Prerequisite

The plug-in has been created.

API Definition

```
JS_SetSecretKey (
  iKeyType
)
```

Parameters

Parameter Name	Required or Optional	Description
[IN] iKeyType	Required	Encryption types: 0-not encrypt; 1-encrypt by AES algorithm.

Return Value

None.

Example

Sample Code of Setting Stream Key

```
oJSPlugin.JS_SetSecretKey(4);
```

2.24 JS_SetVolume

Set the volume.

Prerequisite

The plug-in has been created.

API Definition

```
JS_SetVolume (
  iWndNum,
  iVolume
)
```

Parameters

Parameter Name	Required or Optional	Description
[IN] iWndNum	Required	Display window No., which starts from 0.
[IN] iVolume	Required	Volume value, which ranges from 0 to 100.

Return Value

None.

Example

Sample Code of Setting Volume

```
oJSPlugin.JS_SetVolume (0, 60);
```

2.25 JS_Slow

Enable slow forward during playback.

Prerequisite

- The plug-in has been created.
- The playback has started.

API Definition

```
JS_Slow (
  iWndNum
)
```

Parameters

Parameter Name	Required or Optional	Description
[IN] iWndNum	Required	Display window No., which starts from 0.

Return Value

Promise object.

Remarks

The playing speed will be halved for each time calling this API.

Example

Sample Code of Enabling Slow Forward

```
oJSPlugin.JS_Slow (0);
```

2.26 JS_StartSaveEx

Start recording.

Prerequisite

The plug-in has been created.

API Definition

```
JS_StartSave (
  iWndNum,
  szFileName
)
```

Parameters

Parameter Name	Required or Optional	Description
[IN] iWndNum	Required	Display window No., which starts from 0.
[IN] szFileName	Required	Video file name, the default file suffix is .mp4.

Return Value

Promise object.

Example

Sample Code of Starting Recording

```
oJSPlugin.JS_StartSave (0, "10.17.137.229_01_20170101000000.mp4");
```

2.27 JS_StartTalk

Start two-way audio.

Prerequisite

The plug-in has been created.

API Definition

```
JS_StartTalk (
  talkUrl
)
```

Parameters

Parameter Name	Required or Optional	Description
talkUrl	Required	URL for two-way audio.

Return Value

Promise object.

Example

Sample Code of Starting Two-Way Audio

```
oJSPlugin.JS_StartTalk (wss://10.2.145.66:655/EUrl/CLJ52BW);
```

2.28 JS_Stop

Stop playing.

Prerequisite

The plug-in has been created.

API Definition

```
JS_Stop (
  iWndNum
)
```

Parameters

Parameter Name	Required or Optional	Description
[IN] iWndNum	Required	Display window No., which starts from 0.

Return Value

Promise object.

Example

Sample Code of Stopping Playing

```
oJSPlugin.JS_Stop (0);
```

2.29 JS_StopDownloadFile

Stop downloading file stream. This API is to force stop downloading.

Prerequisite

The plug-in has been created.

API Definition

```
Promise JS_StopDownloadFile ()
```

Parameters

None.

Return Value

Promise object.

Example

Sample Code of Stop Downloading File Stream

```
oJSPlugin. JS_StopDownloadFile (downloadUUID)
```

2.30 JS_StopRealPlayAll

Stop the live view of all windows.

Prerequisite

The plug-in has been created.

API Definition

None.

Parameters

None.

Return Value

None.

Example

Sample Code of Stopping Live View of All Windows

```
oJSPlugin.JS_StopRealPlayAll ();
```

2.31 JS_StopSave

Stop recording.

Prerequisite

The plug-in has been created.

API Definition

```
JS_StopSave (
  iWndNum
)
```

Parameters

Parameter Name	Required or Optional	Description
[IN] iWndNum	Required	Display window No., which starts from 0.

Return Value

Promise object.

Example

Sample Code of Stopping Recording

```
oJSPlugin.JS_StopSave (0);
```

2.32 JS_StopTalk

Stop two-way audio.

Prerequisite

The plug-in has been created.

Return Value

Promise object.

Example

Sample Code of Stopping Two-Way Audio

```
oJSPlugin.JS_StopTalk ();
```

2.33 JS_TalkSetVolume

Set volume of two-way audio.

Prerequisite

The plug-in has been created.

API Definition

```
JS_TalkSetVolume (
  volume
)
```

Parameters

Parameter Name	Required or Optional	Description
volume	Required	The volume of two-way audio, which ranges from 0 to 100.

Return Value

Promise object.

Example

Sample Code of Seting Volume of Two-Way Audio

```
oJSPlugin. JS_TalkSetVolume (50);
```

2.34 JS_VideoSearch

Search for video.

Prerequisite

The plug-in has been created.

API Definition

```
Promise JS_VideoSearch (
  oParams
)
```

Parameters

Parameter Name	Required or Optional	Description

[IN] oParams	Required	Download parameters, for example:
		{
		domain: "", //Domain
		accessToken: "", //Token
		deviceSerial: "", //Serial No.
		channelNo: "", //Channel No.
		startTime: "",//Start time, in the format of "20240429T101000Z"
		endTime: "", //End time, in the format of "20240429T101200Z"
		storageType: 1 //1-cloud storage, 2-local storage
		}

Return Value

Promise object.

Example

Sample Code of Searching for Video

```
oJSPlugin. JS_VideoSearch ({
domain: " https://isgpopen.ezvizlife.com",
```

```
accessToken: "at.dn1l5mk57txef4bpcmwxbnr15m",
deviceSerial: 5,
channelNo: 1,
startTime: "20240429T101000Z",
endTime: "20240429T121000Z",
      storageType: 1   //1-cloud storage, 2-local storage
});
```

2.35 JS_InitDataTransform

Initialize file for trans-encapsulation.

Prerequisite

The plug-in has been created.

API Definition

```
Promise JS_InitDataTransform (
  fileName,
  dstType,
  head,
  secretKey
)
```

Parameters

Parameter Name	Required or Optional	Description
[IN] fileName	Required	Name of the file after trans-encapsulation.
[IN] dstType	Required	Target file type: 2-PS stream, 5-MP4 stream.
[IN] head	Required	40-byte header information of the file, null by default.

Return Value

Promise object.

Example

Sample Code of Initializing File for Trans-Encapsulation

```
let szUUID = await oJSPlugin.JS_InitDataTransform("test.mp4", 5, null, "123456");
//szUUID is the trans-encapsulation ID used for inputting data for trans-encapsulation, and for releasing resources after trans-encapsulation is completed
```

2.36 JS_InputTransformData

Input data and start trans-encapsulating.

Prerequisite

The plug-in has been created.

API Definition

```
Promise JS_InputTransformData (
  szUUID,
  data
)
```

Parameters

Parameter Name	Required or Optional	Description
[IN] szUUID	Required	Trans-encapsulation ID returned from ***JS_InitDataTransform*** .
[IN] data	Required	Data for trans-encapsulation: Uint8Array.

Return Value

Promise object.

Example

Sample Code of Inputting Data and Starting Trans-Encapsulating

```
oJSPlugin.JS_InputTransformData(szUUID, data);
```

2.37 JS_StopTransformData

Complete trans-encapsulation.

Prerequisite

The plug-in has been created.

API Definition

```
Promise JS_StopTransformData (
  szUUID
)
```

Parameters

Parameter Name	Required or Optional	Description
[IN] szUUID	Required	Trans-encapsulation ID returned from ***JS_InitDataTransform*** .

Return Value

Promise object.

Example

Sample Code of Completing Trans-Encapsulation

```
oJSPlugin.JS_ StopTransformData(szUUID);
```

2.38 JS_StartEZUITalk

Start two-way audio.

Prerequisite

The plug-in has been created.

API Definition

```
Promise JS_StartEZUITalk (
  oParams
)
```

Parameters

Parameter Name	Required or Optional	Description

[IN] oParams	Required	Parameter object, for example:
		{
		channelNo: "", //Channel No.
		deviceSerial: "", //Serial No.
		accessToken: "", //Token
		  env: {
		  domain: "" //Domain
		  }
		}

Return Value

Promise object.

Example

Sample Code of Starting Two-Way Audio

```
oJSPlugin. JS_StartEZUITalk ({
channelNo: "",    //Channel No.
deviceSerial: "",   //Serial No.
accessToken: "at.dn1l5mk57txef4bpcmwxbnr15m",   //Token authentication information
          env: {
domain: " https://isgpopen.ezvizlife.com"     //Domain
}
      }).then(function() {
          //todo, succeeded
      },function () {
          //todo, failed
   });
```

2.39 JS_StopEZUITalk

Stop two-way audio.

Prerequisite

The plug-in has been created.

API Definition

```
Promise JS_StopEZUITalk (
)
```

Parameters

None.

Return Value

Promise object.

Example

Sample Code of Stopping Two-Way Audio

```
oJSPlugin. JS_StopEZUITalk ();
```

Appendix A. Appendixes

A.1 Sample Code of Starting Live View via jsDecoder SDK

The following contents show the sample code of starting live view via jsDecoder SDK. For more details, refer to demo_window_simple_preview.html.

For high performance, the following 3 request headers should be added when the web resource is returned by server:
add_header Cross-Origin-Embedder-Policy require-corp;
add_header Cross-Origin-Opener-Policy same-origin;
add_header Cross-Origin-Resource-Policy cross-origin;

Reference JS File

```
<script src="jsDecoder/polyfill2.js"></script>
  <script src="jsDecoder/jsPlugin-3.0.0.min.js"></script>
  <script src="jsDecoder/jquery-1.12.1.min.js"></script>
  <script src="jsDecoder/jquery.cookie.js"></script>
  <script src="jsDecoder/cryptico.min.js"></script>
  <script src="jsDecoder/uuid.js"></script>
```

Create jsDecoder Instance

```
//Initialize the plug-in
var jsDecoder = new JSPlugin({
  szId: "playWind",
  iType: 2,
  iWidth: 600,
  iHeight: 400,
  iMaxSplit: 4,
  iCurrentSplit: 2,
  szBasePath: "./dist",
  oStyle: {
    border: "#343434",
    borderSelect: "red",
    background: "#4C4B4B"
  }
});
```

Start Live View

```
jsDecoder.JS_Play(url, {
  playURL: playUrl, //Stream URL for live view
  auth: deviceUser + ":" + devicePassword,  //Authentication information, i.e., user name and password of device
  token: token
}, iWind).then(function() {
  console.log("realplay success");
```

```
},function () {
  console.log("realplay failed");
});
```

A.2 Dependencies between OpenAPI and jsDecoder SDK

OpenAPI Name	Function of Video jsDecoder SDK
Get camera information by No.: /api/resource/v1/cameras/indexCode	Live view and playback
Get information of a decoding device: /api/resource/v1/encodeDevice/indexCode/encodeDeviceInfo	Live view and playback (search for device information to get access protocol type)
Get live view stream URL of camera: /api/video/v1/cameras/previewURLs	Live view
Get playback stream URL of camera: /api/video/v1/cameras/playbackURLs	Playback