

TIMAK DRILLING MACHINE

Technical Specifications

The Drilling Machine is a special equipment that can be applied on the Self Propelled Pile driving machine for the drilling of road pavement in every hard condition. The Downhole drill hammer drills every kind of soil, reinforced concrete, rock and granite.



Drilling Machine Standard Equipment

Chassis & Mobility

Rubber-tracked crawler base for stable off-road operation

Grappling hooks for safe loading and unloading

Integrated hook for pile extraction

Operating Weight: approx. 3.7 tons

Powertrain

Engine: DEUTZ air-cooled, 3-cylinder diesel engine

Power Output: 34 kW (45.6 HP) @ 2800 rpm

Fuel Tank: 80 L with level indicator

Hydraulic System

Hydraulic Hammer: Working weight 490 kg; impact energy 1060 J; frequency 500-900 bpm

Hydraulic Oil Tank: 80 L with level indicator

Hydraulic Oil Heat Exchanger for thermal management

Auxiliary Couplings for additional attachments

8-Level Proportional Control System

Drilling & Pile Driving

Maximum Post Dimensions: 160 × 120 mm

Maximum Post Height: 3.9 m

Column Inclination Adjustment: ±15° (transverse and longitudinal)

Optional Equipment

Automatic Column Leveling System

Earth Auger Drilling Unit

Rock Drilling Attachment

Steel Track System for enhanced durability

Kubota Liquid-Cooled Diesel Engine (4-cylinder, 35.9 kW / 48.1 HP @ 2800 rpm)

Hydraulic Front Blade for surface leveling or trench cutting



HEAVY-DUTY DRILLING SYSTEM



FOR DEMANDING TERRAIN