

TIMAK GUARDRAIL PILE DRIVER MACHINE

Technical Specifications

Guardrail Pile Driver Machine is specially designed for driving the highway poles required within the scope of Highway Road Safety precautionary works. It offers a professional solution in accordance with the required power and other features for the installation of signs, barriers and guardrails used on highways.



Guardrail Pile Driver Standard Equipment

Height: 3500-4200 mm

Engine: 34 kW DEUTZ diesel, air-cooled, 3-cylinder
(45.6 HP @ 2800 rpm)

Tracks: Continuous rubber tracks for enhanced traction

Hammer Impact Energy: 850-1060 J

Hammer Frequency: 600-1140 bpm

Hydraulic Hammer: 300 kg, 840 J, 390-1000 bpm

Maximum Post Size: 160 × 120 mm, height up to 2.8 m

Machine Weight: 2.5-4 tons

Column Inclination: ±15° (transverse and longitudinal)

Column Leveling: Automatic hydraulic system

Track Pads: Plastic (steel optional)

Fuel Tank Capacity: 80 L (with level indicator)

Hydraulic Tank Capacity: 80 L (with level indicator)

Cooling System: Hydraulic oil heat exchanger

Controls: 9-level proportional joystick



Optional Equipment

Automatic Column Leveling

Kubota Diesel Engine: Liquid-Cooled, 4 Cylinders, 35.9 kW
(48.1 HP) @ 2800 rpm

GPS Tracking System

Remote Control Unit

Auxiliary Hydraulic Coupling

LED Work Light Kit

Camera System with Monitor

Lockable Tool Storage Compartment



GUARDRAIL PILE DRIVER MACHINE IS STABLE & COMPACT

