

# FathGrid

developer documentation

[www.fathsoft.com](http://www.fathsoft.com)

## Contents

Installation.....	1
Initialization .....	1
Configuration options.....	2
Column configuration options.....	2
Grid data .....	3
Inline data.....	3
Dynamic data.....	4
Server-side data.....	4
API .....	4
How to... ..	5
Display calculated columns .....	5
Group by expression.....	5
Add column footer .....	5
Change appearance of some rows .....	5
Editing.....	5
Insert new row .....	5
Delete row .....	5
Show sub-grid.....	6

## Installation

Just add fathgrid.js to your page HEAD section

```
<script src="fathgrid.js"></script>
```

## Initialization

First, make sure you have a table with an ID attribute in your HTML:

```
<table id="table1" class="table table-hover table-bordered ">
  <thead class="thead-light"></thead>
  <tbody></tbody>
</table>
```

To initialize FathGrid object in place of a table, use JavaScript code:

```
var t1=FathGrid("table1",{ ...configuration_options });
```

## Configuration options

Configuration options is an object set as second parameter to FathGrid initialization call. It can contain the following fields:

Field	Description	Default
size	page size	10
page	page number	1
filterable	allow filters in table header	true
editable	allow editing when clicking on cells	false
pageable	allow paginator	true
sortable	allow sorting by clicking on column headers	true
showFooter	show table footer	false
showGroupFooter	show group footer	false
data	data array	[]
rowClass	function (item,idx) which returns string of class names to add to each TR element in table body	
onChange	function to be called whenever cell data is changed	function(item, col, oldval, newval)
groupOn	function (item, index) which returns grouping string	function(item. idx){}
sortBy	array of column indices for fixed filter	[]
columns	array of column configuration objects	[]
serverURL	templated URL to retrieve JSON data from	null
loading	message to show while loading data	'Loading...'
selectColumns	allow hiding/showing columns	false
onInitFilter	function which is called when filter row is created. Useful for customizing appearance of filter controls	function(tr_element){}
onInitTable	function which is called when table body is rendered. Useful for customizing appearance	function(tbody_element){}

## Column configuration options

Column configuration object can contain the following fields:

Field	Description	Default
name	field name	
visible	if false, hide this column	true
filter	list-of-values for filter or <b>null</b> to automatically create list from table data	undefined
value	function(item) which returns text to display in column	
html	function(item) which return HTML for column cell	
header	text to show in column header	
footer	function(items, element) which returns text to display in footer cell	
groupFooter	expression or a function(items) which returns grouping value	
editable	allow cell editing when clicked	false
type	HTML input type for cell editor	text
pattern	HTML validation pattern for input element	
title	input title or a message to show when editing	
listOfValues	array of values to choose from when editing cell value	
class	column class string. Usefull to add text-alignment to the column	

## Grid data

Table data can be loaded from:

1. Inline HTML table
2. Dynamic JavaScript array
3. Server-side API endpoint

### Inline data

Simply put data in table HTML in TBODY TR TD elements:

```
<table id="table1" class="table table-hover table-bordered ">
  <thead class="thead-light">
    <tr><th>Code</th><th>Description</th><th>Qty</th><th>Price</th></tr>
  </thead>
  <tbody>
    <tr><td>100</td><td>first description</td><td>1</td><td>30</td></tr>
    <tr><td>200</td><td>other description</td><td>2</td><td>20</td></tr>
    <tr><td>300</td><td>some text</td><td>3</td><td>10</td></tr>
  </tbody>
</table>
```

## Dynamic data

Configuration option “data” allows setting data from JS array:

```
var demodata=[
  ['100','Service title 100', 2, 134],
  ['120','Some stuff', 10, 160],
  ['310','Goods', 5, 2000],
];
var t1=FathGrid("table1",{
  data: demodata
});
```

## Server-side data

To load data from server, set **serverURL** configuration option to string template:

```
t1=FathGrid("table1",{
  serverURL:'https://jsonplaceholder.typicode.com/posts?_page=${page}&_limit=${size}&_sort=${sort}&_order=${order}&q=${search}&${filters}',
```

note that URL string has these placeholders:

- \${size} replaced with page size setting
- \${page} page number (1,2,3...)
- \${sort} sort field names
- \${order} order of sort, “asc” or “desc” for sort fields
- \${search} search term (if any)
- \${filters} replaced with filter name/value pairs (eg: name=test&price=1)

## API

FathGrid object has the following methods:

Method	Parameters	Description
getData		returns read-only copy of table data
setData	<b>data</b> :array	sets new data
export	<b>format</b> : ‘txt’, ‘csv’, ‘xls’, ‘pdf’... <b>filename</b> : downloaded file name	downloads data-export file
render		re-draws the table
sort	<b>column_index</b> : 1-based column <b>desc</b> : true for descending order <b>multi</b> : true for multicolumn sort	sort data by field
getSort		returns array of field indices by which data is sorted
setSort	<b>new_sort</b> : array of column indices	sets sort fields
filter	<b>column_index</b> : column <b>value</b> : filter value	sets data filtering
getFilter		returns current filter
editCell	<b>rownum</b> : 1-based row index <b>col</b> : 1-based column index	starts editor in cell

search	<b>q</b> : search term	sets instant search term
getSelectedItem		returns data item from currently selected row
deleteRow	<b>rownum</b> : 1-based row index	deletes a row
insertRow	<b>rownum</b> : 1-based row index <b>item</b> : new item data	insert new row
setServerURL	<b>url</b> : string	set new server URL
wrapperEl		returns FathGrid wrapper HTML Element
selectRow	<b>rownum</b> : 1-based row index	selects specified row
showSubgrid	<b>subgrid</b> : details FathGrid <b>html</b> : custom HTML to add before sub-grid	insert sub grid below currently selected row

## How to...

### Display calculated columns

See column configuration **value** and **html** options.

### Group by expression

See **groupOn** and **showGroupFooter** configuration options.

### Add column footer

See **footer** column configuration option.

### Change appearance of some rows

See **rowClass** config option.

### Editing

If config.editable is true, call **editCell(row,col)** API function to start editor.

Shift+arrow keys move editor across table. Columns with **editable=false** option set are skipped.

### Insert new row

Call **insertRow** API function.

### Delete row

Call **deleteRow** API function.

### Show sub-grid

First, create second FathGrid object which will hold sub-grid data, then, call **showSubgrid** on main grid to insert details grid under currently selected row.