TCS Self Learning
JFLAP Software

1) Deterministic Finite Automata

DeterministicFiniteAutomaton (DFA)


A DFA is a finite state machine that accepts or rejects finite strings of symbols. Each input string produces exactly one computation, and on any finite input the DFA halts and either accepts or rejects. A DFA M recognizes the language L(M), the set of all strings M accepts.

Formal definition

A DFA is a 5-tuple $(Q, \Sigma, \delta, q_0, F)$, where:

- Q is a finite set of states
- Σ is a finite set of input symbols (the alphabet)
- $\delta: Q \times \Sigma \rightarrow Q$ is the transition function
- $q_0 \in Q$ is the start state
- $F \subseteq Q$ is the set of accept states

Example: This DFA over the alphabet {a, b} recognizes the language consisting of only the string "a". It accepts "a" and rejects everything else.




State	a	b
q_0	q_1	q_2
q_1	q_2	q_2
q_2	q_2	q_2

Every state has exactly one transition for each symbol of the alphabet. Because the next state is uniquely determined, the automaton is deterministic.


Example:
Considerthe regular language L over the alphabet { a, b, c } comprised of all strings that begin and end
with c. Let's construct a DFA M to recognize that language.
Some strings in the language include: c, cc, ccc, cac, cabc, cabcbabc
Some strings not in the language include: λ, a, ac, cb, ccca

Execution:


Step 1: Create initial state q0




Step 2: Create a new state, q1, as the destination of a or b fromq0 and which traps all subsequent substrings




Step 3: Create a new state, q2, as the destination of transition c from q0 and which is an accept state




Step 4: Add a c transition to and from q2



Step 5: Add state q3 with a transition of a or b from q2. Add transitions to remain in q3 for a or b. Add transition from q3 back to q2 for c



Testing with inputs:



Therefore the DFA accepts all strings that start and end with c

2) NonDeterministicFinite Automata

AnNFAisafinitestatemachinethataccepts or rejectsfinite strings of symbols, like a DFA, but its computationonanyinputneednotbeunique. From a given state on a given symbol, it may have severalpossiblenextstates,ornone.An NFA N recognizes the language L(N), the set of all strings for whichatleastonecomputationpath ends in an accept state.

*Example:*ThisNFAover{a,b}recognizes the strings that end in "ab". In q_0 it keeps reading and, wheneveritseesana,canguessthatthis a is the second-to-last symbol and move to q_1. It then needs a b to reachq_2,andanyfurthersymbolkills that path.

Formal definition


An NFAisa5-tuple(Q,Σ,δ,q_0,F),where:

- Qis afiniteset of states
- Σisafinitesetofinputsymbols (the alphabet)
- $\delta: Q \times (\Sigma \cup \{\varepsilon\}) \rightarrow P(Q)$isthetransition function, which returns a set of states (possibly empty)
- $q_0 \in Q$ is the start state
- $F \subseteq Q$isthesetofaccept states


Example:

Define an NFA that recognizes the following language L over Σ = {a, b}:
L= { w | w ends with aa }.

Execution:



Testing:



Therefore, this NFA successfully accepts all strings ending with aa.

3) NFA to DFA Conversion

Every NFA has an equivalent DFA that recognizes the same language. The subset construction builds it by making each DFA state a *set* of NFA states, so the DFA tracks every state the NFA could be in after reading the input so far.

Construction

Given an NFA $N=(Q, \Sigma, \delta, q_0, F)$, build a DFA $D = (Q', \Sigma, \delta', q_0', F')$, where:

- $Q' = P(Q)$:each DFA state is a subset of NFA states
- $q_0' = \{q_0\}$:the start state is the set containing only the NFA's start state
- $\delta'(S, a) = \bigcup \delta(q, a)$ for $q \in S$:onsymbola,movetotheunionofallstates reachable from any state in S
- $F' = \{S \in Q' \mid S \cap F \neq \emptyset\}$: aDFA state accepts if it contains at least one NFA accept state

If the NFA has ε-transitions, take theε-closure (all states reachable by ε-moves alone) of the start state and of every result of δ'.

Procedure

1. Start with the DFA state $\{q_0\}$ (or its ε-closure).
2. For each new DFA state S and each symbol a, compute $\delta'(S, a)$ as the union of the NFA transitions.
3. If the result is a new subset, add it as a state.
4. Repeat until no new subsets appear.
5. Mark every subset containing an NFA accept state as accepting.

Only subsets reachable from the start are needed, so the DFA is usually much smaller than the full 2^n.

Example

Convertthe NFA frombefore (strings over {a, b} ending in "ab", start q_0, accept q_2):

State	a	b
q_0	$\{q_0, q_1\}$	$\{q_0\}$
q_1	$\emptyset$	$\{q_2\}$
q_2	$\emptyset$	$\emptyset$

Starting from $\{q_0\}$:

- $\{q_0\}$ on a → $\{q_0, q_1\}$; on b → $\{q_0\}$
- $\{q_0, q_1\}$ on a → $\{q_0, q_1\} \cup \emptyset = \{q_0, q_1\}$; on b → $\{q_0\} \cup \{q_2\} = \{q_0, q_2\}$
- $\{q_0, q_2\}$ on a → $\{q_0, q_1\} \cup \emptyset = \{q_0, q_1\}$; on b → $\{q_0\} \cup \emptyset = \{q_0\}$

No new subsets appear, so the DFA has three states. Naming $A = \{q_0\}$, $B = \{q_0, q_1\}$, and $C = \{q_0, q_2\}$, the DFA is $(\{A, B, C\}, \{a, b\}, \delta', A, \{C\})$, with δ' given by:

State	a	b
A	B	A
B	B	C
C	B	A


C is the only accepting state, since it is the only subset containing q_2. The other five subsets ($\varnothing$, $\{q_1\}$, $\{q_2\}$, $\{q_1, q_2\}$, $\{q_0, q_1, q_2\}$) are unreachable, so they are left out.

Key points


- The construction proves NFAs and DFAs recognize exactly the same languages, the regular languages.
- The DFA can need up to 2^n states for an n-state NFA, and some languages really do require this blowup.
- The empty set $\varnothing$ acts as the DFA's "dead" state when it is reachable.

Example:

Convert the following NFA to an equivalent DFA



Final DFA



4) DFA Minimization

Different DFAscan recognize the same language, but every regular language has a unique minimal DFA: the one with the fewest states, unique up to renaming. Minimization finds it by removing unreachable states and merging states that behave identically.

Key idea

Two states p and q are equivalent if, for every string w, starting from p and starting from q lead to the same accept/reject outcome. Equivalent states can be merged without changing the language. If some string w gives different outcomes, the states are distinguishable.

Procedure (partition refinement)

1. Remove unreachable states. Delete any state that can't be reached from q_0.
2. Split by acceptance. Start with two groups: accepting states F and non-accepting states Q \ F.
3. Refine. Split a group if two of its states send some symbol a to different groups. Repeat until no group splits.
4. Merge. Each final group becomes one state of the minimal DFA. The start state is the group containing q_0, the accept states are the groups inside F, and transitions follow the group of the target.

Equivalently, the table-filling method marks pairs of states as distinguishable, starting with (accepting, non-accepting) pairs, then marking any pair that moves to an already marked pair on some symbol. Unmarked pairs at the end are equivalent.

Example

Take this DFA over {a, b} with start state 0 and F = {2, 3}:

State	a	b
0	1	2
1	1	3
2	1	3
3	1	2
4	0	4

- Step 1: State 4 is unreachable, so remove it.
- Step 2: The groups are {0, 1} (non-accepting) and {2, 3} (accepting).
- Step 3: In {0, 1}, on a both states go to 1 (same group), and on b they go to 2 and 3 (same group). In {2, 3}, on a both go to 1, and on b they go to 3 and 2 (same group). Nothing splits, so the partition is final.
- Step 4: Merge into P = {0, 1} and Q = {2, 3}.

The minimal DFA is ({P, Q}, {a, b}, δ, P, {Q}), with δ given by:

State	a	b
P	P	Q
Q	P	Q

It recognizes the strings that end in b. Five states reduced to two.
Already minimal


The 3-state DFA from the NFA conversion (strings ending in “ab”) is already minimal. The initial groups are {A, B} and {C}. On b, A goes to A but B goes to C, so {A, B} splits, leaving three singleton groups.

Key points


- Minimization never changes the language, only the number of states.
- The minimal DFA is unique, which gives a way to test whether two DFAs are equivalent: minimize both and compare.
- This relies on the Myhill-Nerode theorem: the number of states in the minimal DFA equals the number of distinguishable classes of strings for the language.
- Hopcroft’s algorithm does the refinement in O(n log n) time for n states.

Example:
Consider the language L1 = {w ∈ Σ∗ | w is λ or w ends in a}.

Execution:
DFA:



Minimized DFA:



5) DFA to Regular Grammar Conversion

Every DFA can be convertedinto an equivalent **regular grammar**, a grammar that generates exactly the language the DFA recognizes. The idea is to turn each state into a non-terminal and each transition into a production, so that a derivation mirrors a run of the DFA.

Regular grammars

A **right-linear grammar** has productions of the form $A \to aB$, $A \to a$, or $A \to \varepsilon$, where A and B are non-terminalsand a is a terminal. Each rule produces at most one terminal followed by at most one non-terminal, at the right end. Right-linear grammars generate exactly the regular languages.

Construction

GivenaDFAD=$(Q,\Sigma, \delta, q_0, F)$, build a grammar $G = (V, \Sigma, P, S)$, where:

- **V = Q**:eachstate becomes a non-terminal
- **S = q_0**:thestart state becomes the start symbol
- **Transition rule:** for each $\delta(p, a) = q$, add the production **p → aq**

- **Accept rule:** for each p ∈ F, add the production **p → ε**

Reading a symbol corresponds to producing a terminal and moving to the next non-terminal. Reaching an accept state allows the derivation to end with ε.

Procedure

1. Name a non-terminal for each state, with thestart state as the start symbol.
2. For every transitionp —a→q, write p→aq.
3. For every accept state p, write p → ε.
4. Optionally, drop any non-terminal thatcan never lead to a string (a dead or trap state) along with the productions that use it.

Example

TaketheDFAfrom the NFA conversion (strings over {a, b} ending in "ab"), with start state A and accept state C:

State	a	b
A	B	A
B	B	C
C	B	A


The grammar has V = {A, B, C}, start symbol A, and these productions:

- A→aB|bA
- B→aB|bC
- C→aB|bA | ε

Derivation of "aab": A ⇒ aB ⇒ aaB ⇒ aabC ⇒ aab

This matches the DFA's run on "aab": A →a→ B →a→ B →b→ C, which ends in the accept state C. A string like "aba" fails: the derivation reaches C after "ab", but then the only way to continue is a → B, which cannot end in ε.

Example;:
Consider this DFA



State q0 labeled R we have the following (→ is pronounced reduces to)

R → cS

R → aR


R → bR

S → aT

S → cS

T → null

Step 1:



Therefore DFA has been converted to Grammer

6) DFA to Regular Expression Conversion

Every DFA can be converted into an equivalent regular expression, one that describes exactly the language the DFA recognizes. The standard method is state elimination: remove the DFA's states one at a time, replacing transition labels with regular expressions, until a single expression remains.

Key idea
Allow edges to be labeled with regular expressions instead of single symbols. This is called a generalized NFA (GNFA). When a state is removed, every path that went through it is replaced by a direct edge whose label is the regular expression for that detour. The language does not change.
Procedure

1. Add a new start state S with an ε-edge to the old start state.
2. Add a new accept state F with ε-edges from every old accept state. These old states are no longer accepting.
3. Merge parallel edges. If several edges gofrom p toq, replace themwithoneedge labeled by the union ($R_1 \mid R_2 \mid \ldots$). If there is no edge, treat it as ∅.
4. Eliminate each original state qone at a time. Forevery pairof states pand r withanedge into q and an edge out of q, add or extend the edge p → r with the label R_pq (R_qq)* R_qr:
    - R_pq is the label from p to q
    - R_qq is the label of the loop on q (use ε if none)
    - R_qr is the label from q to r
    - If p → r already exists,union thenew label with the old one.
5. Stopwhen only S and F remain. The label on the edge S → F is the regular expression.

Example
Take theDFA from the earlier sections (strings over {a, b} ending in "ab"), with start state A and accept state C:

State	a	b
A	B	A
B	B	C
C	B	A

After adding S and F, the edges are:

- S→A:ε
- A→A:b,A→B:a
- B→B:a,B→C:b
- C→B:a,C→A:b,C→F: ε

Eliminate A (loop b, so the middle term is b*):

- S → B: ε · b* · a = b*a
- C → B: a | (b · b* · a) = a | b⁺a = b*a

Eliminate C (no loop; the only edge in is from B on b, and the edges out are to B on b*a and to F on ε):


- B → B: a | (b · b*a) = b*a
- B → F: b


Eliminate B (loopb*a, so the middle term is (b*a)*):

- S → F: b*a · (b*a)* · b = (b*a)⁺b

The regular expression is (b*a)⁺b. It is equivalent to the more familiar (a|b)*ab, since a string ends in "ab" exactly when it is a string ending in a (that is, (b*a)⁺) followed by b.

Example
Consider the following DFA





Therefore we have successfully converted DFA to RE

7) Combining Automata
Regularlanguagesareclosed under union, intersection, difference, complement, concatenation, and star. Each has a construction on finite automata.

Product construction (union, intersection, difference)

Given DFAs $M_1 = (Q_1, \Sigma, \delta_1, q_1, F_1)$ and $M_2 = (Q_2, \Sigma, \delta_2, q_2, F_2)$ over the same alphabet, run both in parallel:

- States: $Q_1 \times Q_2$
- Start: (q_1, q_2)
- Transition: $\delta((p, q), a) = (\delta_1(p, a), \delta_2(q, a))$
- Accept states:
    - Union: $p \in F_1$ or $q \in F_2$
    - Intersection: $p \in F_1$ and $q \in F_2$
    - Difference $L_1 \setminus L_2$: $p \in F_1$ and $q \notin F_2$

Only accept set changes between operations.

Complement

Swap accepting and non-accepting states: $F' = Q \setminus F$. The DFA must be complete (a transition on every symbol from every state).

ε-NFA constructions

- Union: add a new start state with ε-edges to both start states.
- Concatenation L_1L_2: add ε-edges from each accept state of M_1 to the start state of M_2. Only F_2 accepts.
- Star L*: add a new accepting start state with an ε-edge to the old start state, and ε-edges from each old accept state back to the old start state.

Example

Let M_1 accept an even number of a's (states E, O) and M_2 accept strings ending in b (states N, Y). The product starts at (E, N):


State	a	b
(E, N)	(O, N)	(E, Y)
(E, Y)	(O, N)	(E, Y)
(O, N)	(E, N)	(O, Y)


(O, Y)	(E, N)	(O, Y)


- Intersection: accept {(E, Y)}
- Union: accept {(E, N), (E, Y), (O, Y)}
- Difference $L_1 \setminus L_2$: accept {(E, N)}


Example:
In this Exercise, we will use the "Combine Automata" featureof JFLAP to find the intersection of two DFA. For the alphabet Σ = {a, b}, consider thelanguages
L1 = {w ∈ Σ∗|w has anoddnumber of a's},and
L2 = {w ∈ Σ∗|w does not have ab as a substring}

Step 1: Load the files odd-a.jflap and no-ab.jflap in two separatewindows, as below









Hence this DFA accepts all strings that have odd no. of a's and have no ab substring

8) Regular Expression to DFA conversion
Regular Expression to DFA Conversion

Build an **ε-NFA** from the expression (**Thompson's construction**), then convert it to a DFA (**subset construction**). Minimizing afterwards is optional.

Step 1: Thompson's construction

Each piece has one start state and one accept state:

- **a (a symbol):** start —a→ accept
- **R | S:** a new start with ε-edges to the starts of R and S, and ε-edges from their accept states to a new accept state
- **RS:** an ε-edge from R's accept state to S's start

- **R*:** a new start and a new accept state. The new start has ε-edges to R's start and to the new accept. R's accept has ε-edges back to R's start and to the new accept.

Step 2: Subset construction

1. The start state is the **ε-closure** of the NFA's start state (all states reachable by ε-moves alone).
2. For each DFA state S and symbol a, compute **ε-closure(move(S, a))**.
3. Repeat until no new sets appear.
4. A set is accepted if it contains the NFA's accept state.

Example: (a|b)*ab

The Thompson NFA gives four DFA states:

- **A**=ε-closure of the start state
- **B**=thestate reached after reading an a (the NFA is now ready to read b)
- **C**=thestate reached after reading "ab" (contains the NFA accept state)
- **D**=thestate reached after reading a b from A, B-less (same behavior as A)


State	a	b
A	B	D
B	B	C
C	B	D
D	B	D

C is theonlyaccepting state. A and D have identical rows, so minimization merges them:

State	a	b
A	B	A
B	B	C
C	B	A

This is the 3-state DFA for strings ending in "ab" from the earlier sections.

Example: Convert the following Regular Expression to a DFA aba U ba*



9) Mealy Machine

AMealy machineisa finite automaton that **produces output**. Instead of accepting or rejecting, it writes an output symbol on every transition, so the output depends on the current state and the input symbol.

Formal definition

A Mealy machine is a 6-tuple $(Q, \Sigma, \Delta, \delta, \lambda, q_0)$, where:

- **Q** is a finite set of states
- **Σ** is the input alphabet
- **Δ** is the output alphabet
- **δ: Q × Σ → Q** is the transition function
- **λ: Q × Σ → Δ** is the output function
- $\mathbf{q_0}$ is the start state

There are no accepted states. The output has the same length as the input.


Example: detect "ab"

Over {a, b}, output 1 whenever the symbol just read completes "ab", and 0 otherwise. The states are A (last symbol was nota)and B (last symbol was a). Each cell shows next state / output:

State	a	b
A (start)	B / 0	A / 0
B	B / 0	A / 1

On input "aab": A —a/0→ B —a/0→ B —b/1→ A, so the output is 001.

Example:
Constructa Mealy machine which takes a binary number and replaces the first 1 with a 0 from every substring starting with 1. For example, 0001001110 becomes 0000000110. This type of "bit stuffing" may be used in data transmission and telecommunications for run--length coding to limit the number of consecutive bits of the same value. A bit of the opposite value is inserted after the maximum allowed number of consecutive bit



10) Moore Machine
AMooremachineisafinite automaton that **produces output**, where the output depends **only on the current state**.Eachstate carries an output symbol, which is written whenever the machine enters that state.

Formal definition

A Moore machine is a 6-tuple $(Q, \Sigma, \Delta, \delta, \lambda, q_0)$, where:

- **Q** is a finite set of states
- **Σ** is the input alphabet
- **Δ** is the output alphabet
- **δ: Q × Σ → Q** is the transition function
- **λ: Q → Δ** is the output function, defined on states
- **q_0** is the start state


There are no accepted states. The output has length |input| + 1, since the start state also produces an output before any symbol is read.

Example: detect “ab”

Over {a,b}, output 1 whenthelast two symbols read are “ab”, and 0 otherwise. The states are A (last symbolwas not a), B (lastsymbol was a), and C (just completed “ab”). Each state has an output, and each cellshows the nextstate:

State	Output	a	b
A (start)	0	B	A
B	0	B	C
C	1	B	A

On input “aab”: A —a→ B —a→ B —b→ C, so the outputs are 0, 0, 0, 1, giving **0001**. The first 0 comes from the start state. Dropping it gives 001, the same as the Mealy machine.



Example:
Constructa Moore machine which takes a binary number and replaces the first 1 with a 0 from every substring starting with 1. For example, 0001001110 becomes 0000000110. This type of “bit stuffing” may be used in data transmission and telecommunications for run--length coding to limit the number of consecutive bits of the same value. A bit of the opposite value is inserted after the maximum allowed number of consecutive bits.

Conclusion

Thus, the experiments were successfully performed using JFLAP software to understand and implement different concepts of automata theory. The experiments demonstrated the construction and testing of Deterministic Finite Automata (DFA) and Non-Deterministic Finite Automata (NFA), conversion of NFA to DFA, DFA minimization, conversion of DFA into regular grammars and regular expressions, and the combination of automata to perform language operations. The conversion of regular expressions into finite automata was also explored. Additionally, Mealy and Moore machines were implemented to understand how finite-state machines generate outputs based on transitions and states, respectively. Overall, these experiments provided practical knowledge of finite-state machines, regular languages, and their applications using JFLAP.