



FEED FORWARD MULTILAYER NEURAL NETWORK

XOR with backpropagation
Handwritten digits recognition
Handwritten alphabet recognition




SRI SAI VIJAYA ADITYA NITTALA

ROLL NUMBER: 177163

REGISTRATION NUMBER: 841775

The architecture of a 3-layer Neural Network is shown below:



Where,

- X: Input features fed into the Neural Network.
- W: Weights associated with the activations of the Neural Network.
- B: Bias term introduced to the Neural Network.

A Neural Network can be used for classification purposes. The algorithm that is used to classify is called **Backpropagation**. An overview is given below:

Algorithm: Backpropagation. Neural network learning for classification or numeric prediction, using the backpropagation algorithm.

Input:

- D , a data set consisting of the training tuples and their associated target values;
- l , the learning rate;
- *network*, a multilayer feed-forward network.

Output: A trained neural network.

Method:

```

(1) Initialize all weights and biases in network;
(2) while terminating condition is not satisfied {
(3)   for each training tuple  $X$  in  $D$  {
(4)     // Propagate the inputs forward:
(5)     for each input layer unit  $j$  {
(6)        $O_j = I_j$ ; // output of an input unit is its actual input value
(7)     }
(8)     for each hidden or output layer unit  $j$  {
(9)        $I_j = \sum_i w_{ij} O_i + \theta_j$ ; // compute the net input of unit  $j$  with respect to
        the previous layer,  $i$ 
(10)       $O_j = \frac{1}{1 + e^{-I_j}}$ ; // compute the output of each unit  $j$ 
(11)    }
(12)    // Backpropagate the errors:
(13)    for each unit  $j$  in the output layer
(14)       $Err_j = O_j(1 - O_j)(T_j - O_j)$ ; // compute the error
(15)    for each unit  $j$  in the hidden layers, from the last to the first hidden layer
(16)       $Err_j = O_j(1 - O_j) \sum_k Err_k w_{jk}$ ; // compute the error with respect to
        the next higher layer,  $k$ 
(17)    for each weight  $w_{ij}$  in network {
(18)       $\Delta w_{ij} = (l) Err_j O_i$ ; // weight increment
(19)       $w_{ij} = w_{ij} + \Delta w_{ij}$ ; // weight update
(20)    }
(21)    for each bias  $\theta_j$  in network {
(22)       $\Delta \theta_j = (l) Err_j$ ; // bias increment
(23)       $\theta_j = \theta_j + \Delta \theta_j$ ; // bias update
(24)    }
  }

```

In this assignment, using the **backpropagation** algorithm, the following have been implemented:

1. **Exclusive OR (XOR) gate implementation:**


The truth-table of an XOR gate is given below:

Input		Output
A	B	A xor B
0	0	0
0	1	1
1	0	1
1	1	0

Information about the implementation:

- Number of neurons in input layer: 2
- Number of hidden layers: 1
- Number of neurons in the hidden layer: 2
- Number of neurons in output layer: 1
- Input: Dataset is essentially the truth-table of XOR but 0s are represented by 0.1 and 1s with 0.9 as sigmoid cannot compute exactly 0 or 1.
- Number of iterations: 1000
- Learning rate: 0.1
- Weights are update after each forward-backward pass, i.e, not a batch update.
- Test data: truth-table of XOR

2. **Handwritten Digit recognition:**




The dataset used for this application is the **MNIST** dataset. It consists of images, each of size **28x28** pixels (total 784 per image). Number of training and testing examples taken is less due to infrastructure constraints. Code attached at the end contains more information about the input.

Information about the implementation:

- a. Number of neurons in input layer: 784
- b. Number of hidden layers: 1
- c. Number of neurons in hidden layer: 50
- d. Number of neurons in output layer: 10
- e. Input:
 - a. Number of training examples considered: 1000
 - b. Number of testing examples considered: 100
- f. Learning rate: 0.01
- g. Number of iterations: 10

3. **Handwritten alphabet recognition:**



The dataset used for this application is the **EMNIST** dataset. It is very similar to the previously described MNIST dataset. Contains images of size **28x28**, total of 784 pixels. More information is provided as comments in the code attached below.

Information about the implementation:

- a. Number of neurons in input layer: 784
- b. Number of hidden layers: 1
- c. Number of neurons in hidden layer: 50
- d. Number of neurons in output layer: 26
- e. Input:
 - a. Number of training examples considered: 2400
 - b. Number of testing examples considered: 600
- f. Learning rate: 0.01
- g. Number of iterations: 10