

Bashmatic Usage Docs (v2.2.0)

Table of Contents

File lib/pids.sh.....	5
pids.stop-by-listen-tcp-ports().....	5
Example	5
pid.stop-if-listening-on-port().....	5
Example	5
File lib/bashit.sh.....	5
bashit-prompt-terraform().....	5
bashit-install().....	5
File lib/array.sh.....	6
array.has-element()	6
Example	6
array.includes().....	6
array.join()	6
Example	6
Arguments	6
array.sort()	7
Example.....	7
array.sort-numeric()	7
Example.....	7
array.min().....	7
Example.....	7
array.max().....	7
Example.....	7
array.uniq()	8
Example	8
array.from.command().....	8
Example	8
File lib/asciidoc.sh.....	8
asciidoc.rouge-themes()	8
File lib/output-utils.sh	8
is-dbg()	8
dbg()	9
File lib/brew.sh.....	9
package.is-installed()	9

File lib/output.sh	9
section()	9
Arguments	9
File lib/video.sh	9
is.sh	9
File lib/path.sh	9
path.strip-slash()	10
path.dirs()	10
Arguments	10
path.dirs.size()	10
path.dirs.uniq()	10
path.dirs.delete()	10
Arguments	11
path.uniq()	11
path.append()	11
path.prepend()	11
path.mutate.uniq()	11
path.mutate.delete()	11
path.mutate.append()	11
path.mutate.prepend()	11
PATH_add()	11
File lib/osx.sh	11
osx.app.is-installed()	12
Example	12
Arguments	12
Exit codes	12
File lib/db.sh	12
db.config.parse()	13
Example	13
db.psql.connect()	13
Example	13
db.psql.connect.just-data()	13
Example	13
db.psql.connect.table-settings-set()	13
Example	13
db.psql.db-settings()	13
Example	14
db.psql.connect.db-settings-pretty()	14
Example	14

Arguments	14
db.psql.connect.db-settings-toml()	14
Example	14
Arguments	14
db.actions.pga()	14
File lib/shdoc.sh	14
lib/shdoc.sh	14
File lib/git.sh	15
git.cfgu()	15
Example	15
git.open()	15
Example	15
Arguments	15
File lib/package.sh	15
package.ensure.is-installed()	16
package.ensure.command-available()	16
Example	16
File lib/time.sh	16
time.with-duration.start()	16
Example	16
File lib/shasum.sh	16
shasum.set-command()	17
shasum.set-algo()	17
Example	17
shasum.sha()	17
shasum.sha-only()	17
shasum.sha-only-stdin()	17
shasum.to-hash()	17
Example	17
shasum.all-files()	17
Example	18
shasum.all-files-in-dir()	18
Example	18
File lib/pg.sh	18
pg.is-running()	18
pg.running.server-binaries()	18
pg.running.data-dirs()	18
pg.server-in-path.version()	18
File lib/dir.sh	19

dir.short-home()	19
File lib/config.sh	19
config.get-format()	19
config.set-file()	19
config.get-file()	19
config.dig()	19
Arguments	19
config.dig.pretty()	19
File lib/net.sh	20
net.is-host-port-protocol-open()	20
Arguments	20
File lib/is.sh	20
__is.validation.error()	20
Arguments	20
Exit codes	20
is-validations()	21
__is.validation.ignore-error()	21
__is.validation.report-error()	21
whenever()	21
Example	21
File lib/util.sh	21
util.rot13-stdin()	21
Example	21
File lib/pdf.sh	21
Bashmatic Utilities for PDF file handling	22
File bin/install-direnv	22
direnv.register()	22
File bin/regen-usage-docs	22
File bin/pdf-reduce	22
pdf.do.shrink()	23
File bin/scheck	23
manual-install()	23
Copyright & License	23

NOTICE: [shdoc](#) documentation is auto-extracted from the Bashmatic Sources.

File lib/pids.sh

- [pids.stop-by-listen-tcp-ports\(\)](#)
- [pid.stop-if-listening-on-port\(\)](#)

pids.stop-by-listen-tcp-ports()

Finds any PID listening on one of the provided ports and stop them.

Example

```
pids.stop-by-listen-tcp-ports 4232 9578 "${PORT}"
```

pid.stop-if-listening-on-port()

Finds any PID listening the one port and an optional protocol (tcp/udp)

Example

```
pid.stop-if-listening-on-port 3000 tcp  
pid.stop-if-listening-on-port 8126 udp
```

File lib/bashit.sh

- [bashit-prompt-terraform\(\)](#)
- [bashit-install\(\)](#)

bashit-prompt-terraform()

Possible Bash It Powerline Prompt Modules

aws_profile battery clock command_number cwd dirstack gcloud go history_number hostname in_toolbox in_vim
k8s_context last_status node python_venv ruby scm shlvl terraform user_info wd

bashit-install()

Installs Bash-It Framework

File lib/array.sh

- `array.has-element()`
- `array.includes()`
- `array.join()`
- `array.sort()`
- `array.sort-numeric()`
- `array.min()`
- `array.max()`
- `array.uniq()`
- `array.from.command()`

`array.has-element()`

Returns "true" if the first argument is a member of the array passed as the second argument:

Example

```
$ declare -a array=("a string" test2000 moo)
if [[ $(array.has-element "a string" "${array[@]}") == "true" ]]; then
  ...
fi
```

`array.includes()`

Similar to `array.has-elements`, but does not print anything, just returns 0 if includes, 1 if not.

`array.join()`

Joins a given array with a custom string.

Example

```
$ declare -a array=(one two three)
$ array.join "," "${array[@]}"
$ array.join "-> " true "${array[@]}"
-> one
-> two
-> three
```

Arguments

- `@arg1`

- @arg2
- @arg3.

array.sort()

Sorts the array alphanumerically and prints it to STDOUT

Example

```
declare -a unsorted=(hello begin again again)
local sorted="$(array.sort "${unsorted[@]}")"
```

array.sort-numeric()

Sorts the array numerically and prints it to STDOUT

Example

```
declare -a unsorted=(1 2 34 45 6)
local sorted="$(array.sort-numeric "${unsorted[@]}")"
```

array.min()

Returns a minimum integer from an array. Non-numeric elements are ignored and skipped over. Negative numbers are supported, but non-integers are not.

Example

```
$ declare -a array=(10 20 30 -5 5)
$ array.min "," "${array[@]}"
-5
```

array.max()

Returns a maximum integer from an array. Non-numeric elements are ignored and skipped over. Negative numbers are supported, but non-integers are not.

Example

```
$ declare -a array=(10 20 30 -5 5)
$ array.min "," "${array[@]}"
30
```

array.uniq()

Sorts and uniqs the array and prints it to STDOUT

Example

```
declare -a unsorted=(hello hello hello goodbye)
local uniqed="$(array.sort-numeric "${unsorted[@]}")"
```

array.from.command()

Creates an array variable, where each element is a line from a command output, which includes any spaces.

Example

```
array.from.command music_files "find . -type f -name '*.mp3'"
echo "You have ${#music[@]} music files."
```

File lib/asciidoc.sh

Provides helper functions for dealing with asciidoc format.

- [asciidoc.rouge-themes\(\)](#)

asciidoc.rouge-themes()

Installs gem "rouge" and prints all available themes

File lib/output-utils.sh

- [is-dbg\(\)](#)
- [dbg\(\)](#)

is-dbg()

Checks if we have debug mode enabled

dbg()

Local debugging helper, activate it with DEBUG=1

File lib/brew.sh

- [package.is-installed\(\)](#)

package.is-installed()

For each passed argument checks if it's installed.

File lib/output.sh

- [section\(\)](#)

section()

Prints a "arrow-like" line using powerline characters

Arguments

- @arg1 Width (optional) ~~2-2~~ only interpreted as width if the first argument is a number.
 - @args Text to print
-

File lib/video.sh

is.sh

video conversions

File lib/path.sh

Utilities for managing the \$PATH variable

- `path.strip-slash()`
- `path.dirs()`
- `path.dirs.size()`
- `path.dirs.uniq()`
- `path.dirs.delete()`
- `path.uniq()`
- `path.append()`
- `path.prepend()`
- `path.mutate.uniq()`
- `path.mutate.delete()`
- `path.mutate.append()`
- `path.mutate.prepend()`
- `PATH_add()`

`path.strip-slash()`

Removes a trailing slash from an argument path

`path.dirs()`

Prints a new-line separated list of paths in PATH

Arguments

- `@arg1` A path to split, defaults to `$PATH`

`path.dirs.size()`

Prints the total number of paths in the path argument, which defaults to `$PATH`

`path.dirs.uniq()`

Prints all folders in `$PATH`, one per line, removing any duplicates, Does not mutate the `$PATH`

`path.dirs.delete()`

Deletes any number of folders from the PATH passed as the first string argument (defaults to `$PATH`). Does not mutate the `$PATH`, just prints the result to STDOUT

Arguments

- @arg1 String representation of a PATH, eg `"/bin:/usr/bin:/usr/local/bin"`
- @arg2 An array of paths to be removed from the PATH

`path.uniq()`

Removes duplicates from the \$PATH (or argument) and prints the results in the PATH format (column-joined). DOES NOT mutate the actual \$PATH

`path.append()`

Appends a new directory to the \$PATH and prints the result to STDOUT, Does NOT mutate the actual \$PATH

`path.prepend()`

Prepends a new directory to the \$PATH and prints to STDOUT, If one of the arguments already in the PATH its moved to the front. DOES NOT mutate the actual \$PATH

`path.mutate.uniq()`

Removes any duplicates from \$PATH and exports it.

`path.mutate.delete()`

Deletes paths from the PATH provided on the command line

`path.mutate.append()`

Appends valid directories to those in the PATH, and exports the new value of the PATH

`path.mutate.prepend()`

Prepends valid directories to those in the PATH, and exports the new value of the PATH

`PATH_add()`

This function exists within direnv, but since we are sourcing in .envrc we need to have this defined to avoid errors.

File `lib/osx.sh`

OSX Specific Helpers and Utilities

- [osx.app.is-installed\(\)](#)

osx.app.is-installed()

Checks if a given parameter matches any of the installed applications under /Applications and ~/Applications

By the default prints the matched application. Pass `-q` as a second argument to disable output.

Example

```
> osx.app.is-installed safari
Safari.app
> osx.app.is-installed safari -q && echo installed
installed
> osx.app.is-installed microsoft -c
6
```

Arguments

- `$1(a)`: string value to match (case insensitively) for an app name
- `$2..`: additional arguments to the last invocation of `grep`

Exit codes

- `0`: if match was found
- `1`: if not

File `lib/db.sh`

- [db.config.parse\(\)](#)
- [db.psql.connect\(\)](#)
- [db.psql.connect.just-data\(\)](#)
- [db.psql.connect.table-settings-set\(\)](#)
- [db.psql.db-settings\(\)](#)
- [db.psql.connect.db-settings-pretty\(\)](#)
- [db.psql.connect.db-settings-toml\(\)](#)
- [db.actions.pga\(\)](#)

db.config.parse()

Returns a space-separated values of db host, db name, username and password

Example

```
db.config.set-file ~/.db/database.yml
db.config.parse development
#=> hostname dbname dbuser dbpass
declare -a params=($(db.config.parse development))
echo ${params[0]} # host
```

db.psql.connect()

Connect to one of the databases named in the YAML file, and optionally pass additional arguments to psql. Informational messages are sent to STDERR.

Example

```
db.psql.connect production
db.psql.connect production -c 'show all'
```

db.psql.connect.just-data()

Similar to the db.psql.connect, but outputs just the raw data with no headers.

Example

```
db.psql.connect.just-data production -c 'select datname from pg_database;'
```

db.psql.connect.table-settings-set()

Set per-table settings, such as autovacuum, eg:

Example

```
db.psql.connect.table-settings-set prod users autovacuum_analyze_threshold 1000000
db.psql.connect.table-settings-set prod users autovacuum_analyze_scale_factor 0
```

db.psql.db-settings()

Print out PostgreSQL settings for a connection specified by args

Example

```
db.psql.db-settings -h localhost -U postgres appdb
```

db.psql.connect.db-settings-pretty()

Print out PostgreSQL settings for a named connection

Example

```
db.psql.connect.db-settings-pretty primary
```

Arguments

- @arg1 dbname database entry name in ~/.db/database.yml

db.psql.connect.db-settings-toml()

Print out PostgreSQL settings for a named connection using TOML/ini format.

Example

```
db.psql.connect.db-settings-toml primary > primary.ini
```

Arguments

- @arg1 dbname database entry name in ~/.db/database.yml

db.actions.pga()

Installs (if needed) pg_activity and starts it up against the connection

File lib/shdoc.sh

lib/shdoc.sh

Helpers to install gawk and shdoc properly.0

see `${BASHMATIC_HOME}/lib/shdoc.md` for an example of how to use SHDOC. and also [project's github page](#).

- [gawk.install\(\)](#)

gawk.install()

Installs gawk into /usr/local/bin/gawk

File lib/git.sh

- [git.cfgu\(\)](#)
- [git.open\(\)](#)

git.cfgu()

Sets or gets user values from global gitconfig.

Example

```
git.cfgu email
git.cfgu email kigster@gmail.com
git.cfgu
```

git.open()

Reads the remote of a repo by name provided as an argument (or defaults to "origin") and opens it in the browser.

Example

```
git clone git@github.com:kigster/bashmatic.git
cd bashmatic
source init.sh
git.open
git.open origin # same thing
```

Arguments

- **\$1** (optional): name of the remote to open, defaults to "origin"
-

File lib/package.sh

- [package.ensure.is-installed\(\)](#)
 - [package.ensure.commmmand-available\(\)](#)
-

`package.ensure.is-installed()`

fr

`package.ensure.command-available()`

Example

In this example we skip installation `if` 'gem' exists and `in` the PATH.
Otherwise we install the package and `retry`, and `return` `if` not found

File `lib/time.sh`

- `time.with-duration.start()`

`time.with-duration.start()`

Starts a time for a given name space

Example

```
time.with-duration.start moofie
# ... time passes
time.with-duration.end   moofie 'Moofie is now this old: '
# ... time passes
time.with-duration.end   moofie 'Moofie is now very old: '
time.with-duration.clear moofie
```

File `lib/shasum.sh`

SHA Functions

SHASUM related functions, that compute SHA for a single file,
collection of files, or entire directories.

- `shasum.set-command()`
- `shasum.set-algo()`
- `shasum.sha()`
- `shasum.sha-only()`
- `shasum.sha-only-stdin()`

- [shasum.to-hash\(\)](#)
- [shasum.all-files\(\)](#)
- [shasum.all-files-in-dir\(\)](#)

shasum.set-command()

Override the default SHA command and algorithm Default is shasum -a 256

shasum.set-algo()

Override the default SHA algorithm

Example

```
$ shasum.set-algo 256
```

shasum.sha()

Compute SHA for all given files, ignore STDERR NOTE: first few arguments will be passed to the shasum command, or whatever you set via shasum.set-command.

shasum.sha-only()

Print SHA ONLY removing the file components

shasum.sha-only-stdin()

Print SHA ONLY removing the file components

shasum.to-hash()

This function populates a pre-declare associative array with filenames mapped to their SHAs, but only in the current directory Call `dbg-on` to enable additional debugging info.

Example

```
$ declare -A file_shas
$ shasum.to-hash file_shas $(find . -type f -maxdepth 2)
$ echo "Total of ${#file_shas[@]} files in the hash"
```

shasum.all-files()

For a given array of files, sort them, take a SHA of each file, and return a single SHA finger-printing this set of files. # NOTE:

the files are sorted prior to hashing, so the return SHA should ONLY change when files are either changed, or added/removed. Only computes SHA of the files provided, does not recurse into folders

Example

```
$ shasum.all-files *.cpp
```

shasum.all-files-in-dir()

For a given directory and an optional file pattern, use `find` to grab every single file (that matches optional pattern) and return a single SHA

Example

```
$ shasum.all-files-in-dir . '*.pdf'
cc35aad389e61942c75e111f1eddb634d74b4b1
```

File lib/pg.sh

- [pg.is-running\(\)](#)
- [pg.running.server-binaries\(\)](#)
- [pg.running.data-dirs\(\)](#)
- [pg.server-in-path.version\(\)](#)

pg.is-running()

Returns true if PostgreSQL is running locally

pg.running.server-binaries()

if one or more PostgreSQL instances is running locally, prints each server's binary postgres file path

pg.running.data-dirs()

For each running server prints the data directory

pg.server-in-path.version()

Grab the version from postgres binary in the PATH and remove fractional sub-version

File lib/dir.sh

- [dir.short-home\(\)](#)

dir.short-home()

Replaces the first part of the directory that matches `${HOME}` with `'~/`

File lib/config.sh

- [config.get-format\(\)](#)
- [config.set-file\(\)](#)
- [config.get-file\(\)](#)
- [config.dig\(\)](#)
- [config.dig.pretty\(\)](#)

config.get-format()

Get current format

config.set-file()

Set the default config file

config.get-file()

Get the file name

config.dig()

Reads the value from a two-level configuration hash

Arguments

- `@arg1` hash key
- `@arg2` hash sub-key

config.dig.pretty()

Uses `jq` utility to format JSON with color, supports partial

File lib/net.sh

- [net.is-host-port-protocol-open\(\)](#)

net.is-host-port-protocol-open()

Uses pingless connection to check if a remote port is open Requires sudo for UDP

Arguments

- @arg1 host
 - @arg2 port
 - @arg3 [optional] protocol (defaults to "tcp", supports also "udp")
-

File lib/is.sh

Various validations and asserts that can be chained and be explicit in a DSL-like way.

- `<<isvalidationerror,is.validation.error(>>`
- [is-validations\(\)](#)
- `<<isvalidationignore-error,is.validation.ignore-error(>>`
- `<<isvalidationreport-error,is.validation.report-error(>>`
- [whenever\(\)](#)

__is.validation.error()

Invoke a validation on the value, and process the invalid case using a customizable error handler.

Arguments

- @arg1 func Validation function name to invoke
- @arg2 var Value under the test
- @arg4 error_func Error function to call when validation fails

Exit codes

- 0: if validation passes

is-validations()

Returns the list of validation functions available

__is.validation.ignore-error()

Private function that ignores errors

__is.validation.report-error()

Private function that ignores errors

whenever()

a convenient DSL for validating things

Example

```
whenever /var/log/postgresql.log is.an-empty-file && {  
  touch /var/log/postgresql.log  
}
```

File lib/util.sh

Miscellaneous utilities.

- [util.rot13-stdin\(\)](#)

util.rot13-stdin()

Convert STDIN using rot13

Example

```
echo "test" | util.rot13-stdin
```

File lib/pdf.sh

Bashmatic Utilities for PDF file handling

Install and uses GhostScript to manipulate PDFs.

- [pdf.combine\(\)](#)

pdf.combine()

Combine multiple PDFs into a single one using ghostscript.

Example

```
pdf.combine ~/merged.pdf 'my-book-chapter*'
```

Arguments

- **\$1**(pathname): to the merged file
 - ... (the): rest of the PDF files to combine
-

File bin/install-direnv

Add direnv hook to shell RC files

- [direnv.register\(\)](#)

direnv.register()

Add direnv hook to shell RC files

File bin/regen-usage-docs

Regenerates USAGE.adoc && USAGE.pdf

File bin/pdf-reduce

- [pdf.do.shrink\(\)](#)
-

pdf.do.shrink()

shrinks PDF

File bin/scheck

- [manual-install\(\)](#)

manual-install()

Manually Download and Install ShellCheck

Copyright & License

- Copyright © 2017-2021 Konstantin Gredeskoul, All rights reserved.
- Distributed under the MIT License.