

# AI.COM “Micro CMS”

Version 0.3 – February 23, 2016

## Introduction

This is a very basic Content Management System that I made for my website, [AdolfIntel.com](http://AdolfIntel.com).

In its current state this project is no good for inexperienced users, but it's not meant to replace Wordpress, it's just a very small CMS aimed at people like me who want a Portfolio/Blog website.

## Features

- Based on modern technologies
- Very lightweight
- Responsive
- Indexable by search engines
- Compatible with browsers as old as IE6 with minimum limitations

## Features that I am not planning to introduce in future releases

- Any form of user authentication
- Article editor

## Features that may be introduced in future releases

- Administrative area to add/remove articles and comments

## Installation

### Requirements

- Apache Web Server with PHP and MySQL
- A few Mbytes of free space

### How to install

- Extract the contents of *AI\_MINI* to the root of your server (usually it's the *htdocs* folder)
- Enter PHPMyAdmin or another MySQL administration software
- Create a new database, empty
- Import *db.sql* into it
- Add an user with SELECT, UPDATE and INSERT permissions.
- Edit *\_config.php* and insert the parameters for accessing the database (username and password of the newly created user, database name and the DB server address)
- Save

## Basic customization

At this point, the site will have a Home page, an “About me” page and 2 sections (Projects and Blog) with an article each. All the content is placeholder text so you'll have to fill it.

## Essential Info

- Edit *\_config.php* and change Site\_Title, Site\_Description, Site\_Keywords and Site\_Author to match your site
- Save
- Replace *favicon.png* and *favicon.ico* with the icon you want for your site (both 128x128)

- Replace *campaign-icon.png* with the image you want to show when a link to your site is shared on a Social Network (~512x512)

### Editing the Home page

- Edit *home.frag* and replace the placeholder text with whatever you want to show on the Home page
- Save

### Editing the “About me” page

- Edit *about.frag* and replace the placeholder text with something about you
- Replace *photo.jpg* and *photo\_small.jpg* with a picture of you. The first one can be any resolution, but the second one should be smaller (~800x600, <100KB)
- Save

## Creating an Article

The easiest way to create a new article is to start by copying one of the 2 included examples, and change it to your needs.

- Copy one of the examples
- Edit *index.frag*. Keep in mind that ALL paths have to be relative to the root, because the .frag file is loaded by *index.php* (or *basic.php*), which is at the top level. An article can link to another .frag file, using a link like `<a onClick="loadFragment('path/page.frag',true)">Text</a>`. Never “a href” to a .frag file. Needless to say, .frag files can be .php files if you need to use PHP.
- Save
- Enter PHPMysqlAdmin or another MySQL administration software and add a new entry into the *articles* table. Parameters:
  - *Section*: the id of the section you want to add the article to (by default, 1=Projects, 2=Blog)
  - *Frag*: path to the .frag file of your article
  - *Description*
  - *Icon*: path to an icon file (~200x200) for the article. If left null, nullicon.png will be used
  - *CampaignIcon*: image that will be shown when the article via social media (~512x512). If null, default campaign-icon is used
  - *Title*
  - *Date*
  - *Relevance*: a decimal between 0 and 1. Articles in a section are sorted by relevance first, then date.
  - *Keywords*: keywords separated by commas (for search engines)
  - *UpdateFreq*: how often the article is updated. If left empty, it will be set to never. Valid values are daily, weekly, monthly, yearly and never.

## Adding/Removing Sections

Sections do not actually exist, *articles.php* simply fetches all articles from the DB that match a given section id, therefore, adding and removing sections is very simple.

- Edit *nav.php*: this is the file that contains the menu on top of the screen.
- You will see lines that look like this:  
`<a onClick="loadFragment('articles.php?s=2',true)">Blog</a>`
- Simply add/remove such lines. Make sure each section has its unique id (shown in red here) and name (shown in blue here)
- Save

As a direct consequence of this mechanism, it is possible to implement “secret” sections by adding articles with a section id that’s not in the menu and loading it manually using `loadFragment(‘articles.php?s=id’, true)` in your browser’s console (usually F12). Note that this provides no real security.

## Comments

This micro CMS has basic support for user comments that doesn’t require login.

Each .frag file can have a comment section, by simply adding `<div id=“_comments_”></div>` where you want to create the comment section. Note that that can only be 1 comment section per page. The provided examples already have this implemented.

Keep in mind that comments are not shown when the site is in basic mode.

The comments system is protected against basic SQL Injection (uses parametric queries) and XSS attacks (uses HTML Purifier).

In the DB, comments are stored in the *comment* table. Each comment has a pointer to the page where it belongs to (the .frag file) and the comment text.

## Removing comments

At the moment, comments can only be deleted from PHPMYAdmin or some other MySQL administration software.

## Customizing the background

By default, this project uses MuhTriangles.js as the background.

### Replacing the background

- Edit *\_config.php* and change *Background\_Page* to a page you want to show in the background. Keep in mind that backgrounds are only shown when the site is in full mode. Parameters can be passed to the background page, they’re simply added to the URL like this: *?parameters*. This is done automatically, you just have to specify the default parameters in *Background\_DefaultConfig*. If you want to see how to customize MuhTriangles.js, see the project here: <http://adolfintel.com/index.php?p=muhTriangles.js/index.frag>
- Save

## More customization

The system uses a few .css files that you can edit to change the appearance of the website. These files are:

- *main.css*: contains all the basic rules to display the documents. It is included in both basic and full mode.
- *basic\_overrides.css*: contains changes to main.css that only apply to basic mode (for instance, using .eot fonts instead of regular .woff and .otf ones)
- *articleList.css*: style for the *articles.php* page, to show the list of articles in a section
- *article.css*: rules common to articles
- *thumbnail.css*: rules for thumbnails

## Basic mode and Full mode

A site based on this project will have 2 modes: Full and Basic.

### Full mode (index.php)

- For modern browsers

- Responsive
- AJAX
- CSS Animations
- Animated background
- Comments

### Basic mode (basic.php)

- For old browsers and search engines
- Not responsive
- Static
- No animations
- Static background
- No comments

### Compatibility

On AdolfIntel.com, Basic mode is compatible with browsers as old as IE6, while full mode requires 2012-2013 browser at least (IE10, FF12, Chrome 30).

Needless to say, YOU are responsible for writing .frag files that keep compatibility with older browsers.

Links are interchangeable: if a user with an old browser receives a link that points to the full version, it will be redirected to the basic version, and vice versa.

Search engines and bots will only see basic mode.

**Javascript must be enabled**, even in basic mode.

## Creating .frag files from scratch

### Basics

The first thing to do is to create a new empty file, and give it a name, such as *test.frag*.

The basic structure of a .frag file is very simple:

```
<div>
    CODE
</div>
Inside that div, you will put all your content. Content is organized in stripes. Each stripe element contains a
content element, where you will put your text, images, ...
<div>
    <div class="stripe">
        <div class="content">
            Text.....
        </div>
    </div>
</div>
```

There can be more than one stripe, of course, but there should only be 1 content element per stripe.

Titles can be added inside the content element using the h2, h3, ..., h6 elements.

The content is organized in sections, each with 1+ paragraphs.

```
<h2>My page</h2>
<div class="section">
    <p>First paragraph</p>
    <p>More text...</p>
</div>

<div class="section">
    <p>Some text</p>
</div>
```

## Javascript functions that can be called from .frag files

### isBasicMode()

Returns true if in basic mode, false otherwise. This is the easiest way to find out whether you are in basic mode or not using JS.

### hideNav()

Hides the menu on top. Will be shown again when a new .frag file is loaded.

### showNav()

Shows the menu on top if it was hidden.

### hidePage()

Hides the .frag file. Will be shown again when a new .frag file is loaded

### showPage()

Shows the .frag file if it was hidden.

### openLightbox(url)

Opens the image at the specified URL in a lightbox. In basic mode, it opens it in a new window.

### closeLightbox()

Closes a previously opened lightbox. In basic mode, it does nothing.

### loadFragment(url, pushState)

Loads a .frag file at the specified URL. The second parameter should always be true. If you forget it or set it to false, the new .frag file won't be added to history and it won't be possible to go back/forth between pages.

In full mode, the .frag file is loaded via AJAX, but in basic mode it will trigger a full page reload.

### setBackgroundCfg(cfg)

Sets a new background config, stores it in localStorage and applies it by reloading the background page. In basic mode, it does nothing.

## Local CSS

A .frag file can define its CSS rules that will only apply to that fragment. To do so, simply add this at the beginning of your .frag file, right after opening the initial <div>

```
<style type="text/css" scoped="scoped">
  CSS RULES
</style>
```

## Importing a CSS file

To import a .css file, simply add this at the beginning of your .frag file, right after opening the initial <div>

```
<link rel="stylesheet" type="text/css" href="path/to/file.css" />
```

## Local JS

### Running a script when the .frag is created

Simply add this code somewhere in your .frag file (inside the <div>, of course)

```
<script type="text/javascript">
  CODE
</script>
```

### Defining JS functions to use in the current .frag file

Simply add this code at the beginning of your .frag file, right after opening the initial <div>

```
<script type="text/javascript">
    window.functionName=function(param1, param2, ...){
        //FUNCTION CODE
    }
</script>
```

### Importing a JS file

Unfortunately, due to browser limitations, it is not possible to use `<script type="text/javascript src="path/file.js"></script>` like you would on a normal page.

In these cases, I suggest you use an `iframe` to embed a full webpage.

### "Am I in Basic or Full mode?"

#### JS

`isBasicMode()` returns true if in basic mode, false otherwise

#### CSS

When in basic mode, the fragment is inside an element that has class `basic`. The code below will only apply when in basic mode.

```
.basic myRule{
    ...
}
```

#### PHP

Simply check if the URL contains `basic.php`.

```
If(strops($_SERVER['PHP_SELF'],'basic.php')!==false){
    //basic code
}else{
    //full code
}
```

### basic\_only and basic\_hide classes

Some elements in your `.frag` files can be shown/hidden in a specific mode.

```
<div class="basic_hide">
    <div class="stripe">
        <div class="content">
            <h2>An exclusive stripe</h2>
            This stripe is only visible in full mode.
        </div>
    </div>
</div>

<div class="basic_only">
    <div class="stripe">
        <div class="content">
            <h2>Filthy old browsers</h2>
            This stripe is only visible if your browser A SHIT!
        </div>
    </div>
</div>
```

### Embedding a full webpage

`Iframes` can be used to embed other pages. Due to really crappy support from older browsers, it is best to use them only in full mode.

#### Using `iframe.frag`

This code can be used in a script or in a link.

```
loadFragment('iframe.frag?p=url',true)
```

Using an iframe

```
<iframe src="url" style="width:100%"></iframe>
```

## Licenses

This project is licensed under the [GNU GPLv3](#) license.

## Frameworks

Nothing

## Libraries

Uses [HTML Purifier](#), under the [GNU LGPL v2](#) license.

## Fonts

Uses the Bebas Neue font by [Fontfabric](#)

Uses the Roboto font by [Christian Robertson](#) (Google)