Employee Attrition Prediction Using Non-Probabilistic and Probabilistic Classification with Feature Selection



Adolfo Borrego González

Practical Applications 1 and 2 — Machine Learning

Abstract

Employee attrition is studied as a binary supervised classification problem using 1,470 observations from the IBM HR Analytics Employee Attrition & Performance dataset.

Practical Applications 1 and 2 compare K-NN, Decision Tree, Support Vector Machine, Neural Network and RIPPER classifiers with Mixed Naive Bayes, Logistic Regression, Linear and Quadratic Discriminant Analysis. Each family is evaluated with all valid predictors, univariate and multivariate filters, and a forward-selection wrapper; Bagging, AdaBoost and Stacking extend the probabilistic comparison.

Predictive performance is estimated through stratified 10-fold cross-validation, with preprocessing and selection fitted within each outer training fold; the tree-based wrapper uses internal five-fold selection; RIPPER uses a bounded three-step search with two internal folds.

The full-feature Neural Network leads PA1 in F1 (0.4738). In PA2, full-feature Logistic Regression obtains F1 0.5373 and the highest AUC (0.8375), while Stacking marginally increases F1 to 0.5394 and achieves the lowest probability-vector Brier score (0.1846). Full-feature Mixed Naive Bayes provides the highest PA2 recall (0.6453). Feature selection offers smaller representations but does not outperform the strongest complete-feature models.

Recurring predictors, including overtime, job level, stock-option level and company tenure, support predictive interpretation without implying causality.

Contents

1 Introduction **3**

2 Problem Description **3**

3 Methodology **4**
3.1 PA1: Non-Probabilistic Classification 4
3.1.1 Data Preprocessing 4
3.1.2 Classification Algorithms 4
3.2 Shared Evaluation Protocol and Metrics 4
3.3 PA1: Feature Selection Strategies 5
3.4 PA2: Probabilistic Classification 5
3.4.1 Model-Specific Representations 5
3.4.2 Feature Selection on Original Predictors 6
3.4.3 Metaclassifiers 6

4 Results **7**
4.1 PA1: Non-Probabilistic Classification 7
4.1.1 Original Feature Set 7
4.1.2 Univariate Filter 7
4.1.3 Multivariate Filter 7
4.1.4 Wrapper 7
4.1.5 Overall Comparison 7
4.1.6 Selected Variables 8
4.2 PA2: Probabilistic Classification 8
4.2.1 All Valid Predictors 8
4.2.2 Univariate Filter 9
4.2.3 Multivariate Filter 9
4.2.4 Wrapper 9
4.2.5 Metaclassifiers and Overall Comparison 9

5 Discussion **12**
5.1 PA1 Performance and Dimensionality 12
5.2 Integrated Performance and Probability Quality 12
5.3 Interpretation of Employee Characteristics 13
5.4 Limitations 14

6 Conclusion **14**

1 Introduction

Employee attrition describes employees leaving an organisation. In this application, recorded employee characteristics are used to distinguish employees who leave from those who remain, giving a supervised binary classification task. The analysis concerns associations in the available data rather than explanations of individual decisions to leave.

Feature selection can reduce dimensionality, remove irrelevant or redundant information and make the retained employee characteristics easier to interpret. These potential benefits need to be assessed against predictive performance: a smaller representation need not preserve all useful information.

This integrated study compares non-probabilistic classifiers (PA1) and probabilistic classifiers (PA2) under four analyses: all valid predictors, univariate filtering, multivariate filtering and wrapper selection. PA2 additionally evaluates representative metaclassifiers. The research question is: *Which employee characteristics repeatedly support attrition prediction, and how do classifier choice and feature selection affect predictive performance, minority-class sensitivity and probability quality?* The comparison considers these objectives alongside dimensionality and model complexity.

2 Problem Description

The IBM HR Analytics Employee Attrition & Performance dataset contains 1,470 employee observations and 35 original columns, including the binary target `Attrition`. Its distribution is summarised in Table 1. The dataset is distributed through Kaggle [1]. Predictors cover demographics (age and marital status), professional attributes (department and job role), compensation (monthly income and stock options), satisfaction and involvement, experience (working years and company tenure), and working conditions (overtime and business travel).

Table 1: Dataset characteristics and target distribution.

Characteristic	Value
Observations	1,470
Original columns, including target	35
Valid original predictors after removal	30
Numerical / categorical predictors	23 / 7
Missing values	0
`No`: employee remains	1,233 (83.88%)
`Yes`: employee leaves	237 (16.12%)

Both applications use this dataset and define `Yes` as the positive class. Its minority status means that accuracy alone does not adequately describe attrition detection: always predicting `No` would obtain 83.88% accuracy while detecting no attrition cases. The identifier `EmployeeNumber` and the constant columns `EmployeeCount`, `Over18` and `StandardHours` are removed during preprocessing. With 30 valid predictors and 1,470 observations, the dataset exceeds the assignment's minimum of 15 variables and 100 observations. The numerical/categorical counts describe raw storage types; PA2 additionally distinguishes continuous and ordinal predictors for model-specific processing.

3 Methodology

3.1 PA1: Non-Probabilistic Classification

3.1.1 Data Preprocessing

The four non-predictive columns identified above are removed, leaving 30 original predictors. No imputation is needed because there are no missing values. The target is encoded as `No`=0 and `Yes`=1. For K-NN, Decision Tree, SVM and Neural Network, the 23 numerical predictors are standardised using `StandardScaler`; the seven categorical predictors are encoded using `OneHotEncoder` with `handle_unknown="ignore"`. Integer variables representing ordinal levels retain their ordered numerical representation. The complete encoded representation contains 51 transformed features.

For K-NN, Decision Tree, SVM and Neural Network, a scikit-learn `Pipeline` [2] combines preprocessing, optional selection and classification; RIPPER uses explicit DataFrame fits and predictions. Fitted preprocessing from structural inspection is not reused for evaluation. Transformations and selectors are fitted on each outer training fold, and then applied to its held-out fold.

3.1.2 Classification Algorithms

Five classifiers are evaluated in each of the four PA1 experiments: K-NN, Decision Tree, SVM, Neural Network and RIPPER. K-NN classifies from neighbouring observations; Decision Tree uses successive feature splits; SVM constructs a separating boundary; Neural Network learns a multilayer representation; and RIPPER induces an IF–THEN rule set. The implementations are `KNeighborsClassifier()`, `DecisionTreeClassifier` (random seed 42), `SVC()`, `MLPClassifier` (random seed 42; maximum 2,000 iterations) and `wittgenstein` 0.3.5 RIPPER (random seed 42). Other parameters remain at their defaults. The tree is scikit-learn's implementation, not an exact implementation of ID3 or C4.5. Hyperparameters are not tuned, and no resampling or class weighting is applied.

RIPPER grows, prunes and optimises rules using training data. It preserves nominal strings and unscaled numerical values; numeric bins are learned on training data only and reused for validation. Under the two filters, it uses the same 15 selected transformed columns as the other classifiers, with numerical columns restored to original units and selected dummy indicators kept binary. Its wrapper instead searches original predictors with two inner stratified folds, F1 scoring and at most three forward additions, retaining the best prefix. Every candidate refits RIPPER and discretisation within its inner training split. Fold-level rules, selections and metrics are retained for interpretation. Feature counts from original predictors and transformed columns are not directly comparable.

3.2 Shared Evaluation Protocol and Metrics

Every configuration is evaluated using `StratifiedKFold` with ten shuffled folds and random seed 42. Stratification approximately preserves class proportions. Each outer held-out fold is excluded from fitting preprocessing, selecting features and training the classifier, providing an honest estimate for each fixed configuration. Reported scores are arithmetic means of the ten held-out-fold scores.

Accuracy measures the proportion of correct predictions. Precision (positive predictive value) measures the proportion of predicted attrition cases that are positive; recall (sensitivity) measures the proportion of actual attrition cases detected. Specificity measures the proportion of negative cases correctly identified. F1-measure is the harmonic mean of precision and recall. Positive-class metrics refer to `Attrition=Yes`. PA1 records accuracy, precision, recall, F1 and balanced

accuracy; the latter averages sensitivity and specificity and is retained as a supplementary PA1 measure.

PA2 reports accuracy, precision, recall, specificity, F1, area under the ROC curve (AUC), and Brier score. AUC evaluates discrimination across decision thresholds. Brier evaluates squared error in the complete predicted class-probability vector:

$$B = \frac{1}{n}\sum_{i=1}^{n}\sum_{c\in\{0,1\}}\left(p_{ic} - \mathbf{1}\{y_i = c\}\right)^2.$$

Lower values indicate better probability predictions. This implementation is twice the binary Brier score computed from the positive-class probability alone. Brier reflects both calibration and discrimination, rather than calibration alone. Balanced accuracy is not a primary PA2 metric. Predictions use the implemented classifiers' default decision rules; thresholds are not optimised for recall.

3.3 PA1: Feature Selection Strategies

All Features. All 30 valid original predictors are retained. K-NN, Decision Tree, SVM and Neural Network receive 51 transformed columns; RIPPER receives the original predictor columns with its training-fold discretisation.

Univariate Filter. After preprocessing, `SelectKBest` with `f_classif` and $k = 15$ retains the 15 transformed features with the highest individual ANOVA F-scores. It assesses association with the target separately for each feature [4].

Multivariate Filter. The existing custom greedy selector retains 15 transformed features. It first selects the feature with the greatest estimated mutual information with the target. Subsequently it maximises target mutual information minus the mean absolute Pearson correlation with already selected features. Mutual information is computed using `mutual_info_classif` with random seed 42. This is an mRMR-inspired relevance–redundancy implementation [3], rather than a canonical library implementation of mRMR: redundancy is measured by correlation rather than mutual information.

Wrapper. For K-NN, Decision Tree, SVM and Neural Network, `SequentialFeatureSelector` performs forward selection of 15 transformed features using a `DecisionTreeClassifier` with random seed 42, F1 scoring and internal five-fold CV [4]. RIPPER uses the bounded original-predictor search described above. Selection is nested within the outer ten-fold evaluation: inner CV chooses the subset, while outer held-out folds estimate predictive performance. For the tree-based selector, preprocessing is fitted on the outer training fold before inner CV and is not refitted within each inner split. The outer test fold remains excluded throughout.

For interpretation only, separate selector pipelines are fitted to the full dataset to export selected-feature lists. These fits do not generate the reported predictive scores. Their overlap describes agreement across the three strategies in these descriptive fits, rather than selection frequency across CV folds. One-hot categories are mapped back to their original variables.

3.4 PA2: Probabilistic Classification

3.4.1 Model-Specific Representations

PA2 retains the same 30 valid original predictors and target. One representative implementation is used per family. Mixed Naive Bayes estimates Gaussian class-conditional distributions for continuous predictors and discrete class-conditional probabilities with Laplace smoothing ($\alpha = 1$) for

ordinal and nominal predictors. It combines these contributions under conditional independence given the class.

Logistic Regression models the log-odds of attrition as an additive function of its transformed predictors. Its pipeline applies `StandardScaler` to continuous and ordinal variables and `OneHotEncoder` with one reference category to nominal variables. `LogisticRegression` uses a maximum of 2,000 iterations and random seed 42, with remaining parameters at defaults.

LDA and QDA model class-conditional distributions with shared and class-specific covariance matrices, respectively. Their pipelines standardise numerical/ordinal predictors and retain one numerically encoded column per nominal predictor, avoiding the rank deficiency introduced by expanded dummy variables. These nominal codes do not imply a meaningful order; their numerical use is a representation limitation. The implementations are `LinearDiscriminantAnalysis()` and `QuadraticDiscriminantAnalysis()`. Thus, the families do not receive an identical transformed matrix. Every representation is fitted using training data only.

3.4.2 Feature Selection on Original Predictors

All Features. All 30 valid original predictors are retained before model-specific preprocessing.

Univariate Filter. A type-aware selector evaluates continuous predictors with ANOVA F-statistics and ordinal/nominal predictors with mutual information. Scores are standardised separately within these two families because their scales differ. The 15 highest-ranked original predictors are retained inside each training fold, before model-specific transformation.

Multivariate Filter. Correlation-based Feature Selection (CFS) evaluates subset relevance to the target and redundancy between predictors using Symmetrical Uncertainty. Continuous variables are discretised into up to five quantile bins using training data only for this criterion; selected predictors retain their original values for classification. For a subset of size k, the merit is

$$M = \frac{k\overline{SU}_{Xy}}{\sqrt{k + k(k-1)\overline{SU}_{XX}}},$$

where the averages describe predictor–target association and pairwise predictor redundancy. Greedy forward search considers up to 15 original predictors and retains the subset with the highest merit found. This CFS procedure differs from PA1's mRMR-inspired selector.

Wrapper. Classifier-specific sequential forward selection searches up to 15 original predictors and retains the subset with the highest internal mean F1. Each classifier conducts its own search in each outer training fold. Internal stratified five-fold CV evaluates candidate model pipelines, refitting preprocessing within each inner training split. The selected pipeline is then fitted on the outer training data and evaluated on its held-out fold using the shared ten-fold protocol. Feature search and final performance estimation are therefore separated; PA1's common tree-based wrapper is not reused.

Separate full-data PA2 filter fits are descriptive only. Fold-level selections are also recorded to assess recurrence under the evaluation protocol, providing information distinct from PA1's descriptive agreement counts.

3.4.3 Metaclassifiers

Representative Bagging, AdaBoost and Stacking configurations are evaluated with all valid predictors. Bagging aggregates 100 Decision Trees; AdaBoost combines 100 decision stumps (trees with maximum depth one). Stacking uses Logistic Regression and LDA as base learners and

Logistic Regression as the final estimator, trained on internally generated probability predictions with five-fold CV. QDA was excluded from stacking because covariance estimation became numerically unstable in its internal folds.

The ensemble pipelines standardise numerical/ordinal predictors and one-hot encode nominal predictors with a reference category. This shared ensemble representation differs from the standalone LDA/QDA representation. Preprocessing is fitted on each outer training fold before the ensemble's internal operations; it is not independently refitted inside stacking's internal folds. The outer held-out fold remains excluded, so the reported ensemble scores are honest outer-fold estimates, although the internal stacking representation has this limitation. Ensemble variants beyond these representatives are not evaluated.

4 Results

4.1 PA1: Non-Probabilistic Classification

4.1.1 Original Feature Set

With all features, the Neural Network achieves the highest mean F1 (0.4738) and balanced accuracy (0.6765), with recall 0.4219. SVM obtains the highest accuracy (0.8653) and precision (0.8363), but recall is 0.2241. Decision Tree obtains F1 0.3620 and balanced accuracy 0.6206; K-NN obtains F1 0.2115 and balanced accuracy 0.5577. RIPPER, using 30 original predictors, obtains F1 0.2866 and balanced accuracy 0.5818.

4.1.2 Univariate Filter

Decision Tree remains the highest-F1 classifier under univariate selection, with F1 0.3809 and balanced accuracy 0.6347. Its F1 and balanced accuracy improve relative to the baseline, as do those of K-NN (F1 0.2968). SVM and Neural Network obtain lower F1 and balanced accuracy than with all features. RIPPER obtains F1 0.2316 and balanced accuracy 0.5645 with 15 selected transformed components.

4.1.3 Multivariate Filter

The Neural Network has the highest F1 within this strategy, at 0.3902, with balanced accuracy 0.6341. Decision Tree obtains F1 0.3748. Both K-NN and SVM score below their baselines; SVM recall falls to 0.0511 and F1 to 0.0910. RIPPER obtains F1 0.2280 and balanced accuracy 0.5653 with the same 15-component filter criterion.

4.1.4 Wrapper

Under the tree-based wrapper, the Neural Network has the highest F1 (0.3919), with balanced accuracy 0.6286. K-NN improves from baseline F1 0.2115 to 0.3146 and from recall 0.1350 to 0.2364. Neither the wrapper Neural Network nor the other reduced configurations exceed the full-feature Neural Network in F1 or balanced accuracy.

The RIPPER wrapper obtains F1 0.3996 and balanced accuracy 0.6557, leading the reduced configurations. It retains a mean of 2.6 original predictors (range two to three) across outer folds. This differs from the 15 transformed components selected by the tree wrapper. It improves RIPPER's all-feature F1 without exceeding the full-feature Neural Network.

4.1.5 Overall Comparison

Table 2 lists the highest-F1 configuration within each strategy. Figure 1 shows all 20 F1 comparisons. Among reduced configurations, the RIPPER wrapper has the highest F1 (0.3996)

and balanced accuracy (0.6557). K-NN, Decision Tree, SVM and Neural Network retain 15 of 51 transformed features under selection, a 70.59% reduction; RIPPER counts use the units described above.

Table 2: PA1 highest mean F1 configuration per strategy. BA denotes balanced accuracy; all metrics are ten-fold means.

Experiment	Model	Number of Features	Accuracy	Precision	Recall	F1	Balanced Accuracy
All Features	Neural Network	51.000000	0.849000	0.549200	0.421900	0.473800	0.676500
Multivariate	Neural Network	15.000000	0.824500	0.450100	0.353400	0.390200	0.634100
Univariate	Decision Tree	15.000000	0.778900	0.354600	0.421900	0.380900	0.634700
Wrapper	RIPPER	2.600000	0.782300	0.364000	0.468700	0.399600	0.655700




Figure 1: PA1 mean F1-score by classifier and feature-selection strategy.

4.1.6 Selected Variables

Table 3 reports original variables retained by at least two strategies in the separate full-data interpretation fits. Seven original variables appear in all three strategies. A categorical variable is counted as selected when at least one of its dummy features is retained, even when strategies choose different categories of that variable.

4.2 PA2: Probabilistic Classification

4.2.1 All Valid Predictors

Full-feature Logistic Regression obtains the highest F1 among individual probabilistic baselines (0.5373), with accuracy 0.8823, precision 0.7344, recall 0.4259 and specificity 0.9700. It also provides the highest PA2 AUC (0.8375), with Brier 0.1857. Mixed Naive Bayes has the highest recall of all PA2 configurations (0.6453), but lower precision (0.4208), F1 (0.5083), AUC (0.7851) and poorer probability quality (Brier 0.2902). LDA obtains F1 0.4256 and AUC 0.8146; QDA obtains F1 0.3946 and AUC 0.7211.

Table 3: Agreement between descriptive full-data selections at original-variable level. U: univariate; M: multivariate; W: wrapper.

Original variable	U	M	W	Count
BusinessTravel	Yes	Yes	Yes	3
JobInvolvement	Yes	Yes	Yes	3
JobRole	Yes	Yes	Yes	3
MaritalStatus	Yes	Yes	Yes	3
MonthlyIncome	Yes	Yes	Yes	3
OverTime	Yes	Yes	Yes	3
StockOptionLevel	Yes	Yes	Yes	3
Age	Yes	–	Yes	2
JobSatisfaction	Yes	Yes	–	2
NumCompaniesWorked	–	Yes	Yes	2
TotalWorkingYears	Yes	–	Yes	2

4.2.2 Univariate Filter

Mixed Naive Bayes has the highest F1 within this strategy (0.4600), with recall 0.6033. QDA improves from baseline F1 0.3946 to 0.4240, recall 0.3755 to 0.3924, and AUC 0.7211 to 0.7302, while Brier decreases from 0.2786 to 0.2628. Logistic Regression deteriorates substantially: F1 falls from 0.5373 to 0.3736 and recall from 0.4259 to 0.2708. Thirteen original predictors are retained in all ten folds, including overtime, job level, stock-option level, company tenure, age and monthly income.

4.2.3 Multivariate Filter

CFS selects between 3 and 11 original variables per fold (mean 7.8); the separate descriptive full-data fit retains nine. `JobLevel`, `OverTime` and `StockOptionLevel` appear in all ten fold-level subsets, and `YearsAtCompany` in nine. Mixed Naive Bayes obtains the highest F1 within this strategy (0.3962), with recall 0.3531. The compact subsets therefore lose predictive performance relative to the strongest complete-feature baseline, although its Brier improves from 0.2902 to 0.2386.

4.2.4 Wrapper

Logistic Regression obtains the highest F1 among all reduced-feature PA2 configurations (0.4696), with AUC 0.8206 and Brier 0.1976. Mixed Naive Bayes obtains recall 0.4087 and F1 0.4358; QDA obtains F1 0.3848, AUC 0.7165 and Brier 0.2535. Mean selected original-variable counts are 13.1 for Mixed Naive Bayes, 14.6 for Logistic Regression, 13.5 for LDA and 12.9 for QDA. These classifier-specific searches do not outperform the strongest complete-feature baseline.

4.2.5 Metaclassifiers and Overall Comparison

Stacking obtains the highest PA2 F1 (0.5394) and lowest Brier (0.1846). Relative to full-feature Logistic Regression, the F1 improvement is marginal, recall is identical (0.4259), and AUC is slightly lower (0.8365 versus 0.8375). AdaBoost obtains F1 0.4676, recall 0.3380 and AUC 0.8314, but its Brier is 0.3773. Bagging obtains F1 0.3407 and recall 0.2362.

Table 4 summarises the highest-F1 configuration per strategy; Table 5 identifies the metric-specific leaders. Figure 2 contrasts F1 with probability-vector error across the evaluated configurations. Rankings use observed cross-validation means and do not establish statistically significant differences.




Figure 2: PA2 mean F1 (top) and full class-probability-vector Brier score (bottom). Higher F1 and lower Brier are preferable.

Table 4: PA2 highest mean F1 configuration per strategy. All scores are ten-fold means; lower Brier is better.

Strategy	Model	Recall	F1	AUC	Brier
Metaclassifier	Stacking	0.425900	0.539400	0.836500	0.184600
All Features	Logistic Regression	0.425900	0.537300	0.837500	0.185700
Wrapper	Logistic Regression	0.355100	0.469600	0.820600	0.197600
Univariate	Mixed Naive Bayes	0.603300	0.460000	0.763300	0.319000
Multivariate	Mixed Naive Bayes	0.353100	0.396200	0.761600	0.238600

Table 5: PA2 leading configurations by objective metric.

Metric	Strategy	Model	Value
F1	Metaclassifier	Stacking	0.539400
Recall	All Features	Mixed Naive Bayes	0.645300
AUC	All Features	Logistic Regression	0.837500
Brier	Metaclassifier	Stacking	0.184600

5 Discussion

5.1 PA1 Performance and Dimensionality

The imbalance explains why accuracy must be considered alongside minority-class metrics. The full-feature SVM combines accuracy 0.8653 and precision 0.8363 with recall 0.2241: its positive predictions are relatively precise, but it identifies only a small proportion of employees leaving. The full-feature Neural Network offers the strongest observed balance according to F1 and balanced accuracy, although recall 0.4219 still indicates substantial missed attrition cases.

Selection does not universally improve performance. K-NN benefits from univariate and wrapper selection, with the wrapper yielding its largest F1 improvement; multivariate selection instead lowers its F1. Removing dimensions can change which observations are considered neighbours, so retaining a useful subset can help this classifier. This interpretation is consistent with the observed improvements but does not establish the mechanism. Decision Tree improves moderately with the filters. All reduced Neural Network configurations lose performance relative to its complete representation, suggesting that the omitted information is useful in that experimental setting.

The filters assess feature–target association, with the multivariate filter also penalising redundancy. For example, the univariate subset retains both complementary overtime indicators, whereas the multivariate subset retains only `OverTime_Yes`. For K-NN, Decision Tree, SVM and Neural Network, the wrapper evaluates candidate additions through a Decision Tree's F1, so the resulting representation is linked to that estimator rather than independently optimised for every final classifier. These different criteria explain why the methods need not choose identical subsets or favour the same classifier. The 70.59% reduction offers a more compact representation, but 15 transformed features do not necessarily represent 15 distinct employee characteristics. No selection strategy is best on every metric.

RIPPER's rule-based predictions can be inspected through explicit IF–THEN conditions. Its classifier-specific wrapper raises F1 from 0.2866 to 0.3996 and provides the highest reduced-feature F1, while the complete Neural Network remains best overall. The wrapper averages 2.6 original predictors, whereas the filters select 15 transformed columns. Different units and the bounded two-fold/three-step search prevent attributing these differences solely to classifier choice. The overlap tables describe descriptive full-data selector fits, whereas RIPPER's wrapper selections vary across outer folds.

The induced rules explain positive predictions through explicit conjunctions, rather than feature retention alone. For example, the first outer training-fold wrapper model includes the rule `OverTime=Yes` AND `StockOptionLevel=0` AND `JobRole=SalesExecutive`; a matching employee is classified as attrition. Another rule in that same model requires `StockOptionLevel=0` and `JobRole=SalesRepresentative`, without an overtime condition. Thus overtime is not required by every positive rule. Across wrapper folds, overtime is selected in all ten, job role in eight and job level in three; stock-option level appears in two, while company tenure, department and work-life balance each appear in one. These are selections, not condition frequencies or causal effects. Conditions within each rule are joined by AND; rules are joined by OR, with no matching rule predicting no attrition. Fold-specific rule sets illustrate model behaviour and should not be presented as a single universal full-data rule set. They provide a more direct explanation of decisions than the Neural Network's performance scores or descriptive feature-overlap lists.

5.2 Integrated Performance and Probability Quality

Full-feature Logistic Regression in PA2 exceeds PA1's full-feature Neural Network in observed F1, while their recall is similar. Its additive log-odds model offers a comparatively simple probabilistic representation. Retaining all predictors allows jointly useful associations to contribute even when

individual filter scores are modest; its default regularisation also limits coefficient magnitude. These properties plausibly explain its competitiveness, rather than establish the mechanism. Comparisons between PA1 and PA2 reflect both classifier and representation choices, so they do not isolate an effect of probabilistic modelling alone.

Aggressive filtering can discard complementary information. PA2's univariate ranking assesses predictors individually, while CFS favours relevance with low redundancy rather than optimising classifier F1. CFS therefore produces compact subsets but can omit information useful jointly or under a particular model representation. QDA's univariate improvement is consistent with reduced covariance-estimation demands, although it remains below Logistic Regression. Even PA2's classifier-specific wrapper does not recover the strongest complete-feature F1: greedy search bounded at 15 original predictors need not identify the most useful joint representation. PA1's counts concern transformed features, so dimensionality reductions are not directly interchangeable across applications.

Mixed Naive Bayes detects more minority-class cases than the other PA2 configurations, at the cost of lower precision and higher probability-vector error. Its conditional-independence assumption may be restrictive for related career and compensation predictors. Multiplying dependent evidence can distort estimated probabilities, although these experiments do not establish this as the sole explanation. Higher recall therefore does not imply better probability quality. AdaBoost's competitive AUC but much larger Brier similarly distinguishes ranking discrimination from accurate probability estimates.

Stacking adds an internal fitting stage and a final estimator, yet improves F1 and Brier only marginally relative to Logistic Regression, with unchanged recall and slightly lower AUC. Its related linear base learners may provide limited complementary information. Without uncertainty estimates or a formal paired comparison, these small differences do not justify claiming a meaningful advantage. Full-feature Logistic Regression is consequently competitive when balancing discrimination, probability quality and simplicity; Mixed Naive Bayes is preferable among the tested PA2 configurations when recall is the principal objective. Compact CFS subsets serve a different objective: reducing the number of recorded characteristics. No configuration dominates all objectives.

5.3 Interpretation of Employee Characteristics

Four predictors are selected in at least eight folds by both PA2 filters: `OverTime`, `JobLevel`, `StockOptionLevel` and `YearsAtCompany`. Overtime describes working conditions; job level describes organisational position; stock-option level represents a compensation attribute; and company tenure describes experience within the organisation. Their recurrence indicates that these complementary aspects repeatedly support predictive discrimination under different selection criteria. It does not establish that any attribute causes attrition, nor does selection alone reveal the direction or magnitude of an association. Overtime and stock-option level also appear in all three PA1 descriptive selections.

PA2's stable univariate selections further retain age, job role, involvement, monthly income and career-experience variables, supporting a multidimensional predictive interpretation. Relationships between professional level, compensation and experience also caution against interpreting each selected variable independently. PA1 agreement counts below come from separate full-data fits, whereas PA2 frequencies count outer training-fold selections. The latter indicate recurrence under overlapping resamples, not independent replication or a causal importance ranking. The repeated original variables describe several complementary aspects of the employee context. `BusinessTravel` and `OverTime` concern working conditions; `JobInvolvement` records involvement in work; and `JobRole` distinguishes professional functions. `MonthlyIncome` and `StockOptionLevel` describe compensation, while `MaritalStatus` describes personal circumstances. Their selection by all three strategies identifies recurring associations relevant to classification in this dataset, without establishing causal effects or the direction of each association.

The existing descriptive analysis provides context for overtime: attrition is 30.53% among employees with overtime and 10.44% among those without it. These rates support interpreting overtime as associated with attrition-related classification patterns, rather than as a cause of leaving. `Age`, `JobSatisfaction`, `NumCompaniesWorked` and `TotalWorkingYears`, each selected by two strategies, add demographic, satisfaction and career-experience information.

Dummy categories must be interpreted together at original-variable level. For example, `OverTime_Yes` and `OverTime_No` encode the same employee characteristic; different retained `JobRole` categories still refer to job role. Agreement across methods makes the selected representation easier to discuss, but does not by itself provide a ranked importance measure or explain individual Neural Network predictions.

5.4 Limitations

The IBM dataset is synthetic/fictitious, so these findings should not be treated as evidence about a specific real workforce. Class imbalance remains present and minority-class recall is limited. Hyperparameters and decision thresholds were not optimised; conclusions concern the chosen configurations. PA1 fixes reduced subsets at 15 transformed features; PA2 ranks or searches original predictors, retaining at most 15. Neither setup establishes a globally optimal subset.

Numerical nominal codes in standalone LDA/QDA introduce representation dependence without meaningful ordering. QDA's instability inside stacking illustrates the sensitivity of covariance estimation to the available representation and sample size. PA1's wrapper and PA2's stacking fit preprocessing before their internal folds, as disclosed in Methodology; outer held-out folds remain excluded from all fitting. Cross-validation provides honest estimates for fixed configurations, but choosing the highest observed mean among many configurations may favour sampling variation. No independent external validation or statistical significance claim is provided. Logistic Regression's form is comparatively interpretable, but no fitted coefficient analysis is reported here; selection describes retained information rather than explaining individual predictions.

6 Conclusion

PA1 and PA2 address one attrition-prediction problem using honest stratified cross-validation, with outer held-out data excluded from preprocessing, feature selection and model fitting. The full-feature Neural Network leads PA1 in F1, while probabilistic Logistic Regression and Stacking are particularly competitive across the integrated comparison. Stacking's F1 and Brier gains over Logistic Regression are marginal; Mixed Naive Bayes provides the highest PA2 recall.

Feature selection reduces dimensionality and benefits some classifiers but does not systematically improve the strongest complete-feature models. Repeated retention of overtime, job level, stock-option level and company tenure in PA2, together with recurring PA1 characteristics, supports interpretation of predictive associations without causal claims. The practical choice therefore depends on the trade-off between predictive performance, sensitivity to attrition, dimensionality and model complexity.

References

[1] IBM HR Analytics Employee Attrition & Performance. Kaggle dataset page, `https://www.kaggle.com/datasets/pavansubhasht/ibm-hr-analytics-attrition-dataset`. Accessed 9 October 2026.

[2] Fabian Pedregosa, Gaël Varoquaux, Alexandre Gramfort, Vincent Michel, Bertrand Thirion, Olivier Grisel, Mathieu Blondel, Peter Prettenhofer, Ron Weiss, Vincent Dubourg, Jake Vanderplas, Alexandre Passos, David Cournapeau, Matthieu Brucher, Matthieu Perrot, and Édouard

Duchesnay. Scikit-learn: Machine learning in python. *Journal of Machine Learning Research*, 12:2825–2830, 2011.

[3] Hanchuan Peng, Fuhui Long, and Chris Ding. Feature selection based on mutual information: Criteria of max-dependency, max-relevance, and min-redundancy. *IEEE Transactions on Pattern Analysis and Machine Intelligence*, 27(8):1226–1238, 2005.

[4] scikit-learn developers. Feature selection. scikit-learn documentation, `https://scikit-learn.org/stable/modules/feature_selection.html`. Accessed 9 October 2026.