

Create DAX Calculations in Power BI Desktop

[Lab story](#)

[Get started](#)

[Create the Salesperson calculated table](#)

[Create the Date table](#)

[Create calculated columns](#)

[Complete the Date table](#)

[Mark the Date table](#)

[Create simple measures](#)

[Create additional measures](#)

[Lab complete](#)

Lab story

In this lab you'll create calculated tables, calculated columns, and simple measures using Data Analysis Expressions (DAX).

In this lab you learn how to:

- Create calculated tables
- Create calculated columns
- Create measures

This lab should take approximately 45 minutes.

Get started

To complete this exercise, first open a web browser and enter the following URL to download the zip folder:

<https://github.com/MicrosoftLearning/PL-300-Microsoft-Power-BI-Data-Analyst/raw/Main/Allfiles/Labs/04-create-dax-calculations-in-power-bi-desktop\04-intro-dax.zip>

Extract the folder to the **C:\Users\Student\Downloads\04-intro-dax** folder.

Open the **04-Starter-Sales Analysis.pbix** file.

Note: You can dismiss the sign-in by selecting **Cancel**. Close any other informational windows. Select **Apply Later**, if prompted to apply changes.


Create the Salesperson calculated table

In this task, you'll create the **Salesperson** calculated table (direct relationship to **Sales**).

A calculated table is created by first entering the table name, followed by the equals symbol (=), followed by a DAX formula that returns a table. The table name can't already exist in the data model.


The formula bar supports entering a valid DAX formula. It includes features like auto-complete, Intellisense and color-coding, enabling you to quickly and accurately enter the formula.

1. In Power BI Desktop, in Report view, on the **Modeling** ribbon, from inside the **Calculations** group, select **New Table**.




2. In the formula bar (which opens directly beneath the ribbon when creating or editing calculations), type **Salesperson =**, press **Shift+Enter**, type **'Salesperson (Performance)'**, and then press **Enter**.

Note: For your convenience, all DAX definitions in this lab can be copied from the snippets file, located in **04-intro-dax\Snippets.txt**.



⚠ This table definition creates a copy of the **Salesperson (Performance)** table. It copies the data only, however model properties like visibility, formatting, etc. aren't copied.

3. In the **Data** pane, notice that the table icon has an additional calculator in front of it (denoting a calculated table).



⚠ **Note:** Calculated tables are defined by using a DAX formula that returns a table. It's important to understand that calculated tables increase the size of the data model because they materialize and store values. They're recomputed whenever formula dependencies are refreshed, as will be the case for this data model when new (future) date values are loaded into tables. Unlike Power Query-sourced tables, calculated tables can't be used to load data from external data sources. They can only transform data based on what has already been loaded into the data model.

4. Switch to Model view, and notice that the **Salesperson** table is available (you may need to reset view to find table).
5. Create a relationship from the **Salesperson | EmployeeKey** column to the **Sales | EmployeeKey** column.
6. Right-click the inactive relationship between the **Salesperson (Performance)** and **Sales** tables, and then select **Delete**. When prompted to confirm the deletion, select **Yes**.
7. In the **Salesperson** table, multi-select the following columns, and then hide them (set the **Is Hidden** property to **Yes**):
- EmployeeID
 - EmployeeKey
 - UPN
8. In the model diagram, select the **Salesperson** table.
9. In the **Properties** pane, in the **Description** box, enter: **Salesperson related to Sales**

⚠ You may recall that descriptions appear as tooltips in the **Data** pane when the user hovers their cursor over a table or field.


10. For the **Salesperson (Performance)** table, set the description to: **Salesperson related to region(s)**

The data model now provides two alternatives when analyzing salespeople. The **Salesperson** table allows analyzing sales made by a salesperson, while the **Salesperson (Performance)** table allows analyzing sales made in the sales region(s) assigned to the salesperson.

Create the Date table

In this task, you'll create the **Date** table.

1. Switch to Table view. On the **Home** ribbon tab, from inside the **Calculations** group, select **New Table**.



2. In the formula bar, enter the following DAX:

Code

Copy

```
Date =  
CALENDARAUTO(6)
```

✕

✓

1

Date =

2

CALENDARAUTO(6)

🔗 The `CALENDARAUTO()` function returns a single-column table consisting of date values. The “auto” behavior scans all data model date columns to determine the earliest and latest date values stored in the data model. It then creates one row for each date within this range, extending the range in either direction to ensure full years of data is stored.

This function can take a single optional argument that is the last month number of a year. When omitted, the value is 12, meaning that December is the last month of the year. In this case, 6 is entered, meaning that June is the last month of the year.

3. Notice the column of date values which are formatted using US regional settings (that is, mm/dd/yyyy).

Date
07/01/2017 00:00:00
07/02/2017 00:00:00
07/03/2017 00:00:00
07/04/2017 00:00:00
07/05/2017 00:00:00
07/06/2017 00:00:00

4. At the bottom-left corner, in the status bar, notice the table statistics, confirming that 1826 rows of data have been generated, which represents five full years’ data.

TABLE: Date (1,826 rows)


Create calculated columns

In this task, you’ll add more columns to enable filtering and grouping by different time periods. You’ll also create a calculated column to control the sort order of other columns.

🔗 **Note:** For your convenience, all DAX definitions in this lab can be copied from the **Snippets.txt** file.

1. On the **Table Tools** contextual ribbon, from inside the **Calculations** group, select **New Column**.

🔗 A calculated column is created by first entering the column name, followed by the equals symbol (=), followed by a DAX formula that returns a single-value result. The column name can’t already exist in the table.



2. In the formula bar, type the following (or copy from the snippets file), and then press **Enter**:

🔗 The formula uses the date’s year value but adds one to the year value when the month is after June. It’s how fiscal years at Adventure Works are calculated.

Code

Copy

```
Year =  
"FY" & YEAR('Date'[Date]) + IF(MONTH('Date'[Date]) > 6, 1)
```

3. Use the snippets file definitions to create the following two calculated columns for the **Date** table:

- Quarter

- o Month

4. Verify the new columns have been added.

Date ▾	Year ▾	Quarter ▾	Month ▾
7/1/2017 12:00:00 AM	FY2018	FY2018 Q1	2017 Jul
7/2/2017 12:00:00 AM	FY2018	FY2018 Q1	2017 Jul
7/3/2017 12:00:00 AM	FY2018	FY2018 Q1	2017 Jul
7/4/2017 12:00:00 AM	FY2018	FY2018 Q1	2017 Jul
7/5/2017 12:00:00 AM	FY2018	FY2018 Q1	2017 Jul
7/6/2017 12:00:00 AM	FY2018	FY2018 Q1	2017 Jul
7/7/2017 12:00:00 AM	FY2018	FY2018 Q1	2017 Jul


5. To validate the calculations, switch to Report view.

6. To create a new report page, select the plus icon next to Page 1.



7. To add a matrix visual to the new report page, in the **Visualizations** pane, select the matrix visual type.

Tip: You can hover the cursor over each icon to reveal a tooltip describing the visual type.



8. In the **Data** pane, from inside the **Date** table, drag the **Year** field into the **Rows** well/area.

Visualizations

Build visual

Rows

Year


Data

Search


- Targets
- ☒ Date
 - ☐ Date
 - ☐ Fiscal
 - ☐ Month
 - ☐ MonthKey
 - ☐ Quarter
 - ☒ Year
- Product
- Region
- Reseller
- Sales
- Salesperson
- Salesperson (Performance)

9. Drag the **Month** field into the **Rows** well/area, directly beneath the **Year** field.

10. At the top-right of the matrix visual (or bottom, depending on the location of the visual), select the forked-double arrow icon (which will expand all years down one level).



11. Notice that the years expand to months, and that the months are sorted alphabetically rather than chronologically.



By default, text values sort alphabetically, numbers sort from smallest to largest, and dates sort from earliest to latest.

12. To customize the **Month** field sort order, switch to Table view.

13. Add the **MonthKey** column to the **Date** table.

Code

Copy

MonthKey =
(YEAR('Date'[Date]) * 100) + MONTH('Date'[Date]))

This formula computes a numeric value for each year/month combination.


14. In Table view, verify that the new column contains numeric values (for example, 201707 for July 2017, etc.).

1 MonthKey =
2 (YEAR('Date'[Date]) * 100) + MONTH('Date'[Date]))

Date	Year	Quarter	Month	MonthKey
7/1/2017 12:00:00 AM	FY2018	FY2018 Q1	2017 Jul	201707
7/2/2017 12:00:00 AM	FY2018	FY2018 Q1	2017 Jul	201707
7/3/2017 12:00:00 AM	FY2018	FY2018 Q1	2017 Jul	201707
7/4/2017 12:00:00 AM	FY2018	FY2018 Q1	2017 Jul	201707
7/5/2017 12:00:00 AM	FY2018	FY2018 Q1	2017 Jul	201707
7/6/2017 12:00:00 AM	FY2018	FY2018 Q1	2017 Jul	201707
7/7/2017 12:00:00 AM	FY2018	FY2018 Q1	2017 Jul	201707

15. Switch back to Report view. In the **Data** pane and select **Month**.

16. On the **Column Tools** contextual ribbon, from inside the **Sort** group, select **Sort by Column**, and then select **MonthKey**.




17. In the matrix visual, notice that the months are now chronologically sorted.

Year
FY2018
2017 Jul
2017 Aug
2017 Sep
2017 Oct
2017 Nov
2017 Dec
2018 Jan
2018 Feb
2018 Mar

Complete the Date table

In this task, you'll complete the design of the **Date** table by hiding a column and creating a hierarchy. You'll then create relationships to the **Sales** and **Targets** tables.

1. Switch to Model view. In the **Date** table, hide the **MonthKey** column (set **Is Hidden** to **Yes**).
2. On the **Data** right side pane, select the **Date** table, right select on the **Year** column, and select **create hierarchy**.
3. Rename newly created hierarchy to **Fiscal** by right select and **Rename**.
4. Add the follow two remaining fields to the Fiscal hierarchy by selecting them in the **Data** pane, right clicking, selecting **Add to hierarchy** -> **Fiscal**.
 - Quarter
 - Month



5. Create the following two model relationships:
 - **Date | Date** to **Sales | OrderDate**
 - **Date | Date** to **Targets | TargetMonth**

 The labs use a shorthand notation to reference a field. It will look like this: **Sales | Unit Price**. In this example, **Sales** is the table name and **Unit Price** is the field name.

6. Hide the following two columns:
 - Sales | OrderDate
 - Targets | TargetMonth

Mark the Date table

In this task, you'll mark the **Date** table as a date table.

1. Switch to Report view. In the **Data** pane, select the **Date** table (not the **Date** field).
2. On the **Table Tools** contextual ribbon, from inside the **Calendars** group, select **Mark as Date Table**.
3. In the **Mark as a Date Table** window, slide the **Mark as a Date Table** property to **Yes** and in the **Choose a date column** dropdown list, select **Date**. Select **Save**.

Mark as a date table



To enable the creation of date-related visuals, tables and quick measures using this table's date data, mark it as a date table.

Keep in mind any built-in date tables that are already associated with this table will be removed. Visuals or DAX expressions referring to them may break. [Learn more](#)

Mark as a date table



On

Choose a date column

Validated successfully

4. Save the Power BI Desktop file.

Power BI Desktop now understands that this table defines date (time). This design approach for a date table is suitable when you don't have a date table in your data source. If you have a data warehouse, it would be appropriate to load date data from its date dimension table rather than "redefining" date logic in your data model.

Create simple measures

In this task, you'll create simple measures. Simple measures aggregate values in a single column or count rows of a table.

1. In Report view, on **Page 2**, in the **Data** pane, drag the **Sales | Unit Price** field into the matrix visual.

Year	Unit Price
FY2018	\$748.68
2017 Jul	\$655.59
2017 Aug	\$758.93
2017 Sep	\$741.85
2017 Oct	\$677.45

2. In the visual fields pane (located beneath the **Visualizations** pane), in the **Values** field well/area, notice that **Unit Price** is listed as the **Average of Unit Price**. Select the down-arrow for **Unit Price**, and then notice the available menu options.

The screenshot shows the Power BI Visual Fields pane with the 'Values' section highlighted. The 'Average of Unit Price' measure is listed in the 'Values' field well. A red box highlights the 'Average of Unit Price' measure. To the right, a context menu is open, showing various options for the measure. The 'Average' option is highlighted with a red box.

Visual Fields Pane	Context Menu
Rows	Remove field
Year	Rename for this visual
Month	Move to
	Add a sparkline
	Conditional formatting
	Remove conditional formatting
Columns	Sum
Add data fields here	✓ Average
	Minimum
	Maximum
	Count (Distinct)
	Count
	Standard deviation
	Variance
	Median
Values	Show value as
Average of Unit Price	New quick measure


Visible numeric columns allow report authors at report design time to decide how column values will summarize (or not). It can result in inappropriate reporting. Some data modelers don't like leaving things to chance, however, and choose to hide these columns and instead expose aggregation logic defined in measures. It's the approach you'll now take in this lab.

- 3. To create a measure, in the **Data** pane, right-click the **Sales** table, and then select **New Measure**.
- 4. In the formula bar, add the following measure definition:

Code Copy

Avg Price =
AVERAGE(Sales[Unit Price])

- 5. Add the **Avg Price** measure to the matrix visual, and notice that it produces the same result as the **Unit Price** column (but with different formatting).
- 6. In the **Values** well, open the context menu for the **Avg Price** field, and notice that it isn't possible to change the aggregation technique.



It's not possible to modify the aggregation behavior of a measure.


- 7. Use the snippets file definitions to create the following five measures for the **Sales** table:
 - Median Price
 - Min Price
 - Max Price
 - Orders
 - Order Lines

The **DISTINCTCOUNT()** function used in the **Orders** measure will count orders only once (ignoring duplicates).

The **COUNTROWS()** function used in the **Order Lines** measure operates over a table.

In this case, the number of orders is calculated by counting the distinct **SalesOrderNumber** column values, while the number of order lines is simply the number of table rows (each row is a line of an order).

- 8. Switch to Model view, and then multi-select the four price measures: **Avg Price**, **Max Price**, **Median Price**, and **Min Price**.
- 9. For the multi-selection of measures, configure the following requirements:
 - Set the format to two decimal places
 - Assign to a display folder named **Pricing**




10. Hide the **Unit Price** column.

ⓘ The **Unit Price** column is now not available to report authors. They must use the pricing measures you've added to the model. This design approach ensures that report authors won't inappropriately aggregate prices, for example, by summing them.

11. Multi-select the **Order Lines** and **Orders** measures, and then configure the following requirements:

- Set the format use the thousands separator
- Assign to a display folder named **Counts**



12. In Report view, in the **Values** well/area of the matrix visual, for the **Unit Price** field, select **X** to remove it.

13. Increase the size of the matrix visual to fill the page width and height.

14. Add the following five measures to the matrix visual:

- Median Price
- Min Price
- Max Price
- Orders
- Order Lines

15. Verify that the results look sensible and are correctly formatted.

Year	Avg Price	Median Price	Min Price	Max Price	Orders	Order Lines
☐ FY2018	\$748.68	\$419.46	\$4.75	\$2,146.96	739	8,459
2017 Jul	\$655.59	\$419.46	\$5.19	\$2,146.96	38	352
2017 Aug	\$758.93	\$419.46	\$4.75	\$2,146.96	75	785
2017 Sep	\$741.85	\$419.46	\$5.19	\$2,146.96	60	593
2017 Oct	\$677.45	\$419.46	\$5.19	\$2,146.96	40	499
2017 Nov	\$752.31	\$419.46	\$5.01	\$2,146.96	90	1,106
2017 Dec	\$734.58	\$419.46	\$5.01	\$2,146.96	63	803

Create additional measures

In this task, you'll create more measures that use more complex formulas.

1. In Report view, select **Page 1** and review the table visual, noticing the total for the **Target** column.

Salesperson	Sales	Target
Amy Alberts	\$10,288,626	\$19,450,000
Brian Welcker	\$77,548,570	\$221,700,000
David Campbell	\$12,004,822	\$19,625,000
Garrett Vargas	\$13,875,633	\$23,675,000
Jae Pak	\$8,410,883	\$13,575,000
Jillian Carson	\$7,633,387	\$13,675,000
José Saraiva	\$13,875,633	\$18,875,000
Linda Mitchell	\$25,634,503	\$40,850,000
Lynn Tsoflias	\$1,391,025	\$3,210,000
Michael Blythe	\$21,987,348	\$31,150,000
Pamela Ansman-Wolfe	\$30,005,939	\$53,850,000
Total	\$77,548,570	\$676,210,000

2. Select the table visual, and then in the **Visualizations** pane, remove the **Target** field.
3. Rename the **Targets | Target** column as **Targets | TargetAmount**.

 *Tip: There are several ways to rename the column in Report view: In the **Data** pane, you can right-click the column, and then select **Rename**—or, double-click the column, or press **F2**.*

4. Create the following measure on the **Targets** table:

Code

Copy

Target =
IF(
HASONEVALUE('Salesperson (Performance)'[Salesperson]),
SUM(Targets[TargetAmount])
)

 *The HASONEVALUE() function tests whether a single value in the **Salesperson** column is filtered. When true, the expression returns the sum of target amounts (for just that salesperson). When false, BLANK is returned.*

5. Format the **Target** measure for zero decimal places.

 *Tip: You can use the **Measure Tools** contextual ribbon.*

6. Hide the **TargetAmount** column.

 *Tip: You can right-click the column in the **Data** pane, and then select **Hide**.*

7. Add the **Target** measure to the table visual.
8. Notice that the **Target** column total is now BLANK.

Salesperson	Sales	Target
Amy Alberts	\$10,288,626	\$19,450,000
Brian Welcker	\$77,548,570	\$221,700,000
David Campbell	\$12,004,822	\$19,625,000
Garrett Vargas	\$13,875,633	\$23,675,000
Jae Pak	\$8,410,883	\$13,575,000
Jillian Carson	\$7,633,387	\$13,675,000
José Saraiva	\$13,875,633	\$18,875,000
Linda Mitchell	\$25,634,503	\$40,850,000
Lynn Tsoflias	\$1,391,025	\$3,210,000
Michael Blythe	\$21,987,348	\$31,150,000
Pamela Ansman-Wolfe	\$30,005,939	\$53,850,000
Total	\$77,548,570	

9. Use the snippets file definitions to create the following two measures for the **Targets** table:

- Variance
- Variance Margin

10. Format the **Variance** measure for zero decimal places.

11. Format the **Variance Margin** measure as percentage with two decimal places.

12. Add the **Variance** and **Variance Margin** measures to the table visual.

13. Resize the table visual so all columns and rows can be seen.


Salesperson	Sales	Target	Variance	Variance Margin
Amy Alberts	\$10,288,626	\$19,450,000	(\$9,161,374)	-47.10 %
Brian Welcker	\$77,548,570	\$221,700,000	(\$144,151,430)	-65.02 %
David Campbell	\$12,004,822	\$19,625,000	(\$7,620,178)	-38.83 %
Garrett Vargas	\$13,875,633	\$23,675,000	(\$9,799,367)	-41.39 %
Jae Pak	\$8,410,883	\$13,575,000	(\$5,164,117)	-38.04 %
Jillian Carson	\$7,633,387	\$13,675,000	(\$6,041,613)	-44.18 %
José Saraiva	\$13,875,633	\$18,875,000	(\$4,999,367)	-26.49 %
Linda Mitchell	\$25,634,503	\$40,850,000	(\$15,215,497)	-37.25 %
Lynn Tsoulias	\$1,391,025	\$3,210,000	(\$1,818,975)	-56.67 %
Michael Blythe	\$21,987,348	\$31,150,000	(\$9,162,652)	-29.41 %
Pamela Ansman-Wolfe	\$30,005,939	\$53,850,000	(\$23,844,061)	-44.28 %
Total	\$77,548,570			

ⓘ While it appears all salespeople aren't meeting target, remember that the table visual isn't yet filtered by a specific time period. You'll produce sales performance reports that filter by a user-selected time period in the **Design a Report in Power BI Desktop** lab.

14. At the top-right corner of the **Data** pane, collapse and then expand open the pane.

ⓘ Collapsing and reopening the pane resets the content.

15. Notice that the **Targets** table now appears at the top of the list.



Tables that comprise only visible measures are automatically listed at the top of the list.

Lab complete