

■ Features

- Ultra Wide Band: 1-6GHz
- Gain: 55dB
- Output Power Psat: 50dBm
- Bias: Vd=30V;Id=12A

■ Applications

- Research and Development
- Telecommunications
- Wireless Infrastructure
- TR Modules

□ Electrical Specifications

Parameter	Min.	Typ.	Max	Units
Frequency Range	1-6			GHz
Small Signal Gain	50	53		dB
Power Gain Flatness		±4	±5	dB
Input /Output VSWER		1.5	2.0	-
Output Power for 1 dB Compression (P1dB)		48		dBm
Saturated Output Power (Psat)	50			dBm
Input Max Power(no damage)			10	dBm
Internally Generated Spurious	-60			dBc
Harmonics		-15		dBc
Spurious Non-harmonics	-60			dBc
DC Current (Vcc=+30V) (@Pout=100W)		10	13	A
Impedance	50			Ω
Supply Voltage	220V/50Hz			
Input Output Connector	SMA-k/N-K			
Material	Aluminum			
Function	Overtemperature protection overcurrent protection VSWR protection			
Dimension	19inch 4U			

□ Environmental Conditions

Environmental Specifications:

- ※ Operational Temperature $-30^{\circ}\text{C}\sim+70^{\circ}\text{C}$
- ※ Storage Temperature $-45^{\circ}\text{C}\sim+85^{\circ}\text{C}$



OBSERVE
PRECAUTIONS ELECTROSTATIC
SENSITIVE DEVICES

□ Absolute Maximum Ratings

NOTE:

1. The product is designed to meet environmental ratings but not tested. If you need to test environmental condition, please contact our sales department.
2. HiMicrowave technologies co., Ltd. reserves the right to change the above information without notice.

Heat Sink required during operation