

MODEL HIPA02184045AC

2-18GHz Power Amplifier



■ Features

- Ultra Wide Band: 2-18GHz
- Gain: 40dB
- Output Power Psat: 45dBm
- Bias: 110~220V/50~60Hz

■ Applications

- Research and Development
- Telecommunications
- Wireless Infrastructure
- TR Modules

□ Electrical Specifications

Parameter	Min.	Typ.	Max	Units
Frequency Range	2-18			GHz
Small Signal Gain	40			dB
Gain Flatness		± 2.5		dB
Gain Variation Over Temperature			± 1.5	dB
Input VSWR		1.5	2.0	-
Output Power for 1 dB Compression (P1dB)		42		dBm
Saturated Output Power (Psat)	45			dBm
NF		8		dB
Harmonic Rejection		15		dB
Input Max Power(no damage)			10	dBm
Internally Generated Spurious		-60		dBc
Supply Voltage	110~220V/50Hz			
Impedance	50			Ω
Input Output Connector	SMA-k/SMA-K			
Material	Aluminum			
Weight	5kg			

Environmental Conditions

Environmental Specifications:


- ※ Operational Temperature $-25^{\circ}\text{C} \sim +70^{\circ}\text{C}$
- ※ Storage Temperature $-55^{\circ}\text{C} \sim +125^{\circ}\text{C}$



OBSERVE
PRECAUTIONS ELECTROSTATIC
SENSITIVE DEVICES

Outline Drawing

All Dimensions in mm (inches) Tolerance ± 0.25 (0.01)



NOTE:

1. The product is designed to meet environmental ratings but not tested. If you need to test environmental condition, please contact our sales department.
2. HiMicrowave technologies co., Ltd. reserves the right to change the above information without notice.

*****Heat Sink required during operation*****